



Det Tronics

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Det Tronics Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Det Tronics T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

| ¼r¼n | A¼ıklama |
|----------------------------------|--|
| GT3000 | H2S 50PPM Det-Tronics GT3000 |
| Flexview UD-10 | |
| x3301 ir exproof | +Mounting Feet |
| U5015-A-2-M-13-A | Explosion-Proof Smoke Detector |
| 028258-001 | X3301A4N13T1 |
| 007168-2005 | Pirecla1B1T2 3/4,4-20W |
| DETECTOR:GAS;IR, | METHNE,24VDC,SS316 GAS DETECTOR TYPE: GAS ANALYZER OF HYDROCARBON GASES STATIONARY INFRARED MODEL MODEL: PIRECLB1A1SK2 GAS DETECTOR CALIBRATION GAS: METHANE OUTPUT SIGNALS: 4 - 20 MA; HART HYDROPHOBIC FILTER POWER SUPPLY: 24 VDC BODY MATERIAL: STAINLESS STEEL 316 CABLE PORT: 2 X M25*1.5MM ISO IP66/IP67 EX D IIC T4-T5 GB FIXING BOLTS, STAINLESS STEEL ADDITIONAL CERTIFICATE: MIN SIL-1 REQUIRED MODEL - DET-TRONICS |
| | ,IR,24VDC,SS316 DETECTOR:FLAME TYPE: MULTISPECTRUM TRIPLE IR SENSITIVE: VERY HIGH CONE OF VISION: 90 |

| | |
|--|--|
| DETECTOR:FLME;TRPL | HORIZONTAL, 75 VERTICAL RESPONSE TIME: 3 SEC FOR HEPTANE&METHANE TRANSMISSION SIGNAL: 4-20 m; FIRE, FAULT & AUX RELAYS MATERIAL BODY: SS316, RED CONNECTION: 4xM25*1.5mm ADDITIONAL CERTIFICATE: SIL CERTIFICATE-MIN SIL-1 REQUIRED MODEL - DET-TRONICS |
| CGSS1C6V2R1X M20,6LW,CV | COMBUSTIBLE GAS SENSOR 006824-004 |
| CGSS1C6C2R1X | |
| CGSS1C6V2R1X M20,6LW,CV | 006824-004 |
| U7698E | Operating Voltage: 18-30 VDC Nominal Power: 2 W Maximum Power: 4.5 W Output Signal: 4-20 mA Methane Flame Length: 76 cm Field of View: 80° Explosion Protection Ratings: Class I, Division 1, Groups B, C & D Class I, Division 2, Groups A, B, C & D (T4) Class II/III, Division 1, Groups E, F, & G Class II/III, Division 2, Groups F & G (T4) Enclosure: Type 4X CENELEC Certification: EEx d IIC T6 (Tamb = -40°C to +70°C) EEx d IIC T5 (Tamb = -40°C to +75°C) EEx d IIC T4 (Tamb = -55°C to +125°C) Ingress Protection: IP66 Gosstandart Certification: 1 Ex d IIC T6 (Tamb = -40°C to +70°C) 1 Ex d IIC T5 (Tamb = -40°C to +75°C) 1 Ex d IIC T4 (Tamb = -55°C to +125°C) |
| CTX10A3F2T | CTX10 replacement for 505 transmitter 014394-002 |
| PIRECLA1A1W1 GAS DETECTOR | |
| 005434-004 | SENSOR, H2S, DES434-004 H2S ELECTRO CHEMICAL CELL, 0-50PPM |
| X33301a | flame detector |
| 007371-003 | EQ3700DW DCIO |
| Eq2453ne 3/4npt 5p Fm/Csa/Atex | 006941-009 |
| 028128-001 | X3301A4N14W2 FLAME DETECTOR |
| 027752-001 | X3301,HEAD, AL, EX D E |