Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Dilo

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Dilo Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Dilo Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
05-0493-R001	Cover cap 5001879 3-308-R006 for plug-in coupling spring part
6-1161-R015	Hose connection DN7 Plug-in coupling spring part DN7 with measuring device connection coupling Pressure level: PN30 Total length: 128 mm Material: aluminum (3.2315)
3-308-R002 T	PLUG-IN COUPLING SPRING PART Plug-in coupling spring part DN7 Pressure level: PN30 Screw-in thread: M20x1.5 Wrench size: SW27 Total length: 80 mm Material: aluminum (3.2315)
3-308-R003 T	Plug-in coupling groove part DN7 PN30, screw-in thread G3 / 8A
3-038R-R201 Multi-Analyser SF6-V2-B	(Vol .-%, moisture) * Dual measuring device with feedback for measuring Volume and moisture concentrations on SF6-filled circuit breakers and systems. With WLAN router and integrated antenna: enables wireless connection via mobile End device such as smartphone, tablet, I-Pad or laptop. * Specifications:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Percentage measuring range: 0 - 100 volume% SF6 / N2 Humidity measuring range: -60 ° C to + 20 ° C dew point temperature * Scope of delivery: - Transport case with trolley function - 6 m connection hose - DILO couplings DN8 and DN20 - 2 m connection cable with mains plug - USB stick * Display: color touch panel capacitive (7 inches) Pressure range: 0.2 - 35 bar pe Internal data memory: 500 measured values * Operating voltage: Mains operation 90-264 VAC / 50-60 Hz Battery operation via Li-Ion battery ********** DANGER: The device contains lithium-ion batteries! ********** * Operating instructions (multilingual) *
3-393-R115	3-393-R115 SF6 gas refill device SF6 gas refill device in the case with rubber hose NL = 5000 MM Coupling DN8 Adapter DN8 to DN6 Pressure reducer 0 - 2.5 bar * 2 pieces of operating instructions in 3 languages (German English French) Dimensions: 53 x 47 x 19 cm / piece Gross weight approx: 10 kg / piece
3-001-4-R002	
VK/F-02/8 T	1023181 CLUTCH SPRING PART DN8 Coupling spring part DN8 Pressure level: PN64 Screw-in thread: M20x1.5 Connection thread: M26x1.5 Wrench size: SW32 Material: aluminum (3.2315)
1002066	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1002248	
1002406	
1002481	
1002483+5010343	
1003867	
1004383	
1004392	
1004396	
1004397	
1006172	
1006174	
1006280	
1006287	
1006292	
1006705	
1006761	
1007164	
1008238	
1008239	
1009159	
1016840	
1016954	
1017047	
1019637	
1022091	
1023156	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1023173	
1031057	
1031982	
1033516	
1035548+1006705+1035787	
1035564	
1035651	
1035787	
1040128	
1040128+5010344+1009492	
1040231	
1040231+1004397	
1041583	
1042186	
1042918	
1042919	
1043079	
5000132	
5000150	
5004659	
5006192	
5007198	
5010343	
5010354	
6-0004-R039	
B077-10	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
GS0108L01000	
J1B 16 G C	
1023179-	VK/F-02/8 P coupling spring part DN8 Coupling spring part DN8 Pressure rating: PN64 Screw-in thread: M20x1.5 Connection thread: M26x1.5 Wrench size: SW32 Material: Brass (2.0401)
3-037-R001	Portable Moisture Meter V1 with dew point display (digital) * Measuring range: -60°C to +20°C Measurement via 2 fine adjustment valves and electronic flow meter, Operation with NiMH rechargeable batteries or integrated mains charger, Connection hose 2 m with couplings DN8 and DN20, Robust housing with mounting and carrying handle, mains plug with connection cable 2 m, Black plastic case * Power supply for mains charger: 100-240VAC / 50-60Hz * operating manual ********** During the measurement process, SF6 emissions occur with this single meter. Due to the current IEC standards, SF6 Emissions are avoided wherever technically possible. DILO recommends the following devices to protect the SF6 during the measurement process: - B151R40 sample gas collection device - B151R95 sample gas collection bag ********** * Net weight 6,770 KG HS code 902710 Country of origin Federal Republic of Germany
B151R95	Sample gas collection bag For mobile storage of SF6 sample gas when using SF6 measuring devices. capacity 52l Dimensions: 300x600x80 mm (empty) 600x900x300mm (full)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Weight: 1.2kg Standard equipment: 1m measuring hose with self-closing couplings DILO coupling DN8 with hose connection * 2 operating instructions in 3 languages (German English French) Net weight 1,250KG HS code 902710 Country of origin United States
3-393-R002 SF6	gas refill device portable in case with rubber tube and coupling DN8 and DN20 1002483 basic equipment: Pressure reducer for SF6 0-10ba with thread W 21.8x1/14" Hose DN8/5m long Coupling spring part DN8 Coupling spring part DN20 Pressure gauge reading in bar .kPa,psi
SF6 Gas charging/discharging	We need Dilo device and SF6 gas analyzer.
3-033-R002 SF6-Leak Pointer	1037858 gas leak detector Standard version with carrying case, 2 alkaline batteries 1.5V (not included), 1 spare sensor * Operating instructions (multilingual)
5007540	05-1730-R002 Smart Sensor complete
5007547	05-1730-R009 Front Filter Pack of 10
6-1045-R029	DN20-DN12 Angle piece with groove part DN20 VK/B-03/20 and coupling spring part DN12 3-888-R001
3-033-R002 SF6-Leak Pointer (DILO)	gas leak detector Standard version with carrying case, 2 alkaline batteries 1.5V (not included), 1 spare sensor
3-033-R002 Sf6-Leak Pointer 1037858	
05-1730-R002 Smart Sensor komplett	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
5009047	05-1881-R012 Flaschendruckminderer SF6
1001890	3-227-R001 P Adapter DN8 Adapter DN8 Pressure rating: PN64 Thread: d3=M20x1.5 L=32mm m1=18mm s1=24mm Material: brass (2.0401)
1023126	VK/A-02/8 P coupling groove part DN8 Coupling nut part DN8 Pressure rating: PN64 Screw-in thread: M20x1.5 Connection thread: M26x1.5 Total length: 48mm Width across flats: SW27 Material: brass (2.0401)
1006301	6-1042-R300 Rubber hose 30m long on both sides
1007058	6-1206-R001 Adapter DN20 / DN8 Coupling spring part DN20/DN8 Pressure rating: PN64 Screw-in thread: M26x1.5 Connection thread: M45x2 Total length: 95mm Material: brass (2.0401)
SF6 THROTTLE ADAPTER	
SF6 GAS DETECTOR	
3-033-R002 SF6-Leak Pointer	Gas leak detector Standard version with carrying case, 2 alkaline batteries 1.5V (not included), 1 replacement sensor
09.00	
1016915	M1AW16 C ANGLE WELDED SCREW JOINT Angle welded pipe joint with welded ends on both sides Pressure range: up to PN100 Nominal diameter: DN16 Material: 1.4571 Pipe connection dimensions: d1=18, s=2 With acceptance test certificates 3.1 according to DIN EN 10204
1037858	3-033-R002 SF6 Leak Pointer (DILO)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	gas leak detector Standard version with carrying case, 2 alkaline batteries 1.5V (not included), 1 replacement sensor * Operating instructions (multilingual) *
1037858-	3-033-R002 SF6 Leak Pointer (DILO) Gas leak detector Standard version with carrying case, 2 alkaline batteries 1.5V (not included), 1 replacement sensor * Operating instructions (multilingual)
3-038R-R413	(Vol.-% N2/CF4, humidity, SO2-500, HF) * Quadruple measuring device with feedback for measuring Volume, humidity, SO2 and HF concentrations on SF6-filled circuit breakers and systems. With Wi-Fi router and integrated antenna: enables wireless connectivity via mobile devices Device such as smartphone, tablet, iPad or laptop. * Specifications: Percentage measurement range: 0 - 100 volume % SF6/N2 and SF6/CF4 Humidity measuring range: -60°C to +20°C dew point temperature SO2 measuring range: 0 - 500 ppmv RF measurement range: 0 - 10 ppmv * Scope of delivery: - Transport case with trolley function - 6 m connection hose - DILO couplings DN8 and DN20 - 2 m connection cable with mains plug - USB stick * Display: 7-inch capacitive color touch panel Pressure range: 0.2 - 35 bar pe Internal data storage: 500 measured values * Operating voltage: Mains operation 90-264 VAC / 50-60 Hz Battery operation via Li-ion battery
3-393-R002 SF6 gas refilling device	3-393-R002 SF6 gas refilling device

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Portable in a case with a rubber hose and coupling DN8 and DN20 * Basic equipment: Pressure reducer for SF6 0-10 bar with thread W 21.8 x 1/14" Hose DN8/5 m long DILO clutch spring part DN8 DILO clutch spring part DN20 Pressure gauge display in bar, kPa, psi * 2 operating manuals in 3 languages (German/English/French)
4-200-81	4-200-81 Replacement compressor for 4-200-00 Compressor TM5.0B (new) 5.7 m³/h (50 Hz), pe 50 bar Operating voltage: Three-phase 208-240V, 380-460V 50/60Hz Operating instructions (2-part) in ()German ()English ()French
5005485	05-1239-R002 Pressure gauge NG63 0-60bar
5011845	05-0078-R005 Cu seal G1/4 manometer
1023142	VK/B-03/8 T Coupling groove part DN8 Coupling groove part with O-ring DN8 Pressure rating: PN64 Screw thread: M16x1.5 Connection thread: M26x1.5 Total length: 48 mm Wrench size: SW27 Material: Aluminum (3.2315)
1023140	VK/B-03/8 E Coupling groove part DN8 Coupling groove part with O-ring DN8 Pressure rating: PN64 Screw thread: M16x1.5 Connection thread: M26x1.5 Total length: 48 mm Wrench size: SW27 Material: Stainless steel
Jh1b25g D	JH1B25G D hot steam screw-in seal Hot steam screw-in pipe fitting with Whitworth thread Operating temperature: up to 500 ° C Pressure range: up to PN100 Nominal diameter: DN25 Material: 1.7335 Pipe connection dimensions: d1 = 34, s = 4 Threaded connection: d4 = G 1 1/2 "
1019589	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Z340r21	
1002372	
6?1092?R006	
B143r11	
M1m10/51 C	
Sf6	ANALYZER
6-1076-R100	
3-001-R001	
3-906-06	
3036r001	ANALYZER
1023179	
3 - 033 - R002 Gaslecksuchgerã196;T	
3-001-4-R022	
3-001-4-R002A	3-001-4-R002A evacuation + refill from 8/15 Evacuation and refilling device * For evacuating air and refilling SF6 gas, Mobile as cylinder trolley with metal bellows hoses DN8, Coupling DN8 and DN20 Vacuum pump 16m³ / h, ultimate vacuum <1 mbar Painting: orange (RAL2004) Pressure gauge with 3-fold scale (bar / kpa / psi) * Operating voltage: 220-240 V / 50-60 Hz alternating current 2 pieces of operating instructions in 3 languages (German English French) Dimensions: 80 x 65 x 159 cm / piece Gross weight approx: 110 kg / piece * ATTENTION: Packaging not suitable for storage purposes. Unpack immediately upon receipt. Store the device in a dry place!
3-377-08	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1000678 , Type 3-027-R002	
1023173 Vk/F-02/20 E Kupplungs-Federteil Dn20	
1023174	
B077-10 (3-899-06)	
Filter Particle For Sf6	
3-033-R002 Sf6-Leak Pointer (Dilo) 1037858	gas leak detector Standard version with carrying case, 2 alkaline batteries 1.5V (not included), 1 spare sensor * Operating instructions (multilingual) * Country of origin: China Net weight 11,000 KG HS code 902710
6?1206?R001	
3-001-R002 Sf6	
6-1076-R050	
1023174 Vk/F-02/20 P Kupplungs-Federteil Dn20.Werkstoff 2.0401	
1019637 Ml1-Ad22-14 P Einschraubstutzen M.O-Ring	
1002406 3-383-R001 P Kugelhahn Dn20	
3-033-R002 1031057	
B143r01 By B143r11	
1033134	
05-0091-R001	
Jh1b25g Q	JH1B25G Q hot steam screw-in seal Hot steam screw-in pipe fitting with Whitworth thread Pressure range: up to PN100 Nominal diameter: DN25 Material: 1.4922 Pipe connection dimensions: d1 = 34, s = 4 Threaded connection: d4 = G 1 1/2 A

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1002248 3-365-R001 P Kugelhahn Dn8werkstoff 2.0401 Messing	
1015329	
1023126	
1006909	
3-558-R001	
05-1602-R304	
3-899-06	
3-690-R201	
1001964	
1005084	
6-1045-R003	
1040819	
3-393-R001 Sf6 1002481	
3-393-R039	
Gs0108l01000 Gummischlauch Nl=1000mm	
1019590	
M1-16-8 C	
1006281	
1023126 Vk/A-02/8 P Kupplungs-Nutteil Dn8werkstoff 2.0401 Messing	
1023156 Vk/Bg-03/20 P Kupplungsnutteil Dn20mit O-Ring1" Einschraubgewinde	
3-033-R002 Sf6-Leak Pointer (Cps)	
1006031	
3-393-R001	
1006010	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Z340r11	
3-033-R002 Sf6-Leak Pointer (Cps) , By 3-033-R002 Sf6-Leak Pointer (Dilo)	
Z340r21á;(1024497)	
3-038R-R303	Multi-Analyzer SF6-V2-B (Vol.-%, moisture, SO2-500) * Triple measuring device with feedback for measuring Volume, humidity and SO2 concentrations on SF6-filled circuit breakers and systems. With Wi-Fi router and integrated antenna: enables wireless connectivity via mobile devices Device such as smartphone, tablet, iPad or laptop. * Specifications: Percentage measuring range: 0 - 100 volume % SF6/N2 Humidity measuring range: -60°C to +20°C dew point temperature SO2 measuring range: 0 - 500 ppmv * Scope of delivery: - Transport case with trolley function - 6 m connection hose - DILO couplings DN8 and DN20 - 2 m connection cable with mains plug - USB stick * Display: 7-inch capacitive color touch panel Pressure range: 0.2 - 35 bar pe Internal data storage: 500 measured values * Operating voltage: Mains operation 90-264 VAC / 50-60 Hz Battery operation via Li-ion battery
5000150 05-0057-R039 O-Ring Id=39,0xw=2,5 Epdm	
A2949	
3-001-R021	
1006037	
Z340r14	
K072r.. 1014455	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Z300r11	
1006218	
1006052	
B048r13	
3-393-R001 1002481	SF6 gas refill device portable with rubber hose and coupling DN8 and DN20 * basic equipment: Pressure reducer for SF6 with thread W 21.8 x 1/14" Hose DN 8/5 m long DILO coupling spring part DN8 DILO coupling spring part DN20 Pressure gauge display in bar, kPa, psi * 2 operating instructions in 3 languages (German English French) Net weight 45,000 KG HS code 848110
6-1076-R0	
3-245-R003	
0-7302-61	
3-033-R002 Sf6(1031057)	
Z340r21 Adapterset Im Kunststoffkoffer	
3-393- R002(1002483)	
B178r01	
Kd-01/G1/2a G	
1002483	
3-037-R001	
Z619r01	
3-001-4-R002a	
1001905	
M1a16 C	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
3-558-R010/A	
B046r03 1007721	
1006910	
3-315-R001 2.0401	
1032565	
0-7302-67	
1022091 Sm0120l05000 Metallbalgschlauch Nl5000mm	
Z340r12	
1001027	
3-775-R026-C	
3-001-4-R002 Vakuumpumpe	
1006022	
Vk/F-02/8 P Element Nut Und Feder Verbindung Mit Dem Vorsprung	
5000132 05-0057-R010 O-Ring Nr. 117 (20,29x2,62)	
3-334-R001 2.0401	
3 - 3 9 3 - R 0 0 1 - S F 6	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.