

## Dk Lok



Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Dk Lok** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Dk Lok Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Dfs-2-S</a>	Dk-Lok clamp ring set 1/8 stainless steel
<a href="#">Vh36c-D-16m-1-S</a>	D-Pro check valve Dk-Lok 16 mm spring 1 PSI (0.07 bar) stainless steel
<a href="#">V82A-F-2N-B DK-LOK</a>	
<a href="#">V823A-F-2N-B DK-LOK</a>	
<a href="#">V824A-F-2N-B DK-LOK</a>	
<a href="#">TU-6M-10-L</a>	Tube 6 x 1.0 mm seamlessly cold drawn Bright annealed ASTM A269 / A213, EN 10216-5 TCI D4 / T3 DIN EN ISO 1127 Stainless steel 1.4435 Delivery length 6m
<a href="#">DMC 6M-4R-S</a>	Dk-Lok screw connection 6 mm - R 1/4 stainless steel
<a href="#">DCF 6M-4GG-S</a>	
<a href="#">DLA 6M-S</a>	
<a href="#">DGV 4-S</a>	
<a href="#">DGV 16-S</a>	
<a href="#">HM6-T-6M-410-S</a>	
<a href="#">HM6-T-6M-410-S</a>	
<a href="#">DGV 12-S</a>	
<a href="#">V15B-D-8M-A-R-S</a>	D-Pro angle regulating valve Dk-Lok 8 mm stainless steel
<a href="#">VH36B-D-10M-1-S</a>	D-Pro check valve Dk-Lok 10 mm spring 1 PSI (0.07 bar) stainless steel
<a href="#">V82A-D-2T-S</a>	D-Pro ball valve packing PTFE Dk-Lok 1/8 stainless steel
	D-Pro 3 way ball valve packing PTFE Dk-Lok 1/8 stainless

<a href="#">V823A-D-2T-S</a>	steel
<a href="#">DFS-2-S</a>	Dk-Lok clamp ring set 1/8 stainless steel
<a href="#">VC86C-F-12N-S</a>	
<a href="#">V16B-D-6T-GF-A-L</a>	D-Pro angle shut-off valve ball tip Dk-Lok 3/8 pack Grafoil stainless steel 316L
<a href="#">VC86C-D-16T-S</a>	D-Pro ball valve Dk-Lok 1" stainless steel seat PEEK seal O-ring HNBR pressure 24bar Temperature -45° to 180°C
<a href="#">V16B-D-6T-GF-A-S</a>	D-Pro angle shut-off valve ball tip Dk-Lok 3/8 pack Grafoil stainless steel
<a href="#">VC86B-F-8N-S</a>	D-Pro ball valve 1/2 NPT i PEEK stainless steel
<a href="#">V15C-F-4N-S.</a>	D-Pro shut-off valve V-spindle 1/4 NPT i stainless steel
<a href="#">400 BAR</a>	1" 4 PCS 3/4" 4 PCS 1/2" 8 PCS 3/8" 4 PCS
<a href="#">V66-F-4N-D-CE</a>	D-Pro angled overflow valve 1/4 NPT internal with spring, adjusting pressure 103 - 155 bar CE Stainless steel certificate
<a href="#">V66-F-4N-C-CE</a>	D-Pro angled overflow valve 1/4 NPT internal with spring, adjusting pressure 51.6 - 103 bar CE Stainless steel certificate
<a href="#">V63-F-4N-L-CE</a>	D-Pro angled overflow valve 1/4 NPT internal Adjustable spring 0.68 - 17.2 bar CE certified stainless steel
<a href="#">V66-F-4N-E-CE</a>	D-Pro angled overflow valve 1/4 NPT internal with spring, adjusting pressure 155 - 206 bar CE Stainless steel certificate
<a href="#">V66-F-4N-A-CE</a>	D-Pro angled overflow valve 1/4 NPT internal with spring, pressure adjustment 3.4 - 24 bar CE Stainless steel certificate
<a href="#">PSV,P01-YCZ-102</a>	
<a href="#">SPARE KIT,PSV,P01-YCZ-102</a>	
<a href="#">PSV,20229921005</a>	
<a href="#">V15B-D-6M-R-S</a>	D-Pro regulating valve Dk-Lok 6 mm stainless steel
<a href="#">PSV,1",2.400 PSI,81-17151V13G11</a>	
<a href="#">PSV,1",2.400 PSI,81-17151V11G11</a>	
<a href="#">PSV,2",2.000 PSI,81-43-2-51V15G11</a>	
<a href="#">DTR 10M-10M-12M-S</a>	Dk-Lok T-reducing fitting 10 mm - 10 mm - 12 mm stainless steel Minimum order quantity: 20 pcs
<a href="#">V76C-M-8N-90-S</a>	D-Pro T Filter 1/2 NPT a 90 micron stainless steel
<a href="#">FE73C-90</a>	Filter element 90 micron D-Pro Filter V73C 73D V76B 76C

	stainless steel
<a href="#">V81C-F-8N-TF-S</a>	V81C-F-8N-TF-S
<a href="#">Threaded plug 1/4" NPT (M), SS 316</a>	Threaded plug 1/4" NPT (M), SS 316
<a href="#">Needle valve 1/4" NPT (M) / 1/4" NPT (F), SS 316</a>	1/4" NPT (M) / 1/4" NPT (F), SS 316
<a href="#">Compressed type connector 1/4" NPT (M) for 1/2" O.D. tubing, SS 316</a>	Compressed ty /4" NPT (M) for 1/2" O.D. tubing, SS 316
<a href="#">Seamless instrument tubing 1/2" O.D.x0,049" W.T., SS 316</a>	Seamless /2" O.D.x0.049" W.T., SS 316
<a href="#">Compressed type cap for 1/2" O.D. tubing, SS 316</a>	Compressed type cap for 1/2" O.D. tubing, SS 316
<a href="#">Compressed type connector 1/2" NPT (M) for 1/2" O.D. tubing, SS 316</a>	Compressed ty / for 1/2" O.D. tubing, SS 316
<a href="#">V81c-F-8n-Ld-S</a>	D-Pro Ball Valve 1/2 NPT i 140 bar Locking Device stainless steel
<a href="#">V81c-F-8n-Tf-Ld-S</a>	D-Pro Ball Valve 1/2 NPT i 140 bar Locking Device stainless steel
<a href="#">V15c-F-4n-S</a>	D-Pro Shut-off Valve V-Spindle 1/4 NPT i stainless steel
<a href="#">Dk-Lok V15c-F-4n-S Valf</a>	