Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Dmn Westinghouse

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Dmn Westinghouse Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Dmn Westinghouse Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
DN200	
DN300	
Discharge lock	similar to serial number RVNL170568 1.1 Customer specifications PRODUCT NAME: Plastic additive Properties: dry, non-abrasive, free-flowing Bulk density: 0.3 kg/l Grain size: 0.1 mm Product temperature: 60 °C Conveying air temperature: max. 40 (assumed) °C Ambient temperature: 5 - 40 °C Performance (1): 1,500 kg / h Performance (2): 5,000 ltr / h Dosing of quantity: NO Pressure difference: _ mbar Pressure is present: _ please specify -> above or below the lock NOTE: PLEASE SUPPLY ANY MISSING PRODUCT AND APPLICATION DATA. CORRECT INCORRECT! -- Component performance data -- Rotor speed: 12 rpm Filling level (estimated): 70 % Performance: 5,292 l/h 1.2 ATEX (protection system) - internal zone 20 (II1D), external zone 22 T200°C (II3D) Pressure resistant and flameproof up to 10 bar Dust explosion class 2 (Kst 0-300 bar.m.s-1), organic dust MIE >4 mJ and MIT >300°C Note: The MESG value must be greater than 1.39 mm! AL 200-Dairy- standard version Rotor volume: 10.5 l/rev. Housing/cover: stainless steel 1.4408 (AISI 316), vent not drilled - flange connection DIN PN10 Quickly removable design with hexagon bolt Rotor: stainless steel 1.4404 (AISI 316L)

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Rotor blades: ## pieces with rounded rotor pockets, fixed and ground on 3 sides Product contact surfaces polished 0.8 µm (Ra) Shaft seal: see following items Weight including attachments (without gear motor): approx. 144 kg
Modification of the rotary valve as ATEX	protection system APS 1.) 10 rotor blades instead of standard 2.) Rotor reinforced
MZC rotor extraction device	for quick-disassembly version / Dairy incl. inductive sensor - make P&F
Additional charge for	MCZ sensor make P F according to ATEX Zone 2/22 II3GD Type NCB2-12GM40-E2-3G-3D, 10 - 30 VDC with 2m cable (instead of standard sensor)
Safety switch Steute according to ATEX	Zone 1/21 (II2GD) Type EEx AZ 16 1ˆ/1S-5M-30N
Shaft seal:	Air shaft seal (Mat.Viton FDA, Code 37) Note: Gas supply (regulated) is required!
Accessories shaft seal	FESTO according to ATEX 2/22 (II3GD) Filter pressure regulator type MS4-LFR with solenoid valve MFH-3-1/4-S-EX with pressure gauge 0-4 bar Coil 24 VDC type MSFG-24-EX II3GD EEx nA II T130°C X, 4.5 W with plug MSSD-F-M16, incl. shut-off valve, plastic hoses ÿ 10 mm Ambient temperature 5°C to +40°C incl. assembly
Helical gear motor	Type R57/II2GDEDRN80MK4/3GD/KCC/TF/AL according to ATEX zone 2/22 (II3GD T3/T120°C) 0.55 kW, 220-240/380-415 V, 50 Hz, IP 65, ISO class F, KKL 180°, design M5 Output speed: 16 rpm, 330 Nm, fB = 1.35 Rated current 1.38 A (400V) incl. TF-3 PTC thermistor sensor (without trigger device) Weight of gear motor approx. 30 kg incl. adjustment/small parts and assembly for chain drive Chain wheel motor 5/8" - Z .. - ÿ 35 mm Sprocket rotor 5/8" - Z .. - ÿ 32 mm
AL 400-1 - Standard version	Rotor volume: 91 l/rev. Housing/cover: grey cast iron GGG40 - flange connection DIN PN10 Vent holes drilled, including blind plugs Rotor: steel with reinforcement bars Rotor blades: # pcs. see following items

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Shaft seal: See following items Weight including attachments (without gear motor): approx. 650 kg
Rotor with 10 rotor blades instead of standard	(8 sheets)
Rotor blades made of HARDOX 450 (3 MM) instead of mild steel -	interchangeable
Rotor blades (replaceable) relief ground on one side	
Shaft seal: Air/stuffing box "Teadit FDA" (Code 33)	Note: Gas supply (regulated) is required!
Shaft seal accessories	Filter pressure regulator type MS4-LFR II2GD T6/T60°C with on/off valve MS4 ATEX 3GD T4/T105°C Coil 24 VDC 1.8 W, connector MSSD-EB-M12-24VDC-SD-EX IP65, pressure gauge 0-4 bar, shut-off valve Plastic hoses Ø 10 mm Ambient temperature -5°C to +40°C incl. assembly
helical gear motor,	Type R87 DRN100LM4/TF - Efficiency class IE3 2.20 kW, 220-240/380-415 V, 50 Hz, IP 65, ISO F, Type M5, n2=23, 920 Nm KKL 180° rated current 4.75 A (at 400 V) incl. TF-3 PTC thermistor sensor (without trigger device) Weight of gear motor approx. 88 kg including assembly and attachments for chain drive Sprocket motor 1" - Z .. - Ø 60 mm Sprocket rotor 1" - Z .. - Ø 48 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.