



Doseuro S.R.L.

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Doseuro S.R.L. Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Doseuro S.R.L. Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Piston Gasket Set, Pos.3 And 12, For A125n-12/C-32	+ Stuffing box, pos.6, for A125N-12/C-32
D101n-90/B-13 Tn	Diaphragm metering pump 1 x mechanisch angetriebene Membrandosierpumpe mit manueller Hublngenverstellung 0-100% Typ: D101N-90/B-13 Dosiermenge: 0 - 271 l/h max. Betriebsdruck: 5 bar Hubfrequenz: 120 Hbe/min AnschluŐ: 3/4" AuŐengewinde Material: Pumpenkopf: PVC Membran: PTFE beschichtet Ventile: PVC Ventildichtungen: Viton Motor: 0,18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55 Gewicht, brutto: ca. 12 kg
A350n-89/B-11, Ss/Nbr	Piston metering pump directly controlled piston metering pump with manual stroke length adjustment 0-100% Type: A350N-89 / B-11 Dosing quantity: 0 - 1,458 l / h Max. Operating pressure: 4 bar Stroke frequency: 112 strokes / min Connection: 1 1/2 "external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.75kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
A250N-76/B-11, SS/NBR	Piston metering pump 1 x directly linked piston metering pump with manual stroke length adjustment 0-100% Type: A250N-76 / B-11 Dosing quantity: 0 - 766 l / h Max. Operating pressure: 6.5 bar Stroke frequency: 112 strokes / min Connection: 1 "external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.55kW, 3ph, 230 / 400V, 50Hz, 4 pol., IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 26 kg / 30 kg
D101N-90/B-13	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D101N-90 / B-13 Dosing amount: 0 - 271 l / h Max. Operating pressure: 5 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.25 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy

	Weight, net / gross: 10 kg / 13kg
Pump head, PVC, ø90mm	Customs tariff number: 84139100 Country of origin: Italy Weight, net / gross: 0.4 kg / 0.6 kg
Valve set, AC13-13, PVC / Viton, for D101N-90 / B-	consisting of suction and pressure valve Customs tariff number: 84139100
Membrane with support plate, ø90mm	Zolltarifnummer: 84139100 Herkunftsland: Italien Gewicht, netto/brutto: 0,15 kg / 0,25 kg
D90 DIAPHRAGM AND PROTECTION POZ.20 + POS.22	
D100N-90/B-13 TN	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 Dosing amount: 0 - 271 l / h Max. Operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
AC5-31	Valve set, AC5-31, PP / Viton consisting of suction and pressure valve
AC13-14	Valve set, AC13-14, PVC / Viton consisting of suction and pressure valve
AB13	Valve set, AB13, SS / Viton consisting of suction and pressure valve
AC8-31	Valve set, AC8-31, PP / Viton consisting of suction and pressure valve
D050N-50/B-13	Diaphragm metering pump D050N-50 / B-13, PVC / Viton, for FeCl3 mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D050N-50 / B-13 Dosing amount: 0 - 49 l / h Max. Operating pressure: 10 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy
D100N-70/B-13	Diaphragm metering pump D100N-70 / B-13, PVC / Viton, for Polyelectrolyte mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-13 Dosing amount: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 10 kg
FM50N-50/B-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / B-12 DV Dosing amount: 0 - 47 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP

	Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 IT
FM50N-50/D-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h Max. Operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D100N-70/B-11, SS/Viton	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-11 Dosing amount: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316 Membrane: PTFE coated Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 12 kg
B125N-12/C-43 DV	Diaphragm metering pump hydraulically linked diaphragm metering pump with manual stroke length adjustment 0-100% Type: B125N-12 / C-43 DV Dosing amount: 0 - 7.4 l / h max.operating pressure: 10 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
Diaphragm, ø65 / 50, PTFE, for B125N-12 / C-43	Membrane
FM50N-50/B-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / B-12 DV Dosing amount: 0 - 47 l / h max.operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy
Diaphragm	Membrane with support plate, ø50mm. for FM50N-50
Membrane with support plate, ø50mm. for FM50N-50	
Valve set, AC5-31, PP / Viton	consisting of suction and pressure valve
Valve set, AC13-13, PVC / Viton	for D100N-90 / B-13
FM50N-50/B-12	mechanically driven diaphragm metering pumps with manual Stroke length adjustment 0-100% Type: FM50N-50 / B-12 Dosing amount: 0 - 47 l / h max.operating pressure: 5 bar Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Weight:

	approx 8 kg Customs tariff number: 84135040 Country of manufacture: Italy
Membrane with support plate, ø30mm.	for D050N-30 / F-12
D100N-90/B-13 TN	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 13kg
Piston, ø89, ceramic, for A250	
Piston, ø89, ceramic, for A350	
Gearbox 250	Gearbox A250, without motor, without pump head, with pump holder and motor bell
Gearbox 350	Gearbox A350, without motor, without pump head, with pump holder and motor bell
A125N-11/C-11 DV	Piston metering pump directly linked piston metering pump with manual stroke length adjustment 0-100% Type: A125N-11 / C-11 DV Dosing amount: 0 - 6 l / h max.operating pressure: 20 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
D100N-90/B-13 TN	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 10 kg / 13k
Typ: D100N-70/C-12 DV TN	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Dosing amount: 0 - 146 l / h max.operating pressure: bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 10 kg
D=100N-90/B-13TN	Q=27-330 litre/hours Pmax= 5 bar Power= 0.18 Kvt
	Piston metering pump directly linked piston metering pump with manual stroke length adjustment 0-100%, High pressure version Type: A125N-12 / C-77 DV Dosing amount: 0 - 7.2 l / h max.operating pressure: 88 bar Stroke frequency: 96

A125N-12/C-77 DV	strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Piston: ceramic Piston packing: PTFE engg Valves: SS316L Valve seals: PTFE or similar Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 8 kg / 11 kg
D101N-120/C-11	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D101N-120 / C-11 Dosing amount: 0 - 334 l / h max.operating pressure: 3 bar Stroke frequency: 96 strokes / min Connection: 1 "external thread Material: Pump head: SS316L Membrane: PTFE coated Valves: SS316L Valve seals: Viton Motor: 0.37 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D100N-120/F-13	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-120 / F-11 Dosing quantity: 0 - 219 l / h max.operating pressure: 1.5 bar Stroke frequency: 58 strokes / min Connection: 1 "external thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D050N-50/C-11 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D050N-50 / C-11 DV Dosing amount: 0 - 39 l / h max.operating pressure: 10 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Membrane: PTFE coated Valves: SS316L Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
D100N-70/B12 DVTN	
Piston packing set, ø89mm, Viton, for A250N	2 x packing rings, 1 x wiper Material resistance must be checked by the customer before ordering Push rod, item 208, for A250N Spring, for adjustment, item 213, for A250N Scale, item 225, adhesive picture, for A250N Spring, for gear, item 226, for A250N
Piston packing set, ø89mm, Viton, for A350N	2 x packing rings, 1 x wiper Material resistance must be checked by the customer before ordering. Push rod, item 208, for A350N Spring, for adjustment, item 213, for A350N Scale, item 225, sticker, for A350N Spring, for gear, item 226, for A350N
Pos.3 A250NandA350N	Piston packing set, ø89mm, Viton, for A250N and A350N 2 x packing rings Material resistance must be checked by the customer before ordering.
Pos.10 A250NandA350N	Wiper, ø89mm
Push rod, item 208, for A250N	
Spring, for gear, item 226, for A250N	
Push rod, item 208, for A350N	
Spring, for gear, item 226, for A350N	
Adjustment, complete, for A250	Item 210, 211, 212, 213, 221, 222, 225, 263

A350N ADJUSTMENT LEVER	Adjustment, complete, for A350 Item 210, 211, 212, 213, 221, 222, 225, 263,
NN HOSE	Suitable for Ragazzini Psf1 Pump
A175N-38/C-34 Piston metering pump	directly linked piston metering pump with manual stroke length adjustment 0-100%, High pressure version Type: A175N-38 / C-34 Dosing amount: 0 - 115 l / h max.operating pressure: 13 bar Stroke frequency: 96 strokes / min Connection: 1/2 "male thread Material: Pump head: SS316L Piston: SS316L Piston packing: EPDM Valves: SS316L Valve seals: EPDM Motor: 0.25kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
FM50N-50/D-12 DV	Diaphragm metering pump mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h max.operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55 Customs tariff number: 84135040 Country of origin: Italy Weight, net / gross: 4.5 kg / 6 kg
Motor - 230V - Hp 0,75	Degree of protect - IP54 Flow rate 102 l/min Tank capacity - 40l Pressure - 1,8bar High circulation pump for descaling, cleaning and power lushing traditional and underfloor heating systems. Ergonomic and easy to handle. Fitted with flow reverser. With cleaning powder.
D100N-90/B-13	
D-100N-90/B-13TN	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-90 / B-13 TN Dosing quantity: 0 - 271 l / h max.operating pressure: 3 bar Stroke frequency: 120 strokes / min Connection: 3/4 "male thread Material: Pump head: PVC Membrane: PTFE coated Valves: PVC Valve seals: Viton Motor: 0.18 kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
FM50N-50/D-12 DV	mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: FM50N-50 / D-12 DV Dosing amount: 0 - 34 l / h max.operating pressure: 5 bar Stroke frequency: 82 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP / PVC Valve seals: Viton Motor: 0.09kW, 3ph, 230 / 400V, 50Hz, 4 poles, IP55
Piston packing set	Piston packing set, ø76mm, NBR, for A250N, item 3 + 10 2 x packing rings and 1 x wiper
D100N-70/C-12 DV TN	Diaphragm metering pump D100N-70 / C-12 DV TN, PP / Viton mechanically driven diaphragm metering pump with manual stroke length adjustment 0-100% Type: D100N-70 / C-12 DV TN Dosing amount: 0 - 146 l / h max.operating pressure: bar Stroke frequency: 116 strokes / min Connection: 1/2 "male thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55

D0B07010122N1AA00	Diaphragm dosing pump D-100N-70/B-12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
Valve set, AC13-13	Valve set, AC13-13, PVC / Viton, for D101N-90 / B-13 TN consisting of suction and pressure valve
Diaphragm for D100N-70/B-12 DVTN	Diaphragm with support plate, ø70, for D100N-70/B-12 DVTN
AP A-125N-16/C-82 DV	AP A-125N-16/C-82 DV SPRING RETURN - PLUNGER DOSING PUMP
Diaphragm for D100N-90/B-13 TN	Diaphragm with support plate, ø90, for D100N-90/B-13 TN
D121N-120/B13 - 230400V 50/60Hz - 3phase	
FM50N-50/B12 - 230/400V 50/60Hz - 3pahse	
D100N-70/C12	230/400V 50/60Hz - 3pahse
A250N ADJUSTMENT LEVER-Doseuro to A350n-A250n	
A350N ADJUSTMENT LEVER-Doseuro to A350n-A250n	
OIL LEVEL INDICATOR-Doseuro will be suitable for	A350n-A250n.
27MM*35*MM*7MM PRESSURE SEAL-It will be suitable	for Doseuro A350n-A250n.
OIL FILLING DRAIN PLUG - It Will Be Suitable For	Doseuro A350n-A250n.
D100N-70/F13 DV	Dosing Pump
KIT0MS00700000000	Membran + Schild KIT
KIT0MS01200000000	Membran + Schild KIT
D100N-70/B12	
KIT0MS00900000000	Diaphragm and diaphragm shield (pos. 20+22) for pump D100N, article number KIT0MS00900000000
D100N-70/B12 DV	
AC00000022000M020	DOSEURO SUCTION CHECK VALVE AC-22/20N BODY PVC, BALL SS316, O-RING FPM 1" FOR D121N-120/B 13 PUMP (POLYMER DOSAGE) Set consisting of suction and pressure valve
KIT0MS01200000000.	DOSEURO DIAPHRAGM AND DIAPHRAGM PROTECTION D.120 P. 20 + P. 22, FOR PTFE/NBR D121N-120/B 13 PUMP
A125N-12/C-77 DV.	Model Description : Piston metering pump

A125N-30/B20	<p>Chemical to dose: CHLORINE WATER Cl₂ + H₂O Max Chem. Temp (°C): 40 Working Pressure (Barg): 2.00 Max Viscosity (Cps): -1.00 Suction Pressure (Barg): N.A. Ambient Temperature: (-20 / +40) °C ΔP (Barg): 2.00 Req. Capacity (Lt/h): 60.00 Model: A125N-30/B-20 Mechanism Type: SPRING RETURN Max Capacity (Lt/h):62 @50Hz Pump Type: Plunger Stroke per minutes: 116 @50Hz Max Pressure (Barg): 14.00 Metal, 10.00 Plastic Stroke length (mm): 12.50 Adjustment: Manual 0 - 100% of stroke length Connection: 1/2" BSPPm Diaphragm Ø (mm): N.A. Valve Type: Double ball Plunger Ø (mm):30 Pump Area: SAFE AREA PUMP HEAD PVC DIAPHRAGM N.A. BALL VALVE* PYREX PLUNGER S.S.316L PLUNGER GASKET NBR VALVE O-RING FPM * for pump with valve size 1 INCHES - ball valve is in PTFE Power Supply:3PH - TRI-PHASE 4 POLES Area: SAFE AREA Protection:IP55 Insulation Class:F Installed Power: 0,18KW Voltage: 400.00 Frequency: 50 HZ Inverter Use: NO</p>
A250N-64/C19	
A175N-38/C19	
FM050N-50B-12	<p>Filtered Level Floater Type: Float with Filter Supply: 24 V DC Signal: 4-20 Ma Model: Axial Inner Coating: Plastic</p>
Dosing pump D100N-70/C12	
FM050N-50/D12	
FM050N-50/F-03	
FM050N-50/F-12	
D100N-105/C-12	
D100N-120/I-23	
SDI-175-12/B-05 DV	<p>E.motor 0,25 KW 3Ph 4 Poli IP 55 Cl. F 400-440V 50-60Hz Size 71 B14 IE2 KIT PRESSURE GAUGE INOX 0-16 BAR</p>
Diaphragm Dosing Pump with Electric Motor SR Serie	<p>SDI-175-12/B-05 DV Type or Name of Liquid: BELGARD EV 2050-100% V/V</p>
Diaphragm Dosing Pump with Electric Motor SR Serie	<p>Model: SDI-175-12/B-05 DV Type or Name of Liquid: BELITE M8-5-7% V/V</p>
D0C09010111N1AA00	<p>type: PUMP D-101N-90/B-11 - - TN 4/3PH-230/400/50/60 SPRING RETURN - MECHANICAL DIAPHRAGM DOSING PUMP required capacity: N.S. l/h max: 271 l/h required pressure: N.S. bar max: 5 bar</p>
AC13/14 Valve	<p>item number AC00000013000M014 (AC 13/14 N (PVC + PYREX + FPM) in ¾" suitable for D100N-90/B13) Both valves are included in the valve set, i.e. suction and pressure side.</p>
CHECK VALVE UNDERSET.	<p>For dosing pump with code d-100n-90/b-13</p>
D100N-70/B12	<p>Diaphragm dosing pump</p>

D 101 N 408 L//sa	
D 100 N 374 L//sa	
D 101 N 408 L//sa	
D 100 N 374 L//sa	
D 100 N 374 L//sa	
D 101 N 408 L//sa	
D 100 N 374 L//sa	
D 101 N 408 L//sa	
D 101 N 408 L//sa	
D 100 N 374 L//sa	
A125N-25/B-20	Execution: 20 PUMP HEAD PVC PLUNGERS S.S.316L PLUNGER GASKET NBR VALVE SEAT PVC VALVE BALL PYREX VALVE GASKET FPM Please check the execution. In the best case, tell us the operating points or the materials.
SUCTION CHECK VALVE AC-13/14N	Art. Nr. AC00000013000M014
SUCTION CHECK VALVE AC-13/14N,	Art. Nr. AC00000013000M014
STAFSJÖ WB DN150 PN10/16 NBR	Manual Knife Valve
Piston dosing pump A125N-25/I-11 with servomotor	4-20 mA
Mechanical dosing pump D-050N-50/C-23 DV	
BTM0D000700081P13	PP pump head
KIT0MS00700000000	Membran
6115145778477	Expansion Tank LR119079046S
FM050N-50/B-11 340/400V 50/60Hz	
KIT0MS00300000000	membrane+membrane shield
A250N-89/C37	piston pump
PRESSURE CHECK VALVE D70/12 AC-8/31N	
SUCTION CHECK VALVE D70/12 AC-8/31N	
ACD0000008000M031	Suction and discharge valve SET AC8/31,
EDI0S006350000G02	Piston Gasket set d64 in FPM
A-125N-11/B13	piston dosing pump

D121N-120/F13	diaphragm dosing pump
RELIEF VALVE VSC-10/43 PVC	VS000000100000043
PISTON GASKETS SET G10-8 P7-8	
S.S.420 PISTON D.14	
PISTON GASKET SET G10-14 P7-14	
CERAMIC PISTON D.8 WITH GRAINS 6X8	
D-121N-120/B-13 - 4/3PH-230/400/50/60	D0I1201013111AA00
Diaphragm dosing pump FM-50N-50/B12 DV, 230/400V	50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 47l/h - max. pressure 5 bar - 1/2" BSP male connection
D-101N-90/B-13	TN 4/3PH-230/400/50/60 D0C09010131N1AA00
FM050N-50/B-12 DV	F0B050301221AA05
D-101N-105/B-13 - - - 4/3PH-230/400/50/60	D0C1051013111AA00
D-101N-70/C-11	TN 4/3PH-230/400/50/60
D-101N-105/B-13	4/3PH-230/400/50/60
A175	Ball check valve part located in the inlet and outlet line of A175 piston dosing pump
KIT0MS01050000000	Membrane with support plate, ø105mm, Pos.20+22
Suction and pressure valve AC13/14 (PVC+PYREX+FPM)	
A125N-8/B-32 DV	
PUMP D-101N-90/B-12 - - TN 4/3PH-230/400/50/60	D0C09010121N1AA00
SUCTION/DELIVERY VALVE SET AC-13/14N G/M	AC00000013000M014
SUCTION/DELIVERY VALVE SET AC-13/31N	AC00000013000M031
SK10MS00+0205	SCL K10MS TMS BPA MOR IE3 M.E. Gr.132 - 11kW - 13kW 660-720/380-415V 50Hz 760-830/440-480V 60HzIE3 - ATEX 3GD - IP65 - CL. F - TROP. PTO - PAINTED - ANOD.+IMPR.+V.INOX II 3GD - Ex h IIC T3 Gc - Ex h IIIC T200°C Dc
PUMP A-250N-89/B-20 - - 4/3PH-230/400/50/60	A0H0891020111AA00
FM050N-50/B-12 DV, 230/400V 50/60Hz	

A0E01620822111110	AP A125N-16/C-82 DV, 1PH SINGLE-PHASE 4 POLES 230V IP55 50 HZ
PUMP AI-350-89/A-13, 400V 50 Hz 1.1 KW, IP55	Eexd II C T4 with ABB Motor Atex Zone 2G T4 IOL08940111110201
DOB09010131N1AA00	Diaphragm metering pump D-100N-90/B-13, 230/400V 50/60Hz in PVC version with 0-100% manual Stroke length adjustment. - max. dosing rate 271 l/h - max. pressure 3 bar - 3/4" BSP male connection
D-100N-90/B-13, 230/400V 50/60Hz	D0B09010131N1AA00 in PVC version with 0-100% manual Stroke length adjustment. - max. dosing rate 271 l/h - max. pressure 3 bar - 3/4" BSP male connection
B0H0752043111AA00	PUMP B-250N-75/C-43 - -- 4/3PH-230/400/50/60
KIT0R001750000000	GEAR BOX O-RING KIT FOR 175N/D-101N/D-121N Pos 219;220;221;222;235;263
EDR00050150000G02	O-RING GASKET 50 X 1,5 FPM Pos. 7
D0C07010122N1AA00	Membrandosierpumpe D101N-70/B12 DV, 230/400V 50/60Hz, in PP version with 0-100% manual Stroke length adjustment. - max. dosing rate 159 l/h - max. pressure 10 bar - 1/2" BSP male connection
ACD0000008000M031	Ventil-Set AC 8/31N DV (PP+PYREX+FPM)
KIT0MS009000000000	Membrane with support plate, ø90mm, Pos.20+22
KIT0MS012000000000	Membrane with support plate, ø120mm, Pos.20+22
KIT0MS007000000000	Membrane with support plate, ø70mm, Pos.20+22
AC00000013000M014	SUCTION/DELIVERY VALVE SET AC-13/14N G/M
AC00000022000M014	SUCTION/DELIVERY VALVE SET AC-22/14N G/M
AAP00001000000L01	CRANK SHAFT D-100N
ZZZ	ASS000R1010001006 - Push-rod support
ASL00001010000X05	PUSH ROD D-100-101-121N
AMN0C001750000P03 - Adjustment knob (complete)	
AC00000022000M014	SUCTION/DELIVERY VALVE SET AC-22/14N G/M
AC00000022000M014	SUCTION/DELIVERY VALVE SET AC-22/14N G/M
AAP00001210000L01	SHAFT D121N
ASS000R1010001006 - push rod support	
ASL00001010000X05	PUSH ROD D-100-101-121N
ZZZ	AMN0C001750000P03 - Adjustment knob (complete)

BTM0D001200220P01	Pump head in PVC for D-series size 120
ALT0D001200000A05	HEAD LANTERN D.120 FOR D PUMP
ACD0000008000M014	Suction and pressure valve AC-8/14 DV (PVC/PYREX/FPM)
ACD0000008000M014	Suction and pressure valve AC-8/14 DV (PVC/PYREX/FPM)
AAP00001000000L01	CRANK SHAFT D-100N
ASS00001250001A06	PUSH ROD BEARING 125-175N 100N ZAMA
ASL00001010000X05	PUSH ROD D-100-101-121N
AMN0C001700000P03	COMPLET KNOB 50-125-175-101N
BTM0D000700081P01	PVC D.70 PUMP HEAD FOR D PUMP (8holes)
ALT0D000700000P02	HEAD LANTERN D.70 FOR D PUMP
DOB07020122N1AA00	Diaphragm metering pump D100N-70/C12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. metering rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
DOB07020122N1AA00	Membrandosierpumpe D100N-70/C12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
BTM0D001200220P01	Pump head in PVC for D-series size 120
KIT0MS01200000000	Membrane with support plate, ø120mm, Pos.20+22
DOI1201013111AA00	Diaphragm metering pump D121N-120/B13, 230/400V 50/60Hz, in PVC version with 0-100% manual stroke length adjustment. - max. metering rate 570 l/h - max. pressure 5 bar - 1" BSPm connection
DOB07010122N1AA00	Diaphragm metering pump D100N-70/B12 DV, 230/400V 50/60Hz, in PP version with 0-100% manual stroke length adjustment. - max. metering rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
DOC09010131N1AA00	PUMP D-101N-90/B-13 - - TN 4/3PH-230/400/50/60
PUMP A-125N-14/F-32 DV	4/3PH-230/400/50/60 A0E0143032211AA00
PUMP D-101N-105/B-13 - - - 4/3PH-230/400/50/60	D0C1051013111AA00
DOA0501012211AA00	Membrandosierpumpe D050N-50/B12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 49 l/h - max. pressure 10 bar - 1/2" BSP male connection
DOA0505012211AA00	Membrandosierpumpe D050N-50/I12 DV, 230/400V 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 14 l/h - max. pressure 10 bar - 1/2" BSP male connection

KIT0MS00500000000	Membrane with support plate, ø50mm, Pos.20+22
ACD0000005000M031	Suction and pressure valve AC-5/31 DV (PP/PYREX/FPM) G1/2" male
Suction and pressure valve AC-5/31 DV (PP/PYREX/FPM)	G1/2" male ACD0000005000M031
D-100N-90B-13 TN 271 LT	
PUMP SDI-350-130/B-03 - 230/400V 50/60Hz 2,2 kW	
Pulsation damper PVC with a volume of 6Lt and 1 1/2" connection	
Pulsation damper PVC with a volume of 10Lt and 2" connection	
DCAL0550020001P01	Calibration cylinder CP55 G.2" PVC/TFM/GLASS
WESVS000500000143	pressure control valves VSC 50/43
PUMP SDI-350-120/B-05 - 400V 50Hz 2,2kW	M0L12010051110400
KIT0MS00900000000 - Pos 1	For Pump D-101N-90/B-11
ALT0D000900000P02	Membrane with support plate, ø90mm, Pos.20+22 Pos. 2
EVRG0001750110000	HEAD LANTERN D.90 FOR D PUMP (8 HOLES) Pos. 3
ESM00016240050G01	ENDLESS SCREW/WORM WHEEL GROUP T.1/11,5 175-101N Pos. 4
EVRG0001250120000	For Pump D-100N-70/C-12 DVTN: Pos. 5 ENDLESS SCREW/WORM WHEEL GROUP T.1/12 125N
Diaphragm metering pump D100N-70/B12 DV, 230/400V	50/60Hz, in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
Diaphragm metering pump D100N-70/C12 DV, 230/400V	50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
FM-50N-50/B12 DV, 230/400V	diaphragm metering pump 50/60Hz in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 47l/h - max. pressure 5 bar - 1/2" BSP male connection
A0S0472034111AA10	PUMP AP A 175T 47 C 34 4/3PH 230/400/50/60
PUMP D-100N-105/B-13 - - 4/3PH-230/400/50/60	D0B1051013111AA00
SUCTION/DELIVERY VALVE SET AC-13/14N G/M-	AC00000013000M014
Diaphragm Pump D-100N-90/B-13	

D0B07010122N1AA00	Diaphragm metering pump D100N-70/B12 DV, 230/400V 50/60Hz, in PP version with 0-100% manual Stroke length adjustment. - max. dosing rate 176 l/h - max. pressure 5 bar - 1/2" BSP male connection
D0B07020122N1AA00	Diaphragm metering pump D100N-70/C12 DV, 230/400V 50/60Hz in PP version with 0-100% manual Stroke length adjustment. - max. dosing rate 146 l/h - max. pressure 5 bar - 1/2" BSP male connection
Membrane with support plate ø120mm, PTFE/NBR, for	D101N-120/B-11
A-125N-11/C-11 DV	Piston dosing pump 1 x directly coupled piston dosing pump with manual stroke length adjustment 0-100% Type: A-125N-11/C-11 DV Dosage: 0 - 6 l/h max. operating pressure: 20 bar Stroke frequency: 96 strokes/min Connection: 1/2" external thread Material: Pump head: SS316 Piston: SS316 Piston packing: NBR Valves: SS316 Valve seals: Viton Motor: 0.18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
Dosing chemicals with pumps with 0.01 ml precision	1) Formula: CuSO4 5H2O Molecular weight: 249.68 g/mol CAS No.: 7758-99-8 EC No.: 231-847-6- solution 2) Sodium hydroxide pellets for analysis EMSURE® Product Number / SDS No. : 1.06498 Index No.: 011-002-00-6 CAS No.: 1310-73-2 solution 3) 95%-97% sulfuric acid 4) Chromotropic acid disodium salt dihydrate GR for analysis ACS, Reag. Ph Eur Product Number / SDS No. : 1.02498 Catalog/SDS No.: 102498 CAS No.: 5808-22-0 solution
D-101N-120/B-13	Valve set AC22-13, PVC/Viton consisting of suction and pressure valve
E-800/4 MP	0.09 (1PH) 940rpm, PP
D100N-70/B-12	Doseuro membrane dosing pump 230/400V Art. DEU-PMP-1222 Motor: 0.18 kW, 3-phase, 230/400V (+/- 10%), 50-60Hz, IP55 0-176 l/h, 5 bar, PP head, seals: FKM/Viton, connection: 1/2"
2xD122N-160/A-23	230V 50Hz with Rapida
Membrane with support plate ø70mm, PTFE/NBR, for D100N-70	
Spring (Pos.226)	
D-100N-70/B-12 DV, 230/400V 50/60Hz	D0B07010122N1AA00 mechanically driven diaphragm dosing pump with manual stroke length adjustment 0-100% Type: D100N-70 / B-12 Dosage: 0 - 176 l / h Max. Operating pressure: 5 bar Stroke frequency: 116 strokes / min Connection: 1/2 "external thread Material: Pump head: PP Membrane: PTFE coated Valves: PP Valve seals: Viton Motor: 0.18kW, 3ph, 230 / 400V, 50Hz, 4-pole, IP55
D101n-90/B13	
A0e25m3011v11aa00	

Metering Pump Doseuro Typ A250n-89/B-19	1 x plunger pump with manual stroke length adjustment 0-100% Type: A250N-89/B-19 Capacity: 0 - 1042 l/h max. pressure: 4,8 bar stroke frequency: 112 strokes/min connection: 1" male thread Material: Pumphead: SS316L Plunger: SS316L Plunger packing: Viton Valves: SS316L Valve gaskets: Viton Motor: 0,55kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
Type : D-101n - 120/B 11	
Push Rod Gasket (Pos.223)	
D101N-70/B12 DV, 230/400V	diaphragm metering pump 50/60Hz, in PP version with 0-100% manual stroke length adjustment. - max. dosing rate 159 l/h - max. pressure 10 bar - 1/2" BSP male connection
D- 105/90 Ptfe/ Nbr	Diyafram For this pump (B-175N-40/c)
Set Of Endless Screw (Pos.205) And Worm Wheel (Pos.206), For Model A250	
Metering Pump Doseuro Typ A125n-14/F-33	plunger dosing pump type DOSEURO A125N-14/F-33 with manual stroke length adjustment 0-100% Capacity: 6 l/h Max. operating pressure : 65 bar Strokes frequency : 58 strokes/min Connection: 1/2" BSP male Material : Pumphead: SS316 Plunger: SS420 Plunger packing: PTFE Valves: SS316 Valve gaskets: PTFE Motor: 0,18kW, 3ph, 230/400V, 50Hz, 4 poles, IP55
206- Worm Wheel	
A-125n-11/C-19	
Flexible Coupling (Pos. 209/1/2/3)	
209/2- Flexible Insert	
Key, 5 X 5 X 20mm (Pos.227)	
Fm50-50/B-12	Metering Pump Doseuro mechanical diaphragm dosing pump with manual stroke length adjustment 0-100% Type: DOSEURO FM50-50/B-12 Capacity: 47 l/h Max. operating pressure : 5 bar Strokes frequency : 116 strokes/min Connection: 1/2" BSP male Material : Pumphead: PP Diaphragm: PTFE coated Valves: PP Valve gaskets: Viton Motor: 0,09kW, 3ph, 230/400V, 50Hz, 4 poles, IP65
209/3- Flexible Coupling (Top)	
Dosing Pump D-101n-70b-11 Tn Membranes	2 MEMBRANES FOR PUMPS THAT DİSTRİBUTE SOLUTION TO FURNACE