

Duk

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Duk Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Duk Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
BTD2	
FSL-LHPw-10/3-L50V	
LHP-10/2-L50	
Conveyor Belt Misalignment (offtrack) Switch, type LHPE-10/1-L50	1 contact NC + 1 contact NO @ approx. 15° displacement of lever, each 230VAC 8A Double ball-bearing stainless-steel roller lever Ø50mm Thick walled fibre glass reinforced polyester housing IP67 yellow
LHPE-10/2EX-R	
LHPE-10/2-L50V	
LHPE-10/2-L50V-S	
LHPE-18/2-R2	
LHPEw-10/1-B	
LHPEw-10/1-BSL	
LHPEw-10/1-BSR	
LHPEw-18/1-B	
LHP-EX1010-L50	
LHP-EX12-L50-S	
LHPw-16/1-B	
LHPw-EX21-B-S	
SZN-LHPEw-10/2-B	
SZN-PEW-NOX-S1100- B08-NNN	

Ürün	Açıklama
Rotation speed monitor type Al-Ni8	trip speed 120rpm up to 6000rpm equipped with monostable relays also as spare part for overspeed switches series ZGF and ZGL, motion controls type FW heavy duty, saline worthy, anodized aluminium housing IP67
LHPEw-10/1-B-S	Pull cord switch.
Pull cord switch, type SNS22	single side pull cord max. 25m length 2 contacts NC, each lth 10A, AC15 230 V 3 A Metal housing IP67, pullcord to the right
Conveyor Belt Misalignment (offtrack) Switch, type LHPE-10/2-L50V-EX	approved for use in ATEX-Zone 22, group II, category 3D 1 contact NC + 1 contact NO @ approx. 7° displacement of lever and 1 contact NC + 1 contact NO @ approx. 15°, each 230VAC 8A Double ball-bearing stainless-steel roller lever Ø50mm Thick walled fibre glass reinforced polyester housing IP67 black
Pull Cord Switch, type LHPEw-10/2-B-EX	approved for use in ATEX-Zone 22, group II, category 3D 2 contacts NC + 2 contacts NO, each 230VAC 8A Thick walled fibre glass reinforced polyester housing IP67 black
Squence Switch Lm	
R677 25d 471520	
Lhp-10/4-R2	
Lhpe-10/2-R2	
Zgl3 - 1/25	
Typ Spf-W	
Typ Sh7	
Typ RI5f	
Lhpew-10/2-L50v	
Lhpew-10/1 -Bru-S Oem For *Vvv Most	
Zgl3-1/16	
Zgl3-1/40	
Lhpew-10/1-B-S Oem	
Lhpew-10/2-B	