Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Dunkermotoren

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz. **Dunkermotoren** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Dunkermotoren Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
88439.02360 Gr 53x58	SNR: 8843902360 24VDC 3000 rpm. IN 2,9A PLG 52 8885101752
Sg80k	
88442d1270	typ:GR63X55
E1at1s12-1	24V DC MOTOR ,REDUKTOR UND ENCODER MOTOR: GR63X55 REDUKTOR: SG120 İ=30/1 ENCODER: RE20-2-100 (Lieferung in Montierten zustand)
Gr65x55	(Neu anschaffung)
BG62SX60	
GR63X55	
88437 07503	
88442 02560	Gr63X55 24volt 3350rpm 4.9 Amper
88710 05090	
G30.2 - 12V	
88444.05920 GR 63x55	DC-Motor Antrieb (GR63) Nominal voltage 24 V CE marked motor No. Nominal current 4.90 A UL mark No. Rated speed 3,350 rpm Rated power 94.70 W. Insulation class E (120 ° C) Operating mode S1 (continuous) IP protection IP50 shaft AS diameter 5.0 mm AS shaft length 20.0 mm 88851.03011 PLG 52 Reduction 28.125 nominal torque at the output 800 Ncm Number of levels 2 IP protection IP50 IP protection IP50 output shaft diameter 12.0 mm Output shaft length 25.0 mm Lubricant standard grease A
88427.02201 GR 42x40	92427.00000 DC motor drive (GR42 Nominal voltage 40 V CE marked motor No. UL mark Yes Nominal speed 3,400 rpm Interference suppression Description 2L nominal power 20.30 W. Insulation class E (120 ° C) Operating mode S1

	(continuous) IP protection IP50 shaft AS diameter 5.0 mm AS shaft length 45.0 mm
8843902360	24VDC 3000 rpm. IN 2,9A
8854507000	
88442.07155 GR 63x55	U 60V / 3350 rpm / IN2 A 99 4 0206603 / 24*99
8885701920	
88544.06000 BG 44x50 SI	BG motor drive (BG44) Nomenclature number: 85013100 88544.06000 BG 44x50 SI Nomenclature number: 85013100 Nominal voltage 24 V CE marked motor Yes Nominal current 2.52 A UL mark No. Rated speed 3,440 rpm Rated power 36.70 W. Insulation class E (120 ° C) Operating mode S1 (continuous) IP protection IP40 shaft AS diameter 6.0 mm AS shaft length 20.0 mm 88711.05202 cover Nomenclature number: 76042990 Aluminum cover, without seal for size 42, size 45
27573 40660	
27573 35695	
27573 40650	
92808.00000	Accessories / gears 27573.40660 Z_KABEL KPL BG75 3000 G POWER 4POL Commodity number: 85444290 3 m cable with 4-pin connector plug, for power supply for BG 75 Hall/SI/PI/CI/PB/EC/MI 27573.35695 Z_KABEL KPL BG65 6000 G WD 6POL PHG Commodity number: 85444290 6 m cable with 6-pin connector, non-rotatable, for signals or Brake for RE 30, RE 56, E90, E300 27573.40650 Z_KABEL KPL BG75 3000 G 12POL AMPH Commodity number: 85444290 3 m cable with 12-pin connector, rotatable, for signals and logic supply for BG 75 SI/PI/CI/PB/EC/MI
27573.35695	Z_KABEL KPL BG65 6000 G WD 6POL PHG 6 m cable with 6-pin connector, non-rotatable, for signals or Brake for RE 30, RE 56, E90, E300
27573.40650	Z_KABEL KPL BG75 3000 G 12POL AMPH 3 m cable with 12-pin connector, rotatable, for signals and Logic supply for BG 75 SI/PI/CI/PB/EC/MI
27573.40660	Z_KABEL KPL BG75 3000 G POWER 4POL 3 m cable with 4-pin connector plug, for power supply for BG 75 Hall/SI/PI/CI/PB/EC/MI
Typ: D249	
DR52.0X60-2/SG80	
DR52.1X60-2/SPEZIAL	
88437.01044 GR 53x30	Rated voltage 24 V CE mark motor no Rated current 2.30 A UL mark Yes Rated speed 3,600 rpm Rated power 37.70 W Insulation class E (120°C) Operating mode S1 (continuous) IP protection class IP50 Shaft AS diameter 6.0 mm Shaft AS

	length 20.0 mm
ST-34	
BG 62x60 88562.01980	
TYP ;GR 53X58 , 24 V DC , 3000 rpm , 2,9 A ,05/15	REDUCER PLG52 M 800 Ncm İ 20.25 :1
BG75X25PI+2XPLG75	
GR63*25 24V DUNKER WL1 LEFT SET	
PLG52	
Typ : GR 63x25	SNR: 8844303590 U24 V+- 3300 rpm N 2,7A BG1CL.F 8871004960 RE30-2-100 M : Ncm i: 1
8885102292	
DSY62.1x60-4	
KD 62.1X60-4	9W 230V i=64 rated speed 20,3 1/min rated torque3,58 Nm
DR62.1X60-4	14W 400V i=64 rated speed 18,8 1/min rated torque 5,81 Nm
TYP GR63X25	
GR42x25	
BG62X60 U 40V	88562 3530rpm 50/10 3,9a 55A
GR 53X15	SNR 88437 04270
8844207250	
BG 42X15 dCore, 8854201100	
PLG 52 EB, 8885107044	
RE30, 8871004721	
8844203280	
92565.00000 BG motor drive (BG65)	Product status: Product release 88565.05499 BG 65x50 SI Product status: Product release Statistical commodity number: 85013100 Rated voltage 24 V CE Mark Motor Yes Rated current 5.20 A UL mark cULus Rated speed 2,950 rpm Rated power 80.00 W Insulation class E (120°C) Operating mode S1 (duration) IP protection class IP50 Shaft AS diameter 5.0 mm Shaft AS length 20.0 mm Weight 1,430kg 29000.02096 Firmware BGE65 SI Product status: Product release Statistical commodity number: 85423261 88711.05200 Cover ZB25 Statistical commodity number: 76042990 Aluminum sealing lid, without seal for BG 65 27579.89250 Nameplate standard DC motor / CCC Product status: Product release Statistical commodity number: 39191080

88565 05488 8856302450	
8871006506	
crankshaft, connecting piece and bearing	
GR 63x55	1/30 REDUCER ENCODER BRUSH DC MOTOR SET
RE-20	1/30 REDUCER ENCODER BRUSH DC MOTOR SET
8844208395	
8885101761	
8844201262	
BG65x50 SI	
5018082599	
8843803120	
Gr 63x55	88442.03280
8842702201	
PLG 63LN 88863 01505-MN:12	
SNR88566 01121	
BG 65X25 SI+ 2142DF27-1	
BG 65X25 SI+2142DF28-1	
PLG52-8885102292	
PLG 52	8851 01761, 39/21, 800Nc i: 28,125:1 ONLY GEARBOX
i: 28,125:1	
88565.05499 BG 65X50 / 24V / AS 5x20 / SI-ST12	
88851.01761 PLG 52 / 28,125:1 / Ø12 / 25	
29000.02096 Firmware BGE65 SI	
88711.05200 LID / BG65+BG65	
Gr80?80+plg63+re30-3-500ti	
Plg 75sp	
Gr 22 / Plg 24 (88402.01923)	
88851 01760	

Kd 62.1x60 4 (88139.03056) Kunden-Matnr.92139.00000	
96955.01559	
Plg75	
Gr63x25 S/N: 8844301100 Oem	
8882401007	
88565-05077	GEAR MOTOR 5.6AMP 3090RPM 8:1RATIO 24VDC
Gr63ã215;55+sg80+re-20	
Plg52 88851 01610	
Bg 65x50 Si	SNR: 8856505499
Gr42x25 886164-003	
96183.00382 Kddr 62_0 / Plg 75ln	88183.03350 DR 62.0x60 2 Statistical commodity code: 85015100 Rated voltage I 400 V Rated voltage II 230 V Frequency I 50 Hz Frequency II 60 Hz Rated speed I 2,600 rpm Circuit star / delta Rated power I 65.0 W Number of poles 2 Operating mode Continuous. Insulation class F (155 ° C) Thermal switch No Degree of protection Motor DIN EN 60034 IP54 Shaft AS Diameter 8.0 mm Shaft AS Length 25.0 mm 88875.01511 PLG 75LN Statistical commodity number: 84834021 Reduction 23,100 Nominal torque at output 3,000 Ncm Number of stages 2 Degree of protection IP52 Output shaft diameter 19.0 mm Output shaft length 49.0 mm Bearing Bearings Lubricant Grease Standard A
88711.07080 Re30-2-500	
D554	
88183.03129 Dr 62.0x80 2	
Gr-53x58-Re-30-2-500	MOTOR W/ENCODER 24V
Type Gr63*55 Snr:8844208253	U 20 V 3300 RPM IN 5,6A Motor - Type : GR63*55 SNR:8844208253
84834021	
R561025m01	MOTOR DC BRUSHLESS BG62X60 3530RPM 55AMP
27577.05074	
Gr80?80+plg75+re30-3-500ti	
88427 01937	
88851-02380	
000000065547100102	
Gr63x25 Snr 88442-07093 For Assa Abloy	

Sn: 8844208395 Gr63x55	
060801 Replaced By D259 Motor	
18005411150	
Gr-63x55 Motor	
88851-01664	
Gr42x40-24v	
4172370	
Gr 53x58	
Plg52h	MOTOR
D839 Art Nr. 96955.01525	Statistical commodity code: 85014020 88955.01894 D839 Statistical commodity code: 85014020 Rated voltage 230 V UL mark No Rated frequency 50 Hz VDE mark Yes Degree of protection motor DIN EN 60034 IP54 rated speed 23 rpm Connection length (motor) 500 mm Nominal torque 9.5 Nm Output 6K7 rated power consumption 218 W Direction of rotation R / L Right CCC capable Yes
Sgf 120 B14	
8emo120	
Gr53x58	8843703214 with PLG52 S/N 88438
Snr 88440 03798 Typ Gr 63x55 Obsolete Replaced By 92440.00000	
Type 88710.04560	
96565 01052 - Bg 65	
Typ Gr 80x40 Snr 8844803153	
Plg24,81,2:1	
Typ Gr42x25, Snr 88427 01780	
Gr63x55 M. Adapter	
92808.00000 Rs200	
49797.59620	
88442.03280 Gr 63x55	DC motor drive (GR63) Nomenclature number: 85013100 Rated voltage 48 V CE-marked motor No. Nominal current 2.50 A UL mark Yes Nominal speed 3,200 rpm Nominal power 94.10 W. Insulation class E (120 ° C) Operating mode S1 (duration) Protection class motor DIN EN 60034 IP50 shaft AS diameter 8.0 mm Shaft AS length 25.0 mm Shaft NS diameter 8.0 mm Shaft NS length 15.0 mm

Gr53x58 U 24 V 5002778820	
Sg80k 88842 08006	
Gearbox For Gr 53x30 Snr 8843901372 Oem!!	
Gr42x25	SNR 88427 01006 Beachten Sie bitte den Anhang
Plg52, 88851 02981	
Gr-63x55+sg80+plg52	MOTOR 24VDC 3350RPM W/SG80 GEAR AND PLG72 GEAR
88184.05999	
88119 01448 Motor	
85013100	
Plg 75ln	88875.01523 gearbox Statistical commodity code: 84834021 Reduction 29,400 Nominal torque at the output 2,400 Ncm Number of stages 2 Degree of protection IP52 Degree of protection IP52 Output shaft diameter 19.0 mm Output shaft length 49.0 mm Bearing output shaft ball bearing Lubricant grease standard A
3 Meter 12 Pin Kabel	
Dc Motor Drive (Gr80)	Statistical commodity code: 85013100 88445.01721 GR 80x80 Statistical commodity code: 85013100 Rated voltage 24 V CE mark motor No Rated current 10.00 A UL mark Yes Rated speed 3,200 rpm nominal power 214,00 W Insulation class E (120 ° C) operating mode S1 (duration) Degree of protection Motor DIN EN 60034 IP50 Shaft AS Diameter 6.0 mm Shaft AS Length 25.0 mm Shaft NS Diameter -5.0 mm Shaft NS length -10,0 mm 88875.01523 PLG 75LN Statistical commodity code: 84834021 Reduction 29,400 Nominal torque at the output 2,400 Ncm Number of stages 2 Degree of protection IP52 Degree of protection IP52 Output shaft diameter 19.0 mm Output shaft length 49.0 mm Bearing output shaft ball bearing Lubricant grease standard A
Tbx3806-Es-D-Cd5-Tz	SERVO MOTOR MAGNETIC TUBE
3 Meter 6 Pin Kabel	
91110.99999	
Gre53x58	MOTOR
Typ Gr 63x55 U 40 V= Snr 88440 03793	
Bg 62x30	88562 01930
8629.61.0.01.448	
88438 02061	

Bg65x75	SERVO MOTOR W/ENCODER AND CABLE
Gr53x30 50v - Oem	
88442-01192	
Dr62.0x60/2asto-90°-Ad320-52164	
92544.00000	
88442.01201 Gr63x25	
Dr621x30-2-Asto+plg52h	
8071000000	
Gr 63x55 Snr 88442 07193 Oem	
88442 0260	
Plg32	
080418 Obsolete Replaced By D839	
1322696a	
88850-01107	GEAR MOTOR .45AMP 24VDC 50:1 RATIO
Gr-42x40 + Re-30-2-500 + Sg62	
Bg62x30	STRAPPING MACHINE CIRCLE UNLOADING ENGINE
Plg52-8885102292	
88851-02236	
88183-03037	
92808.00000 (27573.35584+27573.35531)	
Gr63x55custom	MOTOR
61.144.1141/01	
Bg65x25si	SNR: 88565 04482
Bg65x50si	
91500.00002	
Me 7747	
Dr620x602	
88437.02004	
S3m219	
Dunkermotoren-Gr-42x25-8842701006-F3;R-Sachnummer-8885102335-	

Istanbul-Turkiye	
Gr42x40-Snr8842702994+sg62/8884301440	
Gr63x25 Snr 88442 07093 33/12	SIEHE ANHANG
8844101867	
88851 01763 - Plg 52	
92437.00000	DC-Motor Antrieb (GR53) Statistical commodity code: 85013100 88439.02309 GR 53x58 not safety compliant Statistical commodity code: 85013100 Rated voltage 180 V CE mark motor Yes UL mark Yes Rated speed 3,400 rpm Rated power 60,50 W Insulation class E (120 ° C) Operating mode S1 (duration) Degree of protection Motor DIN EN 60034 IP50 Shaft AS Diameter 6.0 mm Shaft AS Length 45.0 mm Shaft NS Diameter 5.0 mm Shaft NS Length 15.0 mm 88843.04030 SG 62 Statistical commodity code: 84834025 Reduction 8,000 rated torque at output 150 Ncm Shaft position 1 - left Protection class IP54 Output shaft diameter 8.0 mm Output shaft length 25.0 mm Bearings Gear Bearings Lubricant Grease Standard C 88710.04822 RE 30-2-100 Statistical commodity number: 90328900 Encoder Supply voltage 5 V Encoder Impulse 100 Encoder channels 2 Connection mounting plug Hood No for engine GR53
Plg32 88856 01161	
Dr621x30-2-Asto	
92445.00000	
Plg 52 1:288	
27573 35 566	
88184.03032	
Gr53x58884370290	MOTOR
Plg52 88851 02927	
03040-608x60	
27577 05092	
Bg65x75si+sg120	BG65X75SI MOTOR SG120 GEARBOX
Plg52_ Article Code Gearbox: 8885101613	
	92565.00000 BG-Motor Antrieb (BG65) Statistical commodity code: 85013100 88565.05497 BG 65x50 SI Statistical commodity code: 85013100 Rated voltage 24 V CE mark motor Yes Rated current 5.20 A UL mark Yes Rated speed 2,950 rpm Rated power 80,00 W Insulation class E (120 ° C) operating mode S1 (duration) Degree of protection motor DIN EN 60034 IP50 Shaft AS Diameter 8.0 mm Shaft AS length

88565.05497	55.0 mm 88842.03788 SG 80 Statistical commodity code: 84834025 Reduction 38,000 Rated torque at output 350 Ncm Shaft position 1 - left Protection class IP54 Degree of protection IP54 Output shaft diameter 10.0 mm Output shaft length 30,0 mm bearing output shaft ball bearing Lubricant grease standard C 29000.02001 Firmware BGE65 SI Statistical commodity code: 85423261 88711.05200 Cover ZB25 Statistical commodity code: 85030099 Aluminum cover, without seal for BG 65 27573.35530 Z_KABEL KPL BG65 3000 G WD 12POL AMPH Statistical commodity code: 85444290 3 m cable with 12-pi
Gr63x55	88852 88442 24 V DC MOTOR Reduzierverhältnis: 15
Plg52	
Gr 63x25 For Assa Abloy	
8629-61-0-02-448	
92440.00000 Dc-Motor Antrieb (Gr63)	88442.03100 GR 63x55 Statistical commodity number: 90328900 Rated voltage 24 V CE mark motor No Rated current 4.90 A UL mark Yes Rated speed 3,350 rpm rated power 94.70 W Insulation class E (120 ° C) operating mode S1 (duration) Degree of protection motor DIN EN 60034 IP50 Shaft AS Diameter 8.0 mm Shaft AS Length 55.0 mm Shaft NS Diameter 8.0 mm Shaft NS length 15.0 mm 88842.01961 SG 80K Statistical commodity number: 90328900 Reduction 15,000 rated torque at output 350 Ncm Shaft position 1 - left Protection class IP40 Degree of protection IP40 Output shaft diameter 10.0 mm Output shaft length 30,0 mm bearing gear bearings Lubricant grease standard B 88710.05500 RE 20S-2-100 Statistical commodity number: 90328900 Encoder Supply voltage 5 V Encoder Impulse 100 Driver Voltage 5 V Encoder Channels 2 Connection Extension Plug Hood No for engine GR63
3-Meter-4-Pin-Stromkabel	
92437 00000	
Gr 80x80	
Gr42x25-Plg42s-Tg11	MOTOR 15W 24VDC W/ PLG42S GEARBOX TG11 ENCODER
Plg52 _ Article Code Gearbox: 8885101610	
92427.00000 (G42x25+plg42s)	
Gr42x40	SERVO MOTOR 24AMP 12V
080418 Obsolete Replaced By D839 Electric Motor D314	
Typ: Dr62.0x80-2 Snr: 88183 03069	
Pl630 88615 06632 3500 Upm 0.21a Oem	

Typ: Gr 63x25 By 88442.03010 Gr 63x25	
88615 06630 Replaced By 88615.06530	
Gr 53x58 Snr 8843802044 Oem	
91400.00006	
92808.00000 (Zubehã246;Rteile / Getriebe)	
91150.99999	
623533509	
Type 88442.03120	
27577.05092	
88119 01448	
42x25	
Typ Gr53x58 Snr 8843703214	
Sg80 88842 02747	
Gr 53x30 Snr 8843901372 Oem!!	
88851 02753 - Plg52	
Gr63x25 W/Gearbox Plg63	
Dr62.0x60/2asto-Ad8320-52164	
Sts2510s-S-R05x-Br	SERVO MOTOR MAGNETIC TUBE
27573.35531	
91500.00001	
Bg62x60	MOTOR BRUSHLESS 93AMP 3380RPM 24VDC
(Gr63) 92440.00000 Dc-Motor Antrieb	
88843 01443 Obsolere Replaced By 88843.04004	
88442.01285 Gr 63x55	
88710.04815 Re30-2-500	
Me 3408	Motor 60 V / DC brushed Country of origin DE Net weight Pos / KG: 1.2000
Gr22,24v (8840201104) , Gr 22 / Plg 24 (88402.01923)	
88565.04140	
Gr63x25 Nr 88442 02361	

Yursat Dış Tic. Münendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
+90 224 2400304
info@yursat.com.tr
www.yursat.com.tr

Typ Gr 53x30 Snr 88437 01281	
Obsolete (Sachnummer 88632 01006 - G42x25) Possible Replacement (Sachnummer 88851.02335gr - 42x25)	
88710 04817	
88632 01006 - G42x25	
92427.00000	
88851.01752	
92805.00000	
88442.01211 Gr 63x25.	
Bg65x75s1	SERVO MOTOR W/ENCODER AND CABLE [3000RPM]