

Dynafor

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Dynafor Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Dynafor Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
GZ-293359	DYNAFOR Expert 10T Tensile force measuring device Load capacity: 10 t - Measuring step: 2 kg - Measurement tolerance: 0.1 kg - Accuracy 0.1% - Protection class: IP64 (optionally also in IP 67 (extra charge)) - Operating temperature: -20 to +50°C - Complies with Directives 2006/42/EC and 2014/53/EU (RED) - Net weight: 6.45 kg - Features: Bluetooth up to a range of 30 m to any Smartphone/tablet with free Dynafor app (for Android/IOS: dynafor - Load Cell Monitoring) - Scope of delivery: - Setting certificate - 1 set of batteries - CE certificate - Operating instructions - Plastic case - Free APP for Android/IOS - Optionally available: HHD display, matching shackles/hooks
GZ-293399	DYNAFOR Pro 15T Tensile force measuring device - Load capacity: 15 t - Measuring step: 5 kg - Measurement tolerance: 0.2 kg - Accuracy 0.2% - Protection class: IP 64 (optionally also in IP 67 (but with surcharge)) - Operating temperature: -20 to +50°C - Complies with Directives 2006/42/EC and 2014/53/EU (RED) - Weight: 3.66 kg - Features: Bluetooth up to a range of 30 m to any smartphone/tablet with free Dynafor app (for Android/IOS: dynafor - Load Cell Monitoring) - Scope of delivery: - Setting

	certificate - 1 set of batteries - CE certificate - Operating instructions - Plastic case - Free APP for Android/IOS
GZ-293609	Dynafor HHD Kit (Display) (Sold only together with Dynafor device) Features: - Number of sensors at the input: max. 4 - Material of the display unit: ABS V0 - Frequency technology: 2.4GHz 2.4835GHz proprietary - Range: Up to 400 m in the open air - Radio frequency output power: 9.5 dBm - Protection class: IP65 - Batteries: Rechargeable battery, ENIX, LP906090 6,000mAh, 3.7V - Operating temperature: - 20° to +50° C - Weight: approx. 0.45 kg - Dimensions without/with bumper: 149.3/152.5 x 95.3/105 x 26.6/40 mm Scope of delivery: - HD display - Protective case (silicone bumper) - USB charger with EU adapters (British and American) - USB-C to USB-A charging cable - Instructions for use
ANALOG_0-5000 KG	