Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ecodora

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Ecodora Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ecodora Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
6321 261/11	Automatic hose reel closed plastic housing For compressed air and cold water incl. 11m 8 x 12mm polyurethane hose Pressure: max. 20 bar Gasket: Viton Swivel: Brass Arrangement case: horizontal deduction by hand Temperature: +5°C to +40°C Weight: 6.0kg Customs tariff number: 8479 8997 Country of origin: EU-IT
4430/40	(PR-NEWL 4448 GOLD LB BMMC NL) Automatic hose reel, plastic/sheet steel Pressure: max.: 150 bar Arrangement case: horizontal deduction by hand Connection thread Inlet 1/2" Outlet 1/2" for oil, antifreeze and related media Winding length: up to 15m 1/2" -without hose-
6321 540/10	Automatic hose reel with spring return and locking Material: sheet steel - powder-coated Colour: black / yellow RAL 1004 Plain bearing: TENAXID (maintenance-free) Bracket: floor, wall and ceiling mounting Roller window: 3 different setting options Medium: compressed air - cold water Pressure: max. 20 bar Swivel: Brass (KG325) Gasket: Viton Connection Inlet IT 1", Outlet IT 1" Winding length: 20m with an outer diameter of 27mm (3/4") 15m with outer ø 34mm (1")

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	including hose stopper including drilling template without hose
Pneumatic piston pump S. 600, R 3:1 - 14 l/min, with NBR	Seals, bung adapter, and 940 mm intake hose. 180÷220 kg Compression ratio 3:1 Flow rate 14 l/min Compatible fluids Oils, lubricants and the like Motor housing aluminum Intake manifold carbon steel Air supply connection G 1/4" (f) Fluid outlet connection G 1/2" (f) Operating pressure 6÷8 bar Average air consumption 330 l/min Noise level 81 dB Max. viscosity of the oil to be dispensed 130 SAE Barrel ring included standard Suitable for drums or tanks suitable for drums 180÷220 kg

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.