

Econex

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Econex** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Econex Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
B1c2v2-S	Electric actuator AB1C2132-S 230V/50-60Hz - 30s/90° - 3 Nm - pot. 1 kohm - 2 aux. micro - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AB1C2132-S 230V/50-60Hz 30s/90° - 3 Nm - pot. 1 kohm - 2 micro aux. - Auto/Man
Vsar240c	Solenoid valve VSAR240C 1.1/2" 230V/50-60Hz - quick - aluminium - Pmax. 200 mbar - HC 84818099 - Origin EC Elettrovalvola VSAR240C 1.1/2" 230V/50-60Hz Rapida - alluminio - Pmax. 200 mbar
0292.X0003	Solenoid valve VSBR215C - 230V/50-60Hz - quick - brass - Pmax 200mbar - Rp 1/2 HC 84818099 Origin EC
VSAR340C 1.1/2"	Solenoid Valve 230V/50-60Hz - quick - aluminium - Pmax 360mbar 84818099
AB1C3130-S	Econex actuator Type: AB1C3130-S Positioning time: 60s / 90 ° Torque: 5Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Manual / auto operation - 1k ohm potentiometer
AB1C3000-S	Econex actuator Type: AB1C3000-S Positioning time: 60s / 90 ° Torque: 5Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Hand / auto operation
AR2C3150-SM	Econex actuator Type: AR2C3150-SM Positioning time: 60 (50) s / 90 ° Torque: 20Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Bourns potentiometer, 2.5kOhm - Hand / auto operation
	Econex actuator Type: AR2C3130- S18 / S Positioning time: 120s / 180 °

AR2C3130- S18 / S	Torque: 20 Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Hand / auto operation - 1kOhm potentiometer . HC 85011010 Origin EC
AR2C3002 - S	Econex actuator Positioning time: 60 s / 90 ° Torque: 20Nm Ambient temperature: -10 ° to + 60 ° C Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Manual / auto operation - two auxiliary switches
AR2C3132 - S	Econex actuator Type: AR2C3132 - S Positioning time: 60s / 90 ° Torque: 20 Nm Ambient temperature: -10 ° to + 60 ° C Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Manual / auto operation - 1kOhm pot - two auxiliary switches
AR2A2002-SE8	Econex actuator Positioning time: 30s / 90 ° Torque: 15 Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 24V, 50 (60) Hz Setpoint input: 0 (4) to 20mA Setpoint output: 0 (4) to 20mA - manual / auto operation - 2 auxiliary switches
AR2C3130- S	Econex actuator Positioning time: 60s / 90 ° Torque: 20 Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Manual / auto operation - 1kOhm potentiometer . HC 85011010
VSAR350C	Solenoid valve 0292.X0003 - DN50 - 230V/50 - quick - aluminium - Pmax 360mbar HC 84818099 Origin EC Ursprungsland: Italien
CN0045	0292.X9000 Connector with rectifier - - 110V - 220V - Pmax. 200 - 360 mbar For (VSA, VAB, VSC 1/2" - 3/4"
AR2C3130-S18/S	Positioning time: 120s / 180 ° Torque: 20Nm Duty cycle: 100% Degree of protection: IP65 Ambient temperature: -10 ° to + 50 ° C Voltage: 230V, 50 (60) Hz - Hand / auto operation - 1 kOhm potentiometer
VSBR215B	Econex Safety Shut-Off Valve in brass Operation : Quick Max. Pressure : 200mbar Nominal Diameter : Rp 1/2 Supply Voltage : 110V AC 50-60Hz
AB1C3002-S	Econex actuator Positioning time: 60s / 90 ° Torque: 5Nm Ambient temperature: -10 ° to + 60 ° C Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Manual / auto operation - two auxiliary switches . HC 85011010 Origin EC
AR2C3130- S	Econex actuator Positioning time: 60s / 90 ° Torque: 20 Nm Duty cycle: 100% Degree of protection: IP54 Voltage: 230V, 50 (60) Hz - Manual / auto operation - 1kOhm potentiometer . HC 85011010
0292.X9000	Econex Pressure Switch Type : PE500 Range : 100 - 500 mbar P.Max : 1000 mbar Net Weight in kg : 0,15 HC 90322000 Origin Extra EC
SWITCH PE050 2.5-50MBAR	
VSAR340C	Solenoid valve - DN40 - 230V/50-60Hz - quick - aluminium - Pmax 360mbar HC 84818099
VSARP350C	Solenoid gas valve - DN50 - 230V/50-60Hz - quick - aluminium - Pmax 360mbar - max. flow adjustment
0080.X9000	
0292.X0006	
0292.X0009	
0292.X9001	
A2B3V2-S	
A2C3V0-S	
A2C3V0-S18/S	
AB1A2002-SE5/C	

AB1B3002	
AB1C0002-S	
AG8A202-SE2	
AR2B2132-S	
AR2-B-3150S	
AR2B3152-S	
AR2C/A2002-SE5	
AR2C/A3002-SE5F4	
AR2C2002-S	
AR2C3000	
B1B302-S	
B1B3Y2-S	
B1C/A202-SE5	
B1C/A302-SE5	
B1C3V2-S	
B1C3VV2-SO	
BFV DN 65 300 MBAR O 10 MM	
0292.X9000	Econex Butterfly BFV100/80 flanged valve DN100 reduced to DN80 - with free shaft
BFV150/100.B	
BFV80.B	
BS19PD1C300-S	
BS25PD1C3V2-S	
CE-0085AQ0738	
DF8	
FE640/50	
GD3-100	
GD6 V/V DN125	
GD6-100	
KGM8	
LTF112-RQ95A8	
S02-50DC3V2-S	
SVB08A09A01	
SVB-13	
VSAR225C	
VSAR250C	

VSO 40 = Rp 1.1/2"	
VSO320CM	
VSO325CM	
BFV125.B	Econex Butterfly flanged valve DN125 0292.X9000 - with free shaft - Pmax. 500mbar
BFV100.B	Econex Butterfly flanged valve DN100 with free shaft
AB1C3132-S	Econex actuator Type : AB1C3132-S Torque : 5Nm Duty cycle : 100% Degree of protection : IP54 Voltage : 230V, 50 (60) Hz - Hand/Auto operation - 1kOhm pot - two path auxiliary switches . . HC85011010
AB1C3180-S/S2	Econex actuator Actuating time : 60s/90° Torque : 5 Nm Duty cycle: 100% Degree of protection : IP54 Voltage : 230V, 50(60)Hz - Hand/Auto operation - 1kOhm Spectrol
0292.X0009	Gas pressure switch PE150 Range 30-150 mbar Pmax.500 mbar
AR2B3002-S	0292.X9001 Econex actuator Actuating time : 60(50)s/90° Torque : 20Nm Duty cycle: 100% Degree of protection : IP54 Voltage : 115V, 50(60)Hz - 2 additional microswitches - Hand/Auto operation
AB1C3130-S	Econex actuator Actuating time: 60s / 90° Torque : 5Nm Duty cycle : 100% Degree of protection : IP54 Voltage : 230V, 50 (60)Hz - Hand/Auto operation - 1k ohm pot 85011010 IT
AR2C3130- S18	Stellzeit : 120s/180° Drehmoment : 20 Nm Einschaltdauer: 100% Schutzart : IP54 Spannung : 230V, 50(60)Hz - Hand/Auto-Betrieb - 1kOhm Poti
VSAR6050C	Solenoid valve VSAR6050C 2" 230V/50-60Hz - quick - P.max 6 bar - HC 84818099 - Origin IT
VSAR225C	Solenoid gas valve VSAR225C 1" 230V/50-60Hz - quick - alluminium - Pmax 200 mbar - HC 84818099 - Origin IT
VSARP515C	Solenoid gas valve VSAR215C 1/2" 230V/50-60Hz - quick - alluminium - Pmax. 200 mbar - HC 84818099 - Origin IT
VSO325C	Solenoid vent valve VSO325C 1" 230V/50-60Hz - alum - Pmax 360 mbar - NO - HC 84818099 - Origin IT
VSAR215C	Solenoid gas valve VSAR215C 1/2" 230V/50-60Hz - quick - alluminium - Pmax. 200 mbar - HC 84818099 - Origin IT
0292.X9001	Econex Actuator Type : AB1C3132-SO Torque : 5Nm Actuating time : 60s. / 90° Duty cycle : 100% Degree of protection : IP54 Voltage : 230V, 50 (60) Hz - Hand/Auto operation - 1kOhm pot - two path auxiliary switches - Position indicator
AB1C2132-S18	0292.X9001 Actuator Actuating time : 30s/90° Torque : 3Nm Ambient temp.: -10° to +60°C Duty cycle: 100% Degree of protection : IP54 Voltage : 230V, 50(60)Hz - Hand / Auto operation - two path auxiliary switches - 1 kOhm potentiometer - 180° rotation
PE150-U	0292.X9000 Econex Gas positive & differential Pressure Switch Type : PE150-U Range : 30 - 150 mbar P.Max : 500 mbar Net Weight in kg : 0,20
0292.X9000	Econex Butterfly valve type GHD3-150 - DN 150 - for max temperature 350°C - with lever
PRESOSTAT PE15-U 30-150MB	
AR2C3130-S	Type : AR2C3130-S Actuating time : 60s/90° Torque : 20 Nm Duty cycle: 100% Degree of protection : IP54 Voltage : 230V, 50(60)Hz - Hand/Auto

0292.X0003	operation - 1kOhm pot VSBRP215C - DN15 - 230V/50-60Hz - quick - brass - Pmax 200mbar - Max flow adjustment
0292.X9000	Econex Gas Pressure Regulator RV47LM44-G Rp 1/2 - ISO 7-1, Al, Cl.B,Gr.2, EN88 2009/142/EC, CE - Tmax: 80°C - Pmax: 10 kPa
0292.X9000	Econex Pressure regulator RG/2MC 1/2" - P.max 1 bar - Range 10-28mbar
0292.X0003	Solenoid valve VSBRP215C - DN15 - 230V/50-60Hz - quick - brass - Pmax 200mbar - Max. flow adjustment
AR2C 3130-S 220V 7VA POT:1000OHM	
Type: BfV50.B	Econex Butterfly flanged valve DN50 0292.X9000 - with free shaft - Pmax. 500mbar
0292.X0010	Typ : VSAR525C 1" Voltage : 230V / 50-60Hz Pmax : 500mbar
AR2B3132-S	Actuating time: 60 s/90° Torque : 20Nm Duty cycle: 100% Degree of protection : IP65 Ambient temp.: -10+50°C Voltage : 115V ac, 50(60)Hz - Hand/Auto operation - 1kOhm pot - two path auxiliary switches 0292.X9001
AR2C3132-SA1	Torque : 20Nm Actuating time : 60s/90° Duty cycle : 100% Degree of protection : IP54 Voltage : 230V, 50 (60) Hz - Hand/Auto operation - 1kOhm pot - two path auxiliary switches - additional shaft Ø 8mm
AB1B3150-S	Actuating time : 60s/90° Torque : 5Nm Duty cycle: 100% Degree of protection : IP65 Ambient temp.: -10+50°C Voltage : 115V, 50(60)Hz - Hand/Auto operation - 2.5 kOhm pot
AB1B3152-S	Actuating time : 60s/90° Torque : 5Nm Duty cycle: 100% Degree of protection : IP65 Ambient temp.: -10+50°C Voltage : 115V, 50(60)Hz - Hand/Auto operation - 2.5 kOhm pot - 2 position auxiliary switches
AB1C2002-SO	Actuating time : 30s/90° Torque : 3Nm Duty cycle: 100% Degree of protection : IP65 Ambient temp.: -10+50°C Voltage : 230V, 50(60)Hz - Hand/Auto operation - 2 auxiliary switches - Position indicator
AG8A2002-S/S	Actuating time : 30s/90° Torque : 8 Nm Duty cycle: 100% Degree of protection : IP54 Voltage : 24VAC / VDC - 2 additional microswitches - Hand/Auto operation
AG8A2002-SE2/S	Actuating time : 30s/90° Torque : 8 Nm Duty cycle: 100% Degree of protection : IP54 Voltage : 24VAC / VDC Setpoint input : 0 (4) to 20mA or 0 to 10V transfer - 2 additional microswitches - Hand/Auto operation
AB1CA2002-SE5	Actuating time : 30s/90° Torque : 3Nm Duty cycle: 100% Degree of protection : IP65 Ambient temp.: -10+50°C Voltage : 230/24V 50/60Hz - Hand/Auto operation - 2 auxiliary switches - Input signal 4-20mA
AR2C3132-SA1	Econex actuator 0292.X9001 Torque : 20Nm Actuating time : 60s/90° Duty cycle : 100% Degree of protection : IP54 Voltage : 230V, 50 (60) Hz - Hand/Auto operation - 1kOhm pot - two path auxiliary switches - additional shaft Ø 8mm
Solenoid valve VSAR350C 2"	- 230V/50-60Hz - quick - alum. - Pmax.360 mbar
Connector CN0045	with rectifier 110V - 220V for VSA, VSB, VSC 1/2"-3/4" - Pmax. 200-360 mbar
Model-04695306	Type: AB1CA2002-SE5 Positioning time: 30s/90° Torque: 3Nm Duty cycle: 100% Protection class: IP65 Ambient temp.: -10+50°C Voltage: 230/24V 50/60Hz - Hand/Auto operation - 2 auxiliary switches - Input signal 4-20mA
Type: VSAL365C	Econex Solenoid valve - DN65 - 230V/50-60 Hz - Pmax. 360 mbar - slow - aluminium

AB1C3002-S	Type: AB1C3002-S Operating time: 60(50)s/90° Torque: 5Nm Ambient temperature: -10° to +50°C Duty cycle: 100% Protection class: IP54 Voltage: 230V, 50(60)Hz - Hand/Auto switch - two auxiliary switches
Type: VSARP515C 1/2"	Econex Solenoid gas valve 0292.X0003 - 230V/50-60Hz - Pmax. 500 mbar - quick - alum. - max flow adj
Type: VSARP515C 1/2"	Solenoid gas valve - 230V/50-60Hz - Pmax. 500 mbar - quick - alum. - max flow adj
AR2A2002-SE5F4/SI	
Econex BO-0050 Coil	0292.X9000 - 230V for solenoid valve VSB - 1/2 -3/4 - VSA..sr 1/2"
Type: AG16C4002-SE7	Econex electric Actuator - 230VAC - 90s/90° - 16Nm - IP54 - 2 micro aux. - Sign.I/O 4-20 mA/0-10 V
BO-0050 Coil	- 230V for solenoid valve VSB - 1/2 -3/4 - VSA..sr 1/2"
Gas filter FM	0292.X9000 - DN65 - flanged - P.max. 6 bar
AR2C3130-S18	Econex electric Actuator - 230V/50-60Hz - 120s/180° - 20 Nm - pot. 1 kohm - Auto/Man - 180°rotation
Type: MPV-S1	Econex Valve body - 1" - with max flow adjustment
Type: AB1C/A2002-SE5	- 230/24V 50/60Hz - 30s/90° - 3 Nm - Auto/Man - 2 aux. micro - signal 4-20mA
Type: AG16C4002-SE7	Electronic gear motor - 230VAC - 90s/90° - 16Nm - IP54 - 2 Micro aux. - Sign.I/O 4-20 mA/0-10 V
AG8C2002-SE7/H	AG8C2002-SE7/H - 230Vac - 30s/90° - 8 Nm - 2aux. micro - Auto/Man - Sign. in 4-20 mA - out 0-10V
AB1C/A2002-SE5	AB1C/A2002-SE5 - 230/24V 50/60Hz - 30s/90° - 3 Nm - Auto/Man - 2 aux. micro - signal 4-20mA
B1-66 SHN2	
AB1C2132-S	Type: AB1C2132-S Setting time: 30s/90° Torque: 3Nm Ambient temperature: -10° to +60°C Duty time: 100% Protection class: IP54 Voltage: 230V, 50(60)Hz - Manual / Auto operation - Two auxiliary position switches - 1 kOhm potentiometer
HTTRA-230-02	- 230V/50Hz for EFC1 control panel
VSAR365C	0292.X9000 - DN65 - 230V/50-60Hz - quick - aluminium - Pmax 360 mbar GAS SOLENOID VALVE, DN 65, 230 V AC, MAX PRESSURE 360 MBAR
416703 ECONEX AR2C3130-S 220VAC 1000 Ohm	
6487/00002	
AR2C3000-S	- 230V/50-60Hz - 60s/90° - 20 Nm - Auto/Man
AR2C2002 - SF4	Positioning time: 30(25)s/90° Torque: 15Nm Ambient temperature: -10° to +60°C Duty cycle: 100% Protection class: IP54 Voltage: 230V, 50(60)Hz - Manual / Auto operation - two auxiliary position switches - F4 flanges
Type: AB1C3002-S	- 230V/50-60Hz - 60s/90° - 5Nm - Auto/Man - aux. micro
BFV80.B-	- DN80 - with free shaft
25-090 Kelebek Vana	DN80 PN16 Butterfly Valve with servomotor. Price quote and delivery time are requested.

VSO1025C 1"	Econex Solenoid vent valve - 230V/50-60Hz - alum. - Pmax. 1 bar - normally open
VSCR2	230 V/50-60 Hz. Pmax: 200 mbar 20-60°C Rp: 3/8" (DN 10)
Econex Axle joint	zinc plated bore Ø 8 mm thread M8
Econex Lever	adjustable square 9,5 mm with slot [length 70,5 mm - width 8 mm] - centre to centre distance 112,5 mm - fastening with 2 M6screws
Econex Lever-	- hole Ø 10 mm with slot [length 70,5 mm - width 8 mm] -centre to centre distance 112,5 mm - fastening with 2 M6 screws
AG8C2002-SE7/H 230Vac	- 30s/90° - 8 Nm - 2 aux. micro - Auto/Man - Sign. in 4-20 mA - out 0-10V
AG16C4002-SE7/H	- 230VAC 90s/90° - 16Nm - IP54 - 2 Micro aux. - Sign.I/O 4-20 mA/0-10 V
VSARP515C 1/2"	230V/50-60Hz - Pmax. 500 mbar - quick - alum. - max flow adj
Ar2a3002	
Ma0-100	
Ce - 51bl1746	
Bfv50/32.B	
Ar2b2132-F4	
A2b202-S	Electric actuator AR2B2002-S 115V/50-60Hz - 30s - 15 Nm - 2 auxiliary micro - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AR2B2002-S 115V/50-60 Hz 30s/90° - 2 micro ausiliari
Ar2c3152 Servo Motor	
Ar2c 2002 230vac	
Arc3150-S	
AR2C3132-S	- 230V/50-60Hz - 60s/90° - 20 Nm - poti 1 kOhm - 2 aux. micro - Auto/Man
Ar2c3132-Sa1	
Vfw-100(Dgr0036qs99602)	
M1402we	
Ce-0051bp2537/Ed02(Ex0085ar0110)	
A2c3v2-S	
A2c3y0-S	Electric actuator AR2C3150-S 230V/50-60 Hz - 60s/90° - 20 Nm - potentiometer 2,5 kOhm Bourns - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AR2C3150-S 230V/50-60Hz
Butterfly Valve Kiln Pressure Å216;1000mm	
Ab1c 2002-S 220vac	
12321/C - Ab1c3002 - Air Motor	
Arc2c2002	
Ar2a2002-Se1-N	
Ar2c3132-S18	
1/8"	

Ma0-250	
Type: AB1C3132-SO	Econex electric Actuator - 230V/50-60Hz - 60s - 5 Nm - Pot. 1000 ohm - 2 aux. micro - Auto/Man - position indicator
A2b2v2-S	Electric actuator AR2B2132-S 115V/50-60Hz - 30s/90° - 15 Nm - poti 1000 ohm - 2 aux. micro - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AR2B2132-S 115V/50-60Hz 30s/90° - 1 kohm - 2 micro ausiliari
Ab1c3130-S	
Ar2b2002	
Ab1a0002-S	
Ab1c3150-So	
Svb13c15a01	SAFETY SHUT-OFF VALVES SVB SERIES
Ab1b3000	
Ar2c 3132-5	
Ar2b1002-S16	
Bfv80/80.Bdn80	
Ab1c3182-S/S2	
Ab1co132-S	
Off Electric Rotary Gear Motors, Bidirectional, Mod. Ar2c3152-S	
Ab1b0002-S	
Ab1a2002-Se5	
Ar2c3130-S18	
Cv-B166-Shn2	Valve body B1 seat 66 mm - SHN2 - Rp 2" - P.max 200 mbar - Viton seals - HC 84819000 - Origin EC Corpo valvola B1 sede 66 - SHN2 Rp 2" - P.max 200 mbar - VITON
Bfv Dn 65 300 Mbar Å216; 10 Mm	
Ar2b2002-S	
Fe 640/50	
Ar2b2132 - F4	
Ar2b3150	
Ff256	
Mrva40bnca01tt	
Bfv50p1c00000	
Ab1c3130-S 230v/50-60hz	Electric actuator AB1C3130-S 230V/50-60Hz - 60s/90° - 5 Nm - Pot. 1000 Ohm - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AB1C3130-S 230V/50-60Hz 60s/90° - 5 Nm - potenziometro 1 kOhm - Auto/Man
Ar2b3150-S Vol 110vac	
Ar2b 3150-S 110vac	

Ab1c3132-S	
Ar2c3002-S	Electric actuator AR2C3002-S 230V/50-60Hz - 60s/90° - 20 Nm - 2 aux. micro - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AR2C3002-S 230V/50-60Hz 60s/90° - 20 Nm - n. 2 micro ausiliari - Auto/Man
26200012	
Ab1a2002-Se5/C Obsolete, New Ab1a2002-Se5	
Ab1c2002	
Butterfly Valve Cooling Air Exhaust Fan Dn630	
Ab1c3130-S/C	
AB1C3000-S-	- 230V/50-60Hz - 60s/90° - 5Nm - Auto/Man
Ab1-B-3-15-0-S 115v 7va	
Ar2b2002 110vac	
Ab1c0002	
A2c3x2-Sf4	Electric actuator AR2C3182-SF4 230V/50-60Hz - 60s/90° - 20 Nm - poti 1kOhm Spectrol - n. 2 aux. micro - Auto/Man - F4 flanges - HC 85011010 - Origin EC Attuatore elettrico AR2C3182-SF4 230V/50-60Hz 60s/90° - 20 Nm - pot. 1 kohm Spectrol - 2 micro aus. - Auto/Man - flange F4
S03-120eb102-S/04800	
Vfr100	
0292.X9001	AR2C3130- S Econex actuator Actuating time : 60s/90° Torque : 20 Nm Duty cycle: 100% Degree of protection : IP54 Voltage : 230V, 50(60)Hz - Hand/Auto operation - 1kOhm pot HC85011010
Ar2c3130-S18 230v/50-60hz	Electric actuator Item code :A2C3V0-S18 AR2C3130-S18 230V/50-60Hz - 120s/180° - 20 Nm - pot. 1 kohm - Auto/Man - 180°rotation - HC 85011010 - Origin EC
B1c3v0-S	Electric actuator AB1C3130-S 230V/50-60Hz - 60s/90° - 5 Nm - Pot. 1000 Ohm - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AB1C3130-S 230V/50-60Hz 60s/90° - 5 Nm - potenziometro 1 kOhm - Auto/Man
Ma0-60	
Ar2b3132-S	
Ma0-25	
A2c3y2-S	Electric actuator AR2C3152-S 230V/50-60Hz 60s/90° - 20 Nm - pot. 2,5 kohm Bourns - 2 aux. micro - Auto/Man - HC 85011010 - Origin EC Attuatore elettrico AR2C3152-S 230V50-60Hz
Ag16c202-Se7/N	Electronic gear motor AG16C2002-SE7 230VAC 70s/90° - 16Nm - IP54 - 2 aux. micro - signal in/out 4-20 mA/0-10 V - HC 85011010 - Assembled in Swiss Attuatore elettrico AG16C2002-SE7/N 230V/AC 70s/90° - 16Nm - IP54 - 2 Micro aux. - Sign.I/O: 4-20 mA/0-10 V
Ab1b0000	
Fe240f	Filter FE240F DN40 Pmax. 2 bar - filtering 50 microm - HC 84213985 - Origin EC Filtro gas FE240F DN40 FLANGIATO P.max 2 bar 50 microm
Ar2a3002-S	
Ar2c3152-S	

[S03-120 Ac3002s](#)

[Ab1a3232so](#)

[Ab1c2002-S](#)

[Ab1c0002s](#)

[Vsarp225c \(Ex. Sva 25c25t01rp\)](#)

[Bfv40/25.B](#)

[Bsv25.P1/Ab1c3132-S](#)

[Ma0-10b](#)

[Ab1b/A2002-Se5](#)

[Construction According To En 161 Norm With
Product-Id-Number Ce-0085aq0738 Butterfly
Valve Wafer Ty](#)

[Mrva50bnct01](#)