

Eisenbau

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Eisenbau Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Eisenbau Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
GIAN0RGS2ES202S2	* MATERIAL : ALUMINIUM COPPER FREE * CABLE ENTİİİES : M20 x 1,5 N * FİİİİNG BRACKET : NOT İİİCLUDED * POSİİİİON İİİDİİİCATOR : RED CLOSED/GREEN OPEN * AMBIİİİENT : -25°C + 85°C * TERMİİİNAL STRİİİP : Nos.2 EXTRA * SWITCH TYPE : DRY CONTACT EL.MECH.SPDT * SWITCH CODE : ELECTROMECHANICAL SPDT GOLD PLATED CONTACTS SEALED MAX 16V 76mA * SPECIAL FEATURES : SIL2 * TYPE OF BOX : LSB (GI) *EX PROTECTION : ATEX / IECEX: Exia IIB/IIC Ga o Gb <(>&<)> IIIC Da,EISENBAU
GDAN0RGS2MD282	Guardbox Explosion proof Ex II 2GD Ex db IIC T6...T4 Gb Ex tb IIIC T85°C...T135°C Db ATEX IECEEx limit switch box IP66/IP68, AISI316L shaft VDI/VDE3845, independent tool free easy adjustable high resolution patent cams Box material - Copper free aluminium max 0,08 CU, corrosion inhibitor for severe environments and polyester powder coating DARK GREY colour RAL7016 (GI series blue RAL5015) Cable entries - nos.2 1/2" NPTF cable entries Fixing bracket - ISO F05 mounting pattern (fixing bracket not included) Visual ind. - V0 self extinguish and UV resistant polycarbonate dome Red (closed) and Green (open) indicator Ambient temp. - Ambient temperature -25°C/+ 85°C Extra terminal - Pre-wired PCB terminal strip with extra 2 poles terminals for solenoid valve Switch type - Magnetic proximity DPDT Switch qty - Qty 2 Switch code - (82) Hermetically sealed dry contact type, rating max 0,1A@120VAC - 1A@24VDC Special features - no special features added
GIAN0RGS2PN250S2	Guardbox Intrinsically safe Ex II(1_2)*G Ex ia IIB/IIC T6...T1 G*(a_b)_Ex II 1D Ex ia IIIC T135°C Da ATEX IECEEx limit switch box IP66/IP67, AISI316L shaft VDI/VDE3845, independent tool free easy adjustable high resolution

Ürün	Açıklama
	patent cams Material: Copper free aluminium max 0,08 CU, corrosion inhibitor for severe environments and polyester powder coating DARK GREY colour RAL7016 (GI series blue RAL5015) Cable entries: nos.2 M 20 x 1,5 Cable entries ISO F05 mounting pattern (fixing bracket not included) 3D visual indicator: V0 self extinguish and UV resistant polycarbonate dome Red (closed) and Green (open) indicator Ambient temperature range -25°C/+ 85°C Extra terminal: Pre-wired PCB terminal strip with extra 2 poles terminals for solenoid valve Sensor type: Inductive Namur proximity Switch Qty: 2 Sensor code: (50) type NJ2-V3-N nominal voltage 8,2VDC 2 wire,current measuring plate not detected >3mA detected <1mA Safety Integrity Level SIL2
GIAN0RGS2MS281	Guardbox Intrinsically safe Ex II(1_2)*G Ex ia IIB/IIC T6...T1 G*(a_b)_Ex II 1D Ex ia IIIC T135°C Da ATEX IECEx limit switch box IP66/IP67, AISI316L shaft VDI/VDE3845, independent tool free easy adjustable high resolution patent cams Material: Copper free aluminium max 0,08 CU, corrosion inhibitor for severe environments and polyester powder coating DARK GREY colour RAL7016 (GI series blue RAL5015) Cable entries: nos.2 M 20 x 1,5 Cable entries ISO F05 mounting pattern (fixing bracket not included) 3D visual indicator: V0 self extinguish and UV resistant polycarbonate dome Red (closed) and Green (open) indicator Ambient temperature range -25°C/+ 85°C Extra terminal: Pre-wired PCB terminal strip with extra 2 poles terminals for solenoid valve Switch type: Magnetic proximity SPDT Switch Qty: 2 Switch code: (81) Hermetically sealed dry contact type, rating max 0,1A@120VAC - 1A@24VDC
GDAN0RGS2ES201	Guardbox Explosion proof Ex II 2GD Ex db IIC T6...T4 Gb Ex tb IIIC T85°C...T135°C Db ATEX IECEx limit switch box IP66/IP68, AISI316L shaft

Ürün	Açıklama
	VDI/VDE3845, independent tool free easy adjustable high resolution patent cams Material: Copper free aluminum max 0.08 CU, corrosion inhibitor for severe environments and polyester powder coating DARK GRAY color RAL7016 (GI series blue RAL5015) Cable entries: nos.2 M 20 x 1.5 Cable entries ISO F05 mounting pattern (fixing bracket not include d) 3D visual indicator: V0 self extinguish and UV resistant polycarbonate dome Red (closed) and Green (open) indicators Ambient temperature range -25°C/+85°C Extra terminal: Pre-wired PCB terminal strip with extra 2 poles terminals for solenoid valve Switch type: Electromechanical switch SPDT Switch Qty: 2 Switch code: (01) Silver plated contacts, rating max 5A@250VAC - 5A@24VDC