

Elb Füllstandsgeraete

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Elb Füllstandsgeraete Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Elb Füllstandsgeraete Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
TK-312-B-0001	4102-3-0001 Evaluation device (R / I converter) TK-312 Housing: B / plug-in terminal (screwable) Input: resistance transmitter Output: 4... 20 mA Supply voltage: 24... 230V AC / DC
T-200-F-G2"-PE52-PE-V-0	T-200-F level detector for overfill protection Approval no.: Z-65.11-404 Type: T-200-F-G2 "-PE52-PE-V-0 Measuring principle: magnetic immersion probe Thread: G2 "externally adjustable Float type: 1 x PE52 Connection: polyester can LF: 500 mm Note: We recommend for the respective application a contact protection circuit to be provided.
T-202-VA 1A 60W/VA 250V	113CM
TK30015794B	5410-3-0031 Level sensor TK-300PE Type: TK300-PE-A2"10-870-10-M Connection: PE head 90 mm, red cover included PVDF cable gland Material: pipe and screw connection made of PE Float type: PE52 Electronics: TK-100 measuring transducer integrated Supply voltage: 11...35V DC Output: 4...20 mA Tube length: 870 mm Measuring length: 730 mm Resolution: 10mm
T-200-PE	
5410-3-0098	Type: TK308-PE-A1"-11-PO-400-10-M Material: PE

Ürün	Açıklama
	Connection: polyester junction box A1" with PE plate AD 150 mm, 15 mm thick, 2x6.5mm hole on bolt circle 130mm, 180 degrees offset with PVDF cable gland Float type: PE78 Electronics: TK-101 measuring transducer integrated Supply voltage: 11...35V DC Output: 4...20 mA Tube length: 400 mm Resolution: 10mm Protection class: IP65
5410-3-0099	Type: TK308-PE-A1"-11-PO-700-10-M Material: PE Connection: polyester junction box A1" with PE plate AD 150 mm, 15 mm thick, 2x6.5mm hole on bolt circle 130mm, 180 degrees offset with PVDF cable gland Float type: PE78 Electronics: TK-101 measuring transducer integrated Supply voltage: 11...35V DC Output: 4...20 mA Tube length: 700 mm Resolution: 10mm Protection class: IP65
T200PEA2"PE	
Tk-302-Rva-Vva-A 1 1/2"-0-Va44-Po-R = 1,425 Mm-10 Mm Resolution	Statistical commodity number: 90261089 Country of origin: Germany / Hesse