



E.L.B. Füllstandsgeraete

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

E.L.B. Füllstandsgeraete Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız E.L.B. Füllstandsgeraete Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
T202-Va-A11/2"-2x-09-Po	Magnetic immersion probe T202-VA Type: T202-VA-A11 / 2 "-2x-09-PO Material: stainless steel 1.4571 Connection. G1 1/2 "outside, PO box Float type: 2x VA44 Pipe length: 1,150 mm K1 = 120 mm NC above K2 = lowest point NC below Note: We recommend for the respective application to provide a contact protection circuit.
ER-104-B-2-0-1-6	Electrode relay ER-104 Housing type: B / plug-in terminal (screwable) Output: 2 changeover contacts Sensitivity: 2...30 kOhm / 2...300 kOhm Switching delay: 0.5 sec. fixed Supply: 230V AC
ER-104-B-2-0-1-0	Electrode relay ER-104 Housing type: B / plug-in terminal (screwable) Output: 2 changeover contacts Sensitivity: 2...30 kOhm / 2...300 kOhm Switching delay: 0.5 sec. fixed Supply: 24VDC
5519-3-0010	EX level sensor T-204-F for overfill protection with 3 additional contacts Registration number: Z-65.11-404 TÜV 02 ATEX 1795 X SIL2 registration No.: 44 799 13108415 Type: T204F-A11/2"-0-3-3x-09-PO Material: stainless steel 1.4571 Thread: G1/12" male

Ürün	Açıklama
	Float type: 3 x VA44 Connection: with small socket Version: with hose clamps without PTFE buffer disc LF: 1,250 mm K1 = 60 mm above (F-contact) K2 = 155 mm NE top K3 = 230 mm NE top K4 = lowest point NC bottom Note: We recommend for each application a contact protection circuit must be provided.
T200f2"v0pe	Leveler T-200-F-G2 "-PE 52-PE-V-0-PE connection housing, LF = 450 mm / "Z-65.11-404" with PVDF cable gland We recommend for the respective application a contact protection
Tk30015794b	Level transmitter TK-300-RPE PU-A2,0 "-PE52-R = 870 mm, active Measuring length 730 mm, resolution 10 mm, PE head black diameter 90 mm, cover red with PVDF cable gland with built-in R / I converter TK-100, output 4..20 mA Connection voltage 11-35 V DC Dimensions see sketch !!