



Electronicon

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin

info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Electronicon Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Electronicon Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
E90.G58-443300	3,3 kV 50 Hz 150 kVar
E56.A44-50423U	
28,2 kVar 440Vac 3x154µF K	3-phase power capacitor Type: 275.186-515400 221K02 Power: 25.0 kVar / 28.2kVar / 33.3kvar Voltage: 415 Vac / 440Vac / 480Vac / 50Hz Capacity: 3 x 154µF Dimensions: 116 x 230 mm Connection: clamp Fixing: bolt M12 Note: Attach the discharge module separately Customs tariff number: 8532 1000
E62.L95-253G10	Kondensator PE_25mF 1400DC 850AC 65x95 G1 oil BAM
E62.L95-503G10	50,0µF 1.000Vdc/640Vac 65x95 MKP AC Capacitor Capacitance: 50uF Voltage: 1,000 Vdc / 640 Vac Dimension: 65 x 95mm Connection: threaded connection
MKP 276.036 - 506610/221K02	116394 (D) Power capacitor 66 uF400-480V, 50 Hz, single phase 50x145mm, type D1, oil-filled, Double bottle plug
25kVar/ 525V	
20kVar 525V	
10 kVar 525V	
20 kVar 525V	
40 kVar 525V	
70 kVar 525V	

1010056
1020259
1030053
1030065
1051287
118900
275.100-10120
275.188-615400/221402
275.266-607700/221K02
275.288-615400/221K02
4,5?F 280Vac 25x48 K Si
9,0?F 280Vac 25x68 K Si
E12/B58 300600
E33.C68-5006/15220001
E50.R23-105NT0
E50.R29-105N10 12202
E51.L12-681R20
E62.G85-103G10 (package 1 x 21)
E62.G85-682G10
E62.L13-154G10
E62.L16-254G10
E62.N17-403C20 40uF
E62.P17-204C20
E62.R17-303C20
E62.R17-303C60
E62.R24-603C20
E62.S32-105C20
E62-C58-221E10
E63. N17-114C20
E65.P17-204C20
MKP UHD25/440 280.399-313701/221302

MKPg 275.193-516600	
E50.N13-424NT0	Kondensator f¼r Leistungselektronik PK16XC_420µF_1,1kVDC_85x136_NT_rs_NF Gewicht: 0,8kg/ Stk.
50,0µF 450Vac 45x143 U Si	motor capacitor Type: E33.F43-505025 Capacitance: 50.0uF Voltage: 450Vac Dimension: 45*143mm Connection: double flat plug Note: Cond. with overpressure protection
E33.G48-506005/220001	60.0µF 450Vac 50x148F Si AC capacitor Type: E33.G48- 506005/220001 Capacitance: 60.0uF Voltage: 450Vac Dimension: 50*148mm Connection: solder lug Note: Cond. with overpressure protection
276.078-506800/221402	
25,0 kVar 400Vac 3x166µF K	1051287 Power capacitor 3-phase Type: 275.186-516600 221K02 Power: 25.0kVar ; 30.0kVar; 36.0kvar Voltage: 400Vac ; 440Vac; 480Vac Capacitance: 3 x 166uF Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark:
275.186-515400 221K02	28,2 kVar 440Vac 3x154µF K Power capacitor 3-phase Power: 25.0kvar / 28.2kvar / 33.3kvar Voltage: 415Vac / 440Vac / 480Vac / 50Hz Capacitance: 3 x 154uF Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark: Install discharge module separately
275.100-10120	Resistance module 120kOhm for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
275.288-615400 221K02	28,2 kVar 440Vac 3x154µF K EW Power capacitor 3-phase Power: 23.2kVar ; 28.2kvar; 33.4kVar Voltage: 400Vac ; 440Vac 480Vac Capacitance: 3 x 154uF Dimension: 116*245mm Connection: terminal incl. discharge resistor Fastening: M12 bolts
E65.S23-563M30	34,4 kVar 850Vac 3x55,7µF K Art. Nr. 1051286 Power capacitor 3-phase Type: E65.S23-563M30 Power: 25.0kvar; 34.4kVar; 37.9kvar Voltage: 690Vacrms; 810Vaceff; 850Vac RMS Capacitance: 3 x 55.7uF Dimension: 136*230mm Connection: clamp Fastening: M12 bolts Remark: Gas filled Install discharge module separately
275.288-615400 221K02	28,2 kVar 440Vac 3x154µF K EW Art. Nr. 1051316 Power capacitor 3-phase Type: 275.288-615400 221K02 Power: 23.2kVar ; 28.2kvar; 33.4kVar Voltage: 400Vac ; 440Vac 480Vac Capacitance: 3 x 154uF Dimension: 116*245mm Connection: terminal incl. discharge resistor Fastening: M12 bolts Remark:
275.176-707700/221702	
275.546-703800 221K02	Leistung: 7,03kVar; 8,36kVar; 9,87kvar Spannung: 440Vac, 480Vac 525Vac / 50Hz
	Type: 265.278-707700/221K02 Leistung: 11,6kVar

20,0 kVar 525Vac 3x77µF K EW	20,0kVar 24,00kvar Spannung: 400Vac/50Hz 525Vac/50Hz 525Vac/60Hz
28,2 kVar 440Vac 3x154µF K	Leistungskondensator 3-phasig Type: 275.186-515400 221K02 Leistung: 25,0 kVar / 28,2kVar / 33,3kvar Spannung: 415 Vac / 440Vac / 480Vac / 50Hz
40µF 2.000Vdc/1.200Vac 85x176 KB	MKP AC Capacitor Type : E62.N17-403C6W Capacitance: 40uF Voltage: 2,000Vdc / 1,200Vac Dimension: 85*176mm Connection: threaded connection (M10), plastic bushing
E62G12-104G10	
275.176-707700/221702	
50kVAR- 400V- 7%	
50kVAR- 690V- 7%	
E62.G15-103D30	
3x11µF 1080Vac 75x164mm K	3-phase power capacitor Type: E62.M16-113L30 Capacity: 3 x 11.0µF Voltage: 1080Vac / 760Vac eff Dimensions: 75 x 164 mm Connection: terminal Fastening: M12 bolt Note: Install discharge module separately
E62.M16-972L30	
E62.K15-902D30	
E62.G15-902D30	
E62.H15-123D30	
E67.R31-704W40	
E59.G50-255020	
E59.G50-105010	
LA41	
E62.R23-104M30	
E62.R23-104M33	1051423 3x100,0µF 750Vac 116x230 K Power capacitor 3-phase Voltage: 750Vac / 530Vac rms Capacitance: 3 x 100µF Dimension: 116*230mm Connection: M-clamp Fastening: M12 bolts Note: Install discharge module separately
117436	E62.G12-104G10 Capacitor for power electronics 100µF 700VDC 420VAC, 50x124mm, design G1, oil filled MOQ: 105 pcs, PU: 21 pcs
28,2 kVar 440Vac 3x154µF K	Type: 275.186-515400 221K02 1051288 Power: 25.0kvar / 28.2kvar / 33.3kvar Voltage: 415Vac / 440Vac / 480Vac / 50Hz Capacitance: 3 x 154uF Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark: Install discharge module separately

Resistance module 120kOhm	for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
Resistance module 120kOhm	1059009 for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
50,0µF 700Vdc / 420Vac 45x81 U	MKP AC voltage capacitor Type: E62.F81-503D10 Capacity: 50.0µF Voltage: 700Vdc / 420Vac Dimensions: 45 x 81 mm Connection: double flat plug Remark:
E62.K85-223D10	
ECAP480334	
WHD007 400V 50KVAR	
WCK3-74K00	
14,1 kVar 440Vac 3x77µF K	Power capacitor 3-phase Type: 275.166-607700/221K02 Power: 20.0kVar; 16.7kVar; 14.1kVar; 12.5kVar Voltage: 525Vac 480Vac, 440Vac, 415Vac / 50Hz Capacity: 3 x 77µF Dimensions: 95 x 230 mm Connection: terminal Fastening: M12 bolts Note: discharge width. grow additionally
Resistance module 300kOhm	for 3-phase terminals Type: 275.100-10300 Voltage: 760Vac
252µF 1120DC 680AC 85x280 C6 oil BAM for 1ph	Passive Harmonic filter capacitor
168µF 1200DC 750AC 85x245 C6 oil BAM for 1 ph	Passive Harmonic filter capacitor
1030228	25,0µF 1.400Vdc/850Vac 65x95 G MKP AC capacitor Type: E62.L95-253G10 Capacitance: 25.0µF Voltage: 1,400 Vdc / 850 Vac / 600Vaceff Dimensions: 65 x 95 mm Connection: threaded connection
40,0µF 450Vac 45x119 U Si	AC capacitor Type: E64.F19-504025 Capacitance: 40.0µF Voltage: 450 Vaceff Dimensions: 45 x 119 mm Connection: Double flat plug Remark: Capacitor with overpressure protection
40,0µF 450Vac 45x119 U Si	AC capacitor Type: E64.F19-504025 Capacitance: 40.0µF Voltage: 450 Vaceff Dimensions: 45 x 119 mm Connection: Double flat plug Remark: Capacitor with overpressure protection
25,0 kVar 525Vac 3x96µF K	Power capacitor 3-phase Type: 275.268-609600 221K02 Power: 25.0kVar Voltage: 525Vac/50Hz Capacity: 3 x 96µF Dimensions: 95 x 245 mm Connection: terminal incl. discharge resistance Fastening: M12 bolt
420µF 1.100Vdc 85x136 G	MKP DC capacitor Type: E50.N13-424N50 Capacitance: 420µF Voltage: 1,100 Vdc Dimensions: 85 x 136 mm Connection: internal thread M6x10
	8,2 kVar 440Vac 3x154µF K EW 1051316 Power capacitor 3-phase Power: 23.2kVar; 28.2kVar; 33.4kVar Voltage: 400Vac; 440Vac 480Vac Capacity: 3 x 154µF Dimensions:

275.288-615400 221K02	116 x 245 mm Connection: terminal including discharge resistor Fastening: M12 bolt
30 kVAr 480V Tube Capacitor	
E62S24-333CR0	
28,2 kVar 440Vac 3x154µF K EW	Power capacitor 3-phase Type: 275.288-615400 221K02 Power: 23.2kVar; 28.2kVar; 33.4kVar Voltage: 400Vac; 440Vac 480Vac Capacity: 3 x 154µF Dimensions: 116 x 245 mm Connection: terminal including discharge resistor Fastening: M12 bolt
440V 12.5KVAR CYLINDRICAL TYPE THREE PHASE POWER	
440V 25KVAR CYLINDRICAL TYPE THREE PHASE POWER	
1030334	100.0µF 700Vdc/420Vac 50x124G MKP DC/AC voltage capacitor Type: E62.G12-104G10 Capacity: 100µF Voltage: 700 Vdc / 420 Vac Dimensions: 50 x 124 mm Connection: Threaded connection
E62.E58-203D10 20uF 420VAC 700VDC	
E62.E58.203D10	
GPU-CAPACITOR KP7087	
100,0µF 700Vdc/420Vac 50x124 G	MKP DC/AC capacitor Type: E62.G12-104G10 Capacity: 100µF Voltage: 700 Vdc / 420 Vac Dimensions: 50 x 124 mm Connection: threaded connection
E62.G12-104G10	CAP POL ALUMINYUM 100U 420VAC/700VDC (50X124)
E33.F19-504025/220001	CAP POL ALUMINYUM 40U 450VAC D1 PIN (45X119)
123457	E33.E93-502025/220001 capacitor ALU-P2_20µF_450-500V_40x93_2tab_oil_BAM Weight: 0.141 kg/pc, discontinued item
117436 (optional)	E62.G12-104G10 Capacitor for power electronics 100µF 700VDC 420VAC, 50x124mm, design G1, oil filled Weight: 0.300 kg/pc.
123458 (optional)	E33.F19-504025/220001 Kondensator ALU-P2_40µF_450-500V_45x119_2tab_oil_BAM Gewicht: 0,224 kg/ Stk., Auslaufartikel
115034	E62.F81-503D10 Capacitor for power electronics 50µF 700VDC / 420VAC, 45x81mm, design D1, oil-filled MOQ: 128 pcs, PU: 32 pcs, Weight: 0.14kg/pc
E62.C58-471E40	108619 Capacitor for power electronics PE_0.47uF_2800DC_1700AC_E4_oil_BAM D=30mm H=58mm
265.286-709600/221K02	MKP power capacitor MKPg_3x96µF_440-525V_116x230_L4_gas_BAM

275.186-809600/221702	
7,5 KVAR 440V CAPACITOR	CAPACITOR
5 KVAR 440V CAPACITOR	
25 KVAR 440V CAPACITOR	
10 KVAR 440V CAPACITOR	
E50.N13-424N50	Electronicon capacitor for power electronics PK16 XC - 420µF 1.10kVDC, 85x136mm, design N5, dry Technical parameters according to the catalog or data sheet MOQ: 30 pcs, Packaging unit: 10 pcs, Weight: 0.8kg/pc.
2599003	Assembly with standard cable + resistor. l= 300 mm / 40 / 9 AE Assembly: discharge resistor Cover: Cap with nozzle Cable exit: side Cable length: 300 mm Cable insulation: 40 mm stripped Cable ends: Ferrules
E62.G12-104G10	100.0µF 700Vdc/420Vac 50x124G MKP DC/AC voltage capacitor Capacity: 100µF Voltage: 700 Vdc / 420 Vac Dimensions: 50 x 124 mm Connection: Threaded connection
275.266-607700/221K02	14.1 kVar 440Vac 3x77µF K EW 3-phase power capacitor Type: 275.266-607700/221K02 Power: 11.6 kVar; 14.1 kVar; 20.0 kVar Voltage: 400Vac, 440Vac; 525Vac Capacity: 3 x 77µF Dimensions: 95 x 230 mm Connection: Terminal including discharge resistor Fastening: M12 bolt Note: incl. discharge resistor
265.286-709600 / 221K02	25.0 kVar 525Vac 3x96µF K EW 3-phase power capacitor Type: 265.286-709600 / 221K02 Power: 25.0kVar 30kVar Voltage: 525Vac/50Hz 525Vac/60Hz Capacity: 3 x 96µF Dimensions: 116 x 230 mm Connection: Terminal including discharge resistor. Fastening: M12 bolt Note: only 60Hz on the cliché
MKP 1.µF 400VAC	
1051349	20.0 kVar 400Vac 3x137µF K 3-phase power capacitor Type: 275.178-513700 221K02 Power: 20.0 kVar; 25.0 kVar; 30 kVar Voltage: 400Vac; 440Vac; 480Vac Capacity: 3 x 137µF Dimensions: 100 x 245 mm Connection: Terminal Fastening: M12 bolt Note: Attach unloading wing separately.
1051332	15.0 kVar 400Vac 3x100µF K EW 3-phase power capacitor Type: 275.258-410000 221K02 Power: 15.0 kVar; 18.2 kVar Voltage: 400Vac; 440Vac Capacity: 3 x 100µF Dimensions: 85 x 245 mm Connection: Terminal including discharge resistor Fastening: M12 bolt
1051390	10.0kVar 400Vac 3x68µF K EW 3-phase power capacitor Type: 275.548-506800/221K02 Power: 10.0kVar 12.4kvar 14.8kVar Voltage: 400Vac/50Hz 440Vac/50Hz 480Vac/50Hz Capacity: 3 x 68µF Dimensions: 75 x 245 mm Connection:

	Terminal including discharge resistor. Fastening: M12 bolt
1051275	5.0 kVar 400Vac 3x33µF K EW 3-phase power capacitor Type: 275.545-503300 221K02 Power: 5.0 kVar; 6.25 kVar; 7.2 kVar Voltage: 400Vac; 440Vac; 480Vac Capacity: 3 x 33µF Dimensions: 75 x 164 mm Connection: Terminal including discharge resistor Fastening: M12 bolt
1051280	15.0 kVar 525Vac 3x58µF K EW 3-phase power capacitor Type: 275.548-605800 221K02 Power: 8.3 kVar; 10.0 kVar; 15.0 kVar Voltage: 400Vac, 440Vac, 525Vac Capacity: 3 x 58µF Dimensions: 75 x 245 mm Connection: Terminal Fastening: M12 bolt Note: incl. discharge module
1051354	30.0 kVar 525Vac 3x115µF K 3-phase power capacitor Type: 275.186-611500/221K02 Power: 21.0 kVar / 30.0 kVar Voltage: 440Vac / 525Vac Capacity: 3 x 115µF Dimensions: 116 x 230 mm Connection: Terminal Fastening: M12 bolt
1059008	180kOhm resistor module for 3-phase terminals Type: 275.100-10180 Voltage: 600Vac
1051392	14.1 kVar 440Vac 3x77µF K EW 3-phase power capacitor Type: 275.266-607700/221K02 Power: 11.6 kVar; 14.1 kVar; 20.0 kVar Voltage: 400Vac, 440Vac; 525Vac Capacity: 3 x 77µF Dimensions: 95 x 230 mm Connection: Terminal including discharge resistor Fastening: M12 bolt Note: incl. discharge resistor
275.556-705800- Obsolete , Replaced By 15.0-275.556	
275.186-405600/221305 Mkpq Leistungskondensator 3x56µf 600-690v, Dreieckschaltung 116x230mm, Bauf	
275.186-515400 221k02 (1051288)	
478.159-6932a	
Mkpq 275.156-714410221202	
275.176-513700221502	
E51.R11-302r20	
1051140	
275.256-507700/221k02	12,5kVAr 415V QCap Type
E63.R24-105c20	
275.196-406203 221405	
Type: E50.R23-105nt0	
E06.E90-302510 220001	
275.546-506800 221502	

70cpe04175 Capacitor 120 jf	
275.548-506800/221k02	15kVAr 480V QCap
E50.N22-604nt1	
277.169-516600/221402, Obsolete Replaced By 275.186-516600 221402	
E62f10-102b20	
275.186-515400/221402	
458.259	
Ctb 6,0-440	
275.186-516600/275.100-10120(50)	
Electronicon-275186-405600221305-Mkpg- Leistungskondensator-3x56f-600-690v- Dreieckschaltung-116x230mm-Bauform-L- Gasgef3;Llt-Istanbul-Turkiye	
E62.P12-222c20	
112367	
E62.Q16-223I30	
E62. C58-502e10(1x72 Pcs.)	
275.186-405600/221K02	25.0 kVar 690Vac 3x56µF K Power capacitor 3-phase Power: 14.50kvar 25.0kvar Voltage: 525Vac 690Vac Capacitance: 3 x 56µF Dimension: 116*230mm Connection: clamp Fastening: M12 bolts Remark:
275.186-516600/221402	
275.556-508200/421102	
275.186-515400/221402 , 275.186-515400 221k02	
275.186-809600	
1056010	
E62.L95-503g10	
263.190-96400, Obsolete Replaced By E63.R24-105c20	
E50.N13-424nt0 - Dc Kondansatör -420 µf 1100 V	Kondensator PK16XC_420 µf 1,1kVDC_85x136_NT_rs_NF
E62.S32-603cr0	
275.196-616601/275.100-10120(52)	

188-615400/221402	
275.176-513700/421502	
275.156-714410 221202	
114393 Metallized Polypropylene Capacitor	
114392	
E50.N13-424nt0	
275.100-10300 Entlademodul, 3 X 300kohm Discharge Module Cct No 8533210	
15.0-275.556	
1059009	120kOhm resistor module for 3-phase terminals Type: 275.100-10120 Voltage: 480Vac
E50.N25-564nt0	
275.196-616601/275.100-10120(52) Mkpg Capagrip Capacittance 3x166 Q [kvar] At 400v 25 Dimensions 136	
275-116-510000/221502	
Elec20 525	
E62.R16-253I30	
E01.E95-302510, Alternative E06.E90-302510 220001	
276.173-502301/221108	
275.186-515400 221k02	
1030052	
275.546-506800/221k02	3x68mF 400-440V 50 Hz 75x230mm
E50.R23-175nto	
275.186-612300/221302, 112757	
E62.S23-204m30	
E62 E58 203d10	
275.186-516600/421502	
E51.R11-402r20	
265.286-709600 221k02 - Alternativ	
	MKP AC voltage capacitor Type : E62.N17-403C20 Capacity: 40µF Voltage: 2,000 Vdc / 1,200Vac Dimensions:

[40µf 2.000vdc/1.200vac 85x176 Pb](#)

85 x 176 mm Connection: threaded connection (M10),
ceramic bushing

[E50.N21-654nz0](#)