



Eletta

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Eletta Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Eletta Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Typ S2 GL25	140011025 Flow monitor with 2 adjustable switching points and analog display Medium: water Measuring range: 36 - 72 l / min Installation design / direction of flow: Please specify when ordering! Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): 0 - 90 ° C Equipped with: 2 SPDT microswitches Net weight / piece: approx. 3.5 kg
Typ S25 GL40 150011040	Flow monitor with 2 adjustable switching points and analog display Net weight / piece: approx. 4.5 kg
Typ S25 FA65 150012065	with 2 adjustable switching points and analog display Net weight / piece: approx. 7.5 kg
CM5 REDUCER OIL FLOWMETER	DIAMETER: DN50,0-6 L / MiN,
Typ SPG15	Liquid flow relay Medium: water Switching point: 25 l / min Temperature range: 0 - 90 ° C Degree of protection: IP43 Pressure: max. 25 bar
Typ S2 GL40	Flow monitor with 2 adjustable switching points and analog display Medium: Please specify when ordering! Measuring range: Please specify when ordering! Installation design / direction of flow: Please specify when ordering! Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 ° C Equipped with: 2 SPDT microswitches Net weight / piece: approx. 4.5 kg
Typ S25-GL20	Flow monitor with 2 adjustable switching points and analog display Medium: Please specify when ordering! Measuring range: 8 - 40 l / min Installation design / direction of flow: Please specify when ordering! Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 ° C Equipped with: 2 SPDT microswitches Net weight / piece: approx. 3.5 kg
	with 2 adjustable switching points and analog display

Typ S25-GL20	Medium: Please specify when ordering Measuring range: 8-40 l / min Installation design / direction of flow: please specify when ordering Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 ° C Equipped with: 2 SPDT microswitches
101011015	
111011015	
140012032R	
141012100	
150012065	
1800110151	
1800210151	
181021025	
223021025	
251014080	
31A2FSS125"2000"	
31V1GL15 "12"	
31V1GSS25 "32"	
32S25GL20 "75"	
40-50104	
8931011.0011.1XXXX	
8933023.0001.10141	
8933023.0001.11042	
8933033.0001.10142	
M310	
S2 - FA40 STROMUNGSWACHTER	
S2 - GL15	
S2 FA125 (140012125)	
S2 FA40 (140012040)	
S2 FA80 (140012080)	
S25 FA50	
S25 FA50 IP65 (151012050)	

S25-GL25 (150011025)	
S25 GL40	
S25-FA150	
S25-FA80	
S25-FSS25	
S2-FA32	
S2-GL25 -R-, IP65	
S-GL40	
SP-G 15	
TYP: SP-G 15	
V1 GL15	
V1-GL15 -R-	
V1-GL25	
V1-GL25 -R-	
S25-FA300	Flow monitor 2 adjustable switching points, analogue display Medium: Please let us know when ordering! Measuring range: Please let us know when ordering! Direction of flow/direction of installation: Please state this when ordering! Degree of protection: IP43 Pressure: max. 16 bar (PN16) Temperature range (display): -20 to +90°C Equipped with 2 SPDT microswitches
measuring head S25-GL/FA	with 2 adjustable switching points and analogue display Pressure: max. 16 bar Temperature range (display): 0 – 90°C Degree of protection: IP43
Typ M310-G25BR flow meter	Connection: G1" Medium: Please let us know when ordering! Measuring range: 12-120l/min Pressure: max. 10 bar Temperature range max. -10°C – + 100°C Degree of protection: IP67 Material pipe part: brass Material seals: NBR Power supply: 8-28V DC Output: 4-20mA
Type M310-GL40 flow meter	Connection: G11/2" Medium: Please let us know when ordering! Measuring range: 15-150l/min Pressure: max. 10 bar Temperature range max. -10°C – + 100°C Degree of protection: IP67 Material pipe part: brass Material seals: NBR Power supply: 8-28V DC Output: 4-20mA
Typ S25 FA25	flow switch with 2 adjustable switching points. and analogue display Medium: Please let us know when ordering! Measuring range: Please specify when ordering! (see enclosed measuring range list) Installation design / direction of flow: Please specify when ordering! Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches Net weight/piece: approx. 5 kg

Typ S25-FA80	flow switch with 2 adjustable switching points. and analogue display Medium: water Measuring range: 160-800 l/min Mounting style / flow direction: F/R - from bottom to top Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches . *** Total weight: approx. 24 kg ***
S25 GSS20 flow switch	Art. Nr. 150013020 with 2 adjustable switching points. and analogue display Medium: Please specify when ordering Measuring range: 4-20l/min Mounting design / direction of flow: please specify when ordering Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
V1 GL20	flow switch with 1 adjustable switching point. without sight glass Medium: Please specify when ordering Measuring range: Please specify when ordering Mounting design / direction of flow: Please specify when ordering Degree of protection: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT micro switch
40-50160	Repair Kit
S25-FA80	
Typ V1 GL15	flow switch with 1 adjustable switching point. without visual display Medium: Please let us know when ordering! Measuring range: Please specify when ordering! Installation design / direction of flow: Please specify when ordering! Degree of protection: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT micro switch Net weight/piece: approx. 3 kg
S25 FA40	flow switch with 2 adjustable switching points. and analogue display Medium: water Measuring range: 40 - 200 l/min Installation design / direction of flow: Please specify when ordering! Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches Net weight/piece: approx. 6.5 kg
S2 GL25	flow switch with 2 adjustable switching points. and analogue display Medium: water Measuring range: 24 - 48 l/min Installation design / direction of flow: Please specify when ordering! B/L or D/L or E/L Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches Net weight/piece: approx. 3.5 kg
150012032	Flow monitor type S25 FA32 with 2 adjustable switching points. and analogue display Medium: Please let us know when ordering! Measuring range: 20 - 100 l/min Installation design / direction of flow: Please specify when ordering! Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches Net weight/piece: approx. 5 kg
1800130151	Liquid flow relay SPG15, SS, EPDM Switching point: @10 l/min
1800130151	Liquid flow relay SPG15, SS, EPDM Switching point: @22 l/min

1800130151	Liquid flow relay SPG15, SS, EPDM Switching point: @5 l/min with 1 adjustable switching point. without opt. Advertisement Medium: Please specify when ordering! Measuring range: Please specify when ordering! Installation version / flow direction: Please specify when ordering! Protection class: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT microswitch
101011025	Flow monitor type V1 GL25
101011025	Flow monitor type V1 GL25 20 - 40 l/min -A/R- from left to right
101011040	Flow monitor type V1 GL40 60 - 120 l/min -B/L- from right to left
101011040	Flow monitor type V1 GL40 20 - 40 l/min -B/L- from right to left
101011040	Flow monitor type V1 GL40 40 - 80 l/min -B/L- from right to left
101011015	Flow monitor type V1 GL15 with 1 adjustable switching point without optical display Medium: please specify when ordering Measuring range: please specify when ordering Installation type / flow direction: please specify when ordering Protection class: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT micro switch
141012080	Flow monitor type S2 FA80 IP65 with 2 adjustable switching points and analogue display Medium: Please specify when ordering! Measuring range: 240 - 480 l/min Installation type / flow direction: Please specify when ordering! Protection class: IP65 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches Net weight/piece: approx. 8 kg
101011015	Flow switch type V1 GL15 with 1 adjustable switching point without optical display Medium: water Measuring range: 10 - 20 l/min Mounting design / flow direction: A (R) - from left to right Protection class: IP65 (= standard) Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT micro switch
FLOW SENSOR - FOR OIL 0.8 - 4 M³/h G1	
FLOW SENSOR - FOR OIL 7.5 - 30 M³/h G2	
FLOW SENSOR - FOR OIL 2.5 - 12.5 M³/h G2	
FLOW SENSOR - FOR OIL 8 - 40 M³/h G 2 1/2"	
	Flow switch type V1 GL15 with 1 adjustable switch point without optical display Medium: Please specify when

101011015,	ordering! Measuring range: 4 - 8 l/min Mounting type / flow direction: Please state when ordering! Protection class: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT microswitch
S2-GL25-	
SPG15, SS, EPDM	SP-G15 WATER 4 l/MIN FLOW SWITCH 1800130151 Liquid flow relay Medium: Water Switching point: 4 l/min Temperature range: 0 - 90 °C Protection class: IP43 Pressure: max. 25 bar
V1-GL15 FLOW SWITCH	
241012080	Flow monitor type D2 FA80 Protection rating: IP65 Max. process pressure: 16 bar Temperature range (display): 0 - 65 °C Analogue output: 4 - 20 mA + HART D2 (=measurement ratio 1:2)
Typ S2 FA65	with 2 adjustable switching points and analog display Medium: Please specify when ordering! Measuring range: 160 - 320 l/min Installation method / Flow direction: Please specify when ordering! Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
Typ S2 FA15	with 2 adjustable switching points and analog display Medium: Please specify when ordering! Measuring range: 6 - 12 l/min Installation method / Flow direction: Please specify when ordering! Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
140012200	Flow monitor type S2 FA200 with 2 adjustable switching points and analog display Medium: Please specify when ordering! Measuring range: 1600 - 3200 l/min Installation method / Flow direction: Please specify when ordering! Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
101011040	Flow monitor type V1 GL40 with 1 adjustable switching point, without optical display Medium: Oil Measuring range: 60 - 120 l/min Installation direction / Flow direction: A (R) - from left to right Protection rating: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT microswitch
V1 GL15	Flow monitor type V1 GL15 101011015 with 1 adjustable switching point, without visual display Medium: Please specify when ordering! Measuring range: Please specify when ordering! Installation method / Flow direction: Please specify when ordering! Protection rating: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT microswitch
S2 FA50	Flow monitor type S2 FA50 with 2 adjustable switching points and analog display Medium: Water Measuring range: 160 - 320 l/min Installation method / Flow direction: Please specify

	when ordering! Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
Typ S2 FA65	Flow monitor type S2 FA65 with 2 adjustable switching points and analog display Medium: Water Measuring range: 240 - 480 l/min Installation method / Flow direction: Please specify when ordering! Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
V1-GI15-314763	LIQUID FLOW MONITOR OIL SETTING POINT 1-2
Sp-G15	
S2gss25	
V1-GI15-253738	LIQUID FLOW MONITOR OIL SETTING POINT 3.2-6.4
52-Fss65	LIQUID FLOW MONITOR
32s25gl25	
S2-Fa80	
M310-G25br (Not Supplied Anymore)	
V1-GI15-309401	LIQUID FLOW MONITOR OIL SETTING POINT 1-2
S25-GI20á; G 3/4quot;Á; 12-75 Lt/Min Code:Mew40 Cf501	
V15-GI15-110011015r	
S2-GI20	
S2 GI20x5 253383	
Typ V15 GL15	flow switch 111011015 with 1 adjustable switching point. without opt. advertisement Medium: water Measuring range: 8 - 40 l/min Mounting design / direction of flow: Please specify when ordering! Degree of protection: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT micro switch
V1-GI20-5-10-C	LIQUID FLOW MONITOR 5-10LITERS PM
S2 - GI40 Stromungswã196;Chter	
S25 GL25	Flow monitor type S25 GL25 with 2 adjustable switching points. and analogue display Medium: water Measuring range: 10 - 50 l/min Installation design / direction of flow: Please specify when ordering! A/R or C/R or F/R Degree of protection: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches Net weight/piece: approx. 3.5 kg
S2-Fa100	
S2-Fa100 Stromungswã196;Chter	

S2 GI15	
S2-Fa 50-L	
S2-GI-25-40-80-F-Oil	FLOW SWITCH 40-80L/MIN OIL
20-40liter	
S05-Gss15	
32s25fa65	
S2-Fa40	
S25 GI20	
80/160	
S2 - Fa40 Stromungswã196;Chter	
S2-Fss50	
28-56liter	
S25-Fa100	
S25-Fa50-R	
31v1fa65	
V1-S5-220031	LIQUID FLOW MONITOR OIL SETTING RANGE 2.5-5
S25-Fa15	
S25 FA25 IP65, DR	flow switch with 2 adjustable switching points. and analogue display Medium: water Measuring range: 1.44 - 7.2 m³/h (directly readable scale) Mounting design / direction of flow: PLEASE specify when ordering! Degree of protection: IP65 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
32s25gl20 Quot;75quot;	
A2-Fa50	
S2 GL25	Flow monitor type S2 GL25 140011025 with 2 adjustable switching points and analog display Medium: Please specify when ordering! Measuring range: Please specify when ordering! Installation method / Flow direction: Please specify when ordering! Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
Baureihe 89300 Ghr-Nr. 31s2gl40	
V1-GI15-253337	LIQUID FLOW MONITOR OIL SETTING POINT 3.2-6.4
Pr1	
31s2fa50 (S2-Fa50)	

32s25gl40	
S2-GI25-60l/Min	
V1gl20-8-16l/Min.	
S25-Fss40	
Sk6610026 (Ex. -25)	
140012080	Flow monitor type S2 FA80 with 2 adjustable switching points and analog display Medium: Oil Measuring range: 240 - 480 l/min Installation method / Flow direction: Please specify exactly when ordering! A/R or F/R or C/R Protection rating: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
S25-GI20á; G 3/4quot;Á; 12-75 Lt/Min Code:Pab31 Cf101	
31v1gl25	
V1gl25-12-24/L/Min	
V1-GI15	LIQUID FLOW MONITOR 2-4L/MIN WATER
V1-GI15-253336	LIQUID FLOW MONITOR OIL SETTING POINT 3.2-6.4
S2 - GI15 Stromungswã196;Chter	
S2-Fa50	
V15-GI-15rs	
Sk6610030	
60-120liter	
S25-Fa125	
62-Fss65	LIQUID FLOW MONITOR
S25-GI15-L	
S25-Fa32	
A2fa50	
V15-GI15-110011025r	
S2 -Fa50 F/R	
V1 GL20 SG	with 1 adjustable switch and sight glass Medium: Water Measuring range: Please specify when ordering! Mounting type / flow direction: Please specify when ordering! Protection class: IP65 Pressure: max. 16 bar Temperature range (display): 0 - 90 °C Equipped with: 1 SPDT microswitch
32s25fa20	

Ekm-736-O-Cn-Sw	
S25-Fa40	
A15-GI25-171011025rnz	
S25 GI15	
M325-G20br	
S25-Gss25	
V1gl25	
31v1fa50	
V1-S5-220020	LIQUID FLOW MONITOR OIL SETTING RANGE 2.5-5
S25-Fss50	
S2 FA65	with 2 adjustable switching points and analog display Medium: Water Measuring range: 160-320 l/min Mounting type / flow direction: please specify Protection class: IP43 Pressure: max. 16 bar Temperature range (display): -20 to 90 °C Equipped with: 2 SPDT microswitches
31a2fss125quot;2000quot;	
S25-GI-25 6-30 Lpm At 16 Bar	
S2-GL40	1/2"60-120L/DAK
S25-GI-25 12-60 Lpm At 16 Bar	
S25-GI20á; G 3/4quot;Á; 12-75 Lt/Min Code:Mes10 Cf111	
S25-GI15-L-	
S2 - GI25	
31v1gl20	
V1-GI15-253739	LIQUID FLOW MONITOR OIL SETTING POINT 3.2-6.4
S2 Fa50	
Ef-G15	