



Elettorec

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Elettorec Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Elettorec Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Pmc25	Pressure switch 10 - 25bar (100bar) changeover - AG-1 / PMC25 Pressure switch (membrane) - changer including cube connector Switching point adjustment: in the body under the screw plug Setting range: 10 - 25bar Connection thread: G1 / 8 " Material: galvanized steel Seal: NBR Max. static pressure: 100bar Max. ohmic load: 3A at 250VAC Temperature range: -5 ° C - 90 ° C Switching cycles: 100 / min Tolerance at 25 ° C: ± 0.5ba
Pmc10	Pressure switch 0.5 - 10bar (100bar) changeover - AG-1 PMC10 Pressure switch (membrane) - changer including cube connector Switching point adjustment: in the body under the screw plug Setting range: 0.5 - 10bar Connection thread: G1 / 8 " Material: galvanized steel Seal: NBR Max. static pressure: 100bar Max. ohmic load: 3A at 250VAC Temperature range: -5 ° C - 90 ° C Switching cycles: 100 / min Tolerance at 25 ° C: ± 0.3 bar
PMM 50A	IF4VE16/A 856 / 5000 eviri sonuları Flow switch aluminum electr. / opt. 2-16 l / min 0 - 6 cSt Adjustable electrical flow switch with visual display Contact type: normally closed

710-545-01900	contact - opens the contact if the value falls below or exceeds the set value Switching point. Viscosity range: 0 - 6 cSt Material: aluminum Max. Working voltage: 220V - 50Hz Max. Current load in DC operation: 60W Max. Current load in AC operation: 60VA Breakdown voltage: 300V Protection class: IP65 Volume flow: 2 - 16l / min Max. Pressure: 15bar Working temperature: -10 ° C ... + 100 ° C Installation length: 167mm Connection thread: G1 / 2 " Installation position: vertical - max.inclination 15 ° Direction of flow: from bottom to top In accordance with CE 89/336 The flow switch must be installed at least 50mm away from components that influence magnetic fields become. Weight: 0.6500 kg / 0.6500 kg Item number: 90268020 Country of origin: IT
710-405-01100	EBT50CA Thermal switch 50 ° C normally open AG-1/2 " EBT50CA Thermal switch - normally open Switching point: 50 ° C ± 5 ° C max.static pressure: 80bar max.ohmic load: 10A at 250VAC Connection thread: G1 / 2 " Material: brass Available certificates: CE
PMC80	710-331-01200 Pressure switch 25 - 80bar (150bar) changeover - AG-1 / PMC80 Pressure switch (membrane) - changer including square plug Adjustment of switching point: in the body under the screw plug Setting range: 25 - 80bar Connection thread: G1 / 8 " Material: galvanized steel Seal: NBR max.static pressure: 150bar max.ohm load: 3A at 250VAC Temperature range: -5 ° C - 90 ° C Switching cycles: 100 / min Tolerance at 25 ° C: ± 1.0bar
710-331-01100	PMC10 Pressure switch 0.5 - 10bar (100bar) changeover contact - AG-1 PMC10 Pressure switch (membrane) - changer including square plug Adjustment of switching point: in the body under the screw plug Setting range: 0.5 - 10bar Connection thread: G1 / 8 " Material: galvanized steel Seal: NBR max.static pressure: 100bar max.ohm load: 3A at 250VAC Temperature range: -5 ° C - 90 ° C Switching cycles: 100 / min Tolerance at 25 ° C: ± 0.3bar Available certificates: ATEX, RINA, Lloyd's Register, UL, cURus, CE
IF5VE60/OM6SC	Z710-00207-99999 Electric flow meter 5-60l / min Max 15bar - brass - IT 1 "BSP Adjustable electrical flow switch with visual display Contact type: changeover Viscosity range: 6-14.4 cSt Material: brass Max. Working voltage: 220V - 50Hz Max. Current load in DC operation: 60W Max. Current load in AC operation: 60VA Breakdown voltage: 300V Protection class: IP65 Volume flow: 5 - 60l / min Max. Pressure: 15bar Working temperature: -10 ° C ... + 100 ° C Installation length: 190mm Connection thread: G1 " Installation position: vertical - max.inclination 15 ° Direction of flow: from bottom to top In accordance with CE 89/336 The flow switch must be installed at least 50mm away from components that influence magnetic fields will.
	710-540-01200 Electric flow switch ECO 3 - 24 l / min Adjustable electrical flow switch Contact type: normally closed contact - opens the contact when the value falls below or exceeds the set value Switching point. For media with low viscosity, such as water and water / glycol mixtures

IFE4R24	Material: nickel-plated brass Max. Working voltage: 220V - 50Hz Max. Current load in DC operation: 20W Max. Current load in AC operation: 20VA Breakdown voltage: 300V Protection class: IP65 Volume flow: 3 - 24l / min Max. Pressure: 50bar Max. Pressure loss with H2O: 0.5bar Working temperature: -10 ° C ... + 80 ° C Installation length: 115mm Connection thread: G1 / 2 " Installation position: vertical - max.inclination 15 ° Direction of flow: from bottom to top In accordance with CE 89/336 The flow switch must be installed at least 50mm away from components that influence magnetic fields will. When placing your order, please let us know the medium you are using and the viscosity. the specified measured values relate to operation with water.
IFE5R35	710-540-01250 Electric flow switch ECO 6 - 35 l / min Adjustable electrical flow switch Contact type: NC contact - opens the contact when the value falls below the set switching point. For media with low viscosity, such as water and water / glycol mixtures Material: nickel-plated brass Max. Working voltage: 220V - 50Hz Max. Current load in DC operation: 20W Max. Current load in AC operation: 20VA Breakdown voltage: 300V Protection class: IP65 Volume flow: 6 - 35l / min Max. Pressure: 50bar Max. Pressure loss with H2O: 0.5bar Working temperature: -10 ° C ... + 80 ° C Installation length: 132mm Connection thread: G3 / 4 " Installation position: vertical - max.inclination 15 ° Direction of flow: from bottom to top In accordance with CE 89/336
(30121121T10) PSM10R14T10	
(30121121T10_Y22) PSM10R14T10SM	
(30151421TF00_Y02) PSP300SR14T165F17SM	
1379004ZA	
254851	
30121121	
30149121	
30533312	
31015	
31060	
31300	
31300XIA	
31301	
31561B	
31601BE	

[31661B](#)

[31661FNT](#)

[31NA-20080](#)

[32026C](#)

[32036B](#)

[32036C](#)

[32320F](#)

[3454711](#)

[36275A](#)

[36300I](#)

[37075](#)

[37100](#)

[46307LPS](#)

[47108130](#)

[60136741](#)

[65870492600](#)

[710-300-01050](#)

[710-300-01250](#)

[710-305-01050](#)

[710-320-01050](#)

[710-325-01050](#)

[710-331-01050](#)

[710-331-01200](#)

[710-331-01350](#)

[710-355-01000](#)

[710-355-01100](#)

[710-355-01200](#)

[710-355-01250](#)

[710-370-01100](#)

[710-370-01250](#)

[710-420-01250](#)

710-445-01750
710-540-01100
710-540-01150
906-025-01100
921-015-01000
921-015-01600
CFV1B N
CO31560T025
CPPRE00008/SP110
CPPRE00009/SP110
EBT 50BC
EBT....CC
EBT70CC
EBT80CC
GRL/G1F2S2L500
IF1E1/A
IF2VE3/0
IF3E6/AM7SC
IF3VE6/A
IF3VE6/A P 34020201
IF3VE6/I
IF4E16/A
IF4E16/OM8SC
IF4VE16/ASC
IF5E60/AM7
IFE1R3
LEM5M SP (32520001)
LEM5MA (P/N 32521)
LEM6CNCS
LEM7

[LM 2](#)

[LM 2 CFPA 200 \(32126B \)](#)

[LM1 FA430](#)

[LM1/LM2/PIA-EP](#)

[LM1BFP](#)

[LM1CFA](#)

[LM1CFPA200 \(32125B\)](#)

[LM1CTA100](#)

[LM1CTA300 P/N: 32320D](#)

[LM1FA200N](#)

[LM1FA350](#)

[LM1FA450](#)

[LM1FA550NC](#)

[LM1FPA200NCT70NC](#)

[LM1FPA350NC](#)

[LM1PA200](#)

[LM1TA300T60](#)

[LM1TA500 NC](#)

[LM2 CFA 250](#)

[LM2 FA-150](#)

[LM2 PTIA 290](#)

[LM2A](#)

[LM2A250](#)

[LM2A300](#)

[LM2A500](#)

[LM2CTA170ARGL](#)

[LM2CTA-250](#)

[LM2CTA410](#)

[LM2CTA450](#)

[LM2CTA500](#)

LM2CTA500_EP
LM2FIA350
LM2FIA500
LM2TA250
LM2TA250XIA
LM2TBP
LM2TIA250EP
LM2TIA300 P/N: 32410D
LM2TPA200
LM3GA400NA/270NC/80NC
LMA1150
LMA2FA350 P/N: 32071E
LMM1CFA200NC/60NA
LMM1CTA650NCB150NA
LMM1FA150NC/60NC P/N: 32076125
LMM1FA450NC/70NC P/N: 32076F
LMM1TIA140NC/50NA
LMM1TIA150/50 p/n: 32420029
LMM1TIA250B60
M2.B20N.3.0300.S.FSPX.S1L1.C22.280.80
MS 10 SC N T R14 AP
MS 10 SC NT R 14 + CAP 13
MS 10SC NT R18
MS100SC BR14
MS100SC R14
MS100SCBR18
MS10SCBR18
MS10SCR18T3 P/N: 30523111T3
MS50SCWR14
NBT60CA

NR. 072900000 (NSSHOU 5X2,5/2,5 KON.)
Nr°100 LM2FPA300
Nr°100 LM2FPA400
Nr°2 PMC25
Nr°3 LMD1
Nr°5 PMC10
Nr°50 LM2FPA300
Nr°50 LM2FPA400
Nr°50 LM2FPA500
Nr°6 PMC10
Nr°8 PMC10
NTB 47 CA p/n: 3454721
NTB 47 CC
NTB 80 B C
NTB38CA
NTB-47-C-A
NTB47CA MOQ 10 pcs
NTB47CA 47?C
NTB60CA
NTB70C
NTB80CC
NTB80CC P/N: 3458022
NTBC70CC
NTBC80CC
PMC 10 1/8 0,5-10 bar
PMC 25
PMC 5
PMC10GT1.5D
PMC10IV
PMC10S

PMC10XIA
PME50AB 14k
PML10
PMM 10 A
PMM 10 A 2.5 S R18 T2
PMM 10 A B N 14K
PMM 1A NT T 0.18
PMM 2C W 18K
PMM 50 A 18K T20D
PMM 50C 14K
PMM10AB14K
PMM10ABN18K
PMM10ABR18 T2
PMM20AB14K
pmm2a E 14k
PMM2A14K
PMM2ABN18K
PMM2AWE14KTO.5
PMM2C
PMM2CB14K
PMM-2CI-18K-V48/0.5A
PMM300ABN14K
PMM50AB
PMM50AB N14K
PMM50ABE14K
PMM50ABN18K
PMM50AR14
PMM50AT20 p/n: 31660T20
PMM50CB
PMM50CBE14K
PMN 10 A B N 18K

PMN 150C V R14 T85D
PMN 20
PMN 2AVT1 +CAP1
PMN 50
PMN10A18KT
PMN10ABN18NPTSM
PMN10C18NPTAP
PMN150A
PMN150CVR14AP
PMN20A18K
PMN20ABMIR14
PMN20CBS18KCAP1
PMN250CVR14AP
PMN2AB18K
PMN50ABN10K
PMN50AFN14K
PMN50AR14
PMN50CBR14T50
PMN80ABN14KT60
PMN80ABN18K
PMN80C WN18K
PPC 300
PPC150D
PPC150XIA
PPCF150
PPL 150
PS150SCFR14T50
PSK100
PSK100T12
PSK100T13.5

PSK100T14
PSK100T24
PSM 10 I
PSM 50 B N R14
PSM 50 R14
PSM100R14 P/N: 30161121
PSM10BNR14T2D
PSM10BR18
PSM10NTR18T2G
PSM10R18
PSM10WNTR14SGT...
PSM2ER14XIA
PSM2NTR14EP
PSM2WMIR14(11)T1D
PSM50BNR14T50F10
PSM50BR14
PSM50BR18T10.5
PSM50R14 P/N
PSP 150 R14
PSP 300 F N R14
PSP150FNR14
PSP300FSR14
PSP300R14G P/N: 30151121G
PSP300WR14G
PSP300WR14T145
R987199434
SL2FIA500/130CVS1
TBR80C 1/2"
TIPO PMC 10
V9725B

VCM 1 A B N 18K
VCM1A , 18k
VCM1CV18K
VCN 2A B N 14K
VCN 2A B N 18K
VCN2AIV18K
VCN2AWV18K
VSM 1 B N R18
VSM 1 B R18
VSM1BR14T200D
VSM1W-R18-T170
VSM2VR14T800 P/N: 30321221T800
Y-LEF-250-10-A-1 10 .LIVELLOSTATO M Y
Y-LEF-300-10-A-1 10 .LIVELLOSTATO M Y
Z710-00137-99999
Z710-00145-99999
Z710-00166-99999
Z710-00219-99999
Z710-00237-99999
Z710-00239-99999
Z710-00243-99999
Z710-00244-99999
Z710-00245-99999
Z710-00246-99999
Z710-00248-99999
Z710-00285-99999
Z710-00301-99999
Z710-00356-99999
Z710-00389-99999

Z710-00441-99999	
Z710-00442-99999	
Z710-00466-99999	
Z710-00478-99999	
Z710-00481-99999	
Z710-00513-99999	
Z710-00539-99999	
Z710-00540-99999	
Z710-00541-99999	
Z710-00542-99999	
Z710-00549-99999	
Z710-00556-99999	
Z710-00583-99999	
Z710-00584-99999	
Z710-00585-99999	
PMM2 C14K CAP3	
PMC 10	
PSM10FNR14	Z720-00128-99999 Pressure switch 1 - 10bar (300bar) changeover - AG-1/4 PSM10FNR14 Pressure switch (membrane) - changer incl. cube plug Switching point adjustment: Central screw between the contacts Hysteresis adjustment: screw between pin 2 and pin T Setting range: 1 - 10 bar Connection thread: G1/4" Material: galvanized steel Gasket: NBR max. static pressure: 300bar max. resistive load: 6A at 250VAC Temperature range: -5°C - 90°C Switching cycles: 120/min Hysteresis: adjustable 10 - 30% Tolerance at 25°C: ± 0.4 bar Lifetime: 1,000,000 cycles Available certificates: EX, RINA, Lloyd's Register, IMG, CE Goods number: 90268020 Country of origin: IT
32410D - LM2TIA300	Z710-00659-99999 Electrical float switch V2A - 300mm Electrical float switch - changeover max. current consumption: 0.8A at 220V - 50Hz max. viscosity: 150cSt maximum pressure: 10 bar Working temperature: -10°C...+80°C Installation length: 300mm INSTALLATION: Thread: 1 1/4" Flange, immersion tube, circlips and float made of stainless steel Goods number: 90261081 Country of origin: IT
710-370-01200	3456022 NTB60CC Thermal switch 60°C opener AG-1/2" Thermal switch - normally closed with 360° rotatable terminal Switching point: 60°C ± 5°C Hysteresis: 16°C max. static pressure: 200bar max. resistive load: 10A at 240VAC

	Connection thread: G1/2" Material: anodized aluminum Available certificates: CE including cube plug
710-520-01100	LM1FA150NCT60NA Electrical float thermal switch-150mm-60°C Electrical combined float-thermal switch Float switch - normally closed max. current consumption: 0.8A at 220V - 50Hz max. viscosity: 150cSt maximum pressure: 10 bar Working temperature: -10°C...+80°C Thermal switch - normally open Switching point: 60°C ± 7°C max. current consumption: 0.5A at 220V - 50Hz Installation length: 150mm INSTALLATION: Ø tank cap bushing: 35.5mm Fastening: 2x M4 - LK43mm Flange: anodized aluminum Dip tube: brass Float: NBR
Z720-00128-99999	PSM10FNR14 Pressure switch 1 - 10bar (300bar) changeover - AG-1/4 Pressure switch (membrane) - changer incl. cube plug Switching point adjustment: Central screw between the contacts Hysteresis adjustment: screw between pin 2 and pin T Setting range: 1 - 10 bar Connection thread: G1/4" Material: galvanized steel Gasket: NBR max. static pressure: 300bar max. resistive load: 6A at 250VAC Temperature range: -5°C - 90°C Switching cycles: 120/min Hysteresis: adjustable 10 - 30% Tolerance at 25°C: ± 0.4 bar Lifetime: 1,000,000 cycles Available certificates: EX, RINA, Lloyd's Register, IMG, CE
Z711-00139-99999	IF5VE60/OM6SC Flow meter electric 5-60l/min Max 15bar - Brass - IT 1" BSP Electrical flow switch adjustable with visual indicator Type of contact: changeover Viscosity range: 6-14.4 cSt Material: brass Max working voltage: 220V - 50Hz Max. current load in DC operation: 60W Max. current load in AC operation: 60VA Breakdown Voltage: 300V Protection class: IP65 Flow rate: 5 - 60l/min Max pressure: 15 bar Working temperature: -10°C...+100°C Installation length: 190mm Connection thread: G1" Installation position: vertical - max. inclination 15° Flow direction: from bottom to top In accordance with CE 89/336 The flow switch must be installed at least 50mm away from components that affect the magnetic field become.
PMC 10	
PROFINET TYPE C 2X2X22 AWG	
Z711-00139-99999	IF5VE60/OM6SC Electric flow meter 5-60l/min Max 15bar - brass - IG 1" BSP Electric flow switch adjustable with visual display Contact type: changeover Viscosity range: 6-14.4 cSt Material: brass Max. working voltage: 220V - 50Hz Max. current load in DC operation: 60W Max. current load in AC operation: 60VA Breakdown voltage: 300V Protection class: IP65 Volume flow: 5 - 60l/min Max. pressure: 15bar Working temperature: -10°C...+100°C Installation length: 190mm Connection thread: G1" Installation position: vertical - max. inclination 15° Flow direction: from bottom to top In accordance with CE 89/336 The flow switch must be at least 50mm away from components that affect magnetic fields are mounted.
LM2CTPA200	G1

VSM 1	R18
PMM10	CAP.10) (NO CONTACT)
IF2E16AM10SC	SRF-644-001-0001
PSM10BNR18 SWITCH	
LM1A300NC	ALL.LEVEL.FL.18x1,5 MIN.300NC NBR FLOAT REV.
PMC 10 Range: 0.5/10V : 250 VcaCurrent : 3(2) A	
PMC5 0,2-5 BAR 1/8"	
LM2FA550	LIVEL.FL.D.52 ALL.MIN.550SC GALL. NBR
LM2CTPA350	long type
LM2CTPA200	short type
LM2CTA300EP ATEX	
LM2CTA400EP ATEX	
SL1TA500/60CVS3 EP ATEX	
30121121 Pressure Switches Psm10 R14 (250v)	
Pmc10t1.2	
If2ve3/Am7sc	
Pmn80abn18k Switchb: Brassn: Nbr	
If3ve6/Om7o Max. Lt/1? : 6 P Max. Bar : 15 M: E0737d 24 Wolt	
Level Switch Lm2	
Cap16	
Pmc 80 Pressure Switch	
Ms100sc Br14 Pressure Switch	
Drs18-100 100bar	
Ntb 38 Cc Temperature Relay 240 V, 10 A	
V1213b Psp 150 R14 30/150 250 Vac/6(2) A	
V0808a Pressure Switch Rmm 80a 18k V48/0.5 A	
500m X 33050g72037m25	

2_Psm10ntr14t5df0.5
If5ve60am9sc
31na-20080 Sensor-Pressure
Psp/300+
Pmc10 Relais 0,5-10 Bar-
If2ve3am10no
Z710-00309-99999
730-010-1000
. 881078270
Lm2fpa225
Lmm1fa600nc/80nc (Ex.Lmmfa600)
If2ve3/O P/N: 36225o
Pmn10ab18k
Pmn10ab14k
Ebt80cc P/N: 341008022
If3ve6/A If3ve6/Aflow Switch
Ebt50ca Termostato
100m X 33050g72037m68
Ppc150xia Druckschalter 30/150bar
47108130
If4ve16/A Flow Switch
Pmm 20?-14k Pressure Relay 48v, 0,5a
If3ve6/Am8
710-370-01250 Relay Ntb70cc
Pmc80
Lm2fa160
31541 Pmn20a14k
Co32125a
Pmm-2ci-18k-V48/0.5a Eletrotec Pmm
2c W 18k Pressure Sensor
Pmm 50c 14k Pressure Switch

Lm2cta410 Level Sensor 00252/92-005/535
Z710-00296-99999
32012 Level Gage Lm2
Glass (For If4ve16/0 Part No: 362750 Flowmeter)
Lm2bfp
Pmc10 Relais 0,5-10 Bar
Pmm50abn10kt20d
Psm10wsr14sg
If5v60/A
Pmm50a Sensor 14 Zu V48/0.5 F V1018a
Lm2cta450 Level Switch
Psm2wmir14(11)t1d Pressure Switch
Msa 10sc Nt R14 T5.2 1/10 Sensor
If3ve6/A Relais
Ntb 60 Ca Temperature Switch
Drucksensor Pmc-10 0,5-10 Bar
Pmm10abn14k Pressure Switch
710-331-01100 Pressure Relay
Lm1fa200n Fuellstandsensor Reichweite 250 Mm, Spannungsversorgung 24v, Dc
Cap 1
Fmc 41-Ne21pbj11m1
Lm2fpa500
Psm10ber18t4.5
Lm1fa250nc Fuellstandsensor Reichweite 200 Mm, Spannungsversorgung 24v, Dc
Nr°8 Pmc10 Druckschalter
If4ve16/Am10 / 36275am10
Psm50br18 Pneumatische Druckschalter
300m X 33050g72037m66

If2ve3/O 36225e
Lm2fpa250
Lmv1-Fa-250
Z710-00145-99999 Relayife1r3
Ms2scntr14 Pressure Switch
Tb / Oc / C V1308 R 1/2 70;C B Cap 2 (2t) By Ebt70cc
Ife4r 24, Pn 37100
710-320-01000
Pmm 10 A 2.5 S R18 T2 Schmutzindikator
Pmn 20 Pressure Switch
Pmc 10 Pressure Relay
. Pmc25
Ntb47 Thermoswitch (See Attached Files)
Pmm80abn18k
If4ve16/A Durchflussschalter
If4ve16/O
Ps150scfr14t50 Drucksensor
Pmc10t5.2sc
Psm 50 Ce
Ppc 150 Druckbereich Von 30 Bis 150 Bar
Ntb47ca Temperature Relay
Z710-00322-99999
Pmc 10s Druckschalter Druckluft (Sp19)
???10 Drucksensor (0.5-10)
Psm50bnr14t50f10 Pressure Switch F10 Contacts Spdt (10-50 Bar)
Sensor V48/0.5a V1304d
Ps245.10.Br.Hn.O.14
31960
Pml-10

Ntb25ba
36775a
Lm1fa200
Pmm10abn14k Pressure Switch 82
If5e60/Am7 P/N: 36800am7
V0827a Relayvcm 1a18k To 2dv48/0.5a
Lm2fa200 Lm2fa200 P/N. 32036c
Psm 10 Nt Am
Psp300 Fn R14 Drucksensor
Ntbc 105 C A
Lm2-Fa-400
Pmn50ab14k
Lm1-Fa-250
If5ve60/O
If3e6/A
Lm1fia150nc
Z710-00312-99999
31661b Sensor Rmm 50a 14k V48/0,5 A V117c
Pmm2abs14k Druckschalter
Nr°5 Pmc10 Drucksensor 0,5-10bar
Lem5lnsc
36300om6sc
Ppc150(30-150bar) Pressure Sensor Ppc150(30-150bar)
00252/94-051/504a
If4ve16/A Rotadurchflussmesser
Psm-Psp Tf36680
Lm2fa250
??? 80? 18? V48/0.5a Relay V0808a
Pmm10ab14k Druckschalter

Psp 150 R14 30/50 Druckschalter 250voc/6(2)a V124oc
SI2fa620/120cvs1
Z710-00135-99999
Bimetallischer Thermostat Ntbc70cc G1/2 E0447e
Pmc10t3.5d
S300/Nn
Model Pmc 10 Pressure Switch
Ppc 150
Ppc150d Relais
Nr°3 Lmd1 Float Level Switches
Pmm10abn14k Drucksensor
Lm2fa100 Sensor
Z710-00148-99999
Ppc150 Einstellbare Druck-Sensor30- 150bar
Lm2fa500
Vcm1cv18k Einstellbar Vakuumschalter
Psm10b
31300xia Ppc150xia
???-10 Drucksensor 0,5-10bar
Pmn50abn10k Pressure Switch
Psp 150 R14 30/150 Pressure Switch 250voc / 6 (2) A V1142c
Ms50scwr14 Relais
PMN10ABN18K
Psp 150 R14 Pressure Switch 30/150 Bar
Ntb70ca
36275am10
Ife3r18
Pmn2ab18kt1.3

If3ve6/ Am7	
If5ve60/Om7sc	
Pmc 5 Pressure Switch	
Z710-00207-99999	IF5VE60/OM6SC Electric flow meter 5-60l / min Max 15bar - brass - IG 1 "BSP M6 = viscosity up to 14.4 cSt 710 pressure switch + thermal switch
Psp300 (Fn R14)	
Pmc5v	
Lm2a300 Float Level Switch	
Pmm2abs14k Adjustable Pressure Switch	
Nr;100 Lm2fpa400	
Druckschalter Pmc5 0,5-5bar	
Ife4r24 Code 37100	
Nr;50 Lm2fpa500	
Pmm20a-V14k	
Pmc5	
Psm 10 Ce	
Tb / Oc / C V1308 R 1/2 80;C B Cap 2 (2t) By Ebt80cc	
Ife4r24 Flow Switch	
If5ve60/Am 10	
If3ve6/A P 34020201 Flow Switch	
Tb C/C R1/2 80; Cap2(2t) By Ebt80cc	
If4ve16/A	
Lm2fpa200	
710-500-01000	
Ntb70ca Sensor	
3454721	
V0813c	
Vcm 1a	
Nr;100 Lm2fpa500	
Iff1	

If3ve6/O 36250o
Tbfevo105c12 - 1 Box = 5 Pcs.
If4ve16/Am10
Pmc 10 Diaphragm Pressure Switch Elettrotec 0.5-10 Bar
Pmc 10 Pressostato Regolabile Con Contatto Spdt 0.5-10 Bar
SI2fia500/130cvs1
Psp300fnr14
Z710-00166-99999 Valve Pml100
Ppc150xia 30/150bar 47108130
46307lps Tfm07vl150/Ps
Ip65 En80529
If5ve60/I Code 36300i
31015 Protection Cap -3 (Ip 65 Electric Protection)
Vsm1br14t200d Schalter
Pmc5t3
Fmp01vrg1/Ps
Lm1fa300nc
36275a Durchflussschalter
Pmm 50a 4k Pressure Sensor V48 / 05a V1228v
Lm2ta200
Pmm50abn18k Sensor
If3ve6/A Elektrischer Sensor-Flut-Mit Sichtkontrolle
Lm2fa300
Lm2cta500ep
Ife4r24
Vsm1bvr14t450
Lm2fa150
Lm1fa250nc Oelstandssensor

(30151421tf00_Y02)
Psp300sr14t165f17sm Steelpressswi
Psm 2 Ce
If3ve6am10no
1f4ve16/Am10 P/N: 36275am10
Z710-00402-99999+710-250-01000
If3ve6/Om7
881078270
If.. 60w 60va 0.8 A 220v 300v
L500
Psm2 Trasduttore Di Pressione
Lma2fa200
800m X 33050g72037m69
Pmc10 Model Pmc10 Pressure Switch
Psm10mir14t101dg
Pmn50ar14 Pressure Sensor
Vsm1br14
3.6.250o
Ppc150xia Pressure Switch
Ntbc50ca
Lm2gt1a-1000
??? 10 Drucksensor (0.5-10)
Z710-00329-99999
Lm2 Bf
47108130 Ppc150xia
. Pmc10t1.3 P/N: 31200t1.3
Spdt ??? 150 Pressure Switch
Pmn10a14k
Lmv1-Fa-250 Float Level Switch
Ntb60cc
Lm2cta450 Commutatore, Livello Liquido

If3ve6 I
Pmc 5 Elettrotec Pressure Switch Pmc 5pressostato 0.2-5bar, Sensore 220v
Lm1fa350.
Psm10bnr14t2d Pressure Switch T2d Contacts Spdt (1-10 Bar)
Z710-00219-99999 Vacuum Relayvcm1a
If2ve3/0
Pmn10c18k
Ms100scwr14
1f2v2e3/A
710-325-01100
Cap 1 Protection Cap
Ppc 300 Drucksensor
Lm1ta500nc
Z710-00332-99999
Psm50br18
31561b Drucksensormn50ab14k
Lm1ta150nc
Psp300fsr14 Relais
Z710-00243-99999 Level Sensorlm4 Gia 605nc/560nc/B440nc/C320nc/D200nc
Ntb 70cc Relay
Pmc10 Pressure Switches
Lm2fia400
Ife5r35
Ms100scbr18 Adjustable Pressure Switches With Spdt Contacts
Lem6cn
Cap2
Psm 2 Nt Am
If5ve60/Am10sc

Lem5ln
00252/94-010/507a
Pmn250af18k
If2v3/Am11
Pml10 * Pressostato-Pressure Switch Range Bar0,5/10
Lm1fa250.
Vcn2aiv18k
Lm1fa150nct70na
Pnmz Civt05+cap.1 Relay
Pmm50abn18k Drucksensor
2751007
Z710-00240-99999
710-331-01300
Ntb 47 Cc T=47c Ncvac 240/10avo4 30d
SI2fa1800/220cvs1
Z710-00289-99999
3453821
Pmc10 Einstellbare Druckschalter
Ntb47ca
43650 - Pg09 Plug
Lm1fa250nc
Z710-00308-99999
Lm1cfpa200nc
Ntb60ca Schalter T-60grad C. No 240/10a V0307d
If3ve6/A Durchflussschalter
00252/92-021/523
Pmm50abn18k Sensor18kv48/0.5 Av0506c
36250a Durchflussschalter
Lm2fa100

710-250-01150
Sensor Psm2wmir14t1d
Ppc150 Einstellbare Druck-Sensor
Z710-00287-99999
If1e1/A Flow Switch Typep/N 36700a
Z710-00236-99999
If3ve6/Am9sc
L-150mm - Lm2
Ife3r18 Flow-Sensor
31200t1.7
Pmm10abr18 T2 Schmutzindikator
Lm2ta225
32075almm1a200
Ebt70cc P/N: 341007022
Ppc150d Model Ppc150d Pressure Switch
Code 31060
Lmv1-Fa-250 Level Switch
Pmm10ab14k Sensor
Psm50bnr14 Sensor
Ntb47ca Sensor
Ife3r18 P/N: 37075
Es521am2v
Lm2 Cfa 250 Level Sensor
If2ve3/Am10
Pmm50ab14k
Psp150
Lm2fa350
If3ve6/Am7sc
Ife6r60
Lmm1fa150nc/60nc (Ex.Lmm1fa150)

Tipo Pmc 10 Pressostato ; 0,5-10 Bar
Ife4r24 / 37100
Nr;100 Lm2fpa300
(30121121t10) Psm10r14t10 Brass Press Switch 1/1
Vcm1a V48/0.5a V12 Sensor
Lmv1-Fa-250 Min-Drain Electric Level
Lm1fa200nc
710-325-01200
Pmn50ab18k
Pmn20cbs18kcap1 Pressostato
Co166407t04
Psm 100
Pmm50ab14k Sensor
Psp150fnr14 P/N 30149121
Z710-00263-99999
If5ve60/Am10 P/N: 36300am10
Pmm2cb14k Druckschalter
Ife4r24 3-24l/Min G1/2
Lm2fa450
If3ve6/Am9sc P/N: 36250am9sc
Lm2cta450 Switch, Liquid Level
Z710-00245-99999 Pressure Sensor
Pmc 2
Msa 10sc Nt R14 T5.2 Pressure Sensor (1/10, V250/6a, V0720e)
Cls-K-11
Tbf Evo 105 A 12
LM2CTPA250
Psm50bntm12t17
Lm2 Cfa 250 Float Level Switch
Lm2fa400

Pmm50cb Pressostato A Membrana Con Pistone Di Regolazione
Lm2cfa350
Pmm50abn14k Pressure Switch
Z710-00372-99999
Psm 50
Pmm2abs14k
If3ve6/Am9
Psm10wntr14sgt?
Lm2fa200 Description Level Switch With Stem Length 200
Drucksensor Ppc 300
Ife4r24 Ventil
710-331-01150
Pmn 10a
If4e16/Am10
Pmm2a14k Pressure Sensor
SI2fia500/130cvs1 Level Sensors
400m X 33050g72037m61
Ife2r9 Drucksensor Der Firma Elettrotec - Typ Ife2r9 P Max Bar 50 Mq Max Lt/1
Lm2fpa300
Psm-Psp 2wmir1411t1d Sensor
Lm2fa1100
Pmm 50a-14k Pressure Relay 48v, 0,5a
710-405-01100
710-331-01100
Ebt50ca Thermostat
500m X 33050g72037m70
Ebt80cc (341008022)
Lem5cn

Tb C/C R1/2 70; Cap2(2t) By Ebt70cc
Pmm2abn18k Schalter
Ebt105cc
Pmm50ab Pressostato A Membrana Con Pistone Di Regolazione
Lm2cfpa250
Pmm50abn18k Drucksensor18kv48/0.5
Av0506c
Ife6r60r /Ife6r60/
710-365-01150
If2ve3/A
00252/94-050/509
31200dt4
710-331-01250
Psm10br18 Pneumatische Druckschalter
11092
Lma2fa400
Pme2a18kt12v0822e By Pmn2ab18kt1.2
Or Pmn20ab18kt12
SI2fa560/120cvs1
Vcm1ab18k
Psm 2
Lm2fpa400
Z710-00186-99999
Ntb38ca Temperature Relay
Cap3
Cap3 Code 31015
(30121121t10 Y22) Psm10r14t10sm
Brasspressswitch1
Ntb60ca Schalter
Ebt70cc (341007022)
Pmn20ab18kt12
Pmc10 Druckschalter

If4ve16am9sc	
Z710-00244-99999 Schwimmerschalter Lm232012	
If-E5-R35	
E610115310001	
Elettrotec Pmm 10a	
1fe2r9 Flow Relay 1-9 Lt/Dk	
Nr;50 Lm2fpa300	
Pmc10d	
Z710-00261-99999	
LM2CFA150	LIVEL.FL.D.52 ALL.MIN.150SC.GALL.NBR NON REV.
Pmc 10 Air Pressure Sensor With Connection Socket	
Dbsf-1e	
Ife 4r 24 (Ex Ife 4r 24r)	
Co31560t025 , By Pmn50abt25	
Vsm 1 B N R18 Replace Old Vsm 1 R18vaccum Switch Vsm	
Lm2tb	
Z710-00266-99999	
Z710-00265-99999	
(30543172t50d Y02) Ms100sczr14t50dsm Steelpressswit	
Ebt80cc Temperaturschalter	
If4ve16/A Sensor-Flut-Gewinde 1/2"	
If1ve1/A	
37075 Ventilife3r18	
Lm2fa315	
Lm1fa200nasp	
If4e16/O	
Pmc10-V Trasduttore Di Pressione	
Pmn2ab18kt1.2	

SI2fia1200/150cvs1
. If2ve3/O P/N: 36225o
Lm2fia350 Sensor
Ntbc40ca
(32984003sc Y22) Lm1ta170nat70ncsc
Ntbc100ca
Vcm 1 A B N 18k Vacuum Sensor
Pressure Interruptors 1-10barmax 220 Vac, Stainless
If5ve60a/M7
Vsm1bnr14t200d
Ppc150 Relais
(30543672t50d Y02) Ms100scbzt14t50dsm Brasspressswit
If2e3/Am 24 V Dc
Nr;6 Pmc10
Lmm1tia250b60 Level Sensor
Pmm50ar14 Pressure Sensor
Ife2r9 Drucksensor
Lm1lfa100nc
Ntb38ca Temperaturschalter
Psm10wntr14sg
Psp 150 R14 Pressure Switch
Lm2fa200
Z710-00188-99999
If4e16/A Adjustable Electric Flow Switch
Z710-00178-99999
Lm1fpa350nc Electric Oil Level
??? 2? B N 14? Elettrotec Pressure Switch
710-325-01250
Lm 2a 300 Float Switch

Vcn2awv18k Sensor	
Ntb47bc	
Pmm-2ci-18k-V48/0.5a Regulated Predduce Transduces With Terminal Screw: Pmm 2ci 18k V48/0.5a V1121e	
Ebt40dc.	
Ebt30dc.	
Z710-00141-99999	
Psm10br18 Pneumatisches Relais	
Pmn10ab18k Pressure Switch	
Psm 100 Ce	
Pmc10 Pressure Relay	
If5ve60/A	
Z710-00316-99999	
Psm2er14xia	
V1304d Pressure Sensorpmm 2c 14r V48/0.5a	
Ife1r3 Flow Switch	
6274346 Relay Pmn80ab	
Pmn 2avt1 +cap1 Pressure Switchcode: Pn1011	
- Protection Cap -3 (Ip 65 Electric Protection)	
Lm2ctpa150	Z710-00326-99999 elec. Fill level indicator Screw-in thread 1 "BSP Length 150 mm Electric float switch - changeover contact Max. Current consumption: 0.8A at 220V - 50Hz Max. Viscosity: 150cSt Max. Pressure: 10bar Working temperature: -10 ° C ... + 80 ° C Installation length: 150mm Screw thread plastic: AG 1 "BSP
Z710-00340-99999	
2el 2f03	
Lm1ta500nc Flow Switch	
Dbds6k18/190e	
Psm 10	
Ebt70bc	
Ms100sc R14 Pressure Relay 250/6a, 10-	

100bar, E1510b
Ppc 300 Drucksensor P/N 31301
Ntb70c Relay 10a, ~240v, G1/2 21513d
Psm2b
Ms10scbr18 Adjustable Pressure Switches With Spdt Contacts
710-320-01050 30121111 PSM10BNR18 Pressure switch 1-10 bar (300 bar) changeover male thread 1/8" Pressure switch (diaphragm) - changeover switch incl. cube connector Adjustment: Screw between the contacts Adjustment range: 1 - 10 bar Connection thread: G1/8" Material: Brass Seal: NBR Maximum static pressure: 300 bar max. ohmic load: 6A at 250VAC Temperature range: -5°C - 90°C Switching cycles: 120/min Hysteresis: adjustable 10 - 30% Tolerance at 25°C: ± 0.4 bar Lifespan: 1,000,000 cycles Available certificates: ATEX, RINA, Lloyd's Register, IMQ, CE
Ife 3r 18 (Ex Ife 3r 18r)
36825am8
031540
Lmm1cta120na/50naep
Pmc10 Relais
Z710-00127-99999
Pmm10a14k Cap3 Relay
Lm1fpa250nc
Ife2r9
If3ve6/A Flow Switch
36250a
SI2fia500/130cvs1 Der Sensor Funkt.
Nr;50 Lm2fpa400
Ppc 150 Pressure Switch
Z710-00226-99999
Pmn 50 Pressure Switch
V9635e
Lmm1fa450nc/70nc (Ex.Lmm1fa450)
Ntb47ca Temperaturschalter

[Lm2-Fa-550](#)