

Eltherm

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Eltherm Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Eltherm Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
ELSR-M-15-2-AO [15W/m bei 10°C, Un=230V]	Self-regulating heating cable Net weight: 13.2500 kg Technical specifications: Nominal power: 15 W/m at 10 °C Nominal voltage: 230 V Maximum operating temperature when switched on: 65 °C Maximum operating temperature when switched off: 65 °C Minimum installation temperature: -45 °C Minimum bending radius: 25 mm Supply conductor: Cu, nickel-plated, 0.62 mm ² Protective cover: Aluminum foil Protective conductor: Cu, tinned Outer sheath: TPE-O Dimensions: approx. 8.0 x 5.5 mm Weight: approx. 53 g/m ² [Printing] [Meter reading / running meter] eltherm GmbH Burbach ELSR-M-15-2-AO 15 W/m @ 10°C 230VAC [S+] [GL] [EAC Rus] -45°C ≤ Tp ≤ 65°C Tmax=65°C [CE] [UKCA] [Batch number / Batch number]
Eltherm / Eltc-2	
Eltc 70/5 230v/Ac	
B0200310	
Eltc-2 0-100 ; C, 230v, Incl Pt100	
Elsr-M-15-2-Bo	
El-Ws01e 2986900012	
0920059	
Elak-5 0920013	
Elsr-H-45-2-Bot B0221453	

Ürün	Açıklama
2006.08-01 (Sample Line Ait-37301)	
Elvb-Srv Connection Kit F. Elsr-N/L/W	
2006.08-05 (Vent Line Ait-37001)	
Elsr-Ls-10-2-Ao	
El-2500h	
Fx/Lb (50ks)	
Elsr-Ls-25-2-Ao	
Elsr-M-10-2-Af	
El-Ecl Abschluss-Set Fur Elsr-L	
B0200319	
Elsr-Ls-15-2-Ao	
Elak-Rs-S (9ks)	
0x81eh1	
B0200110	
Eltc 40/1	
Elvb-Srv-N-L-W	
Wr-SI	
B0200210	
B0223304	
El-Ecn End Termination Kit F. Elsr-N	
Elsr-N-30-2-Ao	[30W/m at 10°C, Un=230V] Self-regulating heating cable Technical specifications: Nominal power: 30 W/m at 10 °C Nominal voltage: 230 V Maximum operating temperature when switched on: 65 °C Maximum operating temperature when switched off: 80 °C Minimum installation temperature: -60 °C Minimum bending radius: 25 mm Supply conductor: Cu, nickel-plated, 1.23 mm ² Protective cover: Aluminum foil

Ürün	Açıklama
	Protective conductor: Cu, tinned Outer sheath: TPE-O Dimensions: approx. 13.6 x 5.5 mm Weight: approx. 91 g/m ² Equipment class heating cable according to ATEX: II 2G Ex 60079-30-1 IIC Gb II 2D Ex 60079-30-1 IIIC Db Equipment class system according to ATEX: II 2G Ex 60079-30-1 eb IIC T6 Gb II 2D Ex 60079-30-1 tb IIIC T85°C Db
Art. No 0621141 Eltc-40/5, Pt100, -80...+400;C, 3 S	
Elkm-Ag-N 0,0044 [0,0044ohm/M]	
Elmw-9 0941009	
0610008	
09clics	
Elsr-Ls-30-2-Bo	
Eltf-Pt.3	
Kf6025	
Kf9045	
2006.08-02 (Vent Line Ait-37301)	
Eltc-14 Temperaturregler	
Tb50002	
Elak-Rs-T	
Kf9025	
Fx/Pe (20)	
Fx/Al (8ks)	
0620000	
Eltf-Pt.1	
0650003	
Elsr-N-30-2-Bo [30w/M At 10;C,	

Ürün	Açıklama
Un=230v]	
Eltc-70/5, Pt100, -80...+600;C, 3 S	
Elkm-Ag-N 0,00195 [0,00195ohm/M]	