

Emec

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Emec Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Emec Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
VMS-PO 0310, 230 VAC	VPO0301010000V00A000 4x6 Accessories: Standard Magnetic diaphragm metering pump for horizontal use Mounting, IP65 protection rating, Microprocessor control, valves with Double ball (where possible). Constant Dosage, proportional dosage only Multifunctional pumps. Empty signal input for automatic shutdown when empty Storage containers (except T-/V-CO). A Pump type: VMS PO Pressure: 3 bar Flow rate: 10 l/h Dispensing head/O-ring: PVDF FP Customized: --- Electrical connection: 230 VAC + Schuko Case color: Green Packaging: Standard: Injection valve, axial foot filter, control cable for pumps with input inlet, 2 m each Suction/dosing/venting hose. Special feature: --- Product number: 84135040 Weight: 2.500 kg Country of origin: Italy
VCO1001010000A00A000	PUMP VCO 1010 FP 230VAC Solenoid diaphragm dosing pump for vertical mounting, protection class IP65, Microprocessor control, double ball valves (where possible). Constant dosage without level control pressure: 10 bar; Flow rate: 10 liters per hour; Hydraulic parts: PVDF FP (O-ring); Supply voltage: 230 VAC + Schuko; Pump colour: ORANGE Hose connection: 4x6 mm incl. accessories: - Inoculation valve 1/2" - 4x6 PVDF

Ürün	Açıklama
	- Axial foot valve 1/2" - 4x6 PVDF - 2 m each of PVC suction, PE dosing and PVC ventilation hose Country of origin: Italy old article number: VCO1001010000A00A000
10800111	EPHL, pH electrode, 15m fixed cable with BNC connector
Jcph 0b00n135s00	
FCE 0703 FP, 230VAC	Constant pump with rotary knob to regulate the dosing quantity (the knob on the front can be set from 0% to 100% of the pump's rated output). Performance). The stroke frequency is set electronically. To avoid Linearity problem, the pump flow knob must not be between 0% and 10% be set. The FCE can be in constant dosing mode or in on-off mode (using a external signal). The FCE has a divider (x-0.1) to calculate the pump performance by dividing the Reduce pump stroke speed tenfold. Housing color: GREEN Dosing head: PVDF O-rings: FPM Electrical connection: 230VAC - without plug Alt. Code: FCE0700310001V00B000
10800111	EMEC EPHL ELEKTRODE 15M 0-14PH 0-7BAR 0,70C BNC EPOKSI
EM.FCE0500510001V00B000	PUMP,DOSING,LIQUID(EMEC PCE 0505
VMSP0 1505 FP 230VAC	VPO1500510000V00A000 Accessories: Standard Magnet diaphragm metering pump for horizontal mounting, protection class IP65, Microprocessor control, valves with Double ball (where possible). Constant Dosage, quantity-proportional dosage only Multifunctional pumps. Empty signal input for automatic shutdown when empty Storage tank (except T-/V-CO). A Pump type: VMS PO Pressure: 15 bar Flow rate: 5 l/h Dosing head/O-ring: PVDF FP Customer-specific: --- Electrical connection: 230 VAC + schuko

Ürün	Açıklama
	Case color: Green Packaging: Standard: Injection valve, axial foot filter, control cable for pumps with input port, 2 m each Suction/dosing/venting hose. Special feature: ---
VMSP0 1502 FP 230VAC	VPO1500210000V00A000 Accessories: Standard Magnet diaphragm metering pump for horizontal mounting, protection class IP65, Microprocessor control, valves with Double ball (where possible). Constant Dosage, quantity-proportional dosage only Multifunctional pumps. Empty signal input for automatic shutdown when empty Storage tank (except T-/V-CO). A Pump type: VMS PO Pressure: 15 bar Flow rate: 2 l/h Dosing head/O-ring: PVDF FP Customer-specific: --- Electrical connection: 230 VAC + schuko Case color: Green Packaging: Standard: Injection valve, axial foot filter, control cable for pumps with input port, 2 m each Suction/dosing/venting hose. Special feature: ---
10800101	
10800121	
VCO 0215 FP 230VAC	VCO0201510000V00A000 Magnet diaphragm metering pump for vertical Mounting, protection class IP65, Microprocessor control, double ball valves (where possible). Constant dosage without Level control pressure: 2 bar; flow rate: 15 l/h; Hydraulic parts: PVDF FP (O-ring); Supply voltage: 230 VAC + Schuko; Pump color: Green A Hose connection: 6x8 mm including accessories: - Injection valve 1/2" - 6x8 PVDF - Axial foot valve 1/2" - 6x8 PVDF - 2 m each of PVC suction, PE dosing and PVC venting hose
TCO 0420 FP 230VAC	TCO04020K0000V00A000 Accessories: Standard

Ürün	Açıklama
	Magnet diaphragm metering pump for horizontal Mounting, protection class IP65, Microprocessor control, valves with Double ball (where possible). Constant Dosage, quantity-proportional dosage only Multifunctional pumps. Empty signal input for automatic shutdown when empty Storage tank (except T-/V-CO). A Pump type: T CO Pressure: 4 bar Flow rate: 20 l/h Dosing head/O-ring: PVDF FP Customer-specific: --- Electrical connection: 230 VAC + schuko Case color: Green Packaging: Standard: Injection valve, axial foot filter, control cable for pumps with input, 2 m each Suction/dosing/venting hose. Special feature: ---
spare parts	
V-CO 0706,FP 230 VAC	VCO0700610000V00A000 Magnetic diaphragm metering pump for vertical applications Mounting, IP65 protection rating, Microprocessor control, double ball valves (where possible). Constant dosage without Level control pressure: 7 bar; Flow rate: 6 l/h; Hydraulic parts: PVDF FP (O-ring); Supply voltage: 230 VAC + Schuko; Pump color: GREEN A Including accessories: - 1/2" injection valve - 4x6 PVDF - 2 m each of PVC suction hose, PVDF dosing hose and PVC venting hose Weight: Approx. 2 kg
10868661	MEMBRANE OPTIC EOLUM
AMF07020K0000G00A000	AMS MF 0720 FP 230VAC Grey 4 hours 924.00 3,326.4040 days 10% 6x8 Accessories: Standard Magnetic diaphragm metering pump for horizontal use Mounting, IP65 protection rating, Microprocessor control, valves with Double ball (where possible), mechanical Regulation of the stroke volume. Constant Dosage, proportional dosage only with multi-function pumps and AMS/K-Plus.

Ürün	Açıklama
	Empty signal input for automatic Shutdown when the reservoir is empty (Exception AMS-/K-CO). A Pump type: AMS MF Pressure: 7 bar Flow rate: 20 l/h Dispensing head/O-ring: PVDF FP Customized: --- Electrical connection: 230 VAC + Schuko Case color: Gray Packaging: Standard: Injection valve, axial foot filter, control cable for pumps with input inlet, 2 m each Suction/dosing/venting hose. Special feature: ---
2019991	PUMP HEAD (LPV) VISCOSE
Sefls/D	
Kmsa Mf 08 5,5 PvdF Fp 230 Vac	
Ams-Co 0340 (Ex.Cms-Co 0340)	
Kms Mf 0808 Pmma Ep 230 Vac	
07601471	
Ecdindpt	
Lasp4	
Hcl40472567-40472568	
99000405	
Ecdcc/1 Pdvf Electrode K1	
Hcl 1004 Fp 230vac	
Lph 0000g031n00 Obsolete, Replacement 90300000 - Ldph, 90-240 Vac	
Ldph 90/240 Vac 0-10v	
07602001	
Jcph 230 Vac	
07602041	

Ürün	Açıklama
90800000	
Kmsamf	
Ldph, 90-240 Vac (90300000)	
01005171	
00000097	
Lcdri 0000g031n00 Obsolete, Replaced By Ecdindpt	
Jcph 0b00n135s00	
Hcl 1802 Fp 230vac	
07601981	
H-Cl 1802 Fp, 230 Vac	
01016371	
Ldph, 90-240 Vac	
Tco 2005	
K - 4x6 (Pvdf+fp+ce)	
H-Cl 1004 Fp (K-Cl 1005 Fp), 230vac	
Fcl121.5v0000v00b00	
90000008	
00000106	
Ephs	
Kmf 0808	
Hcl 2001 Fp 230 Vac	
Jd Ph 230 Vac	
Eicdc/1	
Hcl	