

Emh

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Emh Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Emh T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
3127783	VARIOMOD XC-LTE
VAXCET-E00	Variomod XC ethernet for LZQJ-XC
VAET-1K1-42A-E00	EMH-VARIOMOD ethernet is a counter modem that enables the meter with CL00, RS232 or RS485 interface to be read remotely via the ethernet network
VAXCLT-1E1-H20	VARIOMOD-XC Variomod XC LTE Generation H for LZQJ-XC and DMTZ-XC
Variomod XC Ethernet for LZQJ-XC and DMTZ-XC	Type code : with RJ socket VAXC ET-E00 List of features: RJ45 Ethernet interface according to IEEE 802.3 10 BaseT/100BaseTx (autonegotiation, auto MDI(X) IP address assignment according to DHCP or fixed IP address Protocols TCP/IP, DNS Client, SMTP (Mail), ICMP (Ping), ARP transparent operation communication channels § IP telemetry according to E DIN 43863-4 § Fixed IP § FTP according to RFC 959 (with adjustable header) · Push to 2 destinations possible · Seamless load gear push Password function (for parameterization and meter reading) Remote / local configurable Firmware update possible locally and remotely

Supports data transmission rates from 300 up to 9600 baud to the meter CE marking, EC declaration of conformity Status LED display for power, connection, error In addition to the integrated meter interface, the VARIOMOD XC has an RS485 interface to connect additional meters to the modem.

[EMH / LZQJ-XC](#)

[EMH-Variomod XC ethernet](#)

Variomod XC Ethernet for LZQJ-XC and DMTZ-XC Type code: with RJ socket VAXC ET-E00 List of features: RJ45 Ethernet interface according to IEEE 802.3 10 BaseT/100BaseTx (autonegotiation, auto MDI(X) IP address assignment according to DHCP or fixed IP address Protocols TCP/IP, DNS Client, SMTP (Mail), ICMP (Ping), ARP transparent operation communication channels § IP telemetry according to E DIN 43863-4 § Fixed IP § FTP according to RFC 959 (with adjustable header) · Push to 2 destinations possible · Seamless load gear push Password function (for parameterization and meter reading) Remote / local configurable Firmware update possible locally and remotely Supports data transmission rates from 300 up to 9600 baud to the meter CE marking, EC declaration of conformity Status LED display for power, connection, error In addition to the integrated meter interface, the VARIOMOD XC has an RS485 interface to connect other meters to the modem.

[LZQJ-XC](#)

[VAXCLT-1E1-H20 V201](#)

Variomod XC LTE Generation H for LZQJ-XC and DMTZ-XC The EMH-Variomod XC lte in generation H is a meter modem that can be inserted into the module shaft of an electricity meter of the -XC series and enables remote reading via the GSM/GPRS and LTE mobile network. The EMH-VARIOMOD XC lte meter modem was developed as a transparent modem and therefore works with various central readout points without any problems. List of features: GSM - 2G (Global System for Mobile Communication) in Band 8 (900MHz), Band 3 (1800MHz) GPRS (General Packet Radio Service) in Class 10; up to 2 uplinks and 4 downlinks – max. 5 links) LTE – 4G (Long Term Evolution) in Band 3 (1800MHz), Band 8 (900MHz) and Band 20 (800MHz) GSM connection with CSD readout, data compression V.42bis IP communication using GPRS and LTE for transparent operation IP telemetry according to E DIN 43863-4 FTP according to RFC 959 (with adjustable header) Push to 2 destinations possible Seamless load gear push Fixed IP or national roaming (configurable) Support up to 2 APN Password function (for parameterization and meter reading) With activated installation control register C.86.0 in the LZQJ-XC / DMTZ-XC an SMS, UDP message or a data push can be sent in the event of events. Remote / local configurable Firmware update possible locally and remotely Supports data transmission rates from 300 up to 9600 baud to the meter Monthly IP data budget monitoring Status LED display for network voltage, connection, error, and active network selection (2G/4G) GSM / GPRS / LTE field strength display via LED In addition to the integrated meter interface, the VARIOMOD XC has an RS485 interface to connect other meters to the modem. This interface is designed as an RJ socket and as a plug-in spring

	clamp terminal (up to 1.5mm ²). Standard FAKRA antenna connector Delivery incl. multi-band antenna, approx. 3 m cable with FAKRA-D connection
emh-lzqj-xc	
VARIOMOD_XC LTE MODEM VAXCLT 1E1-H20	
LZQJ-XC 5SFB-BB-GPB-D4	
Esmu-Ah-W72 Obsolete, No Replacement	
Prh850	HEVY DUTY CORNER HEAD
Prh840	MEDIUM CORNER HEAD
Esmu-Ah-B72	
Variomod Xc	
Lzøj-Xc	
600-560-3	CARD
E100917d	CIRCUIT CARD
191-9535-2	TAKE OUT TONG HOLDER
Lzqj-Xc	