

Enedo

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Enedo Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Enedo T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
OPUS HE 24-7.5 R 12U F	MECHANICAL SPECIFICATION: Rack H533xW438xD395 mm, 20 kg, IP20, 19" frame mounted, RAL 7024, ELECTRICAL SPECIFICATION: IN: 1x(3L+N+PE) 400V-50Hz, 18 A/line, OUT: Pmax 7.5kW, Idcmax 312,5 A, Udc 21/27,24/33 V, DC poles: floating, INCLUDED: user interface unit for controller, 1-pole rectifier input AC MCB 16A: 5 pcs, 1-pole rectifier outp. DC MCB 63A: 5 pcs, 2-pole battery DC MCB 250A: 1 pcs, PACKING (included): carton box: 61x41x64 mm, gross weight: 21 kg, SPACE FOR (must/can be included): system controller VIDİ+I/O kit: 1pc, rectifier module MHE 24-1500: 1-5 pcs, 2-pole load DC MCB+aux 2-63A: 0-6 pcs,
VIDİ+ I/O System Controller 94G910	OPUS DC Systeme
Temperature sensor 5m	for OPUS DC system
AUX Contact Schneider C60H-DC	
MCB C20A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
MCB C25A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	

Rectifier module MHE 24-1500	SPECIFICATION: Input: Uac 1L+N+PE 85/300 V, Iac: 12.5 A, f: 45-66Hz, Output: Udc 21/27.24/33V, Idc 62.5A, Pdc 1500W, Eff: 96%, MBTF: 1840000h. HxWxD: 169x83x357 mm, IP20, 4.6kg Flow cooling, front connection
OPUS USB, ConfUtility and manuals	
OPTION 2 - 110VDC - 1 System	
OPUS HE 110-10.0 R 12U F	MECHANICAL SPECIFICATION: Rack H533xW438xD395 mm, 20 kg, IP20, 19" frame mounted, RAL 7024, ELECTRICAL SPECIFICATION: IN: 1x(3L+N+PE) 400V-50Hz, 24 A/line, OUT: Pmax 10kW, Idcmax 92,5 A, Udc 90/122,58/150,0 V, DC poles: floating, INCLUDED: user interface unit for controller, 1-pole rectifier input AC MCB 16A: 5 pcs, 1-pole rectifier outp. DC MCB 20A: 5 pcs, 2-pole battery DC MCB 100A: 1 pcs, PACKING (included): carton box: 61x41x64 mm, gross weight: 21 kg, SPACE FOR (must/can be included): system controller VIDİ+I/O kit: 1pc, rectifier module MHE 110-2000: 1-5 pcs, 2-pole load DC MCB+aux 2-63A: 0-6 pcs,
VIDİ+ I/O System Controller 94G910	OPUS DC Systeme L x H x B: 218 x 41 x 88 mm
Temperature sensor 5m	OPUS DC System
AUX Contact Schneider C60H-DC	
MCB C16A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
MCB C20A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
Rectifier module OPUS HE	
OPUS USB, ConfUtility and manuals	OPTION 2 - 110VDC - 1 System
17217	17217 Temperature sensor 5m for OPUS DC system + 17473 AUX contact Schneider iC60N + 17474 Circuit breaker C10A 2-p. 72 Vdc/p 230/400VAC/p, 6 kA Schneider iC60N + 17475 Circuit breaker C16A 2-p. 72 Vdc/p 230/400VAC/p, 6 kA Schneider iC60N + 18076 MCB C32A 2-p. 72 Vdc/p, 230/400VAC/p 6 kA Schneider iC60N + 18077 MCB C63A 2-p. 72 Vdc/p, 230/400VAC/p 6 kA Schneider iC60N + 18063 VIDİ2 System Controller - system monitoring and control - remote access to the system + 18064 VIDİ2-EFD module KIT
18078	Wall mounting KIT R 12U IP21 OPUS HE
18059	Battery Midpoint measurement cable 5m
17466	Rectifier module MHE 24-1500 SPECIFICATION: Input: Uac 1L+N+PE 85/300 V, Iac: 12.5 A, f: 45-66Hz, Output: Udc 21/27.24/33 V, Idc 62.5 A, Pdc 1500W, Eff: 96%, MBTF: 1840000h. HxWxD: 169x83x357 mm, IP20, 4.6kg Circuit cooling, front connection
Rectifier module MRC 24-1100	Mechanical specification: Dimensions: 460 x 83 x 350 mm Weight: 4.6 kg

Rectifier module MRC 110-1600	Mechanical specification: Dimensions: 230 x 83 x 350 mm Weight: 4.6 kg
RECTIFIER, MRC 24-1100-92G310	
RECTIFIER, MRC 110-1600-92G300	
18581	Rectifier module MRC 24-1100 Mechanical specifications: Dimensions: 169 x 83 x 357 mm
17327	Rectifier module MRC 110-1600 Mechanical specifications: Dimensions: 169 x 83 x 357 mm
17934	OPUS UIF user interface unit for system controllers Wall or door installed interface unit Price is EXW Estonia or Finland
18582	VIDI+ System Controller 94G900 for OPUS DC systems Dimensions: H 218 x 41 x 88 mm
18583	LMC-EXT EXTENSION UNIT to LCM6 leakage Accessory to LCM6 leakage current monitor unit Price is EXW Estonia or Finland