Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Enedo

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Enedo Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Enedo Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
OPUS HE 24-7.5 R 12U F	MECHANICAL SPECIFICATION: Rack H533xW438xD395 mm, 20 kg, IP20, 19" frame mounted, RAL 7024, ELECTRICAL SPECIFICATION: IN: 1x(3L+N+PE) 400V-50Hz, 18 A/line, OUT: Pmax 7.5kW, Idcmax 312,5 A, Udc 21/27,24/33 V, DC poles: floating, INCLUDED: user interface unit for controller, 1-pole rectifier input AC MCB 16A: 5 pcs, 1-pole rectifier outp. DC MCB 63A: 5 pcs, 2-pole battery DC MCB 250A: 1 pcs, PACKING (included): carton box: 61x41x64 mm, gross weight: 21 kg, SPACE FOR (must/can be included): system controller VIDI+I/O kit: 1pc, rectifier module MHE 24-1500: 1-5 pcs, 2-pole load DC MCB+aux 2-63A: 0-6 pcs,
VIDI+ I/O System Controller 94G910	OPUS DC Systeme
Temperature sensor 5m	for OPUS DC system
AUX Contact Schneider C60H-DC	
MCB C20A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
MCB C25A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
Rectifier module MHE 24-1500	SPECIFICATION: Input: Uac 1L+N+PE 85/300 V, Iac: 12.5 A, f: 45-66Hz, Output: Udc 21/27.24/33V, Idc 62.5A, Pdc 1500W, Eff: 96%, MBTF: 1840000h. HxWxD: 169x83x357 mm, IP20, 4.6kg Flow cooling, front connection

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
OPUS USB, ConfUtility and manuals	
OPTION 2 - 110VDC - 1 System	
OPUS HE 110-10.0 R 12U F	MECHANICAL SPECIFICATION: Rack H533xW438xD395 mm, 20 kg, IP20, 19" frame mounted, RAL 7024, ELECTRICAL SPECIFICATION: IN: 1x(3L+N+PE) 400V-50Hz, 24 A/line, OUT: Pmax 10kW, Idcmax 92,5 A, Udc 90/122,58/150,0 V, DC poles: floating, INCLUDED: user interface unit for controller, 1-pole rectifier input AC MCB 16A: 5 pcs, 1-pole rectifier outp. DC MCB 20A: 5 pcs, 2-pole battery DC MCB 100A: 1 pcs, PACKING (included): carton box: 61x41x64 mm, gross weight: 21 kg, SPACE FOR (must/can be included): system controller VIDI+I/O kit: 1pc, rectifier module MHE 110-2000: 1-5 pcs, 2-pole load DC MCB+aux 2-63A: 0-6 pcs,
VIDI+ I/O System Controller 94G910	OPUS DC Systeme L x H x B: 218 x 41 x 88 mm
Temperature sensor 5m	OPUS DC System
AUX Contact Schneider C60H-DC	
MCB C16A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
MCB C20A 2-p. 250 Vdc/p. 6 kA Schneider C60H-DC	
Rectifier module OPUS HE	
OPUS USB, ConfUtility and manuals	OPTION 2 - 110VDC - 1 System
17217	17217 Temperature sensor 5m for OPUS DC system + 17473 AUX contact Schneider iC60N + 17474 Circuit breaker C10A 2-p. 72 Vdc/p 230/400VAC/p, 6 kA Schneider iC60N +

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	17475 Circuit breaker C16A 2-p. 72 Vdc/p 230/400VAC/p, 6 kA Schneider iC60N + 18076 MCB C32A 2-p. 72 Vdc/p, 230/400VAC/p 6 kA Schneider iC60N + 18077 MCB C63A 2-p. 72 Vdc/p, 230/400VAC/p 6 kA Schneider iC60N + 18063 VIDI2 System Controller - system monitoring and control - remote access to the system + 18064 VIDI2-EFD module KIT
18078	Wall mounting KIT R 12U IP21 OPUS HE
18059	Battery Midpoint measurement cable 5m
17466	Rectifier module MHE 24-1500 SPECIFICATION: Input: Uac 1L+N+PE 85/300 V, Iac: 12.5 A, f: 45-66Hz, Output: Udc 21/27.24/33 V, Idc 62.5 A, Pdc 1500W, Eff: 96%, MBTF: 1840000h. HxWxD: 169x83x357 mm, IP20, 4.6kg Circuit cooling, front connection
Rectifier module MRC 24-1100	Mechanical specification: Dimensions: 460 x 83 x 350 mm Weight: 4.6 kg
Rectifier module MRC 110-1600	Mechanical specification: Dimensions: 230 x 83 x 350 mm Weight: 4.6 kg
RECTIFIER, MRC 24-1100-92G310	
RECTIFIER, MRC 110-1600-92G300	
18581	Rectifier module MRC 24-1100 Mechanical specifications: Dimensions: 169 x 83 x 357 mm
17327	Rectifier module MRC 110-1600 Mechanical specifications: Dimensions: 169 x 83 x 357 mm
17934	OPUS UIF user interface unit for system controllers Wall or door installed interface unit Price is EXW Estonia or Finland
18582	VIDI+ System Controller 94G900 for OPUS DC systems Dimensions:

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	H 218 x 41 x 88 mm
18583	LMC-EXT EXTENSION UNIT to LCM6 leakage Accessory to LCM6 leakage current monitor unit Price is EXW Estonia or Finland

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.