

## Enotec



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Enotec** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Enotec T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">20533-111291</a>	
<a href="#">Ersatzsonde fur ECO-10002110</a>	
<a href="#">FEP-0007</a>	
<a href="#">HEI-2001 + HEI-2001-BP</a>	
<a href="#">KEF-200X</a>	
<a href="#">KES 132.1 (120480)</a>	
<a href="#">KES-1000 InSitu-02-Sonde (Grundgerat), Nr. KES-10000000</a>	
<a href="#">KES-7000</a>	
<a href="#">KEX6002EX</a>	
<a href="#">MLT Z02-0002EX</a>	
<a href="#">MSR-6001EX</a>	
<a href="#">MT2-2001</a>	
<a href="#">MZD-0001</a>	
<a href="#">O2-Sonde KES-2003; Nr. KES-20030000</a>	
<a href="#">OXITEC 5000</a>	
<a href="#">OXITEC 5000 ECO</a>	
<a href="#">OXITEC KES-1000</a>	
<a href="#">PROBE, O2, 18IN</a>	
<a href="#">SIK-132X</a>	
<a href="#">SIK-2001</a>	

<a href="#">SIK-2002</a>	
<a href="#">SIK-2002-R</a>	
<a href="#">SIK-5001EX2T</a>	
<a href="#">SME-53210010</a>	
<a href="#">SMF-200X</a>	
<a href="#">Z02-6001EX</a>	
<a href="#">ECO-10002110</a>	
<a href="#">ECO-1100114E-H2</a>	
<a href="#">SME-5321901Q</a>	(PROBE:KES-2002Q82)
<a href="#">COMTEC® 6000 DustEx</a>	Device shall measure oxygen, carbonmonoxide, humidity and%C values.
<a href="#">OXITEC 500</a>	Seri No : 450512 Voltage : 230V Current : 10 A
<a href="#">COMTEC 6000 CO SENSOR</a>	
<a href="#">OXITEC5000</a>	OXYGEN PROBE DISPLAY SET   ZIRCONIUM O2 ANALYZER
<a href="#">OXITEC 500E</a>	Extractive O <sub>2</sub> Analyzer
<a href="#">Fep-0002</a>	
<a href="#">Kex-50011115a0</a>	
<a href="#">Sik-132x</a>	
<a href="#">Kes-2002</a>	PROBE 6FT 115V
<a href="#">Kes-132010</a>	
<a href="#">Sme-5-3-1-1-0-0-0</a>	
<a href="#">Kes-1321000</a>	
<a href="#">Z02-0001</a>	
<a href="#">Eco-1100105e</a>	
<a href="#">999999</a>	
<a href="#">Zo2-0001</a>	
<a href="#">Zo2-0011</a>	
<a href="#">Oxitec 5000 Eco</a>	
<a href="#">Kes-2004104</a>	
<a href="#">120554</a>	
<a href="#">Fep-0009</a>	

<a href="#">Oxitec Kes-1000</a>	
<a href="#">Zo2-0001for Model Kes132x</a>	
<a href="#">Sme-5</a>	
<a href="#">L-O-000035</a>	
<a href="#">L-O-000080</a>	
<a href="#">Sik-2002</a>	
<a href="#">Sme-5d2f0030</a>	
<a href="#">Kes - 132000s</a>	
<a href="#">Fep-0009-Cg2</a>	
<a href="#">Kes-10004000</a>	
<a href="#">O2-Sonde Kes-5002; Nr. Kes-500200000</a>	
<a href="#">Test Gas - And Reference Air Supply</a>	
<a href="#">Sme-52110000</a>	
<a href="#">Oxitec 5000 Plu-0025 29329372</a>	
<a href="#">Aquatec 1000 ,Order No. 20533-111291 ,Probe Type : Sme- 53200k10</a>	
<a href="#">Kes-10003000</a>	<p>OXITEC Economy sintered metal filter disc Length: 500 mm The filter head is made of corrosion-resistant stainless steel 1.4571 (316ss) and has a sintered metal filter. The basic probe has a filter head with a length of approx. 500 mm, whereby the probe reaches this immersion depth. Larger immersion depths are through correspondingly longer filter heads achieved. The filter head is located in the flue gas duct at the probe tip above the ZrO2 sensor. It is a diffusion filter, even at high dust loads not polluted. For checking the measuring accuracy and at Calibration of the OXITEC-O2 analyzer system is done with air or a any other test gas, with known O2 concentration, the filter volume rinsed and test gas instead of flue gas is measured.</p>
<a href="#">Enotec-Pr3;Fgas-Und-Referenzluftversorgung-Istanbul-Turkiye</a>	
<a href="#">Kes-2003</a>	PROBE 3FT 115V
<a href="#">Kef-200x (120320)</a>	
<a href="#">Eco-00200000</a>	
<a href="#">Oeb-52142s01</a>	
<a href="#">Kes1321</a>	
<a href="#">Kes2002-4-2-0</a>	

[Kes-132090](#)

[Oxitec-5000](#)

GAS ANALYZER SYSTEM FOR O2

[Kes-10000000](#)

OXITEC Economy InSitu O2 Probe 1.4301 / 1.4307 / 1.4571, flange: DN65 PN6 probe Probe model: KES-1000 (basic unit without filter head) Immersion depth: 300 mm \*\* (other lengths see order code) Filter unit: sintered metal 20 µm \*\* Degree of protection plug: IP20 (others on request) Probe material: 1.4571 / 1.4301 Max. Flue gas temperature: 400 ° C Ambient temperature probe: -40 ° C to +80 ° C Flue gas pressure: ± 50 mbar Flow rate: 0-50 m / sec Flange: similar to DN65 PN6 O 2 sensor Response time: approx. 0.5 seconds T-90 time: approx. 5.0 seconds (horizontal installation position) Measuring accuracy: better than 0.2% of the measured value Resolution: better 1 ppm O2 Measuring principle: zirconium oxide Sensor temperature: 800 ° C

[Eco-Ooo01100](#)

[Probe, O2, 18in](#)

[System Oxitec 5000](#)

[Enotec-Referenzluftpumpe-F3;R-Sme5-Artikelnr120554-Istanbul-Turkiye](#)