

Enzfelder

Garanti: 12 ay
Bu őrüne ait Tőrkiye ići kapı teslim fiyat ve teslim sőresi ićen teklifimizi almak ićen **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi ićen +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Enzfelder Markası, tedarik sőresi ićen lőrten bizimle iletiőime gećiniz.

Firmamız Enzfelder Tőrkiye Distribőrőrü veya temsilcisi deėildir. Firmamız sipariő durumunda, belirtilen őrűnlerde sadece Orjinal ve yeni őrűn teklifi sunmaktadır. Bu sitede gősterilen őrzel marka adları ve ticari markalar ilgili sahiplerinin mőrliyetindedir, talep durumunda kaldırılmaktadır.



őrűn	Aćıklama
Enzfelder	
Enzfelder	
SG0030-6-G-U-1(So)-60-M1U-00-B-F-S	140581 FREN spindle gear According to SMS subscription: 23002922 According to dimension sheet: MB0030.19845 Static tensile load: 30kN Dynamic tensile load: 30kN Static pressure load: 30kN Pressure load dyn.: 30kN Lateral forces: 0kN Euler case: III Useful stroke: 60mm Lifting speed: ? mm/min Drive power: ?kW Input speed: ?rpm Drive torque: ? Nm Starting torque: ?Nm Duty cycle: 20%/hour-30%/10min Anti-rotation device: on the system side Limit switch: on the system side Installation position: M1U Gearbox lubrication: Agip GRSM 2 grease Spindle lubrication: Klűberplex GE11-680 grease Ambient temperature: 20°C Environmental influences: none Vibrations: none Reduction: 6:1 Spindle: Tr30x6 Spindle extender: no Stroke per revolution of the worm shaft: 1mm Colour: Transmission primed + painted according to SMS specification Accesories: Spindle end 1 special M22x1.5x32mm leadership F Protective tube S Worm shaft on both sides B Documentation according to SMS regulations Material: Drawing number: SG0030.20612

133775 BG0050-28-G-1-225-M1U-00-B-F-S	FREN spindle gears According to dimension sheet: BG0050.15731b Tensile load stat.: 50kN Tensile load dyn.: ? kN Static compressive load: 50kN Dynamic compressive load: ?kN Lateral forces: 0 kN Euler case: ? Useful stroke: 225mm Stroke speed: ?mm/min Drive power: ?kW Drive speed: ?rpm Drive torque: ?Nm Starting torque: ?Nm Duty cycle: 20%/h- 30%/10min Anti-rotation device: yes - with key Limit switch: System side Installation position: M1U Gearbox lubrication: Grease Agip GRSM 2 Spindle lubrication: Grease-Klüberplex GE11-680 Ambient temperature: 20°C Environmental influences: none Vibrations: none Reduction ratio: 28:1 Spindle: Tr40x7 Spindle extension: Dimension spindle retracted UK gearbox up to and including spindle end 106mm Stroke per revolution of the worm shaft: 0.25mm Color: according to customer requirements, please specify when ordering Accesories: Spindle end 1 (M30-29 long) Guide F Protective tube S Worm shaft on both sides B on both sides 4xM10-12 deep-square dimension 55 for motor flange mounting
133250 SG0150-24-G-U-1-120-M1U-00-B-F-Sf	FREN spindle gears According to dimension sheet: MB0150.15358 VAI Seuthe No: 3113.17.111-404 Tensile load stat.: 150kN Tensile load dyn.: ?kN Statical compressive load: 150kN Dynamic compressive load: ?kN Lateral forces: 0kN Euler case: ? Useful stroke: 120mm Stroke speed: ? mm/min Drive power: ?kW Drive speed: ?rpm Drive torque: ? Nm Starting torque: ?Nm Duty cycle: 20%/h-30%/10min Anti- twist device: system side Limit switch: System side Installation position: M1U Gearbox lubrication: Grease Agip GRSM 2 Spindle lubrication: Customer-side Recommended grease Klüberplex GE11-680 Ambient temperature: 20°C Environmental influences: none Vibrations: none Reduction ratio: 24:1 Spindle: Tr60x12 Spindle extension: no Stroke per revolution of the worm shaft: 0.5mm Color: Gearbox primed RAL 5012 standard or according to customer specifications
Kgt102	
103650	
2	
4	
Sg0150-24-G-U-1so-320-M1u-00- Bso-F-S-VI45	