

Equilibar

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Equilibar Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Equilibar T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
electronic regulator	Electronic regulator that we can adjust the pressure between 0-100 bar we need In addition, electronically controlled 100 bar resistant proportional valves, valves etc. we need
PCS-C-3M-6P-IND-A-WE	Wire end to 6 pin industrial (3 meters) Power, analog and digital signal cable for Alicat instruments
PCS-C-1M-PL/Corded Jack-A-Volt	Power supply 24V/1Amp Plug-in Power supply Global Wall connector for Alicat Instruments
P/N FL2128	
P/N FL2124	
QPV1MANEEZP10PSGAXL	Air Regulator
PCS-DI-FDO4-G10	Equilibar Diaphragm for Back Pressure Regulator FD Series (set of 2 diaphragms) FDO4 Material and thickness: PGL 10.3 mil G10
PCS-DI-FDO4-G10-	Equilibar Diaphragm for Back Pressure Regulator FD Series (set of 2 diaphragms) FDO4 Material and thickness: PGL 10.3 mil G10

LF0	Research Seri Back Pressure Regulator
LF1	Research Seri Back Pressure Regulator
[GSD4SNT5A-NSCP30T40F10VV]	GSD4 Series Equilibr Precision Back Pressure Regulator Process port size: 1/2" Body material: SS316/316L Process port: NPT female Reference port thread: 1/8" NPT female Cap material [non-wetted]: SS316/316L Pressure rating: 30 psig/2 barg Temperature rating: 40°C Diaphragm material: F Virgin PTFE Grade 55 Diaphragm thickness: 10 O-ring material wetted: V FKM grade 75 O-ring material non-wetted: V FKM grade 75 Excluding mounting bracket O2 cleaning not included Certificate package: Not included
GSD4	[TBD Upon Order] GS Series Equilibr Precision Back Pressure Regulator Vacuum use: No GSD4 Process port size: 1/2" Body material: SS316/316L Process port: BSPP ISO 228 Reference port thread: 1/8" BSPP ISO 228 Cap material [non-wetted]: SS316/316L Pressure rating: 300 psig/20 barg Temperature rating: 100°C Diaphragm material: G Glass-reinforced PTFE Diaphragm thickness: 10.3 O-ring material betted: V FKM grade 75 O-ring material non-wetted: V FKM grade 75 Including mounting bracket O2 cleaning not included Certificate package: Not included
EHP-HFE-3GH Cable included	[EHP-HFE-3GH] EHP Precision Electronic Pressure Regulator with IP65 Housing Command input: 0-10 V Pressure Monitor: 0-10 V Calibrated Pressure Range: 0-300 psig Can be used to pilot operate Equilibr back pressure regulators
LF4 (Research Series)	
EPC Cable - 1.5m	[EPC Cable - 1.5m] EPC Cable - 1.5m Sensor/actuator cable, 8-position Free cable end On Socket angled M12 A-coded, cable length: 1.5 m
Gs3-Ss316	
Evr-Bd32ant0-Nscp30t60b10bbbb	
Evr-Bd12ant6c-Nacp30t60b10bbbb Vacuum Use Regulator With Integrated Manual Set Po	
Eq-1035 Gs Series Precision Back Pressure Regula	
Nlb32 (Npt)	
Gsd4sng4b-Nscp30t40f10vv	Equilibr GSD Series Precision Back Pressure Regulator Body Material Stainless Steel 316/316L Process Connection 1/2" NPT Female Inlet & Outlet Machining ports plugged with Stainless Steel 316/316L Wetted Pipe Plugs Dome Fitting 1/8" NPT Female Cap Material Stainless Steel 316/316L (non-wetted) O Ring Size 043 Viton Grade 75 O Ring Size 042 Viton Grade 75 Diaphragm Virgin PTFE, 10 mil, PTFE10 Pressure 30 psi Temperature 40 C
Power Cord Qbt	

[Evr-Bd16ant4d-Nacp30t60b10bbbb](#)

[Eq-1035](#)

[Evr-Bd32ant0-Nscp30t60b10bbbb](#)
[Vacuum Use Regulator With Integrated](#)
[Manual Set Po](#)

[Evr-Bd16ant4d-Nacp30t60b10bbbb](#)
[Vacuum Use Regulator With Integrated](#)
[Manual Set Po](#)

[S23786g\(Obslete Possible Replacement](#)
[Eq-1035\)](#)

[Evr-Bd12ant6c-Nacp30t60b10bbbb](#)

[Qpv1maneezn30ihgxcl](#)