

Fantinelli



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Fantinelli Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Fantinelli Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
SP 308 B2D V16.W04.V92	PRESSURE GAUGE Dial Size 150mm Connection 1/2" NPT-M Range 0/2,5 bar Accuracy class 1 Mounting Vertical / bottom connection Case Type Open front with blow-out rubber disc Case material AISI304 St St Case execution Dry IP55 "Zero stop" Internal on movement with elastic stop Pointer Micrometric adjustable V16 Methacrylate window W04 MONEL wetted parts V92 Individual calibration certificate 5 points rising pressure
Fantinelli	
Fantinelli	
SP 311 B2D	PRESSURE GAUGE Dial Size 200 mm Connection 1/2" Gas-M Range 0/600 Kpa Accuracy class 1 Mounting : Panel / 3 holes front flange / back connection Case Type Open front with blow-out rubber disc Case material AISI304 St St Case execution Dry IP55 Window methacrylate "Zero stop" Internal on movement with elastic stop Pointer Micrometric adjustable

Ürün	Açıklama
	Wetted parts AISI316 St St
PRESSURE GAUGE WITH CONTACT	Fantinelli model SP 308 B2F V26 / CM01-H Dial Size 150 mm Connection 1/2" Gas-M Range 0/400 bar+psi Accuracy Class 1 @ contact excluded Mounting Vertical / bottom connection Case Type Open front with blow-out rubber disc Case material AISI304 St St Case execution Oil filled IP67 Window Methacrylate Wetted parts AISI316 St St V26 Restrictor
Bp 322-D2	
Ps 499 35 ÷ 600 Mbar	
Ma 425	
Sp 200	
Ps 389 8 ÷ 160 Bar	
Ps 389 0,06 ÷ 1,6 Barr	
Cp 331-C	
Np 304-Ff	
Ps 489 5 ÷ 60 Mbar	
Mp 319	
Dp 460-C	
Ps 489 9 ÷ 250 Mbar	
Sp 115	
Ps 389 0,08 ÷ 4 Bar	
Fp 341	
Ps 489 1 ÷ 16 Mbar	
Sf 316	
Dp 460-D	

Ürün	Açıklama
Ps 389 0,09 ÷ 6 Bar	
St 375	
Fp 340	
Bp 322-A3	
Ps 399 0,1 ÷ 2,5 Bar	
St 381	
Ps 399 0,2 ÷ 4 Bar	
Sp 213	
Ps 389 0,06 ÷ 1 Bar	
Mp 320	
Sp 308	
Sp 108	
Dp 460-B	
Sp 208	
Sp 308 A1p V26.92	
Mp 420	
Ps 399 0,2 ÷ 10 Bar	
Bt 385	
Sp 315	
St 383	
St 379	
Dp 334-2	
Fp 342	
Bp 322-B2	
Sp 311	
Se 129-R	

Ürün	Açıklama
Dp 361-B	
Fp 345	
Sp 300	
St 374	
Fp 348	
Cp 330	
Bp 322-A2	
Dp 361-D	
Ps 499 20 ÷ 250 Mbar	
Cp 350	
Sp 111	
Dp 361-C	
Mp 419	
Fp 337	
Sp 308 B2d V09 / Ci 01-H	
Bp 322-C3	
Fp 349	
Ps 389 0,9 ÷ 60 Bar	
Np 301-Ff	
Dp 359	
Bt 392	
Fp 441	
Fp 347	
Sp 311-B2f	
Sp 2308 B2p Dn 100 X 1/2quot;Npt-M	
Sf 317	

Ürün	Açıklama
Sp 308 B2f V09 / Ci 01-H	
St 380	
Fp 337-V62	
Sp 211	
Ps 389 0,06 ÷ 2,5 Bar	
Dp 358-C	
Ps 489 15 ÷ 400 Mbar	
Ps 389 0,4 ÷ 25 Bar	
Ps 489 6 ÷ 100 Mbar	
Fp 346	
Fp 343	
Mp 321	
Np 306-Xk	
Tr 308	
Dp 358-B	
Dp 360-A	
Bp 322-D3	
Ma 325	
Ps 489 18 ÷ 600 Mbar	
Ps 389 6 ÷ 100 Bar	
Dp 360-D	
Ps 499 25 ÷ 400 Mbar	
Np 306-Fk	
Dp 358-A	
Dp 360-C	
Np 301-Xk	

Ürün	Açıklama
Fp 333	
Sp 100	
Fp 350	
Np 306-Ff	
St 378	
Fp 339	
Bt 387	
Np 301-Fk	
Mp 421	
Ps 389 0,6 ÷ 40 Bar	
Ps 399 0,2 ÷ 6 Bar	
Ps 389 0,15 ÷ 10 Bar	
Ps 489 0,7 ÷ 6 Mbar	
Sp 312	
Ps 489 9 ÷ 160 Mbar	
Se 129-D	
Pq 318	
Sp 112	
Se 129-A	
Dp 361-A	
Bp 322-C2	
Ps 489 2 ÷ 25 Mbar	
Cp 331-A	
Fp 351	
Ps 389 0,25 ÷ 16 Bar	
Dp 460-A	

Ürün	Açıklama
Fp 437	
Ps 399 0,1 ÷ 1 Bar	
Sp 308 B2f V90 / Ci 01-H	
Sp 313	
Sp 212	
Fp 338	
Dp 334-1	
Ps 489 5 ÷ 40 Mbar	
Dp 360-B	
Sp 308 B2f / Ci01-H / Fp335-R	
St 380 Kz2 V77 / Cm 11-Q / P3, Ns 150	
Sp 215	
Np 305-Ff	