



Feig Electronic

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Feig Electronic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Feig Electronic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
0185.001.00	
0943.001.00	
1577.000.00	
1686.001.00	
1887.000.00	
2349.000.00	
2557.000.00+2558.000.00	
3104.000.00	
3540.000.00	
3551.000.01	
3621.000.00	
4127.001.00	
4207.000.00	
5020.000.00	
CPR40.30-A	
ID CAB.USB-A, Art N: 1686.001.00	
ID NET.12V-B-EU	
ID NET.12V-B-EU, Art N: 1688.002.00	

Ürün	Açıklama
ISC.PRH101	
VEK E, Art N: 0185.001.00	
VEK M1H-A	
VEK M2E -2	
VEK M2E-A	
VEK MNE1-R24-A, Art N: 4196.000.00	
VEK MNE2-R24-C	
ID CPR40.30-USB Desktop Reader USB	Desktop reader incl. USB cable for reading and writing passive Transponder according to ISO 14443-A/-B and for communication with NFC devices (ISO 18092) for applications such as Access Control, ePayment, eTicketing, public transport, etc. Dimensions: 144 x 84 x 18mm
Id Cpr30 – Lcn9620 / Fcc Id Pjmcpr30	
VEK MNH1-R24-A	5013.000.00 Induction loop detector for presence detection - 1 channel Mounting: DIN rail (TS35) Housing (w x h x d): 22.5 x 94 x 94 mm, ABS plastic 12-24VAC/DC DIP switch 8-pin, USB interface Screw terminals, pluggable and color coded 2 relays (changeover contacts)
5862.000.00	TST PD2-RA-A0R Position encoder - Multiturn: RS485 interface A housing M8 connector, 4-pin
3258.000.00	TST PD-ME-B cable 10m Position sensor - accessories cable: M8 socket 4-pin, opposite side open 10 m shielded connection cable
5930.000.01	ID LRU1002X-EU Industrial UHF long-range reader in housing Dimensions (WxHxD): 190mm x 130mm x 50mm Protocols: ISOHost Mode, Scan Mode, Buffered Read Mode, Notification Mode Interfaces: LAN, USB, RS232, Wiegand M12 and M8 circular connectors

Ürün	Açıklama
5932.000.00	ID LRU DIN rail adapter DIN rail mounting kit for LRU3x00 and LRU1002 incl. 3 self-tapping screws (M4x10, Torx T20)
6602.000.00	ID ANT.U150/150-EU UHF mid-range antenna Compact, robust UHF antenna with SMA connector Frequency range: 865 - 868 MHz Dimensions: 151 mm x 150 mm x 14.5 mm
6832.000.00	ID ANT.U150/150 Antenna connection protective plate Material: 1.4301 (V2A)
1654.003.00	ID ISC.ANT.C6-A UHF antenna cable SMA/SMA 6 m (ID ANT.C6-A) H155 Coaxial cable for UHF readers and antennas with SMA connection Connector SMA - plug/plug Length: approx. 6m
Id Cpr30	
TST PD2-RA-A0R	Electronic Position Detector
TST PD-ME-B - Absolute Encoder Cable	
Id Isc.Prh101-Usb Hf	1524.001.01 ID ISC.PR101-USB HF Handheld Reader Dimensions (W x H x D): 231 x 100 x 80 mm Power supply: via USB (high powered) Transmitting power: approx. 0.5W Antenna: integrated
0036613	
Vek M2h	
Id Cpr30 - Lcn9620 / Fcc Id Pjmcpr30	