

Fischer



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Fischer Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Fischer Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
De90b20040p0000000000	Digital differential pressure transmitter PRO-LINE Measuring range channel 1 -25 + 25mbar Measuring range channel 2 no channel
DE2759M042BP00MW	Digital differential pressure transmitter Measuring range 0 ... 10 mbar Deviation from characteristic <= 1% Process connection plug-in nipple 6/4 mm and 8/6 mm hose Output signal / operating voltage 4 ... 20mA, 2-wire / 24VDC
67CFR-226 0-125 Psi-Regler	Anschluss des Reglers 1/4 " NPS
DVC2000 Series Digital Valve Controller	Single-acting, HART-based, digital valve controller. Temperature range is -40 to +85 deg. C Point-to-point signal: 4-20 mA Local display language: English Includes the CE mark for Europe Does not include mounting method, supply regulator, or drip pot. I/O Package: Digital Valve Controller Only Housing Style: B - Rotary and Sliding Stem Pneumatic & Conduit Connections: 1/4-inch NPT & 1/2-inch NPT Imperial Supply Pressure: 1.3 to 3.4 bar (20 to 49 psig) Approval: ATEX - Intrinsic Safe.
4KB 1-WIRE EEPROM	DS2433+
RNJ66T1199SN 014F395	RNJ JACK 11-99, 7 PIN, 20 SIZE
RNJ67T1199PN 014F395	RNJ PLUG 11-99, 7 PIN, 20 SIZE
DN40 PN40 EU03681738	
DVC2000 - AS PER SERIAL: F001176465	Construction: Aluminum Pipe Away Vent Connection: None Protocol: HART 5 Language: English Control Tier: Not App Action Type: Direct Diagnostic Tier: Auto Calibrate-AC Conduit/Air Port Plastic Plugs: No Approval Agency: ATEX Output/Supply Gauges: None Approval: Intrinsic Safe Custom Configuration: No Position Transmitter: No Input Signal: 4 to 20 mA dc Limit Switches: None Positioner Type: DVC2000 Housing Style: A Supplemental Attribute: Not App Relay Pressure Range: 3.4 to 7.0 barg (50 to 100 psig) World Area Selections: Conduit Connection: M20 Positioner Style: I/P Cable Gland: None Manu

DE85B21K42B90CMW0000	Differential pressure transmitter ECO-LINE Measuring Range: -25 .. +25 mbar Output Signal: 4 - 20 mA Supply Voltage: 24 V DC Pressure Connection: 6/4 mm and 8/6 mm hose successor model DE85
ME1201087BH90V00	0-0,6 BAR 4 -2mA 24 VDC
DVC6200 4-20 MADS PT-PT HARD	052-2015/1004714-1120-03-ATX Positioner, digital controller Digital Valve Controller
0-6 Bar DS11	
İscope Fmp30	
DE90580000P000000000	Digital differential pressure transmitter PRO-LINE Measuring range channel 0...60mbar Process connection G1/8 inside -Alu Output signal 4....20mA 3-wire Approval none
06401995	M12 coupling with 2 M PUR cable 5 pin
06401993	M12 coupling with 2M PUR cable 4-pin with coding steps
67CFRMAX SUPPLY : 250 PSISPRING RANGE :0-125 PSI	
DVC2000	F002636019
VALVE POSITIONER,FISHER,DVC6200-HC	
PRESSURE REGULATOR,FISHER,MR95L	
PRESSURE REGULATOR,FISHER,MR95H	
POSITIONER,FISHER,DVC 6200,ALUMINUM	
PST POSITIONER,FISHER,DVC6200-SIS	
DE90	PRESSURE TRANSMITTER-DE90 BASIC MEASUREMENT RANGE:100MBAR PROGRAMMED SCALA: 0...100MBAR / 0-10000 PA OUTPUT SIGNAL:4..20MA / 0-10 V EX ZONE 2-22
DVC2000 - AS PER SERIAL: F003660135	
DE85	
167DA SERIES	
NPS 1/4 67CFR PED	
2E859602202	
2N130902202	
2E859802202.	
2E669902202	
DVC6200	

DE3801N029FKWDMW	
E61 Initial plate seal GL NBR	
E61 plate seal GL NBR	
E61HHG plate seal GL NBR	
E61 frame ring GL NBR-	
E61HH frame ring GL NBR	
E61FFP start plate seal CL NBR	
E61FFP plate seal CL NBR	
E61 frame ring GL NBR--	
E61 frame ring GL NBR	
COULOSCOPE CMS2	Used for measuring copper-nickel coating thickness on zinc die-cast parts.
DE 27	DE 27 Differential Pressure Transmitter Measuring Range: -25 to +25 mbar Output Signal: 4 - 20 mA Supply Voltage: 24 V DC Pressure Connection: 6/4 mm and 8/6 mm hose Display: None
UP01L08M002S + BK-1-Z-1-Z-A	
UP01L08M002S + BK-1-Z-1-Z-A-KK	
DKBE-103-A-057-130 + E31 103.2/5.7+B	
SF 103 A057-130	
104234	Seri Nr. 13818
104235-104234	
600-820 F1	
600-800	
Egab1.3	
600-782	
512 146	
13765x	
50491 Gb8	
De1602vdyyb9d128	
E32fra32	
E18pressin	

Frau27	
E28pressin	
Stopper-E	
5622	
1e845714012	
E61 Pi	
Akku Set Fmp (Nimh)	
2e859802202	
Dualscope Mp0r Usb	
I2p-100	
600-823 F6	
Ds21010a20bk0w00	
68060	
R667x000502	
600-025	
34b6283x012	
600-771	
Pt 100 Sonda	
Ea14a	
E3 1031.1/6.2 S	
2bst.006009	
Ds21010a20bkw00u0006	Component tested differential pressure measuring and switching device Measuring range 0 ... 0.6 bar Application Thermal oil DIN 4754-2 / water flow 100 Component tested differential pressure measuring and switching device Measuring range 0 ... 0.6 bar Application Thermal oil DIN 4754-2 / water flow 100 Double scale: bar (outside) / psi (inside)
F.0005.5765 [ex.562-443-230]	
E51	
Rpackx00112	
F.0007.3301 [ex.568-293-088]	
1e825827082	

E3 1031.1/6.7 S	
Deltascope Fmp10	
Fhb-A Dyn 16 X 125/50 - 092036	
5624	
E58	
568.490.088	
61224	
Dbee 105z 049-120	
E18 Pi	
E61	
809623.03.037	
605-097 (Ex. 604-555) Dualscope-Mp0r	
48-187	
600-822 F4	
De46 L70041pn03mw	Dig.Differenzdr. Switch / Transmitter Basic measuring range - 100 ... +100 Pa
2450-7I	
De45	
67cfr-226	
Br225-Mc 163/24, 24vdc, Kvs=20 M3/H, Dn40/16	
Frau 32	
48-204	
26a5300x022	
601-793 Egab1.3	
1p788102192	
Isoscope Fmp 10	
E31043/87+b	
De45d80040pk03mw	
10a4557sxbn	FLOW METER
61209	

505528	
Ds3105fm29a1	
M8	
601-793	
Art.No. 602-221 Egab1.3-Fe (Order No. 901-735)	
S104a092-130	
562-089-101	
600-792 2.2mm Grun	
E61pressin	
Frau 27	
603-476	
De1602vdyyb90k00d0579	
7502	
99-903	
48-186	
48-183	
685b689u02	PC BOARD ICOM L-BOARD
00623-50522	
E40pressin	
685b737u01	PC BOARD MEMORY Q-BUS
600-769	
603-384	
600-226	
686b704u01	ETHERNET CARD
E40 / E61	
53mc5412a25bafxcxxxx	PROCESS CONTROLLER 120/240VAC 36VA
40pb3202a	I/O BOARD MODULE D-LOOP FOR HARMONY DCU SYSTEM
Fp-7	
Me12	ME12 pressure transmitter 0-600 mbar 4-20 ma G1 / 2 "
D10a1198r	

M10	
Stopper-A	
Ve3514tr7081	
00627-50558	
De505401f11e	
Aa/Mignon	
Bp9733-500	
50dpf110-3/Bvvabaaa-En	TRANSMITTER 24VDC OUTPUT MADC 4-20 RANGE 1-150 WC
513 226	
50pz1262b1x2	FLOW METER CONTROL UNIT
53su1111a1bdx	SUPERVISOR
De27b2m045bp00mw De27b2m042bp00mw	
E50/51	
26a5288x032	
562-089-000	
Tw30 B190k000	
Fmp20 / 605-023	
Da0234801	
Fp7	
53mc2112a1xdx1	PROCESSCONTROL 120V 50/60HZ
E32	
61180	
600-434	
5621	
53mc5111a25baxdxaxx	PROCESS CONTROLLER 120/240VAC 36VA
Ptc00-3-2024	PRESSURE TRANSMITTER 12-45VDC 0-600VDC 4-20MA
53mc4211a1bb1	PROCESS CONTROLLER DIGITAL 120V 50/60HZ
E6	
00626-50557	
Sch 1216	

Isoscope Fmp 30	
600-829 F11	
040771	
53mc5412abab1cxxxxx	PROCESS CONTROLLER 120/240VAC 36VA
600-772	
Dualscope Fmp20	
600-770	
11767258	
26a5316x012	
39a8550x032	
562 337 460	
40dp2000c	DCU CONTROLLER DISTRIBUTED CONTROL UNIT
18-999-4542	
95v 25w Att.Ba.2	
H1000aq	
53mc5412a24bbxxxxxxx	PROCESS CONTROLLER
61176	
600-791 (1x10)	
16a5544x052	
685b719u01	Q-BUS MEMORY BOARD
1000840.01.005	
E28 Pi	
Me11	ME11 pressure transmitter 0-16 bar 4-20 ma G1 / 2 "
605-097	DUALSCOPE MP0R Handheld measuring device with integrated measuring probe for coating thickness measurement after magnetic induction and eddy current method Characteristics: - Intuitive operation with menu navigation and graphic display - The display automatically rotates like a smartphone - Wear-resistant carbide probe pole - Measurement modes: Standard, IMO PSPC (90/10 rule) and SSPC-PA2 - Measurement memory: 10,000 - USB interface for bi-directional data transmission - Support CD with software FISCHER DataCenter for evaluation and archiving of Measured values as well as PC-DATEX software for data transmission in Excel - with shock protection made of rubber - Manufacturer certificate - Measuring ranges: 0 - 2000 µm NE / Fe, 0 - 2000 µm Iso / NE The price includes case, protective cover, interface cable MP0R-USB, Carrying

	strap, 2 batteries operation manual
Ds3111ade09p1b2ba126	MAGMETER 1 INCH TUBE 285 PSI MAX
600-225	
D55ax1100aa	
De505401p11e	
16a5415x332	
600-768	
De46 Differential Pressure Transmitter	Flow rate: 32440 m ³ / h Pipe inner diameter: 792 mm. (800 x4 mm.) Pressure: 800 mmSS Temperature: 20 ° C Altitude: 568 meters Air Monitor - Volu Prob - 1 aluminum pitot traverse (2 pieces)
602-406	
50dpf100-2-Bvvbb-Ca-Ns	TRANSMITTER PRESSURE DIFFERENTIAL 24VDC 4-20MA OUT
50xm13bxad11aahd224	FLOWMETER 110V 0/6GPM SIGNAL CONVERTER MAGNETIC
E40 Pi	
De27	DE27 pressure transmitter -25 +25 mbar 4-20 ma 24 v dc
48-203	
Art.No. Ds1102va21b10w00	
Tam12(Ex.Slm12c/Bull-Te12x0)	
53mc5412a25bac2dxxxx	CONTROLLER 120/240VAC 36VA
E120	
Ega-2h	
40pb3201a-Re	I/O BOARD MODULE A LOOP FOR HARMONY DCU SYSTEM
Ab25/90	
De2599koyyykd373	
M56240042	
602-563	MANUFACTURING CERTIFICATE M
603-390	
685b500u01	PC CONTROLLER BOARD
600-793 (1x10)	
Egab 1.3 Maã223;E Bohrsel Und Router	
624b355u02	MOTHER/DAUGHTER BOARD W/DISPLAY

9005-12490	CHART RECORDER MODEL 1390
1036777 Rietschoten 12424	
D50-Xm14-Bbax00	SIGNAL CONVERTER 120V 60HZ W/LED DISPLAY
685b522u04	SENSOR CARD
De46 L20041pn03mt	Dig.Differenzdr. Switch / Transmitter Basic measuring range - 50 ... +50 Pa
104	
09173	
E41 Pi	
10w921u01	
10b4657x012	
Anotest Ymp30-S 603-800	
De160vdyyb90k00d0579	
685b522u01	FET AI MUIX BOARD
Kleb	
Fk50	
40lc-1211a	CONTROLLER DUAL LOCAL DCI-4000 DLC
1321cbb01bcx11	CHART RECORDER MICRO-DCI
53mc5111a25bacdxaxx	PROCESS CONTROLLER 120/240VAC 36VA
1-Magmeter-Tube	TUBE 1INCH MAGMETER MAX 285 PSI
10201451	
De2699041yyld187	
Ds21040a23ak0000	
10a4555pxbh	FLOW METER
De1602vdyyb9d128 W597 Oil Flow Meter	
10a4658s	FLOW METER VA MASTER 689KPA 100PSIG 100F
846-738-2452375	
40pb3204a	I/O BOARD MODULE CIO FOR HARMONY DCU SYSTEM
00625-50556	
43676	