

Flowrox

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Flowrox Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Flowrox T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
FR87503227	PVE100AKLVC10-333LF, SBRT Hose pinch valve in DN100 - Closed valve housing - Nominal size: DN100 - Installation length: 250 mm - Single-acting pneumatic drive with mechanical spring (fail close), min. supply air 6 bar, with electro-pneumatic positioner Siemens Sipart PS2 6DR5510-0NG00-0AA1, the Standard input signal is between 4 and 20 mA and an increasing signal value leads to Closing the valve - Flange holes: DIN PN 16 - Max. Working pressure: 10 bar - Material valve housing: aluminum epoxy coated - L = with opening tabs - Sleeve material: SBRT (styrene butadiene) - Max. Operating temperature: 110 ° C - F = filter regulator with pressure gauge - Customs tariff number: 84818099 - Country of origin: Finland - Weight per valve: approx. 110kg
FR87502817	SKW100M10-30S0-NR Intermediate flange knife gate valve in DN100 - Knife slide plate material: AISI 316 - Nominal size: DN100 - Housing material: gray cast iron / steel welded with epoxy coating - handwheel (open / close) - Max. Operating pressure: 10bar - Flange holes: DIN PN 16 - Installation length: 57mm - Max. Operating temperature: 75 ° C - Ring cuff: NO - Flush connections - Customs tariff number: 84818061 - Country of origin: Finland - Weight per knife

	pusher: approx. 30kg
FR87503228	SKW150AU2010-30S0-NR Intermediate flange knife gate valve in DN150 Material knife slide plate: AISI 316 - Nominal size: DN150 - Housing material: gray cast iron / steel welded with epoxy coating - Double-acting pneumatic drive with pneumatic spring (fail-open) and separate Air tank, min. 6 bar - Max. Operating pressure: 10bar - Flange holes: DIN PN 16 - Installation length: 64mm - Max. Operating temperature: 75 ° C - Ring cuff: NO - Flush connections - Customs tariff number: 84818061 - Country of origin: Finland - Weight per knife pusher: approx. 49kg
PVE40M10-631L	DN40 PN10 PVE
ROTOR ASSEMBLY PERISTALTIC PUMP-LPP-T65	TROYA PROSES-FR-Q350358
HOSE GUIDE LPP-T65 LPP-T65	TROYA PROSES-FRQ350750
ROTOR BEARING KIT PREST PUMP-KIT LPP-T65	TROYA PROSES-FR-80625
GEAR COUPLING PERISTALTIC PUMP	GEAR COUPLING LPP-T65-TRYPROS-FR-Q350358
FR87500139	SBRT10250/625/3L2 Replacement cuff SBRT for Hose pinch valve DN250 - Cuff Material: SBRT (Styrene Butadiene) - Pressure class: 10 bar - Inner diameter: 250mm - Cuff Length: 625mm - L = With opening tabs - Flange bores: DIN PN 10 - Max. working temperature: 110°C
FR87500139	SBRT10250/625/3L2 Replacement cuff SBRT for Hose pinch valve DN250 - Cuff material: SBRT (Styrene Butadiene) - Pressure class: 10 bar - Inner diameter: 250mm - Cuff length: 625 mm - L = With opening tabs - Flange holes: DIN PN 10 - Max. operating temperature: 110°C
LPP-T65GM10-2-0-N-D	
FXP65GM10-2-0-N-D,NR	
DN200	OPEN BODY VALVE SLEEVE
Fr87502439	PVE100A10-233LS, SBRT Pinch valve in DN100 - Nominal diameter: DN100 - Installation length: 250 mm - Double-acting pneumatic drive, min. Supply air 6 bar (open-close) - Flange bores: DIN PN10 - Max. Working pressure: 10 bar - Material valve body: aluminum epoxy coated - L = with opening tabs - Cuff material: SBRT (styrene butadiene) - Max. Operating temperature: 110 ° C - S = Magnetic proximity sensors