

Fluitex

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Fluitex Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Fluitex Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
40CM.FLUİTEX E 350-5	
45 CM.FLUİTEX E 350-5	
50CM.FLUİTEX E 350-5	
60CM.FLUİTEX E 350-5	
65CM.FLUİTEX E 350-5	
70CM.FLUİTEX E 350-5	
75CM.FLUİTEX E 350-5	
2022103059900	
2071108049900	
208000031 E 800/4 BREITE 1000MM	
208003041 (AD 800/5 LANGE 50M; BREITE 570MM; DICKE 5MM)	
E 800/5 260x7x250x4	
E 800/5.	
E.800	
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:450 mm used for All air slides FLUITEX® E 350/4
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:600 mm used for All air slides FLUITEX® E 350/4
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:800 mm used for All air slides 250METERS

Ürün	Açıklama
Muhlen Sohn Air slide clothes	(FLUIDIZING FABRICS) width:1800 mm used for All air slides FLUITEX® E 350/5
FLUITEX E 350/5	thickness:5mm width:450mm Material: Polyester Thickness DIN 53855:5mm +/-0 3mm 1 250 Meters Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
FLUITEX E 350/5	Width:600mm thickness:5mm Material: Polyester 2 250 Meters Material: Polyester Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
FLUITEX E 350/5	Width:800mm thickness:5mm Material: Polyester Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
FLUITEX E 350/5	Width:1800mm thickness:5mm Material: Polyester Thickness DIN 53855:5mm +/-0,3mm Pressure loss at 400m3/m2/h:350mmWg****+/-15% Weight:3350g/m2 +/-6% Temperature:-60 to 150 C short periods:200 C Tensile Strength: Warp: 6200N/cm +/-15% Weft: 4200N/cm +/-15%
Fluitex E 800/4 Rollenware	2011108049900
2012103459900	Fluitex AD 350 roll goods 20,14 m ²
An 350	Thickness: 5 mm-1000x1000 mm

Ürün	Açıklama
2011103059900	740 mmFluitex E 350/5 rolls
E800/5 R1	
269996040 (Ad 800/5 7200 Mm X 550 Mm)	
208000031 E 800/4 Breite 1000mm	
208000031 E 800/4 Breite 800mm	
269991040 600 X 400 Mm	
208003041 (Ad 800/5 Lă196;Nge 50m; Breite 570mm; Dicke 5mm)	
3	
Ad 800/5 (2111331500000)	
41507	
208000041 (E 800/5 Lă196;Nge 750m Breite 100mm Dicke 5mm)	
An350/5	
269996040 (Ad 800/5 1200 Mm X 1200 Mm)	
269991040 1990 X 1060 Mm	
Ad350/5 (41507)	
269991040 2450 X 1060 Mm	
208000041 E 800/5	
E 800/5	
Ad 800/5 (2111331300000)	
203000041 E 350/5	
269996040 (Ad 800/5 1610 Mm X 1610 Mm)	
269991040 2410 X 1060 Mm	
269996040 (Ad 800/5 750 Mm X 750	

Ürün	Açıklama
Mm)	
30755	
Ad350/5 (30755)	
20800004 Fluitex E 800/5 Pneumatikgewebe	
Fluitex An 350/5	
Ad 800/5 (2411338800003)	
1	
E 1600/5 (241358800000)	