

FLUX GERÄTE

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

FLUX GERÄTE Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız FLUX GERÄTE Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
10-457 01 003	Collector motor F 457EL 230V / 50Hz, 800W, IP24, USS With electronic speed setting, with undervoltage release, double insulated, protection class II, with overcurrent protection switch, 5 m cable and safety plug
10-41600100	470W/6bar with actuation valve (detectable), with silencer, with hose nozzle DN 10 for compressed air hose Ex marking: II 2G Ex h IIC T6 Gb HS Code: 8412 39 00 Origin: DE Weight/unit: 1.3790 kg
10-42422007	Drum pump FP 424Ex S-43/38-700, FKM With zone separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution: sealless in the liquid area Material: stainless steel (1.4571) Material shaft: stainless steel (1.4571) Shaft bearing: PTFE/carbon Material rotor: ETFE Seal material: FKM Immersion depth / outer Ø: 700 / 43 mm Pressure port: G 1 1/4 A Rotor: axial rotor without hose connection Driven by commutator motor, brushless Motor or air motor possible. *** (Alternative / optional position)***
10-42422010	Drum pump FP 424Ex S-43/38-1000, FKM with zone separation

Ürün	Açıklama
	Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution: sealless in the liquid area Material: stainless steel (1.4571) Material shaft: stainless steel (1.4571) Shaft bearing: PTFE/carbon Material rotor: ETFE Seal material: FKM Immersion depth / outer Ø: 1000 / 43 mm Pressure port: G 1 1/4 A Rotor: axial rotor without hose connection Driven by commutator motor, brushless Motor or air motor possible
10-42422012	Drum pump FP 424Ex S-43/38-1200, FKM With zone separation Ex II 1/2 G Ex h IIB T4...T3 Ga/Gb Execution: sealless in the liquid area Material: stainless steel (1.4571) Material shaft: stainless steel (1.4571) Shaft bearing: PTFE/carbon Material rotor: ETFE Seal material: FKM Immersion depth / outer Ø: 1200 / 43 mm Pressure port: G 1 1/4 A Rotor: axial rotor without hose connection Driven by commutator motor, brushless Motor or air motor possible. *** (Alternative / optional position)***
10-46000047	Collector motor F 460 Ex 230-240 V / 50-60 Hz Connection voltage: 230-240 V Rated power: 0.46 kW Frequency: 50-60 Hz Cable length: 5 m Plug type: CEE 7/7 plug Undervoltage protection: yes Motor protection switch: yes Speed control: no Protection class: IP 55 Ex marking: II 2 G Ex db eb IIC T6 Gb Cooling: externally ventilated Attention: Protective contact plugs must not be used in Ex areas! Ex-protected plugs (CEAG or STAHL) are available separately from us, on Can be installed upon request for an additional charge. - replaces part no. 10-46000006