

## Fotoelektrik Pauly

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Fotoelektrik Pauly** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Fotoelektrik Pauly T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">PP2445/308S</a>	/e4 /q /z3s /2stLU5 /24VDC Hole finder transmitter   Monitoring width 308 mm   Response time characteristic: q = 1.5ms   Plug connections for correspondence line to the recipient and for the customer connection   Switching output 2 x PNP complementary, 60mA, short-circuit proof   light and dark switching   Switch-on / switch-off delay 3 seconds, preset at the factory for a pulse lengthening of 1 s   Customer-supplied connection cable with pre-assembled plug not included in the scope of delivery   4 + 1-pole device plug   light / dark switchable   24VDC
<a href="#">PP2445/308E</a>	/e2 /q /1stLU5 Hole finder receiver   Monitoring width 308 mm   Response time characteristic q = 1.5ms   Connection plug   PNP, 60mA, short-circuit proof   4 + 1-pole device plug   Power supply from the transmitter
<a href="#">PP83201/2</a>	/R /e1 /1M16 /1M20 /z3s /1stLU5 /230VAC Power supply unit   10VA   for 1 hole finder system / pair of light barriers   Relay, -> minimum load 20mA   Optocoupler, 60mA, short-circuit proof   metric screw

	connection   Switch-on / switch-off delay 3 sec   4 + 1- pole device plug   light / dark switchable   230VAC
<a href="#">PP2445CC2</a>	/5m /2stLU5 Connection cable   plugs assembled on both sides (socket & pins)   4 + 1-pole device plug   Length: 5 m
<a href="#">JP105RFZ.55</a>	
<a href="#">1661Ex02</a>	PP2092/2E /e2 /i /stH7 /24VDC Light barrier receiver   PP2092   PNP, 60mA, short-circuit proof   Level indicator "DIANA"   6+1-pin connector   light/dark switchable   Constant light resistant 80kLux   24VDC
<a href="#">4354sx02</a> <a href="#">Pp2445/308s/E4/Q/Z3s/2stlu5/24vdc</a>	
<a href="#">Pp2441-E-154/R27/E2 4312s</a>	
<a href="#">Pp2441s/308/R153/220vac</a>	
<a href="#">2420x19 Pp83201/2</a> <a href="#">/R/E1/1m16/1m20/Z3s/1stlu5/24vdc</a>	
<a href="#">Pp83201/2/R/E1/1m16/1m20/Z3s/1stlu5/24vdc</a> <a href="#">Spannungsversorgung Des Suchsensors</a>	
<a href="#">Pp2445cc2/5m/2stlu5 Kabel, 5 M</a>	
<a href="#">Pp2441q/308/R153/R</a>	
<a href="#">Pp2441 Q/220/R28e/E2/1stlu5</a>	
<a href="#">Pp2441 Q/220/R28s/2stlu5/24vdc</a> <a href="#">Lochsuchsensoren (Transmitter)</a>	
<a href="#">Lichtschanke Cpv1037 /R/2m20/I/230vac</a>	
<a href="#">4350cc2x01 Pp2445cc2 /5m/2stlu5</a>	
<a href="#">7910x01</a>	
<a href="#">Jp105rfz.55 Stellungsgeber</a>	