

Frese

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Frese Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Frese T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
48-5525	Open/Close 24V NC with adapter M30x1.5 2,5mm Hub
53-1364	Frese Optima Compact controller DM IG/IG DN 15 High Flow rate 100-575 l/h 2.5 mm
58-8900	Actuator 24V AD/DC 4-20 mA DC, IP54 1m halogen-free cable and Wieland plug
Actuator motor for AHU LBM BOH 5 / CC system,	Model No 53-1296 - 1
modulating type valve DN 50 / PN 25 C AHU	LBM BOH 5 / CC system, Model No 53-1376 - 1
Valve Driver / Actuator motor for AHU LBM Main	Kitchen 1 / CC system, Model No 53-1297 - 1
modulating type valve DN 50 / PN 25 C AHU LBM Main	Kitchen 1 / CC system, Model No 53-1376 - 1
Valve Driver / Actuator motor for AHU LBZ BOH 1 /	CC + HC system, Model No 53-1296 - 2

Valve Driver / Actuator motor for AHU LBZ laundry	1 / CC + HC system, Model No 53-1297 - 2
Valve Driver / Actuator motor for AHU LGZ Con	Center 3 / HC system, Model No 53-1297 - 1
Valve Driver / Actuator motor for AHU LGZ Con	Center 4 / CC system, Model No 53-1297 - 1
Valve Driver / Actuator motor for AHU LRF GR 11 /	CC + HC system, Model No 53-1296 - 2
modulating type valve DN 50 / PN 25 C AHU LRF GR	11 / CC + HC system, Model No 53-1376 - 2
modulating type valve DN 50 / PN 25 C AHU LRF GR	7 / CC + HC system, Model No 53-1376 - 2
Valve Driver / Actuator motor for AHU LRF GR 8 /	/ CC system, Model No 53-1297 - 1
modulating type valve DN 40 / PN 25 C AHU LGZ	Business center 1 / CC + HC system, Model No 53-1375 - 2
Valve Driver / Actuator motor for AHU LBZ BOH 3 /	/ CC system, Model No 53-1297 - 1
modulating type valve DN 50 / PN 25 C, AHU LGZ	Con Center 1 / CC system, Model No 53-1376 - 1
modulating type valve DN 50 / PN 25 C, AHU LGZ	Meeting Room 1 / CC + HC system, Model No 53-1376 - 2
modulating type valve DN 50 / PN 25 C, AHU LGZ	Pre function 2 / HC system, Model No 53-1376 - 1
modulating type valve DN 50 / PN 25 C, AHU LBM	Gym 1 / HC system, Model No 53-1376 - 1
modulating type valve DN 50 / PN 25 C, AHU LBM	Gym 2 / HC system, Model No 53-1376 - 1
53-1296	24 V AC/ DC actuator Modulating 0-10 v/35s for Optima Compact DN40 - 50
Alpha 49-911 du 150 Pn 16	
53-1297 -	24 V AC/DC actuator DN50-DN125 for Optima flange DN 50-DN125
53-1352	Frese Optima Compact DN20 High Hub 2.5 IG/IG
53-1183	Actuator 0-10V 24V STROKE 2.5mm for OPTIMA Compact HUB 2.5 mm
53-1352 with 53-1183	Frese Optima Compact DN20 High Hub 2,5 IG/IG with Actuator 0-10V 24V STROKE 2.5mm
53-1296-	24 V AC/DC actuator DN 40-50 for Optima Compact DN40 - 50

TYPE-02 53-1297	VALVE ACTUATOR
53-1180	Actuator 0-10V 24V stroke 5.0 - 5.5 mm for OPTIMA Compact HUB 5.0 and 5.5 mm
53-1201-02	Optima controller DN65 LF PN16 including actuator Volume flow 4.4-25.0 m ³ /h
53-1375	Frese Optima Compact regulator DM DN40 hub 15.0 IG/IG Flow rate 1370-9500 l/h, stroke 15.0 mm
53-1376	Frese Optima Compact regulator DM DN50 hub 15.0 IG/IG Flow rate 1400-11500 l/h Stroke 15.0 mm
53-1202-02	Optima regulator DN80 LFPN16 incl. actuator with actuator volume flow 5.3-34.0 m ³ /h
53-1374	Frese Optima Compact DM DN32 Hub 5.5 IG/IG Flow rate 550-4000 l/h 5.5 mm
53-1353	
53-1354	
Type-01 53-1296	
53-2202	Frese Sigma regulator DM DN 20 Low IG/IG
53-2208	Frese Sigma regulator DM DN 25 Low IG/IG with 2 pressure measuring nipples - Volume range: 95-2,000 l/h
53-1302	Frese Optima Compact DN15 Low Hub 2.5 AG/AG Flow rate 30-200 l/h 2.5 mm
53-1308	Frese Optima Compact DN20 High Hub 5.0 AG/AG Volume flow rate 220-1300 l/h 5.0 mm
53-1317	Frese Optima Compact DN25 Low Hub 5.5 AG/AG Volume flow rate 280-1800 l/h 5.5 mm
53-1304	Frese Optima Compact DN15 High Hub 2.5 AG/AG Flow rate 100-575 l/h 2.5 mm
48-5528	230V actuator Stroke 2.5 mm, power consumption 2W
48-5526	230V actuator Stroke 2.5 mm
Combined Balance Valve	
02-53-1297 24v 50hz 6va 800n 60-30s Balancing	
Dn80 -29.7m3 / H 3 Way Motor Vehicle Valves	
53-1297	
Art Nr. 53-1297	24V AC / DC actuator Modulating 0-10V / 35s for Optima DN 50, 65 u. 80 Lot number 90329000 Weight: 1.9000 kg / 1.9000 kg

[Dn65 -29.7m3 / H 2headed Motor](#)