

Friedrichs Filter Systeme

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Friedrichs Filter Systeme Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Friedrichs Filter Systeme Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Fe B32.060.L2-P 139552	fluidtech® filter element - type B 60µm nom./100µm abs. Siebring- u. Lid made of 1.4301 including seal made of NBR
Fe B20.060.L1-P 139251	139251 fluidtech® filter element - type B 60µm nom./100µm abs. Siebring- u. Lid made of 1.4301 including seal made of NBR
141436	FE B50.060.L2-P fluidtech® filter element - type B 60 µm nom./100 µm abs. Sieve ring and cover made of 1.4301 NBR seal
FE B32.060.L2-V	fluidtech® filter element - Type B 60µm nom./100µm abs. Sieve ring and lid made of 1.4301 including FKM seal
138020	DF 4.222-A25.025.L2.B2-P.RL-5.22-2.0-f3.2.0 - drain G1/4 fluidtech double switching filter 4.222 DN25 PN16 according to Z.-No. 4.222-025.002-Z Materials: - Housing made of EN-GJL-250 - Rotary valve made of EN-GJL-150 - Aluminum filter hoods with G1/4 drain - Seals: NBR Connections: - Thread G 1 1/2 (without mating flanges) - Mounting threads 4 x M8 on the back - Flow rate: right to left with 2 built-in filter elements - 25µm nom./60µm abs., design L2.B2 (St vz. / VA / Delo) including differential pressure gauge type 5.22

Ürün	Açıklama
	- Measuring range up to 2.0 bar - Contact f3 at 2.0 bar - with DIN 43650 plug - Viewing lens deltaP® f3
131765	FE A25.025.L2.B2-P fluidtech® Filter Element - Type A 25µm nom./60µm abs. including NBR seal
DF 4.222-A50.025.L2.B1-P.RL-5.22-2,0-f3.2,0 Entleerung G3/8	fluidtech double switching filter 4.222 DN50 PN16 according to Z.-No. 4.222-065.001-Z Materials: - Housing made of EN-GJL-250 - Rotary valve made of EN-GJL-150 - Aluminum filter hoods with G3/8 drain - Seals: NBR Connections: - Flange connection IN/OUT plan with drilling pattern acc. to SAE J518-3 DN65 (2-1/2") (M12 - 88.9 x 50.8 mm; mating flanges not included) - Mounting threads 4 x M8 on the back - Flow rate: right to left with 2 built-in filter elements - 25µm nom./60µm abs., design L2.B1 (St vz. / VA / Delo) - Type designation A-50.025-L2.B1.P (filter area: approx. 4,050 cm²) including differential pressure gauge type 5.22 - Measuring range up to 2.0 bar - Contact f3 at 2.0 bar - with DIN 43650 plug - Viewing lens deltaP® f3
Fe A25.025.L2.B2-P	131765 fluidtech® filter element - type A 25µm nom./60µm abs. Including seal made of NBR Weight (item net): approx. 1.2 kg Volume (item net): approx. 2 dm³ Statist. Lot number: 84219990 Origin of goods: DE