Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Fsg Fernsteuergeraete

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Fsg Fernsteuergeraete Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Fsg Fernsteuergeraete Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Pk620miid-45	Präz.-plastic potentiometers 1576Z81-257.051 in synchro case size. 20 with 2 resistance levels with SD slopes Spinning grinder Resistance I 2 kÛ ± 20% Resistance II 2 kÛ ± 20% Active angle 355 ° each with flat solder connections, short design Shaft 6 mm Ý, length from edition 10.5 mm Wave No. 0003W52-02: 0110 Item weight: 0.076 KG
Pk1023-400	Precise plastic potentiometer in synchro flange housing size. 23 with feathering Spinning grinder Resistance 1 kÛ ± 10% Active angle 355 ° Encoder with PG screw connection with Deutsch plug u. Mating connector 242002-030DT04-3P / 242002-030DT06-3S as well as cable, length 300 mm Pin assignment 11 = A, 12 = C, 13 = B for mounting on SL ... GS130 / GS190 Turning left Item weight: 0.300 KG
PW45W3MII	1304Z10-000.001 Precision rotary resistance Type: PW45W3MII Wrapping: 2x90 / 1080/90 °, stops Resistance value: 2 x 5 kÛ ± 5%

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	to 1080 ° each Shaft diameter 6 mm, Length from support (LF1) 20.5 mm Item Weight: 0.120 KG
WEVi-3-38/N/K16	9242Z53-001.005 Electronic component in plastic housing K16 Input from the ind. Measuring head Output 4-20 mA Direct current at max 600Û corresponding to 0 - 90 ° Power supply 220V 50 Hz
WD620-02/A	Inductive rotary encoder 1708Z90-257.001 in cast housing with 7-pin. plug Connector with mating connector Protection class IP 65 finished device is painted with clear varnish Shaft 6 mm Ý Shaft length 36 mm from the housing support electrically usable angle 0-90 ° Output to separate electronics
PK613-46M	
WEVi-3-38/K16	9242Z03-001.043 Electronic component WEVi-3-38 / K16 in plastic housing K16 Input from the ind. Measuring head Output ± 20mA at max 600 Û corresponding to ± 30 ° i.e. -20 mA .. 0 .. +20 mA corresponds to -30 ° .. 0 .. + 30 ° Supply 20-30VDC / 60mA
1304Z10-000.001 Typ: PW45W3MII	Precision rotary resistance Wrapping: 2x90 / 1080/90 °, stops Resistance value: 2 x 5 kÛ ± 5% to 1080 ° each Shaft diameter 6 mm, Length from support (LF1) 20.5 mm Item Weight: 0.120 KG
SL3002-X1/GS80/ K/F Art.40720002	
1708Z03-096.013	precision rotary resistance PW70A

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	in cast housing IP40 (with PW 1700Z04-096.008) R = 5 kÛ ± 1%/180° stops Shaft 6 mm Ý length from support = 16mm with slip clutch Item weight: 0.440KG
1304Z10-000.001	Precision rotary resistor Type: PW45W3MII Wrapping: 2x90/1080/90°, stops Resistance value: 2 x 5 kÛ ± 5% to 1080° each shaft diameter 6 mm, Length from support (LF1) 20.5 mm Item weight: 0.120KG
1709Z03-360.002	precision rotary resistance Type: PW70IIAII-IP65 in the cast housing of type AII with 2 cable glands Degree of protection IP65 Drive shaft 6 mm Ý Length from pad 16mm Potentiometer PW70II (1700Z04-104.001) with 2 windings on common Winding body with 1 grinder each Winding angle: 70° each, stops with slip clutch Resistance value: 2 x 5 kÛ ± 2% on active angle each 70° Item weight: 0.550KG
1892Z15-265.003	G015-PK620d/MU-i01/2SeN/GS120/FL rotary encoder in the cast housing type GS120 with cable gland and flange Degree of protection IP65 Gear i = 30:1 underspeed, Low backlash gear Drive shaft 10 mm Ý with feather key and groove according to DIN 6885 with rotary encoder PK620d-MU-i01 Output: 4-20 mA = 0-355° at encoder power supply 18-36 V DC, with galvanic isolation Direction of rotation to the right on the drive shaft with adjustable via cam discs switches, number: 2 Item weight: 2,800KG
T-R SL3005-X2/GS130/K	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1302Z10-000.001	precision rotary resistance PW45W3 90 + 1080 + 90° stops R = 5 kÛ +/- 5% / 1080° Shaft 6 mm Ý 20.5 mm long
1304Z10-000.001	Precision rotary resistor Type: PW45W3MII Wrapping: 2x90/1080/90°, stops Resistance value: 2 x 5 kÛ ± 5% to 1080° each shaft diameter 6 mm, Length from support (LF1) 20.5 mm
AN-60-Z/MH-2L/S/H/02 [K;40m/s]	2028S52-008.001 Anemometer for wind speed 0-40 m/s with central attachment with rigidly attached wind cups with electronically controlled shaft heating Measuring system: magnetic Supply: 18-36V DC Output: 4-20mA into 500 ohms max in 2-wire technology electrical connection via cable, Length 2m
40720010	WIRE LENGTH TRANSMITTER SL 3050/GS 190
40720016	WIRE LENGTH TRANSMITTER SL3010 * Total weight 3,700 kg Commodity number: 90318020 Country of origin: Germany Region of origin: Brandenburg AL:N ECCN:N
PW-620-120/G90/IP65	
5930Z01-328.043	rope length sensor SL3010-PK1023-MU/GS130/G/F-01 in aluminum housing of type GS130 Cable length 10 m Measuring wire 1.35 mm Ý with bellows at the rope outlet with attached angle of rotation transmitter Type: PK1023-MU (5710Z03-257.001) Output 4 - 20 mA at max. 600 Û 2-wire technology, preset to 0 - 10 m Supply: 18-33V DC

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	electrical connection via plug Including mating connector
5930Z01-392.114	rope length sensor SL3015-PK1023-MU/GS130/G/F-01 in aluminum housing of type GS130 Cable length : 0 - 15m. Measuring wire diameter: 1.35 mm with bellows with attached angle of rotation transmitter Type: PK1023-MU (5710Z03-257.001) Output: 4-20mA at 600Û max Supply: 18 - 33V DC 2-wire technology preset to: 0 - 15m with straight connector
1304Z10-000.001	Precision rotation resistance Type: PW45W3MII Wrapping: 2x90/1080/90°, stops Resistance value: 2 x 5 kÛ ± 5% to 1080° each Shaft diameter 6 mm, Length from support (LF1) 20.5 mm
SL 3010 –X1 /GS 130 /K 01	Ger-Nr :15297643 Art-Nr :5930Z53-066.001 Meßlänge :10000 mm Max .Seilabzug :10200 mm Sell - ? :1.35 mm
5930Z01-080.075	Cable pull transmitter SL3010-MH1023-MU/GS130/G-01 in aluminum housing size GS130 Measuring length max. 10 m Measuring cable Ý 1.35 mm with built-in magnetic Rotary angle transmitter Type MH1023-MU (5754Z03-096.002) Output 4-20 mA Signal via rear Membrane keyboard programmable preset to 10,000 mm 3-wire system without galvanic isolation Supply 18-33V DC max. load 600Û

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	with mating connector (straight) including mating connector
5932Z01-328.144	Wire-actuated sensor SL3002-PK1023-MU/GS80/F-01 in aluminum housing of GS80 design wire-actuated length max. 2 m measuring wire diameter 1.35 mm wire-actuated outlet with bellows with attached precision transducer type: PK1023-MU (5710Z03-275.015) output 4 - 20 mA at max. 600 Ohm corresponding to wire-actuated length 0 - 2 m supply: 18-33 V DC 4-wire technology with galvanic isolation with plug connection, straight including mating plug
Seillangengeber SL 3002 X1 / GS 80 MEKA.	
5930E01-000.271	Measuring cable for cable length sensor SL3010/GS130 Cable diameter 1.35 mm consisting of: - 10.5 m fine cable - 1 x complete cable suspension according to drawing 5930Z02-65:00010 (corresponding to 5930E01-000.158) - 2 x cable ties EB205-0001
5930E01-000.209	separate cable guide roller for cable length sensor type series SL... /GS80 GS130 GS190 with bracket made of stainless steel sheet roller made of plastic according to drawing 0105BSL-..
1708Z03-320.030	Precision rotary resistor PW70A in cast housing IP65 (with PW 1700Z04-096.033) R = 5714 Û ± 2%/40° stops Shaft 6 mm Ý with slip clutch
1507647687 5686741	FSG PW70A9643 5KOHM 360 DERECE TAM TUR Precision rotary resistor

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Type: PW 70d / A / IP 65 Rotation angle: 360 Winding: 5 k ohm
1708Z03-96.018	PW70A in cast housing IP40 Shaft 6mm
1708Z03-065.011	Precision rotary resistor PW70dA in cast housing IP40 (with PW 1700Z04-065.117) R= 2571 Ω ± 2%/90° + 270° blind Shaft 6 mm Ø Lf1 = 16
1304Z10-000.001 5K PW45	
AN-60-P-MH-3L/S/02	Anemometer measuring range: 0-40m/sec, power supply: 18-36V DC, output: 4-20mA
Typ: Pw70a	1708Z03-096.052 Precision rotational resistance Type: PW70A in the cast housing of type A Protection class IP40 Potentiometer PW70 (1700Z04-096.033) Resistance value: 5714 Û + - 2% / 40 °, attacks Shaft diameter 6 mm Length from 16mm with built-in slip clutch Product weight: 0.400 KG
R-V-2k-02/K16	7522Z01-001.007 switchgear in plastic clamp rail housing Input actual value: 4 - 20 mA Min. / Max. Area code separate adjustable between 0 - 100% 2 output contacts as potential-free changeover contacts Load capacity: 250V, 2A, 50VA Supply: 20-30V DC, approx. 100mA
Pw 70a	Präzisionsdrohwiderstand PW 70A 96101507

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1575z12 001 001	
1570z60 000 009 Pw620 24	
1700z04 064 158	
1304z10-000.001	Typ: PW45W3MII Precision rotary resistance Wrapping: 2x90 / 1080/90 °, stops Resistance value: 2 x 5 k ± 5% at 1080 ° each Shaft diameter 6 mm, Length from rest (LF1) 20.5 mm Product weight: 0.120 KG
1500z05 064 073	
Pw1023-019/90	Encoder Angular Position - (PW1023-019/90) System: Potentiometric, Casing Mat: Aluminium, Protection of Degree: IP65, Angle of Rotation: 360°, Resistance element: Draht, Max Resistance: 10 k?, Linearity: +/-%0,2, Output: 4-20 mA, Supply: 18-33 VDC,FSG
Sl 3015 - 04 / Gs 130 / ...	Seillängengeber / Längensensor 99093405 AN5930Z01 - 128.022 Messlänge : 15000 mm max. Salabzug : 15200 mm Seil-Durchschnitt : 1.35 mm (1.4401) SL 3015 - 04 / GS 130 / ...
Art Nr.: 5930z01-072.028	
1708zc1-000.001	A housing empty with PG screw connection for installation of a PW70 Protection class IP40 Product weight: 0.300 KG
10601 Potentiometer Fg Pw613 180 18d	
1700z04 096 011	
Typ: Pk620miid-17	1576Z12-065.009 Precision plastic potentiometers Type: PK620MIId-17 in the synchro housing size 20 with 2 levels of resistance with SD slopes Screwing grinder with spiral grinder and hold-down

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Resistance 2 x 2 kÛ ± 10% Active angle per 355 ° each with center tap Shaft 6.35 mm Ý, sintered storage Length from the support 14 mm Product weight: 0.100 KG
1511z07 054 104	
Typ SI 3002/X1/Gs80/K/01	actuated encoder Type SL 3002 / X1 / GS80 / K / 01 Measuring drum circumference 204.8 mm Measuring rope diameter 1.35mm with rope attachment spec. f. Fa. GFM after Zg. 5932Z50-00: 15 Drum accuracy 0.05% without gear with adapter 5932Z01-00: 20A for servo flange, incl. coupling Center.Ý Partial.Ý Fastening. Wave Ý 50 mm 42 mm 3 x M4 6 mm Product weight: 1,250 KG
1304z10 000 001	
Ga-Dig-1sez/C/10/56	4279S03-000.003 Wind speed indicator in the panel housing Front frame 72 x 72 mm Measuring range 4-20 mA corresponding to 0 - 40 m / s Measured value representation via green LEDs with adjustable limit switch Power supply 20-30 V DC Product weight: 0.300 KG
1708z03-096.018	Precision rotational resistance PW70A in cast housing IP40 (with PW 1700Z04-096.038) R = 8.57 kÛ + - 1% / 60 ° stops Shaft 6 mm Ý Lf1 = 16 with friction clutch Dimensioned drawing 1708Z03-096M018D
1708z03-352.014	Precision rotational resistance PW70A in the cast housing IP65 (with PW 1700Z04-096.053) R = 9643 Û + - 1% / 60 ° stops Shaft 6 mm d

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Shaft No. 0001W01-0R: 0108 with friction clutch

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.