

Garlock



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Garlock Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Garlock Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
3125 - TC	DESCRIPTION: RING INSIDE DIMENSION(S): 0.787"ID OUTSIDE DIMENSION(S): 1.377"OD THICKNESS: 1/16"THK SHAPE: ROUND
PSSEALSO-68508	GARLOCK PS-SEAL special; Single lip; 50.0 x 68.0 x 8.0 mm; Housing: 1.4571; Lip: black gylon; Stat. Seal: FKM; Max pressure: 10bar; Preload: + 5mm; MEC04-10574
PSSEALSO-55728	GARLOCK PS-SEAL special; Single lip; 55.0 x 72.0 x 8.0 mm; Housing: 1.4571; Lip: black gylon; Stat. Seal: FKM; Max pressure: 10bar; Preload: + 5mm; MEC04-10288
kloruze 64X4083	Sealing technology
PSSEALST-709010	GARLOCK PS-SEAL standard; Single lip; 70.0 x 90.0 x 10.0 mm; Housing: 1.4571; Lip: black gylon; Stat. Seal: FKM; Max pressure: 10bar; Preload: + 5mm; MEC03-10039
GP2091-8K	Garlock Braid Pack; style 2091; 8x8mm; 12.7m/kg; 2kg/spool
(16,15) VAL05-10250	
(19) VAL05-10024	
04-10235	
06-550-003-G064	
07/12 mec 04-10368	
161825	
173090	
2051	
21017-3319	
21086-2441	

[21086-2462](#)

[21086-2468](#)

[21086-2798](#)

[21086-2927](#)

[21086-3059](#)

[21086-3176](#)

[21086-3228](#)

[21086-3316](#)

[21086-3355](#)

[21086-3388](#)

[21086-3406](#)

[21086-3426](#)

[21086-3456](#)

[21086-3492](#)

[21086-3548](#)

[21086-3596](#)

[21086-3606](#)

[21086-3642](#)

[21086-3917](#)

[21086-4502](#)

[21096-3426](#)

[21096-3578](#)

[21238-4147](#)

[21238-4311](#)

[21238-4615](#)

[21597-3355](#)

[21695-1807](#)

[21699-2321](#)

[21699-3436 53X3436](#)

[21852-3946](#)

21852-4093
22502-3390
229602
230966
24600-2377
24600-4614
24602-1187
24699-0181
24752-3963
25003-0893
25003-2522
25003-3059
25003-3548
25003-3917 23X3917
25003-4346
25003-6676
25003-7180 23X7180
25003-8665 23X8665
25003-A890 23XA890
25010-5386
25813-1923
29502-4490
29602-2215
29602-8011
29602-8137
29699-0145
3501 E
35106-6604
3545
3545 1500x1500x3,2
35450-6608

36906-6627
39000M7073
39505M2500
41606-2024
41606-2048
41606-3064
41691-2020
41691-2040
41691-3040
41691-3045
41925-2020
47909-78939001-QS
55X72X10MEC04-10876
7765X85X10PS
7770X90X10PS
7840X55X10PS
7855X72X10PS
78XXX
94314-0624
99905-0600
AK-122-W-MT-150
ANG-FAB01
ANG-FAB02
ANG-FAB05
ANG-FAB07
ANG-HYD05
ANG-KLZ01 21086-3510
ANG-KLZ03
ANG-MEC01
CMP05-10187

[CMP05-10188](#)

[FAB01-10036](#)

[FAB01-10097](#)

[FAB01-10669](#)

[FAB01-11063](#)

[FAB01-11229](#)

[FAB01-11312](#)

[FAB01-11385](#)

[GYLON@style 3504](#)

[KLZ02-10618](#)

[MEC 04-10278](#)

[MEC03-10043](#)

[MEC03-10052](#)

[MEC04-10006](#)

[MEC04-10078](#)

[MEC04-10082](#)

[MEC04-10112](#)

[MEC04-10144](#)

[MEC04-10154](#)

[MEC04-10221](#)

[MEC04-10292](#)

[MEC04-10313](#)

[MEC04-10321](#)

[MEC04-10368](#)

[MEC04-10549](#)

[MEC04-10642](#)

[MEC04-10695](#)

[MEC04-10749](#)

[MEC04-10800](#)

[MEC04-10892](#)

MEC04-11386	
MEC04-11597	
MEC04-11651	
MEC04-11704	
MEC04-11733	
MEC04-11912	
MEC04-12099	
MEC04-12122	
MEC04-12229	
MEC04-12762	
MEC04-12789	
MEC04-12879	
MEC04-13220	
MEC04-13882	
MEC05-10031	
MEC05-10317	
MEC04-10164 75* 95*13 08/10	
SHT06-10004	
TLDH100X80X10F	
VAL01-10026	
MEC03 -10039	
MEC03-10041	
WDRKM53-MRV	Oil seal Klosure model 53 7.750x9.000x0.625 Mill Right V Housing steel, design endless BTN: 84 84 20 000 / USA
Modell 151-125 x 140 x10	Rotary Shaft Seal
Modell 154-195 x 235 x 16	Rotary Shaft Seal
Gylon gasket M01 & M 02 Shell manway, 24",	, THK3*610 ID*746 OD, finishing 125-250-AARH) Note: The material in contact with the gasket is Jet A.
Gylon gasket, M03 Clean-out door, 900x1200,	THK4*1210 ID*1319 OD Actual dimensions for installed Gasket (1447*1137) Note: The material in contact with the gasket is Jet A.
PTFE/Gylon gasket 4.5 mm	THK, ASME B16.47. B SIZE: 26" * #150 (need photos) Note: The material in contact with the gasket is Jet A.

Spiral Wound Gasket,	SS316/FG, 4.5 mm THK, Carbon Steel O/R, SS316 I/R as per ASME B16.47. B SIZE: 26" * #150 Note: The material in contact with the gasket is Jet A.
21238-4333	
16x26x5mm Pure Graphite Gasket	
PSSEALSO-759513,0	GARLOCK PS-SEAL Special; tandem rotated; 75.0 x 95.0 x 13.0mm; housing: 1.4571; Lip: Gylon white; Static seal: Gylon blue; Max pressure: 5bar; Preload: +5mm; Drawing: Ga-5-6935 MEC04-10164
9.000x11.000x0.750	Oil seal Klozure model 53 9,000x11,000x0.750 inches; Mill-Right N Housing CRS version endless
11.000x13.000x1.000	Oil seal Klozure model 53 11,000x13,000x1,000 inches; Mill-Right N Housing CRS version endless
HMMLMGRAFIT20915X5	SALMASTRA GRAFIT GARLOCK 2091 5X5
HMMLMGRAFIT20916X6	SALMASTRA GRAFIT GARLOCK 2091 6X6
PSSEALSO-506510-3	Garlock PS Seal Special, Back to Back 50x65x10 mm housing 1.4571; Lip Gylon White Stat. seal gylon blue, max. pressure 10 bar, preload +-5.0 mm Drawing: Ga-5-8140
PSSEALSO-608010,0-2	GARLOCK PS-SEAL Special; single lip 60.0 x 80.0 x 10.0mm; housing: 1.4571; lip: F; Static seal: FKM; maximum pressure: 10 bar; preload: +-5mm;
WDRKM-MILL-RIGHT-23	Garlock Klozure Wellendichtring 25003-1953 23X1953 Mill-Right N Split; 8.465"ID 9.646"OD .493"THKv
PSSEALST-60758	GARLOCK PS SEAL Standard; single lip; 60x75x8.0mm; Housing 1.4571, Gylon lip black stat. Seal FKM, max. pressure 10 bar
PSSEALST-709010	GARLOCK PS SEAL Standard; single lip; 70.0 x 90.0 x 10.0mm; housing: 1.4571; Lip: Gylon black; Static seal: FKM; MaxPressure:10bar; Preload: +5mm;
2mm THICK GASKET 2626 O.D. X 2386 I.D.	GARLOCK 3200 (THE DRAWING IS ATTACHED - October 1 will be of 12 Pieces)
3mm THK RING TYP GASKET FOR 600	CLASS 150 FLANGE GARLOCK 3200
3mm THK GASKET, RING TYP FOR ASME B16.47 SERIES	B, 900 (36") CLASS 150 FLANGE GARLOCK 3200
WDRKM53-7,00060000,5	Oil seal Klozure model 53 6,000x7,000x0,500 Mill Right N Housing CRS, design endless MOLD 19289 KANBAN
9000-EVSP	
136,4 cm X 107,4 cm X 3,5 cm X 4 mm	a caustic-resistant gasket with 30 cambers and a temperature of 200 degrees
OD:1.625" x ID:1.125" Stack Height:1"	

Number of ri	
OD:1.125" x ID:0.5" H:1 1/16" Number of ring: 6	
OD:3.125" x ID:2.5" H:1 7/32" Number of ring: 7	
OD:1.625" x ID:1" H:32mm Number of ring: 6	
OD:5.25" x ID:4.0" H:" Number of ring: 7	
OD:2.625" x ID:2.0" H:1" Number of ring: 7	
GP5000-11K	Garlock Braid Pack; Style5000; 11x11mm; 6.4m/kg; 2.27kg/box
GP5000-7,9K	Garlock Braid Pack; Style5000; 7.9x7.9mm; 12.4m/kg; 2.27kg/box
GP5000-15,9K	Garlock Braid Pack; Style5000; 15.9x15.9mm; 4.54kg/box
WDRK-300040000,375	Garlock Klozure Oil Seal Model: 23; 3,000x4,000x0.375 inches; Mill-Right N; Execution: endless 25003-5023
WDRK-337545000,500	Garlock Klozure Oil Seal Model: 23; 3.375x4.500x0.500 inches; Mill-Right N; Execution: divided 25003-2324
GKBS0075EU 3/4"	
GKBS0100EK 1"	
GKBS0100EK 1,5"	
GKBS0250EK 2,5"	
GKBS0300EK 3"	
GKBS0400EK 4"	
GKDN020EK 114,3	
GKDN040EK 26,9	
GKDN050EK DN 20	
GKBS0450EK DN 40	
GKBS0075PE DN 50	
GKBS0100PE 3/4"	
GKBS0150PE 1"	
GKBS0250PE 2,5"	
GKBS0300PE 3"	

GKBS0400PE 4"	
GKDN020PE DN 20	
GKDN040PE DN 40	
GKDN050PE DN 50	
Garlock Gylon 3501 E 32x42x3 mm	
Gylon 3501 E 58,5x108x3 mm	
Gylon 3501 E 325x350x3 mm	
Gylon 3501 E 50X	
2328829	12X028X08 PS-SEAL GYLON-BLACK WDR. 012X028X08 Ps-Seal Gylon-Black Wdr, Goods tariff number 84879090 Country of Origin QU Unknown GARLOCK brand Manufacturer part number MEC03-10006
2034282	025X035X08 GYLON Oil seal sealing lip Gylon Black Weight 0.084KG Item weight 0.042 KG Goods tariff number 84879090 GARLOCK brand Manufacturer part number MEC03-10014
MODEL NO 64 20.5"X 22"X 0.75"	
MODEL NO 64 20.5"X 22"X 0.75"	
PSSEALSO-40287	GARLOCK PS-SEAL Special; single lip; 40x28x7.0mm; housing: 1.4571; lip: KF; Static seal: FKM Max pressure: 10 bar; Preload +4mm MEC04-11504
Type: 4632L2M-812.8*863.6*22.22L2M LOTG/1971/	20 COFI
Type: 4348-Model64	I.D. 736.6 mm O.D. 787.4mm THCK. 22.225, OD800-4910-602
End Seals , KG Tip , 620x333,90 Socket Weld	
Gasket(CMG) Graphite Coated SS-304 (Channel)	1/8" OD 19"(483mm) X ID 17 3/4"ID (451) Graphite Coated SS-304(or 316)
Gasket(CMG) Graphite Coated SS-304 (Channelless)	1/8" OD 19"(483mm) X ID 17 3/4"ID (451) Graphite Coated SS-304(or 316)
16"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)
14"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)
6"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)
4"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)

3"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)
2"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)
1.1/2"-150# FLAT GASKET	ASME B16.21, RF, for ASME B16.5, GARLOCK GYLON GS 3501 E, 3mm, (B50)
THERMa- PUR Style 4122-FC (36468-4025)	
SHAFT SEAL	660.4X711X2X22X22 MODEL 64-4325 MATERIAL RIGHT N (NITRILE) 10-11-03-2220- 61912/01
PACKING 127-AFP 3/16X3/16 INCH	
260X304X20 NBR-KLZ02-10544	"Special purchase - please note that the items cannot be returned." 260X304X20 NBR-KLZ02-10544 GARLOCK universal sealing ring 151-1 Nitrile
B2 VISCOSE FELT 180X210X15	
O RING DIN 3771 VITON 38X3	
O RING DIN 3771 220X4 VITON	
O RING 293X4 VITON	
ANG-FAB07 160x160	"Special purchase - please note that the items cannot be returned." Garlock cut; rectangle; 160.0 x 160.0 x 2.4 mm; rectangle; with 5 holes; according to customer drawing; GYLON EPIX white Style 3510 EPX
ANG-FAB07 190x190	"Special purchase - please note that the items cannot be returned." Garlock cut; rectangle; 190.0 x 190.0 x 2.4 mm; rectangle; with 5 holes; according to customer drawing; GYLON EPIX white Style 3510 EPX
ANG-FAB07 265x265	"Special purchase - please note that the items cannot be returned." Garlock cut; rectangle; 265.0 x 265.0 x 2.4 mm; rectangle; with 5 holes; according to customer drawing; GYLON EPIX white Style 3510 EPX
30x47x10 PS SEAL -	30x47x10 PS SEAL - Special purchase - please note that there is no return option for the items." MEC04-10097 GARLOCK PS-SEAL Special; Back to Back; 30.0 x 47.0 x 10.0 mm; Housing: 1.4571; Lip: GYLON Black; GYLON Black; Stat.Seal: FKM; Max.Pressure: 10bar; Preload: +5mm; Drawing: Ga-5-6711
53x2915/21086x2915	
21086/3426	
916492 53x4502	
MEC01-11526	MEC01-11526 - MEC01-11526 GARLOCK PS-SEAL
MEC01-11566	GARLOCK PS-SEAL

Model 23	GARLOCK KLOZURE MODEL 23
RP-RED P2SA34	OIL SEAL 140X160X35MM
50561N	Grayloc - 4" D31 rings seals P/N: 50561N--VS
MEC04-14307	GARLOCK PS-SEAL shaft seal, Dust lip, single lip 75x60x8.0mm Case: 1.4571 MS lip material, Stat.Seal: Gylon Blue, Max pressure: 5 bar; preload: +5mm PSSEAL-75608.0
MEC04-12703	MEC04-12703 GARLOCK PS-SEAL shaft seal, Dust lip, single lip 35x25x8.0mm Case: 1.4571 Lip: Gylon Blue, Stat.Seal: Gylon Blue, Max pressure: 5 bar; preload: +4mm
Split Pillow Block Bearing Isolator Labyrinth Seals	inner diameter: 85
GYLON 3501-E EPX	
21684-3574	OIL SEAL
180X220X15 mm Dummy	180x220x15 mm, PS-Special Sealing technology
21852-3921	Sealing technology Model 64 21852-3921 Garlock KLOZURE® Model 64 Shaft Seal, MILL-RIGHT V, CRS, 203.20 mm Shaft, 241.30 mm Bore, 17.48 mm Width
21247-3984	Sealing technology
21238-4093	Sealing technology Model 64 21238-4093 Garlock KLOZURE® Model 64 Shaft Seal, MILL-RIGHT N, CRS, 330.20 mm Shaft, 368.30 mm Bore, 17.48 mm Width
RG55005154151,0	Flat gasket made of Garlock® Style 5500 Ø 515 x 415 x 1.0 mm
140.170.13	
170.190.10	Viton oil seal
220.250.15	Viton oil seal
240.270.15	Viton oil seal
Mec04-10695 Dichtungps-Seal 55*72*10	
Ang-Klz01 26x7374 Mill-Right N 3.250"ıd4.250"od .500"thkartikel Nr. 24600-7374	
Gylon®?Style 3504	
1002666	
24600-7374 Ang-Klz0126x7374 Mill- Right N 3.250"ıd4.250"od .500"thk	
6av6á; 643-0cb01-1ax1	

21086-3510 Dichtung
23x6756.
21158-1360
35450-6608 Dichtungsplatte; 1500,0 X
1500,0 X3,2 Mm; Gylon Style 3545 Soft
24600-2364
2025du
29602-6648
Klz01-10068
Dn500 Helicoflex
41606-3064 Geflechtspackung ;
Packmaster 6 ;25,4 X 25,4 Mm ; 1" ;
4,536 Kg Box
9,5x9,5
6es7á; 407-0ra02-0aa0
Mec03-10033
Bb051010bp25
64
22502-3390 53g1x3390; Mill-Right V
Crs; 6.250" id; 7.250" od; .625" thk; Gylon
Excluderlip; Mold 17260
Ang-Mec05
21086-3596 53x3596 Mill-Right N Crs
8.000" id 9.250" od .625" thk
25003-6676 23x6676 Mill-Right N Split
9.250" id 10.250" od .500" thk U/C 00002-
1181
Mec04-10294
154 Fkm
Mec04-10329
5-234-10168-0
Gcsd-1.1 Abc, 3-999-04121
23
Mec03-10042
???03 -10039 Ps-Seal Back To Back

Bb101310bp25
Mec03-10013
Mec05-10317 Dichtung Ps-Seal45*62*10
39505m2500 Dichtungsplatte; 1500 X 1500 X 1,0mm; I F G 5500
21684-3574 Manschette Garlock Klokure
24602-1187 Klokure Wellendichtring; Modell:26; 1.969 X 2.835 X 0.315 Inch; Lippe:Mill-Right V
Bb051006bp25
Mec04-10289
21086-2468 53x2468 Mill-Right N Crs 3.750" id 4.999" od .500" thk Mold 18822btn: 84 000 84 20
22502-0796
5-236-10200-0
Tri-Clamp-8quot; 40 Mp-X Sealing
300x400x30x10
938807q
99905-0600 Ret Std Ring A-36 Steel 6.000" id 11.000" od Std Ansi 150
Mec03-10030
21086-3456 53x3456 Mill-Right N Crs Kanban 6.750" id 7.750" od .625" thk
Ang-Klz01 21699-2321 53x2321; Mill- Right V Crs; 3.375" id; 4.375" od; .500" thk; Mold 17344
7855x72x10ps 55 X 72 X 10 Psdichtring
6es7á; 422-1bl00-0aa0
1500x1500x2mm
Mec04-10549 Dichtungps-Seal 40*62*8
Mec03-10039
S-1,6mm
41606-3064 Dichtunggeflechtspackung ; Packmaster 6 ; 25,4 X 25,4 Mm ; 1" ;

4,536 Kg Box13,608 Kg
Sht06-10004 Graphitplatte; 1500,0 X 1500,0 X3,0 Mm; Style 3125 Tc
Mec03-10038
15418e
Ang-Mec04 Ps-Seal Sondergedrehte Lippe Gylon Schwarzstat. Dichtung Fkmabmessung:140 X 165 X 10 Mm
78xxx 40 X 62 X 8 Psdichtring
Mec04-12147
Type 1300 10ã215;10mm
Ang-Klz01
41691-3040 Geflechtspackung ; Style 2091 ; 16x 16 Mm ; 5 Kg Box
Cupplung 70x90x10
24600-0978 Garlock
21086-2468 Lippendichtung 53x2468 Mill-Right N Crs 3.750"od .500"thk Mold 18822
24600-7374 26x7374 Mill-Right N 3.250"od 4.250"thk Hot Mold 24600-7374 - Loc 71b
Ang-Klz01 25003-5118 Garlock Klozure 23x5118mill-Right N Split 4.724"od 5.906"od.500"thk
Mec04-11610
Ang-Fab07 Gestanzte Flachdichtung; 500,0 X610,0 X 3,2 Mm; Gylon Style 3500 Fawn
5889-6x6
Mec03-10002
Mec04-10064
2091r-1/8"
53x2225
Or4550
21238-3145
21238-4367

Mec04-10294 Dichtung	
41606-3064 Garlock Geflechtspackung ; Packmaster 6 ; 25,4 X 25,4 Mm ; 1" ; 4,536 Kg Box	
6se7022-1ep60-Z	
Kammprofile,Ø275xØ255x4mm	DICHTUNGSELEMENT: GRAPHIT METALLTEIL: 1.4571 DICHTUNGSELEMENT: GRAPHIT METALLTEIL: 1.4571 HINWEIS1: KLINGER Maxi-Profil Typ: LA2, Flexitallic-FLEXPRO THERMICULITE 845, GARLOCK Kammprofile 642A
Mec04-10892 Dichtung Ps-Seal 140x165x10	
24752-3963 59g1x3963 Mill-Right V Crs 17.323"id18.898"od .912"thk W/ Gylonexcluder Lip	
06-550-003-G064 Gleitringdichtungang- Mec05garlock Ps-Ii Seal Assyg5 Xe X1/S0/50mm	
111w-Dn125 Pn 16	
Mec04-10876	
N-2,4mm	
24600-0978	
Dn630 Helicoflex	
21086-3426 53x3426 Mill-Right N Crs Kanban6.500"id 7.500"od .625"thk Mold 17261btn: 84 000 84 20	
21086-2927 53x2927 Mill-Right N Crs 5.000"id6.500"od .500"thk	
6es7á; 431-0hh00-0ab0	
S	
Mec03-10031	
Mec04-11762 Dichtung Garlock Ps-Seal 55x72x10 10/13	
8,0x8,0	
Style 2091 ; 32 X32 Mm	
WDRK-506510	Garlock PS-Seal non-standard; Style: Single Lip; 50x65x10mm; case: 1.4571; Lip: Gylon white; Elastomer: Gylon white; pre-load: 5.00 mm MEC04-10075
5-236-10219-0	

1.07.08d17bh Hydraulic Filter
111lug-Dn80 Pn 16
Mec04-10876 Wellenabdichtung55x72x10
21086-3176 Manschette 53x3176 Mill- Right N Crs Kanban5.500" id 6.500" od .500" thk
Mec04-10500
Ptfe
Mec04-10077
Mec03-10001
21238-4499 Klozure 64x4499
21086-3426 Lippendichtung 53x3426 Mill-Right N Crs Kanban6.500" id 7.500" od .625" thk Mold 17261
24600-2462 26x2462 Mill-Right N 3.750" id 4.750" od .500" thk
2007677
Fab01-10036 Garlock Gestanzte Flachdichtung; 90 X 142x 2,0 Mm; Gylon Standard 3501 E
21017-3319 Klozure Wellendichtring; Modell 51; 5.875 X 7.000 X .500 Inch; Lippe: Mill-Rightn
Ang-Klz01 21086-2994
Mod 64 21238-4311 Dichtung
Mec04-10845
3545 1500?1500?3,2 Material
Mec03-10051
6es7á; 432-1hf00-0ab0
T64-4163
64.40.47
21086-3355 53x3355 Mill-Right N Crs Kanban6.000" id 7.000" od .500" thk Mold 19289
6es7á; 400-1ta01-0aa0

Mec03-10007
S-3,2mm
Mec04-10642 Dichtung Ps-Seal 140x165x10
21086-2462 Manschette Klozure Oil Seal 53
Type 1300 15,9ã215;15,9mm
Ang-Fab02 Zuschnitt; 300,0 X 300,0 X 0,5 Mm;Gylon Style 3522??
230966 Ens. Garniture + C- Face~gw~gcs~58~gnbeff
Ang-Fab01 Gestanzte Flachdichtung; 17,0 X23,0 X 2,0 Mm; Gylon Style 3501- Estandard
Type 1304 13ã215;13mm
Mec04-10730
Klz02-10618 Ang-Klz02v-Ring 1500material: Nbr
1a18eln08uc
21086-3492 Manschette
39 26 90 979
Mec04-10800 Ps-Seal40x60x10
21684--3574
21695-1807 63x1807; Mill-Right V Crs; 2.500"od;3.250"od; .375"thk; Mold 18957
41606-2048 Geflechtspackung ; Packmaster 6 ;19,1 X 19,1 Mm ; 3/4" ; 2,268 Kg Box
Mec04-10163
06-550-003-G064 Gleitringdichtung Mechanische
1002745
Ang-Mec01 Ps Lippe; Material: Gylon Schwarz;Abmessung: 60x80x1mm
78xxx 30 X 40 X 7ps Dichtring
.Manschette Garlock Klozure64x4284

Mill-Right V Crs 23.000"ıd25.000".875 Od"thk Nr. 21852-4284
21086-3316 Wellendichtung Flansch
80x100x10
Ang-Fab07 Gestanzte Flachdichtung; 350,0 X450,0 X 3,2 Mm; Gylon Style 3500 Fawn
Mec03-10036
Klz01-10032
21852-4075
Mec04-12448
Mec04-10728
Mec03-10022
21684-3574
25810-1840
Mec04-12075
P/S
Ang-Fab07 Gestanzte Flachdichtung; 500,0 X600,0 X 3,2 Mm; Gylon Style 3500 Fawn
Mec04-10085
Mec04-10728, 25x42x8 Ps-Seal Dichtung
Ang-Fab07 Gestanzte Flachdichtung; 200,0 X340,0 X 3,2 Mm; Gylon Style 3500 Fawn
Mec03-10013 Ps-Seal 25x42x8 12/14
M/M130x100x13
41691-3045 Geflechtspackung ; Style 2091 ; 18x 18 Mm ; 5 Kg Box
21086-3642 Manschette
Mec04-10264
24700-3943
29602-8663
41691-2040 Geflechtspackung ; Style 2091 ; 16x 16 Mm ; 2,5 Kg Box

Mec04-10064 Manschette	
6es7á; 431-7kf10-0ab0	
7840x55x10ps 40 X 55 X 10 Psdichtring	
Mec 04-10482	
1001954	
07/12 Mec 04-10368 Die Stopfbuchse Garlock Ps-Seal 100x130x13	
Manschette Garlock Klosure64x4325 Mill-Right N Crs 26.000" id28.000".875 Od"thk Nr. 21238-4325	
N-3,2mm	
Mec04-10328	Garlock PS-SEAL Special; Twisted Lip; 70x90x10mm; Housing: 1.4571; Lip: GYLON blue; Stat.Dichtung: GYLON Blue; MaxDruck: 5 bar; Bias: 5mm; Drawing: Ga-5-9552 BTN: 84 87 90 90 GERMANY
Mec04-10305	
Mec04-12028 Dichtungen Ps-Seal 30x40x7	
21086-3228 53x3228 Mill-Right N Crs 5.625" id6.625" od .500" thk Mold 18573	
2091r-5/16"	
2151	
Wellenabdichtung Ps-Seal 50x70x10 Doppelte Lippe Auf 5 Bar	
Type 1300 8ã215;8mm	
7770x90x10ps Ps Dichtring	
Mec04-10365	
Mec04-10239	
24600-7374 26x7374 Mill-Right N 3.250" id4.250" od .500" thk Hot Mold24600-7374 - Loc 71b	
41691-3045 3045garlock Geflechtspackung ; Style 2091 ; 18x 18 Mm ; 5 Kg Box	
Dx1.0x1.125x1.0	
Ang-Fab07 Gestanzte Flachdichtung; 450,0 X550,0 X 3,2 Mm; Gylon Style 3500 Fawn	

Dn50pn10
24600-0978 Machette
Mec04-10407
21238-4206
24700-3943 24700-3943wellendichtring
24600-0978 26x0978; Mill-Right N; 4.000"iđ;5.000"od; .375"thk; Hot Mold24600-0978 (32483) - Loc 67e
Mec04-10426
35-50-10 P/S-Seal Gylon
Ttf502qlbp2hg16e
6es7á; 421-1bl01-0aa0
999999950
24600-4557
55x72x10mec04-10876 Stopfbuchse: Dichtung 55x72x10mec04-10876 Ps-Seal
250x290x16
21699-3606
Mec03-10003
Q502210
23x45020.
21699-3606 Dichtung
6es7á; 971-0ba00
1500x1500x3,2mm
47909-7893
Mec04-10144 40x60x10
Klz02-10311
7855x72x10ps 55 X 72 X 10 Psgarlock Ps-Sealstandard;Einfachlippelippe: Gylon Schwarz
21086-3406 53x3406 Mill-Right N Crs 6.375"iđ7.375"od .500"thk Mold 15722
Mec04-10068

[21086-3176 53x3176 Mill-Right N Crs](#)
[Kanban5.500"iđ 6.500"od .500"thkbtn:](#)
[84 000 84 20](#)

[Ang-Klz01 26x0978; Mill-Right N;](#)
[4.000"iđ;5.000"od; .375"thk;Artikel Nr.](#)
[24600-0978](#)

[Ang-Fab01 Gestanzte Flachdichtung;](#)
[45,0 X52,0 X 2,0 Mm; Gylon Style 3501-](#)
[Estandard](#)

[24600-2462 Klozure Oil Sealang-Klz01](#)

[24600-4557 Klozure Oil Sealang-Klz01](#)

[Wc22du](#)

[41925-2020 Geflechtspackung ; Style](#)
[1925 ; 7,9x 7,9 Mm](#)

[35106-6604 Dichtungsplatte; 1500,0 X](#)
[1500,0 X1,6 Mm; Gylon Style 3501-E](#)
[Standard](#)

[15060du](#)

[Ang-Cmp12 Style G-200](#)

[P/S-Seal Gylon 28-47-10](#)

[24700-3943 Dichtung](#)

[31271](#)

MEC04-10355 - MEC04-10355 GARLOCK PS-SEAL special;
"Special purchase - please note that there is no return option
for these items." GARLOCK PS-SEAL special; single lip; 90.0 x
120.0 x 12.0 mm; Case: 1.4571; Lip: GYLON White;
Stat.Seal: GYLON Blue; Max pressure: 10 bar; Preload:
+5mm; Drawing: Ga-5-7529

[Mec04-12807](#)

[39505m2500 Dichtungsplatte; 1500 X](#)
[1500 X 1,0 Mm: Ifg 5500](#)

[25810-0335](#)

[4012583](#)

[21699-2321 53x2321; Mill-Right V Crs;](#)
[3.375"iđ;4.375"od; .500"thk; Mold](#)
[17344](#)

[Gf142n.38523-157065](#)

[25003-6676 23x6676 Mill-Right N Split](#)
[9.250"iđ 10.250"od .500"thk U/C 00002-](#)
[1181](#)

Mec05-10017
Ang-Fab07 Gestanzte Flachdichtung; 150,0 X225,0 X 3,2 Mm; Gylon Style 3500 Fawn
Mec04-10164
Type 2091 10ã215;10mm
Mec04-12028
121620bp25
Mec03-10019
173090 Garniture~gw~58~beff
111wdn200
111w-Dn50 Pn 16
Mec04-10129
Ang-Cmp11
Type 2091 15,9ã215;15,9mm
Ang-Mec03
21695-1807 Ang-Klz0163x1807; Mill- Right V Crs; 2.500"od;3.250"od; .375"thk;
154-M
Mec04-11605
63x1360
Ang-Fab03 Garlock Gestanzte Flachdichtung; 275,0 X290,0 X 1,6 Mm; Gylon Style 3510 Weiss
Hi-Graph Style 212 Nnk
29607-0682
1800x1850,8mm
1002667
53 X 2321 Mill-Right V Crs 3. 21699-2321
Mec04-10147
Type 1300 13ã215;13mm
Dn250
Garlock PS-SEAL Special; BackToBack; 70x90x10mm;

Mec04-11211	Housing: 1.4571; Lip: F; F; Stat. Seal: GYLON Blue; MaxDruck: 10bar; Bias: 5mm; Drawing: Ga-5-12043
01303373	
Meco4-10164 75* 95*13 08/10 Dichtung Ps-Seal	
60-80-8 Bafudslx7 Simrit 72 Nbr 903	
Mec04-11618	
161825 Contre-Face~gcs~58~q8e	
Rot-3501e	
Ps-Seal Mec05-10317 Seal 45x62x10	
64x8037	
24600-7374	
Ang-Fab07 Gestanzte Flachdichtung; 100,0 X170,0 X 3,2 Mm; Gylon Style 3500 Fawn	
Mec04-10334	
Mec03-10018	
6,4x6,4	
21852-4194	
21086-2468 53x2468 Mill-Right N Crs 3.750"i4.999"od .500"thk Mold 18822	
21852-8037	
Mec04-11874	
Mec04-10334 Dichtung Ps-Seal 75x95x10 Mm	
Ang-Fab03 Garlock Gestanzte Flachdichtung; 350,0 X336,0 X 1,6 Mm; Gylon Style 3510 Weiss	
21096-3578 Wellendichtung 53x3578 Mill-Es Crs 7/ 750"i4.925"od. 625"	
47909-7994	
V-Ring Assembly	Fi: 490/450X90MM
04-10235 Ps-Seal (40x55x10)	
3000 Gasket	Garlock 3000 Gasket Dimensions 3mm THK, OD = 222mm, ID = 168mm

206376
0-80-7 Ptfе Tp Zh530298-T78-1-V
Type 2091 8ã215;8mm
Ang-Hyd07
Mec03-10021
41691-2020 Geflechtspackung ; Style 2091 ; 8 X8 Mm ; 2,5 Kg Box
25003-7276
21086-2798 53x2798 Mill-Right N Crs 4.625"ıd5.625"od .500"thk Mold 16236
Ang-Klz02
Ang-Klz01 26x2462 Mill-Right N 3.750"ıd4.750"od .500"thkartikel Nr. 24600-2462
0000003
29607-5112
???03-10041 Ps-Seal Back To Back
Mec03-10010
24700 3940
22-40-8 P/S Seal Gylon
Eac10p020
Mec04 10321 70 X 90 X 10 Psps Dichtring
S-2,4mm
2-234-10176-2
39000m7073 Faserplatte; 1500,0 X 1500,0 X 3,0mm; Blue-Gard Style 3000
Mec04-10714
Mec04-10067
Klz01-10018
Klz01-10025
3x1500x1500
5889
Ang-Mec04

Mec04-12488
Ang-Fab07 Dichtung 3-610*500gylon
21238-4194
8922
Bb101316bp25
29502-4490 Iso-Gard; 15%blue Glass Filledptfe; 1.772" id; 2.756" od; .750" thk; .375" flange
24600-2364 Klozure Oil Sealang-Klz01
6es7á; 492-1al00-0aa0
Mec04-10796
Mec03-1004
Mec04 - 10297
7765x85x10ps 65 X 85 X 10 Ps-Sealdichtring
111w-Dn100 Pn 16
Mec03-10016
24600-2462
Mec03-10041
Klz02-10372
229602 Ens. Garniture + C-Face~gw~gcs~40~gnbeff
Meco4-10164 O-Dreh-Wellen-Ps-Seal, 75*95*13 08/10
111w-Dn200 Pn 16
Ang-Fab07 Gestanzte Flachdichtung; 460,0 X550,0 X 3,2 Mm; Gylon Style 3500 Fawn
Ang-Fab03
658510 65x85x10
21086-3426 53x3426 Mill-Right N Crs Kanban6.500" id 7.500" od .625" thk Mold 17261
Mec03-10026
39505m2500 Garlock Dichtungsplatte;

1500 X 1500 X 1,0 Mm; I F G 5500
Bb121820bp25
Ifg 5500
Mec03-10043 Dichtung Ps-Seal 80x100x10
Mec 04-10278 Ps-Seal 50/70 10
Ang-Cmp12 Style 1333-G Square
6es7á; 412-2ek06-0ab0
21017-3396
01303328
21699--3606
21086-3176 53x3176 Mill-Right N Crs Kanban5.500"id 6.500"od .500"thk