

Gce

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Gce Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Gce Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
EMD 40001 BCE4 G38FG14F FKM	Withdrawal pressure reducer 400 series (single-stage, max. Purity 6.0) (EMD 40001 BCE4 G38FG14F) Material: brass Pre-pressure: 40 bar Back pressure: 0.2 - 4 bar Input: G3 / 8 "f Output: G1 / 4 "f Details: see data sheet / sketch: L000001-00 Gas: H2
ADPTW-B I N14G38 L39	Wall adapter for EMD 400 WALLADAPTER B IN:NPT 1/4"F OUT:G 3/8"M L:39,0MM Material: brass Entrance: G3 / 8 "w Output: NPT ¼ "f Details: see / sketch: 23-3032
CLRIN-B I CL1/4" G1/4" (Optional)	Compression fitting ¼ "on G-thread, enclosed loosely (>> for the output of the EMD at 6 o'clock downwards) CLRIN-B I CL1 / 4 "G1 / 4" Material: brass Entrance: G 1/4 "w Output: ¼ "clamping ring
14001228	
14001229	
6900556006	
6901436002	
6901967001	
A002173R	
ARV0249	

Ürün	Açıklama
ARV0710	
FMD50216	
H03882603	
H27433464	
MSLH0SDP00FXD2BTBTN14FN14FN14F	Battery pressure reducer, new PUR series, for 2x1 bottles (two-stage, with semi-automatic switching, max. 6.0. purity) MSLH0SDP00FXD2BTBTN14FN14FN14F (MAN SST 020Q H0 2SEMIDUA P0 0 200/010 BT BT N14F N14F N14F) Material: stainless steel pre-pressure: 200 bar Back pressure: 0.5 – 10 bar Input / Output: N14F Details: see data sheet / sketch: MSLH0SD.. Gas: ??? >> Please let us know the type of gas used when ordering!
CSLH0DJR0SFXXBTBTN14F00N14F	Bottle pressure reducer, new PUR series (two-stage, with shut-off valve at the outlet, max. 6.0. purity) CSLH0DJR0SFXXBTBTN14F00N14F (CREG SST 020Q H0 DUA 6PORTJR 0S 200/3.0 BT BT N14F00 N14F) Material: stainless steel pre-pressure: 200 bar Back pressure: 0.5 – 3 bar Entrance. N14F >> without bottle connection! Output: N14F Details: see data sheet / sketch: CSLH0DJR.. Gas: ??? >> Please let us know the type of gas used when ordering!

Ürün	Açıklama
BMD502-35-SS-F-10,5-N14-N14 -	Type of BMD502-35 Material: SS=Stainless Upstream Pressure: F=230 bar Downstream Pressure: 10= 1-10,5 bar Inlet: N14= NPT 1/4"f Outlet: N14= NPT 1/4"f
FMD502-16-SS-F-3-N14-N14 -	Type of FMD502-16 Material: SS=Stainless Upstream Pressure: F=230 bar Downstream Pressure: 3= 0.2-3 bar Inlet: N14= NPT 1/4"f Outlet: N14= NPT 1/4"f
MD 40001	BCE4 CL1/4"BC CL1/4"BC H2