Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Georgin

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Georgin Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Georgin Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Model: TXC100LA	Case 100mm SS with bottom connection and wall mounting bracket Case oil filled Range: 0-120°C Capillary: 12 metres SS with PVC cover Connection: ½"BSP type CS3 Stem: 90mm x 14mm Double magnetic contact: M11 Optional SS capillary with SS armor, where the SS armor is PVC covered Surcharge: 85, - Euro net / piece
Ref. BXNP13000-B0	Potentiometer convertor Input: orig: 0-> 30% ext: 70->100% Output: generator 4/20 mA Option: without, clamp terminals Input power supply: 230 Vac Rail DIN mounting interface ATEX information: EC type examination certificate LCIE 02 ATEX 6104X [Ex ia] IIC (-20 °C < Ta < 60 °C) Group II (surface) - category (1) G/D Installation in safe zone barrier for equipment installed in zone 0,1,2 gas or zone 20,21,22 dust See leaflet for a safe use customs code: 8504 3180 FR
FP6KX	Ref. FP6KX Pressure switch F series protection : IP66 housing : mazak, epoxy painted,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	st. st. screws range : -1 to 5 bar max. pressure : 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2""GM switch : 1 tropicalized SPDT adjust. deadband : <0,205 to 1 bar current rating : 10A/240VAC - 0.5A/110VDC cable gland : polyamid M16 (Ø5-10) PED information: material complies with PED 2014/68/EU Category IV article reference: 0FP06BKSY0000 customs code: 9032 2000 country of origin: France / U.E. Gewicht ca. 1,2 kg / Stück
FP-54-P	
FP-6-K	
303020	
30359 REGXPR03	
30392	
30903 XPC180PS0C000	
30994	
401011	
41181	
CPANFQ	
EPPX3FPHX0000	
FD16MX	
FDH34GX	
FKCT33V52KCBYAU	
FKCT33V5-2XCBY-AU	
FKCT35V52XCBYAU	
FP62RX	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
GR5000S00	
IFC6DBPSAA6J0	
IFC6DBRSAA6J0	
IFC6DNPSAA3J0	
OFP06BPSYO3A0 (FP6PX)	
PB30DLX	
SETPOINT 80 BAR INCREASING (?)	
SR5302A	
PDC-1.1.I.0	Pressure switch for non-aggressive liquids and gases Switching differential: Switching differential not adjustable Switching range: 1 to 10 bar Option: none
PDC-1.1.D.0	Switching differential: Switching differential not adjustable Switching range: 0.04 to 0.25 bar Option: none
PDC-1.1.E.0	Switching differential: Switching differential not adjustable Switching range: 0.1 to 0.6 bar Option: none
PDC-1.1.A.0	Switching differential: Switching differential not adjustable Switching range: 1 to 16 mbar Option: none
PDC-1.1.H.0	Switching differential: Switching differential not adjustable Switching range: 0.5 to 6 bar Option: none
PDC-1.1.H.0	Switching differential: Switching differential not adjustable Switching range: 0.5 to 6 bar Option: none
PDC-1.1.H.0	Switching differential: Switching differential not adjustable Switching range: 0.5 to 6 bar Option: none
30980	Ref. C6PX Capillary temperature switch P series protection : IP66 housing : mazak, epoxy painted, st. st. screws range : 25 to 95 °C

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	max. temperature : 105 °C sensing element : 3m capillary-bulb Ø14x150mm material : 316L st. st. capillary protection : st. st. armor switch : 1 SPDT, dry contact adjust. deadband :(low/high of range)4-25°C/2-9°C current rating : 5A/240VAC - 0.5A/110VDC cable gland : polyamid M20 (Ø7.5-13) features: st. st. tag plate PED information: material complies with PED 2014/68/EU Category IV article reference: 0PC06BPSYB0A0 customs code: 9032 1080 country of origin: France / U.E. Gewicht ca. 2,2 kg / Stück *****PLEASE CHECK THE TECHNICAL DETAILS!*****
GR3000A00	Ref. GR3000A00 (0 / 10 bar) Gauge pressure transmitter...GR/GA series housing : stainless steel / protection : IP65 range : 0 - 10 bar max. pressure : 30 bar sensor : ceramic cell on viton gasket process connection : 1/2" BSPM - st.st. 316L electrical connector : DIN43650 power supply : 10...30 Vdc output signal : 4...20 mA max. global error : <0.5% FS article reference: GR3000A00
GRD000S00	30702 Pressure transmitter 0 - 6 bar ATEX GR series pressure transmitter Case: stainless steel Degree of protection: IP65 Measuring range: 0 - 6 bar Maximum pressure: 15 bar Sensor: Ceramic cell, Viton seal Process connection: 1/2" BSPM Material: St. St. 316L electrical connector: DIN 43650 Supply voltage: 10 - 30 VDC

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Output: 4-20mA, 2-wire max error rate: <0.5% FS ATEX information: certificate LCIE 01 ATEX 6137X Ex ia IIC T6 or T5 Ga (-30<Ta<55 or 70°C) Ex ia IIIC T80°C or T95°C Da (-30<Ta<55°C or 70°C) Groupe II - category 1 GD - Zones 0-1-2 or 20-21-22 Ex ia I - Group I (Mines) - Category M1 Production Notification LCIE 02 ATEX Q 8023 Customs tariff number: 9026 2020 Country of origin: France / EU
RDN 210 000	Intrinsically Safe Relay (Isolation Amplifier)2 Channels, 230 VAC Power Supply Input: 2 × switch or proximity sensor (NAMUR) Output: 1 × transistor per channel ATEX Certificate: LCIE 02 ATEX 6104X Mounting: DIN rail Country of Origin: France / EU
0FP34PPAY03A0	FPA34PX pressure switch 0.5 - 10 bar F-Series Pressure Switches Degree of protection: IP66 Housing: Mazak, epoxy resin coated, stainless steel screws Measuring range: 0.5 - 10 bar maximum pressure: 80 bar Sensor element: BunaN membrane Material: BunaN - 316L stainless steel flange Process connection: 1/2" NPTM 2 simultaneous tropicalized SPDT contacts adjustable hysteresis: <0.52 - 2 bar Current: 10A/240VAC - 0.5A/110VDC electrical connection: M20x150 Special feature: stainless steel type plate Item code: 0FP34PPAY03A0 Customs tariff number: 9032 2000 Country of origin: France / EU Ref.FPA34PX Pressure switch F series protection : IP66 housing : mazak, epoxy painted-st. St. screws range : 0.5 to 10 bar
30367	REGFR12 Setting [2 SPDT (FP-FML)] Limit setting + sealing + test report

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Switching point: 3.5 bar *** please specify whether "rising" or "falling" should be set REGFR12 Setting [2 SPDT (FP-FML)] presetting/sealing/ test report set point at 3.5 bar ***direction "increasing" or "decreasing" to be confirmed*** TAG n° MLDP02 CP003
306154	M5000 pressure gauge D: 150 mm 0 - 10 bar M5000 series pressure gauge D: 150 mm - 304 st.st. - 4mm Safety glass Measuring range: 0 - 10 bar (Class 1) Connection: 1/2" NPTM below 316L st. st. Bourdon tube and Process connection 1 x SPDT contact (type 821-3) + filled with silicone oil Item code: M5000ED3P1F00 Customs tariff number: 9026 2040 Country of origin: France / EU Ref. M5000 (Ø150 0/10 bar) pressure gauge M5000 series case: Ø150 - 304 st.st. -safety glass 4mm range: 0...10 bar (class 1) connection : 1/2"NPTM bottom 316L st.st. bourdon tube and process connection 1 x SPDT contact (Type 821-3) + silicon oil filled article reference: M5000ED3P1F00
303003	ACCM5020 stainless steel tag plate ACCM5020 Stainless Steel tag plate material: AISI 304 SS
303007	Calibration certificate 5 points (M5000) 5 points: 0 - 25 - 50 - 75 - 100 % article reference: ACCM5000
40425	FKPT02V62ACBYYL pressure sensor 0.3125 - 5 bar FKP series pressure sensor min./max. Sapnne: 0.3125 - 5 bar max. pressure (overload limit): 15 bar Calibration range: *** please specify

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	if desired*** Accuracy: +/- 0.1% of calibrated span Measuring membrane: 316L st.st. Bride: INOX 316L filled with silicone oil Process connection: 1/2" - 14 NPTI Power supply 10.5 - 45 VDC Electrical connection: 1/2" - 14 NPT Output signal: 4 - 20 mA (2-wire technology) + HART RFI protection according to IEC 801-3 Housing: die-cast aluminum alloy, Polyester coated Digital display (customized scaling) additionally: stainless steel nameplate equipped with Stainless steel fastening clamp for 2 inch pipe assembly Item reference: FKPT02V62ACBYYL
401158	Ref. P30KX Pressure switch P series protection : IP66 housing : mazak, epoxy painted-st. st. screws range : -1 to 3.5 bar max. pressure : 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 2 simultaneous SPDT - tight deadband fixed deadband current rating : 5A/240VAC - 0.5A/130VDC cable gland : polyamid M20 (Ø7.5-13) article reference: 0PP30BKSY0000 include; 30398 REGPR12 presetting+ sealing+ test report set point: 1 bar decreasing
40098	Pressure switch Georgin 0.5-10 bar, type FP62PX Ref. FP62PX Pressure switch F series protection : IP66 / ATEX increased safety housing : mazak, epoxy painted, st. st. screws

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	range : 0.5 to 10 bar max. pressure : 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 1 SPDT Ex d IIC T6 adjust. deadband : <0,45 to 2 bar current rating : 5A/240VAC - 0.4A/250VDC cable gland : brass M16 (Ø4.5-10)-Ex e features: Ex de st. st. tag plate ATEX information: Certificate LCIE 02 ATEX 6161X Ex de IIC T6 (-20°C<Ta<60°C) Ex tD A21 IP66 T80°C Group II (Surface) - Category 2GD Zones 1-2 or zones 21-22 Production Notification LCIE 02 ATEX Q 8023 See leaflet for a safe use article reference: EFP62FPSY0000
FP62FX pressure switch 0...250 mbar ATEX	Ref. FP62FX Pressure switch F series protection : IP66 / ATEX increased safety housing : mazak, epoxy painted, st. st. screws range : 0 to 250 mbar max. pressure : 2 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 1 SPDT Ex d IIC T6 adjust. deadband : <34 to 250 mbar current rating : 5A/240VAC - 0.4A/250VDC cable gland : brass M16 (Ø4.5-10)-Ex e features: Ex de st. st. tag plate ATEX information: Certificate LCIE 02 ATEX 6161X Ex de IIC T6 (-20°C<Ta<60°C) Ex tD A21 IP66 T80°C Group II (Surface) - Category 2GD Zones 1-2 or zones 21-22 Production Notification LCIE 02 ATEX Q 8023 See leaflet for a safe use article reference: EFP62FFSY0000
30335	REGFR01 Setting [1 SPDT (FP-FML)] presetting/sealing/ test report set point at 100 mbar decreasing

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	TAG n°: 5YAX04 38 PSL ???
FP54PX	pressure switch 0.5 ... 10 bar F-series pressure switches Protection class: IP66 Housing: mazak, epoxy resin coated, stainless steel screws Measuring range: 0.5 ... 10 bar Maximum pressure: 15 bar Sensor element: pressure bellows Material: 316L st. st. Process connection: 1/2" GM 2 separately switching tropicalized SPDT contacts adjustable hysteresis: < 0.285 ... 2 bar Current: 10 A/240 VAC - 0.5 A/110VDC Cable gland: polyamide M16 (d: 5-10 mm) Article code: 0FP54BPSY0000
FP6DKX	Pressure switch -1 ... +5 bar F-Series pressure switches Article code: 0FP6DBKSY0000 Protection class: IP66 Housing: mazak, epoxy coated, Stainless steel screws Measuring range: -1 ... +5 bar Maximum pressure: 15 bar Sensor element: pressure bellows Material: 316L st.st. Process connection: 1/2" GM 1 SPDT contact, hard gold-plated Adjustable hysteresis: <0.205 - 1 bar Current: 1-100mA / 4-30VDC Cable gland: polyamide M16 (d: 5-10mm) Article code: 0FP6DBKSY0000
30656	M5000 pressure gauge D: 100 mm 0 - 1 bar M5000 Series Pressure Gauges st.st. housing D: 100 mm - 304 st.st. - 4 mm Safety glass Measuring range: 0 - 1 bar (Class 1) Connection: 1/2" GM bottom 316L st. st. Bourdon tube and Process connection Article code: M5000DD0J1000
EFP62FPSX0200	EFP62FPSY0200

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	F-Series pressure switches Protection class: IP66/ATEX increased safety Housing: mazak, epoxy coated, stainless steel screws Measuring range: 0.5 - 10 bar Maximum pressure 15 bar Sensor element: pressure bellows Material: 316L st.st. Process connection: 1/4" NPTF 1 SPDT contact Ex d IIC T6 adjustable hysteresis: <0.45 - 2 bar Current: 5 A/240 VAC - 0.4 A/250VDC Cable gland: brass M16 (d: 4.5-10mm)-Ex e Special feature: Ex de stainless steel nameplate ATEX information: LCIE 02 ATEX 6161X Ex IIC T6 (-20°C <Ta<60°C) Ex tD A21 IP66 T80°C Group II (surface) - Category 2GD Zones 1-2 or Zones 21-22 Production Notification LCIE 02 ATEX Q 8023
EFP62FPSY0100	F-Series pressure switches Protection class: IP66/ATEX increased safety Housing: mazak, epoxy coated, stainless steel screws Measuring range: 0.5 - 10 bar Maximum pressure 15 bar Sensor element: pressure bellows Material: 316L st.st. Process connection: 1/4" GF 1 SPDT contact Ex d IIC T6 adjustable hysteresis: <0.45 - 2 bar Current: 5 A/240 VAC - 0.4 A/250VDC Cable gland: brass M16 (d: 4.5-10mm)-Ex e Special feature: Ex de stainless steel nameplate ATEX information: LCIE 02 ATEX 6161X Ex IIC T6 (-20°C <Ta<60°C) Ex tD A21 IP66 T80°C Group II (surface) - Category 2GD Zones 1-2 or Zones 21-22 Production Notification LCIE 02 ATEX Q 8023
BXNI2A400	Intrinsically Safe Loop Isolator 2 Channels, galvanic isolation without external power supply Input Signal: 4–20 mA

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Output Signal: 4–20 mA Parameters: Uo = 17.7 V, Io = 100 mA, Po = 440 mW, R = 330 Ω ATEX Certificate: LCIE 02 ATEX 6104X Mounting: DIN rail Country of Origin: France / EU
30503	TIXO3A0-00 Universal Head Transmitter SIL 2, RTD, PT, TE, V, R, HART Input: RTD 100 2/3/4 conductor, Ni 100 2/3/4 conductor, Ni 1000 2/3/4 conductor, TE K/J/N/B/R/S/T/E, Volt, resistance, voltage. Galvanic isolation: 1500 VAC Supply voltage 10 - 30VDC (standard) Power supply via 4...20mA loop
FKPT04V62KCBYYL	40492 Pressure sensor 6.25 - 100 bar ATEX Successor type to FKPT04V52KBY0Y FKP series pressure sensor min./max. Sapnne: 6.25 - 100 bar Maximum pressure (overload limit): 150 bar Calibration range: *** please to be specified*** Accuracy: +/- 0.1% of the calibrated range Measuring membrane: 316L st.st. Bride: INOX 316L filled with silicone oil Standard application Process connection: 1/2" - 14 NPTI Power supply 10.5 - 45 VDC Electrical connection: 1/2" - 14 NPT Output signal: 4 - 20 mA (2-wire technology) + HART RFI protection according to IEC 801-3 Housing: Aluminum die-cast alloy, polyester coated Digital display (customer-specific) Scaling) Additionally: st. st. tag plate equipped with st.st. mounting clamp for 2-inch pipe ATEX Information: certificate DEKRA 14ATEX0016X Ex ia IIC T5 Ga (-40 <Ta<50°C) Ex ia IIIC T100°C Da Ex II 1 GD : Group II (Surface) - Category 1GD Zones 0-1-2 (Gas) or zones 20-21-22 (Dust) Production

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
0fp06bpsx0300	
0fc06bpsxa0a0 Ref. Fc6px	
Tre000s000	
P96kx40bcs1	
Fc6tx	
0fp06bpsy0000	
Gf7013011b	
Article Code : 0pd54bksy0000	Ref. DPB54PX22 Diff.pressure switch P series protection : IP66 housing : mazak, epoxy painted-st.st. screws range : 0.15 to 4 bar min/max static pressure : -1 / 15 bar sensing element : bellows material : 316L st. st. process connection : 1/2"GM switch : 2 separate SPDT, dry contact adjust. from : <0,26 to 1 bar current rating : 5A/240VAC - 0.5A/110VDC cable gland : polyamid M20 (Ø7.5-13) PED information: material complies with PED 2014/68/EU Category IV Article code : 0PD54BKSY0000 customs code: 9032 2000 country of origin: France / U.E.
Hdrhfdhf	
Art.-Code: T7100dd0p1jnr00	Ref. T7100 (100mm 0/100°C) inert gas pressure thermometer T7100 series case : 100mm - 304 st.st. - plain glass 4mm range : 0...100 °C (class 1) stem : bottom connection bulb Ø10 x S= 300mm - 316L st.st. connection : 1/2"GM adjustable magnetic contact 821-11 type + dielectric oil filled Article code : T7100DD0P1JNR00 customs code: 9025 1980 country of origin: France / U.E.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Rdn 110000	
Fkpt02v52acby0y	
17a2e4	
Article Code : T7100dazr1knr00	inert gas pressure thermometer T7100 series case : 100mm - 304 st.st. - plain glass 4mm range : 0...120 °C (class 1) sensing element : bottom connection - back flange capillary 8m - bulb Ø12 x S= 110mm - 316L st.st. capillary protection : no connection : 1/2"GM adjustable magnetic contact 821-11 type + dielectric oil filled Article code : T7100DAZR1KNR00 customs code: 9025 1980 country of origin: France / U.E.
Eppx4fpsx0000	
Fkpt02v52kcby0y	
Fp6px	
Bzg788+	
Gr5000s00 (0/50 Bar)	
Bxne ** 000e	
Gf7013010b	
Fp4k, Art. N: 0fp04bks00000	
Eppx4fps00000	
Fkct22v52acbyau	
Sealing Device - F Series	
Gre000s00	
Mpb10e	
0fp54bqsx0300 Ref. Fp54qx	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Fp6nx 95kpa Range0.1-2bar Max8bar	
P62px	
Fkpt03v52acba0y	
4do Fb621x	
Setpoint 80 Bar Increasing (?)	
S771	
Sr5002a00	
Gr7000s00	
Fkpt02v52acba0y	
Fc 54t	
Fp6sx	
Dpb54px22 0,15/4 Bar	
Article Code : T7100dazr1knr00 (12m)	Ref. T7100 (100mm 0/120 °C) inert gas pressure thermometer T7100 series case : 100mm - 304 st.st. - plain glass 4mm range : 0...120 °C (class 1) sensing element : bottom connection - back flange capillary 12m - bulb Ø12 x S= 130mm 316L st.st. capillary protection : no connection : 1/2"GM adjustable magnetic contact 821-11 type + dielectric oil filled Article code : T7100DAZR1KNR00 customs code: 9025 1980 country of origin: France / U.E.
Fp6k+s680	
Phb96tx	
0fp06brsx0300 Ref. Fp6rx	
C6yx	
0pc06bysy0000	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Fc6gxrtpf	
Phb10rx	
P16ax40a6	
Hm451u3331211	
Fp62p	
199041294	
Grk000s00	
C96pxutox	
Art.-Code: T7100dazr1knr00	T7100 Industrial Inert gas pressure thermometer Industrial inert gas pressure thermometer the T7100 series suitable for heavy environments and corrosive media Housing: d: 100 mm, 304 st.st., 4 mm clear glass Measuring range: 0 - 120 ° C (class 1) Sensor element: bulb, d: 12 mm x S: 110 mm Material: 316L st.st., 8 m capillary Connection radially at the bottom - fastening at the rear Capillary tube protection: no Process connection: 1/2 "GM rotatable magnetic contact 821-11 + filled with dielectric oil Art.-Code: T7100DAZR1KNR00 Customs tariff number: 9025 1980 Country of origin: France / EU
Fp6nx 15kpa Range0-250mbar Max2bar	
Rdn110000	
Article Code : 0fp06bksa0000	Ref. FP6K Pressure switch F series protection : IP66 housing : mazak, epoxy painted-st.st. screws range : -1 to 5 bar max. pressure : 13 bar sensing element : bellows material : bronze

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	process connection : 1/2"GM switch : 1 tropicalized SPDT adjust. deadband : <0,165 to 1 bar current rating : 10A/240VAC - 0.5A/110VDC cable gland : polyamid M16 (Ø5-10) Article code : 0FP06BKSA0000 customs code: 9032 2000 country of origin: France / U.E.
Tschg 100 Q 100 'C X 300 Mm.X Q 12 M11	
Bzg796	
M5000 Dd0w1g00	
Fkct22v52kcbyau	
Phb34sx	
Bvns0b00-00-00	
Fkpt01v52acby0y	
Fkct35v52acbyau	
30167	RDN 211 002 Isolation Amplifier 2 24/48VDC channels 2 inputs (contact or NAMUR). 1 SPDT relay output per channel Supply voltage 24/48 VDC ATEX classification CE 0081 Ex II (1) G/D SIL 2 classification according to IEC 61508 Connection via pluggable spring terminals Customs tariff number: 8504 3180 Country of origin: France / EU Ref. RDN211002 Intrinsic safe relay Input: 2 x switch or proximity sensor Output: 2 x relays (1 RT) per channel Option: without, clamp terminals Power supply: 24/48 Vdc Rail DIN mounting interface ATEX information: EC type examination certificate LCIE 02 ATEX 6104X [Ex ia] IIC (-20 °C < Ta < 60 °C) Group II (surface) - category (1) G/D Installation in a safe zone barrier for equipment installed in zone

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	0,1,2 gas or zone 20, 21, 22 dust See leaflet for safe use
Ofp06bpsx0300	
Ofp06bpsyo3a0	
Pa36k	
Regpr13	Setting [2 SPDT (PL-DIFF)] presetting/sealing/ test report set point at ***to be confirmed***
Pressure Switch=2.5/25 Gerorgin Max30bar	PRESSURE SWITCH=2.5/25 GERORGIN MAX30BAR
Fp54qx	
0fp06bpsx0000	
Ertetert	
0fc06btx0000	
Fc6pxrtpf	
0fd06bmjx0200 Ref. Dfms6mx	
Regfr01	Setting [1 SPDT (FP-FML)] presetting/sealing/ test report set point at 0,5 bar decreasing Zolltarifnummer: 9026 8099 Ursprungsland: Frankreich / EU
0fp06bvlx0300 Ref. Fpl6vx	
Fkpt03v52acby0y	
Fp-6-K -1/5 Bar	
Fp6nx 8kpa Range0-250mbar Max2bar	
Dfsdgdfgd	
Fb621x	
Fkpt03v52kcby0y	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
0pd06bcb00200 Ref. Dmpb6m11	
Txc100la-0/120'C-8m Kss+pvc-A-Cs3-1/2"Bsp 90x14mm-M11	
0fc06btsx0000	
Fp4drx	
P162px	
Fkct33v52acbyau	
0fp04bksa00a0 Ref. Fp4k	
Rdn211	
0fp06bpsy03a0	
Fp6nx 0.1mpa Range-1-5bar Max15bar	
Fp4kx	
Fb54p	
Fp6nx 5kpa Range0-250mbar Max2bar	
P96pxutox1	
Ofp06bssx05h0	
0fp06bssx0300	
199041196	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.