

Goodfellow

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Goodfellow Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Goodfellow Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
FF210376 Stainless steel - material no. 1.4404	Fe / Cr18 / Ni10 / Mo 3 Foil thickness: 0.9mm Condition: annealed Surface quality: mirror-polished on both sides 100 mm x 100 mm PF 10pcs
AL00-WR-000182	
IN00-WR-000130	
IM30-FM-000115	
AL00-WR-000182	
AL00-WR-000182 Aluminium	Wire diameter: 1.0mm Highly pure: 99.999% Condition: as drawn 1 x 50m
IN00-WR-000130 Indium	Wire diameter: 1.0mm Highly pure: 99.999% Condition: as drawn 1 x 10 m
074-952-18	0.025mm; 610mm x 0.5m kapton foil
IN00-WR-000130 Indium	Wire diameter: 1.0mm Highly pure: 99.999% Condition: as drawn 1 x 20 m
IM30-FM-000115 Polyimid	PI Film thickness: 0.025mm Color : Black Grade : DuPont Kapton® B 610mm x 0.5m x 1pc
AU00-MS-000132 Gold	Mesh nominal opening: 0.25mm Wire diameter : 0.06mm Wires/inch : 82x82 open area: 65% purity: 99.9% Type: Woven

Ürün	Açıklama
	20mm x 20mm Tolerances Unless expressly stated otherwise, our standard tolerances apply Thickness: woven: $\pm 10\%$ electrolytic: $\pm 20\%$ Wire diameter: $\pm 10\%$ Large (linear dimension < 100mm: $\pm 1\text{mm}$ >= 100mm +2% / -1%
TI00-FL-000310 Titan	foil thickness: 0.05mm Purity : 98.9% Grade : Grade 2 - ASTM B265N Chemistry Only Condition: annealed 100 mm x 100 mm PF PF films are non-porous and are light tested. NPF films can have pores. Tolerances Unless expressly stated otherwise, our standard tolerances apply Thickness: <0.010mm $\pm 25\%$ 0.01-0.05mm $\pm 15\%$ >0.050mm $\pm 10\%$ Size (linear dimension = < 100mm: $\pm 1\text{mm}$ > 100 mm +2% / -1%
Fe007150	