Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Gossen Muller Weigert

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Gossen Muller Weigert Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Gossen Muller Weigert Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
1108bil511	STQ 1 110 V DC (0,6 W) CONTENT: CIRCUIT VERSION 001: with parallel load LB: APPLICATION 001: conditionally tropical proof LS: WORKING VOLTAGE / OVERVOLTAGE CATEGORY 008: Working voltage 300V (300V CAT III) VB: TOUCH PROTECTION 002: Overall - protection against contact
1280bil511	ST 1 110 V DC (0,6 W) CONTENT: CIRCUIT VERSION 001: with parallel load LB: APPLICATION 001: conditionally tropical proof LS: WORKING VOLTAGE / OVERVOLTAGE CATEGORY 008: Working voltage 300V (300V CAT III) VB: TOUCH PROTECTION 002: Overall - protection against contact
DINALOG A144x36-71	A1400 A: Version 2: double indicator B: Design 2: portrait format BA: Display type 1: luminous strip and digital display BB: color of light band 9: light band color of red BC: Scale color 099: Scale base white, part + number sw C: limit values 0: without limit values DD: measuring ranges for 2 measuring units 007: M1: 4 ... 20mA; M2: 4 ... 20mA; E: Display range of the digital display 92: E1: 0 ... x (x = max. 999) ET: Entry for E 0 ... 100: ED: Decimal point of the digital display M1 1: no decimal point FR: Measured variable for the digital display 9: as specified (max. 3 digits) FRT: Entry for FR%: F: scale 03: 0 ... 100; 0 ... 100

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	FA: Start of the light strips 0: the light strips start at 0 FM: Measured variable for light strip 1 2:% FN: Measured variable for light band 2 2:% FP: scale factor 00: none H: Auxiliary voltage 2: 24V (50 / 60Hz) or 18 ... 36V DC U: Design 0: GMW design W: Operating instructions 0: Operating instructions D / GB / F GMW logo
1281BIL511	LS: WORKING VOLTAGE / OVERVOLTAGE CATEGORY 008: Working voltage 300V (300V CAT III) VB: TOUCH PROTECTION 002: Overall contact protection
1281BIL511	ST 2 110 V DC (0,6 W)
1602WBE22	V-PQ 72-250 an WDL .../ 1 A AC 1.2 times overload 1602WBE22 V-PQ 72-250 to WDL .../ 1 A AC 1.2 times overload IK :NOMINAL FREQUENCY 102 :45...65 Hz ammeter with rectifier LB :APPLICATION 001 : conditionally tropicalized LS :WORKING VOLTAGE/OVERVOLTAGE CATEGORY 009 : working voltage 600V (600V CAT III) MG :GLASS 001 : low-reflection SK : ADDITIONAL QUOTATION 992:2. Numbering, according to specification SKT :Input to SK / 2nd figure . : VB :TOUCH PROTECTION 002 :Total - Protection against accidental contact **** Please also specify primary current SKALA and inscription ***
1602WBF26	V-PQ 72-250 an WDL .../ 110 V AC 1.2 times overload 1602WBF26 V-PQ 72-250 to WDL .../ 110 V AC 1.2 times overload DH :VOLTAGE AT WDL/SPT in kV 220.00: IK :NOMINAL FREQUENCY 103 :45...65 Hz voltmeter with rectifier LB :APPLICATION 001 : conditionally tropicalized LS :WORKING VOLTAGE/OVERVOLTAGE CATEGORY

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	009 : working voltage 600V (600V CAT III) MG :GLASS 001 : low-reflection VB :TOUCH PROTECTION 002 :Total - Protection against accidental contact
1622E	AZQS 144 BFA :MWI: CONNECTION TO VOLTAGE TRANSFORMER 015 :on WDL .../ 110 V BFB :MWII: CONNECTION TO VOLTAGE TRANSFORMER 015 :AN WDL .../110 V BUA :MWI: OVERLOAD 005: 1.2 times overload BUB :MWII: OVERLOAD 005: 1.2 times overload LB :APPLICATION 001 : conditionally tropicalized LS :WORKING VOLTAGE/OVERVOLTAGE CATEGORY 008 : working voltage 300V (300V CAT III) MG :GLASS 001 : low-reflection VB :TOUCH PROTECTION 001 :Single - touch protection *** PLEASE INDICATE PRIMARY VOLTAGE SCALE ****
3290Q73120-0003	SYNCHRONOSCOPE SY 144 GOSSEN, reflex. Glass, bed.trop. 100..120V 50Hz Version SY144 Dimension 144 Rated voltage 100..120V Frequency 50HZ GOSSEN logo Glass REFLECTIVE Special COND. TROPICAL
4330109750	FQ144/2 45-55Hz 2x21 tongues 100-110V Tongue frequency meter low-reflection FZ:GOSSEN bed.tropenfest
1281B-000013	ST2 ST 2 switch position indicator B :MEASURING INPUT 001 :DC current / voltage IL :NOMINAL VOLTAGE 511 :110VDC (0.6W) +/- 20% INH :CIRCUIT VARIANT 001 :with parallel load LB :APPLICATION

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	001 : conditionally tropicalized CB :WORKING VOLTAGE/OVERVOLTAGE CAT. 008 : working voltage 300V (300V CAT III) MA : FRONT FRAME / COLOUR 073 : with front ring diameter 32 mm T :LOGO 989 :GOODS VB :TOUCH PROTECTION 002 :Total - protection against accidental contact
1602W-000013	V-PQ 72-250 FUER AC BF :CONNECTION TO VOLTAGE CONVERTER 026 :at WDL .../ 110 V 1.2 times overload DH :VOLTAGE TO WDL/SPT in kV 400.00 IK :NOMINAL FREQUENCY 102 :45...65 Hz ammeter with rectifier LB :APPLICATION 001 : conditionally tropicalized CB :WORKING VOLTAGE/OVERVOLTAGE CAT. 009 : working voltage 600V (600V CAT III) MG :GLASS 001 : low-reflection ST :COLORED MARK 991 :MARK @@@ AT ### @ STP :Input to ST/1. Brand RED AT 400 T :LOGO 989 :GOODS VB :TOUCH PROTECTION 002 :Total - protection against accidental contact
5120000410	
1108bil224 Stq 1 24 V Dc (0,3 W)	
Mu-Mp3/4-4	
Dpm 24/96-2000 D Uh 230v Ac	
Stq 1 24 V Dc (0,3 W)	LS: WORKING VOLTAGE / OVERVOLTAGE CATEGORY 008: Working voltage 300V (300V CAT III) VB: TOUCH PROTECTION 002: Total contact protection
Mu-P3wu/S Obsolete, Replaced By Mwu-3.1	
1281bil522	
Mu J3 S Mu Mp3 4 4	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
7410000082 Dpm 24 96 2000 D Uh 230v Ac	
N51391	
Ac Power Transducer Mu-P3wu/S	Input:0-100V/0-1A,Output: 0-70MW/4-20mA, Aux Volt:195-265 V AC
Mu-F/S	
Mu Gs/S +/- 60 V, 24 V Dc(18-36 V Dc)	
Mu- J3/S	
Stg 1g 25x25 24vdc	
1700v3200	
1280bil224 St 1 24 V Dc (0,3 W)	
Mu Gs/S +/- 1 V, 24 V Dc(18-36 V Dc)	
7410000082	
1280bil522	
Dlqs 96 Mf Power Meter Ce	AB: POWER 001: Active power 2-wire single-phase AC BE: CONNECTION TO POWER-WDL / NW / THERMOELEM. 011: to WDL ... / 5 A BF: CONNECTION TO VOLTAGE CONVERTER 018: to WDL ... / 250 V BX: SCALE FACTOR I 0,535: CG: POWER ON WDL / NW in A 700,00: DG: VOLTAGE ON WDL / SPT in V 800,00: GL: SCALE 330: 0 ... 300 GM: MEASUREMENT SIZE K13: kW IC: NOM FREQUENCY 040: 50 Hz ... 10 kHz LS: WORKING VOLTAGE / OVERVOLTAGE CATEGORY 010: Working voltage 150V (150V CAT III) SA: SCALE 011: plan - screw scale Country of origin: Czech Republic stat. Product number: 9030 33 80
V-Pq 48-250	
St1g D25 24vdc	
Eq96s/2	
Dpm 24/96-2000 D Uh 24v Dc Obsolete,Replaced By Dpm 24/96-2000 S	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
24 V Dc	
Mu-F/A	
Mu Gs/S 0,,,60 Mv, 24 V Dc(18-36 V Dc)	
Fdq 96s	
Mu Gs/S 0,,,200 Mv, 24v Dc(18-36 V Dc)	
Mu-P3wu/S 0-200 Mw,4-20 Ma,100v	
Xe30065930005	GOSSEN MULLER XE30065930005
Dpm 48/2000 Snt 20	
1604ebf15	
1280bil224	
St 1 24 V Dc (0,3 W)	LS: WORKING VOLTAGE / OVERVOLTAGE CATEGORY 008: Working voltage 300V (300V CAT III) VB: TOUCH PROTECTION 002: Total contact protection
Mu Gs/S Input: 0-200 Mvdc Output: 0- 10 Vdc Power Supply: 24 Vdc	
1604pbc25	
1108bil224	
Mu-P3wg/S	
Stq 1	
St 1	
Pantatherm Kr 4	
Mu Gs/S Input: +- 964 Mv Dc, Out Put: +- 10 V Dc	
Mu - F/S S/N: M2029933 Obsolete, Replaced By Mf-1.1	
1280bil511 St	
Mu Gs/S Input: 0-60 Mv Dc , Output1 : 0-10 V Dc , Output2 :0-10 V Dc, Output3 : 4-20 Masupply:24 V	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
1700v3460	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.