Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Goudsmit

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Goudsmit Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Goudsmit Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
HEB-035x30-0100-GC	Electromagnetic bar magnet EHKAD01000
P193896-01	
RECE-CB-15-X-PVC-30	Conveyor belt E0094039 Article number : E0094039 Product key : RECE-CB-15-X-PVC-30 Product description : Conveyor belt Suitable for belt width : 1500 mm Weight : 25 kg Belt type : 3 mm PVC, black
SEMR353538	Magnetic grid - manual quick cleaning
SBAMA100040-300	Bar Magnet - Neodymium BAR-N-23-300-25-2M8-NW-B
SPSR250009	
TPGC100018	HGR-RO-100-FR-R-G-S Product Description: Magnetic Gripper Type: base Dim.: Ø100 mm Circuit: Pneumatic Advised working load: 140 N (under ideal conditions - with Safety factor 3 according to EN13155) Max. tear-off force: 420 N (under ideal conditions - graphic: see Tab Downloads - Factors influencing lifting performance: see Magnetic Handling) Minimum recommended sheet thickness: 2 mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Interface/connection dimensions: Threaded hole M10 Connections: Pneumatic: G1/8" (2x) Material housing: aluminum Surface Treatment/Coating: Anodized Red color min/max Ambient temperature: 0 to 70 °C Switching pressure: Max. 4 bar Air consumption: 0.86 l/cycle (1x up, 1x down) Magnet system: coarse pole Magnet system: 6 permanent magnet poles Magnet quality: Neodymium GSN-38, Br 12 600 Gauss (at 20 °C), Tmax. 80 °C Additional information: Discontinued item! - Replacement: TPGC070088 / TPGC100088 Diameter: 100mm Height: 70mm Weight: 1.1kg
TPGC040078 HGR	SQ-040-FP-R-M-S 40X40
TPGC100078/621829300	HGR-SQ-100-FL-R-G-S Product description: Pneumatic magnetic gripper Type: Base Dim.: 100 mm Circuit: Pneumatic Recommended working load: 500 N (under ideal conditions - with Safety factor 3 according to EN13155) Max. tear-off force: 1500 N (under ideal conditions - graphic: see table Downloads - influencing factors lifting performance: see About magnetic handling and lifting) Minimum recommended sheet thickness: 3 mm Interface/connection dimensions: threaded hole M6 (8x) Interface/connection dimensions: M10 threaded hole Connections: Pneumatic: G1/8" (2x) Housing material: aluminum Material housing: AISI316L (stainless steel 1.4404) (screw cap) Surface treatment/coating: Anodized Red color Min./max. Ambient temperature: 0 to 70°C Switching pressure: Max. 4 bar Air consumption: 1.352 l/cycle (1x up, 1x down) Magnet system: 8 permanent magnet poles Magnet quality: Neodymium GSN-45, Br 13 700 Gauss (at 20 °C), Tmax. 80 °C Depth: 100mm Width: 100mm

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Height: 70mm Weight: 1.5kg
TPGC070078	HGR-SQ-070-FL-R-G-S Product description: Pneumatic magnetic gripper Type: Base Dim.: 70 mm Circuit: Pneumatic: 2 compressed air connections, or 1 vacuum connection: see 'Gripper connection for vacuum control' (Downloads tab) Recommended working load: 175 N (under ideal conditions - with Safety factor 3 according to EN13155) Max. tear-off force: 530 N (under ideal conditions - graphic: see table Downloads - influencing factors lifting performance: see About magnetic handling and lifting) Minimum recommended sheet thickness: 2 mm Interface/connection dimensions: threaded hole M6 (8x) Interface/connection dimensions: M10 threaded hole Connections: Pneumatic: G1/8" (2x) Housing material: aluminum Material housing: AISI316L (stainless steel 1.4404) (screw cap) Surface treatment/coating: Anodized Red color Min./max. Ambient temperature: 0 to 70°C Switching pressure: Max. 4 bar Switching pressure: vacuum pressure -0.3 bar (switch on) Air consumption: 0.568 l/cycle (1x up, 1x down) Magnet system: 6 permanent magnet poles Magnet quality: Neodymium GSN-45, Br 13 700 Gauss (at 20 °C), Tmax. 80 °C Depth: 70mm Width: 70mm Height: 70mm Weight: 0.7kg
TPGC040078	HGR-SQ-040-FL-R-M-S Product description: Pneumatic magnetic gripper Type: Base Dim.: 40 mm Circuit: Pneumatic: 2 compressed air connections, or 1 vacuum connection: see 'Gripper connection for vacuum control' (Downloads tab) Recommended working load: 77 N (under ideal conditions - with Safety factor 3 according to EN13155) Max. tear-off force: 230 N (under ideal conditions - graphic: see table Downloads - influencing factors lifting performance: see About magnetic

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	handling and lifting) Minimum recommended sheet thickness: 2 mm Interface/connection dimensions: threaded hole M5 (4x) Interface/connection dimensions: threaded hole M8 Connections: Pneumatic: M5 (2x) Housing material: aluminum Material housing: AISI316L (stainless steel 1.4404) (screw cap) Surface treatment/coating: Anodized Red color Min./max. Ambient temperature: 0 to 70°C Switching pressure: 4 bar (recommended), 6 bar (max.) Switching pressure: vacuum pressure -0.3 bar (switch on) Air consumption: 0.160 l/cycle (1x up, 1x down) Magnet system: 4 permanent magnet poles Magnet quality: Neodymium GSN-45, Br 13 700 Gauss (at 20 °C), Tmax. 80 °C Depth: 40mm Width: 40mm Height: 63mm Weight: 0.22kg
Tpgc024078	Magnetic gripper - pneumatic switched Base - # 24 - 34 HGR-SQ-024-FL-R-M-F
Tpmv070028	
Ehkad02000 Heb-035x30-0200-Gc	
M-333410	
Svmn020500	
Tpgc050018	
Svm-N-158x32-0500-F-F1m	
Hgr-Sq-100-Fl-R-G-S	
Tpgc-090001 Obsolete Replaced By Tpgc990001	
Svm-N-204x55-0500-B-F1m	
Ssfm005038	
Tpgc990001	
Tpgc130038	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Tpmv040028	
83.9900015	
Tpgc070078	Magnetic gripper - pneumatic switched Base - # 70 - 530 HGR-SQ-070-FL-R-G-S
Tpgc100038	
Hgr-Ro-020-Fl-R-M-F	
Tpgc070088	
Tpgc040078 E	
Tpgc990004 (Ex Tpgc050)	
Sme8mds24vk-2 5-Oe	
Tpgc990002 A	
Tpgc160078	HGR-SQ-160-FL-F-G-S Magnetic gripper - pneumatic switched
Sealing Kit For Secr043338	
Svmn030500	
Ssfm006538	
E0149812	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.