

Graf-Sytec

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Graf-Sytec Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Graf-Sytec Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
D1520I-400t	7 "touch display, 350 cd / m ² , 800 x 480 pixels Battery-buffered real-time clock, 4 digital inputs, 4 analog inputs (0-10V / 0-20mA), 2 digital outputs, Interfaces: 2x CAN, RS232, Ethernet (Modbus TCP), USB GSe-OS operating and control devices Art.No. 185321 required
185321	GSe-OS operating and control devices Operating system for operating and control devices Device firmware subject to license consisting of Operating system and application framework for visualizations, C programs and process monitoring as well as the underlying Operating system.
190069	D1K100 Connector for D1 devices with I / Os
Mcm 200	digital CAN node 10-32V supply voltage 4 x digital inputs / counters switchable 4 x digital outputs with PWM 4 x analog inputs 0-20mA / 0-10V switchable 8 x digital inputs / outputs switchable Protection class IP67 Measurement of the supply voltage Measurement of the device temperature
Mcm 300	analog CAN node digital CAN node 10 - 32V supply voltage 2 x digital inputs, can also be used as counters 2 x digital outputs 10 x analog inputs 0-20mA 6 x analog output, 0-20mA Protection class IP67 Measurement of the supply voltage Measurement of the device temperature

Ürün	Açıklama
185322	GSe-OS peripherals Operating system for I / O modules Device firmware requiring a license consisting of operating system and Application framework, C programs and process monitoring as well as the underlying Operating system.
Mck 101	29-pin connector with crimp contacts and seal Net weight / device: 0.10 kg
ITS 6200 A100	24 VDC
RS232 X1	
At6500c517a1-A0a1fo	
148184 / Atn8220c1a54	
Pik 524bc	
At 3300c1a00a6-A5b3f1	
Atn8220c1a54-A2aono	
148184	
6500c517a1	
8220c1a52-A5b1h2 Obsolete, Replacement 148184 / Atn8220c1a54!!!	
Pik426b1dc	
Pik314bd4pac Obsolete, Replaced By Pik 314d4pac	
Typ At6820c1a00d0-A3b2h2 Uin 12-24 Vdc No: 604289	
At 6500c517a1-A1b1f1	
Pa621	
Its6500c517 / At 6500c517a1-A1b1f1	
At 6820c1a00d0-A3a5b1	
Atn8220c1m54-A2a5b1	
Pa1085	

Ürün	Açıklama
At 8220c1a52 ? A5b2h2	
At6500c517a1-A0a2f0	
Can-Bus Gcm-401 Analog +/-10v Out	
160254	
Atn8220c1a54-A2a0n0	
Pik 314d4pac	