

Grob

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Grob Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Grob Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
MC25-GL-F-1F-GK-0350-0000-	TR100x16-b-2FR-OM-S Screw Jack Classic Size: MC25 Load: 250 kN static Type: G Version: F Installation position: 1F Translation: L 32:1 stroke per revolution of drive shaft: 0.5mm Stroke: 350mm Spindle extension: VL = 0 mm Lifting spindle: TR100x16 reinforced Head: GK Drive Shaft End: Both Sides Installation dimensions of housing screw-on surface up to (middle hole) GK head retracted: 359 mm Protective tube: round Guide ring: with second guide ring Motor mounting side: without motor Ground: red-brown Special versions: - reinforced spindle Tr100x16 - incl. bellows - incl. anti-rotation device Temperature monitoring: Self-ad. Measuring point for limit value monitoring (+82°C)
MJ3-GN-1F-0850-FP-SF-Bb"A+B"	Screw jack cubic Size: MJ3 Load: 25 kN static Type: basic version Installation position: 1F Translation: N 6:1 stroke per revolution

Ürün	Açıklama
	of drive shaft: 1 mm Stroke: 850mm T dimension: 150 mm Lifting spindle: TR30x6 Head F: FP Housing: Die-cast GROB logo Drilling pattern side A+B Drive shaft end: A+B Protective tube: Ø50x2 x 875 Spindle cover: spiral spring SF 050/1200/075 Lubricant: DIVINOL LITHOGREASE 1500 Paint: NOT painted Temperature monitoring: Self-ad. Measuring point for limit value monitoring (+82°C)
9-34432-0005	trapezoidal thread spindle TR40x7x735mm Right Material: C35 rolled Length: 735mm without end processing
9-34432-0001	Short steel nut KSM TR40x7 To the right Material: 11SMnPb37 Length: 60mm diameter 80 mm
801,031,04,FIG.3	LAMELLA STOP CONTACT
Gmn3360-19.1-90-7	
118020680104041544e00	
Gmm3360-35-71-18	
Kgt25-3-5-215-0-0-01	
G320-1940-1010-01-A21k-1003	
93e-0045	
Gmm3360-13-71-9	
Gmm3360-15-71-58	
Mj1-Gn-Tr18x12p4-0150-Fp-Fb-2e	
Kgt63-3-10-848-0-0-01	
Mj1-Lmn-0160-Z-Efm	

Ürün	Açıklama
Mtz	
Gmm3360-11-111/11	
Gmm3360-12-70-05	
267351 303 Kfw 4820	
Gmm3360-29-111-37	
Mj1-Gn-Tr18x12p4-0150-Fp-Fb-2e Schneckenhubgetriebe In Grundauführung Bis 5kn Belastung	
18-Fett00001	
Gmm3360-12-70-06	
40099900	
G320-1940-2010-01-A21k-1003	
Pl02200110121	
Kgt40-3-10-827-0-0-01	
Ksm Tr40x7	
Gmm3360-13-71-7	
Schneckenwelle N Mj2	
G300-1940-0010-01	
Mj1-Lm0000-S0sw	
118020680104041544e00 Worm Wheel (Schneckenrad)	
Gmm3360-15-70-16	
Mc25 (5-0000001350)	
9-Fett Spindelspray Spindel Montagespray 400ml	
Gmm3360-13-71-30	
2125690	
Gmm3360-35-71-17	

Ürün	Açıklama
Mc25-GI-F-1f-Gk-0350-0000-Tr100x16-B-2fr-Om-S Worm Gear Screw Jack	
Ksm Tr40x7 Threaded Nut	
1-0000021672 , Type Mj4-Gn-0100-Ge	
Gmm3360-13-71-21	
Gmm3360-21-1-110-14-01	
Gmm3360-14-71-30	
Ez20-A/D/D-4000-43-300-1100010	
Gmn3360-15-70-17	
Gmm3360-13-71-6	
Mc25-GI-F-1f-Gk-0350-0000-Tr100x16-B-2fr-Om-S	
9-34432-0003	
Mj1-Lmn-0160-Efm	
Gmn336029110-13+15	
Bz80-9650-37-3	
Ksm Tr40x7 Rechts (9-34432-0001)	
Tr40x7x730mm Rechts (9-34432-0004)	
Gmm3360-15-71-63	
Gmm3360-35-71-15	
Mj3-Gn-0700-As-Gk-Kp	
Gmm3360-35-71-16	
Gmm3360-13-71-8	
1-0000021672 , Type Mj4-Gn-0100-Ge Schneckenhubgetriebe	
Mj3-Gn-0700-As-Gk	
986888	

Ürün	Açıklama
Z501-1930-63-61-02-Et	
Trapezgewindespindel Tr18x12p4	
9-Fett Spindelspray	
Mj1-Lm-0000-Sosw	
Schneckenrad Mj1 Sondergewinde	
Gmm3360-11-113/21	
Kgt40-3-10-432-0-0-01	
9-34432-0003 Trapezgewindespindel	
Gmm3360-13-71-20	
09-R-01-06826-01	