



Haake

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Haake Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Haake Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
HSC B-40 (1210mmx40mm) Safety Edge	
HSC B-40 (738mmx20mm) Safety Edge	
HSC B-40 (165mmx20mm) Safety Edge	
HSC B-40 (2000mmx40mm) Safety Edge	
011-0800	
10223	
222-1693	
227440 - OEM	
399-0112	
60053 / VC0000914	
60056 / VC0001793	
60059 / VC0023834	
60059 / VC0023836	
60060 / VC0023837	
60066	
60213 / VC0008152	
808-0732	
808-0753	

Ürün	Açıklama
AC200-G50 230V/50Hz	
C1	
C270-030-0041	
EDGE HSC 65-35-01 in length of 2700mm	
HSC 40-20-01	
HSC 40-20-02 OEM	
HSC 95-35-02 T	
HSC65-03-2600	
HSM	
HST-TS1	
HST-TSS1	
MT 556-0025	
Spindle for VT02 Plus	
V1	
VT 550	
WK45	
60054 / VC0001746	Switch element HST-SE1 Weight in kg: 0.47098 Design: Installation Ø 5.5 mm Number of locks: 1 Current: 20A Contact assignment: 2NC2NO with the operating key inserted: no Caption: H
HSC95-35-01T	
FVHSC653503T 350mm	
FVHSC40-20-03T 500mm	Rechts+Links
HSC 40-20-01 T	VC0046026 60058 Weight in kg: 1.19017 Sensing edge length [mm]: 1000

Ürün	Açıklama
	Aluminum profile surface: untreated Location of the cable exit: front right Type of cable exit: 2 x grommet x dimension right for cable outlet [mm]: 50.0 Cable length [mm]: 1000 Type of attachment: threaded bolt M8 x 18 mm a dimension [mm]: 50.0 b dimension [mm]: 450.0 c dimension [mm]: 50.0 Number of attachments: 3 Anti-slip device: no
HSC 40-20-01 T (VC0046028)	Safety edge HSC 40-20-01 T Weight in kg: 2.12845 Length of safety edge [mm]: 2100 Aluminum profile surface: untreated Location of the cable exit: front right Type of cable exit: 2 x grommet x dimension right for cable outlet [mm]: 50.0 Cable length [mm]: 1000 Type of attachment: threaded bolt M8 x 18 mm a dimension [mm]: 50.0 b dimension [mm]: 400.0 c dimension [mm]: 50.0 Number of attachments: 6 Anti-slip device: no
HSC 40-20-01 T (VC0046027)	Gewicht in kg: 1,6208 Länge der Schaltleiste [mm]: 1500 Oberfläche des Aluminiumprofils: unbehandelt Lage des Kabelausgangs: vorne rechts Art des Kabelausgangs: 2 x Tülle x-Maß rechts für Kabelausgang [mm]: 50,0 Leitungslänge [mm]: 1000 Art der Befestigung: Gewindebolzen M8 x 18 mm a-Maß [mm]: 50,0 b-Maß [mm]: 350,0 c-Maß [mm]: 50,0 Anzahl der Befestigungen: 5 Rutschsicherung: nein
60056 / VC0001788	Switch element with locking device HST-ME2 Weight in kg: 5.45239 Design: Installation Ø 5.5 mm Power supply: 24 VDC Contact assignment: 2NC2NO Number of locks: 2 with the operating key inserted: yes Labeling:
60056 / VC0001807	Switch element with locking device HST-MA2

Ürün	Açıklama
	Weight in kg: 11.16799 Design: construction steel Power supply: 24 VDC Contact assignment:
Thermostat bath (230 V/50 Hz), -20 to +150 °C	• High-class thermostat with excellent temperature stability • in combination with the aluminum blocks for sample preparation. • Digital temperature setting via front panel. • Temperature range: -20°C to +150 °C • temperature stability: ±0.03 °C • size (W x D x H): 23 x 39 x 65 cm. • bath opening (W x D)/bath depth: 13 x 15 cm / 15 cm, • bath volume: 3 - 4 l Note: • Please order the matching aluminum blocks for sample tube tempering separately.
HST-ME1	
HST-TZ1	
HST-TZ1	Artikel-Nr.: 60053-VC0000914 Seriennummer: 2247466 System: HST-S-C1
1624093 HMS-S 60487 PA1336	
Hsc 65-35-03 T	
Typ 1862-00	
904-04185	
Hsc 3-05 L=446 Cod Swisslog 506269	
Hsc400301/02	
222-1693 Calibration To A Measuring Accuracy Of +/- 1% Fsd	
H-399-0100	
Hsc 100-100-35-03	
Hsc400201/02	
Dynamax 1200	
Hsb 1085-00	

Ürün	Açıklama
Hsc40-01-875	
Typ 1862-10	
Hsm1300x700mm	
Hsc400201/02-1000mm	
Minilab li Analiz Cihazı	
Dc50 110v Circulating Pump	
557-2298	
B1	
Hsc-9502	
808-0732 Coupling For Rotor	
002-1293 Window	
Fisons Vt 500	
E 7	
557-2286.	
222-1688 Battery Charger Incl 4 Batteries Aa	
Hsc 100-50-35-02 1600mm Sx	
Ersatzteil	
Hsc95.02	
Hsc40-02-1150g	
Hsc 40-20-02 1200mm Dx	
Hsm1000x510	
Dx-834620	
Dc50/K35 Circulator System	
557-2190	
Hsc10002/2-1864-00	

Ürün	Açıklama
Mt 556-0025 - , No	
Hsc40-02-1150d	
1863-00-Hsc10002/1	
550 362-0021	
Safety Edge 120 Cm	
002-1292 Coupling Motor/Gear	
Hsm 2632-00	
Hsc 95-35-02	
557-2193	
Hs100-02/02	
557-2299	
H-399-0200	
Hsc 40-20-02 1200mm Sx	
P1	
System-40-Cpu	RHEOCORD SYSTEM 40 1PH 20AMP 220VAC MODEL 80-40-00
Hsc 65.01 L=2645mm	
Cup Nv	
Hsc3-05-506267	
362-0021	
222-1679	
Hsc40-20-01/1030mm	
Rotor Nv	
399-0200 Viscotester	
Haake Viscotester 2plus	
799-0408 Housing Complete For Vt02	
557-2289	

Ürün	Açıklama
F4391	
Ac200-A28	
4263602	TEMP CONTROL
Hsc3-05-506268	
808-0726 Mini-Motor For Vt02	
Hsc 100-50-35-02 1600mm Dx	
Hsc 40-20-02	
Dc10-K10	
Hsb Hsc 100 03-02	
C10-K10	
Hsc 100.03	
Hst-Sv1-4p-20a	
Hsc5502	
Hsc 65.03	
10038561	
10670863	
399-0200	