

Haehne

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Haehne Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Haehne T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
3DX-700026	
BZA1-15-250-S	
BZA2-25-400-S	
bzh-k-01-10kx	
BZH-K01L10k-T	
BZH-K01R10k-T	
BZN1 20A250-S1	
BZN3-40A4000-TQ2	
BZV-K03-200k-T	
DMA3-C	
DMA3-U	
KMB20-4k-T	

MUW100-1600-1830	
MV125GK-N	
MV128N	
PM2-D	
RKS01A1k-T	
SPACE EXPLORER	
SPACENAVIGATOR	
SPACEPILOT PRO	
ZAK-A20-TP	
AME2-C	measuring amplifier DIN - mounting rail housing Dimensions: 99 x 22.5 x 114.5mm (L x W x H) plug-in terminals, power supply 24 V DC 2 voltage outputs (direct / filtered) Technical data see product description Signal output C: 1 current output 4...20mA, direct with sensitivity E = 0.75mV/V (Gain 1333) like serial no. 123507
Belt tension sensor BZA2-20-250-S	Flange design, aluminum design, size 2, For technical data see product description Shaft journal ø 20 Rated force 250N Connection S: Plug connection, angled, MIL Cable length 5m cable length Nominal characteristic 1.5mV/V Net weight 1.6 kg/piece
DK2B0.2k-T	
DA-2-K-2	
Belt tension sensor BZN1-20A1000-T	Flange design, stainless steel version Protection class IP 67, size 1 Technical data see product description Shaft journal ø 20 Design A: with cover open on one side Nominal force 1000N Connection T: cable gland, straight Cable length 5m cable length Nominal characteristic value 1.5mV/V Net weight 1.8 kg/piece
Measuring amplifier MV125GK-N	Field housing 150 x 64 x 36 mm (L x W x H), Screw terminal version, auxiliary power 24 V DC, 2 voltage outputs (direct/filtered), technical data see product description, option U: basic equipment (see above) Signal output N: 1 current output 0...20mA, direct Net weight 0.5 kg/piece
BZA2-20-250-SX	strip tension sensor Flange design, aluminum version, size 2, For technical data see product description shaft journal ø 20 nominal force 250N Connection S: Plug connection, angled, MIL Special version X: Bore d5 = 32.5 nominal value 1.5 mV/V Net weight 1.6 kg/piece
KMB20-10k-TWX2	Load Measuring Pin Rated force: 10 kN Pin diameter: 20 mm Connection: Straight cable gland Cable: 0.3 m fixed Teflon measuring cable Stainless steel special version Rated output: 0.75 mV/V

Connection Cable for Load Pin	15 m Teflon cable, ready for installation UL approved (Style 2750, UR marking) LiTCT 4 × 0.24 mm ² Outer diameter approx. 5.7 mm Cable colour: White Temperature range: -100°C to +200°C
Mv125-Gk-C-G	
Dma2	AMPLIFIER
Bzv-K-01-R-20-X	
Bzv-K02-100k-W	
Bzh-K01I10k-X	
Dma2-Uc	
Bzv-K-01-L-20-X	
Dk6-16k-T	
Mv225c	
Bzh-K01r20k-X	
Bzh-K01r10k-X	
Bza1-17-630-S-G	
Bzn3-40a1600-Swx	
Dma 2 C	DIGITAL MEASURING AMPLIFIER
Mv125gk-C	2016006
Bzh-K01I20k-X	