Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr



Hansford Sensors

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Hansford Sensors Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hansford Sensors Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
HS-AC356-20	Cable assembly, 2 pin MS straight connector on fly end, shielded 2-wire FEP cable blue, Shield not applied, cable length: 5m. The cable is only available in lengths of 5m, 10m, 15m, 20m ..... Special lengths only on request for larger quantities. Weight: 840g / Unit,85444290 UK
HS-AC356	Cable assembly, 2 pin MS straight connector on fly end, shielded 2-wire FEP cable blue, Shield not connected, cable length: 25m. The cable is only available in lengths of 5m, 10m, 15m, 20m ..... Special lengths only on request for larger quantities. Weight: 1040g / Unit,85444290 UK
HS-1001005008	AC accelerometer HS-100 series, acceleration sensor, 100mV / g output, 2 pin MS connector, M8 x 1.25 Grub screw | Please note: A cable assembly is required to operate this sensor - please note your shielding concept.
HS-AC356-30	HS-AC Cable assembly, 2 pin MS straight connector on fly end, shielded 2-wire FEP cable blue, Shield not connected, cable length: 30m. The cable is only available in lengths of 5m, 10m, 15m, 20m ..... Special lengths only on request for larger quantities.
HS-420P0500208-005	4-20 mA Transmitter HS-420 series, 4-20mA vibration sensor, top entry, 4-20 mA output, 0-50 mm / s peak, Integrated shielded ETFE cable armored, M8 x 1.25 threaded pin - cable length: 5 m. Weight: 350g / Unit, Nomenclature Number: 90318080, Country of Origin: UK

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HS-4200105008	4-20 mA Transmitter HS-420 series, 4-20mA vibration sensor, top entry, 4-20mA output, 0-10mm / s RMS, 2 Pin MS connector, M8 x 1.25 threaded pin | Please note: For the operation of this sensor a cable assembly is required - please note your shielding concept. Weight: 150g / unit
HS-AC334-5 (Optional)	HS-AC Cable assembly, 2 pin MS straight connector on fly end, shielded 2-core FEP cable, Shield applied, cable length: 5m. Weight: 240g / Unit,
HS-420I0251222	4-20 mA Transmitter HS-420 series, intrinsically safe group II, 4-20mA vibration sensor according to Ex ia IIC T6 Ga,, 4-20mA = 25 mm / sec RMS, shielded FR-PUR cable in 1/2 "NPT thread adapter, 1/2" - 13 UNC Grub screw - cable length: 300mm. Weight: 150g / Unit, Nomenclature Number: 90318080, Country of Origin: UK
HS-AA042 (Optional)	HS-AA Aluminum terminal head with 1/2 "NPT thread. Weight: 260g, Nomenclature Number: 85389099, Country of Origin: UK
HS-150T1000108-005	AC accelerometer HS-150 series, premium accelerometer with temperature output, top entry, 100mV / g Output, 10mV / ° C output (up to 100 ° C), integrated shielded PUR cable, M8 x 1.25 Grub screw, cable length: 5m.
HS- 420RT1000108- 005	
HS-100I1005008	
HS-100S1000102-100	
HS-1400305714	
HS-140S0305714	
HS-4200100205-005	
HS-4200100208-010	
HS-4200105408	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HS-4200205008	
HS-4200205401	
HS-4200255408	
HS-4201000108-005	
HS-4201005408	
HS-420I0200708-025	
HS-420I0250705	
HS-420I0255401	
HS-420RT0205405	
HS-420S1000706-005	
HS-420SRT0205402	
HS-420T0105405	
HS-420T0255406	
HS-420T0500102-030	
HS-420T1000110	
HS-422SRT0105402	
HS-429 + HS-AC011-40	
HS-4290255408+HS-AC011-20	
HS-4290505408	
HS-510TS150IL1L1	
HS-620 (HS-620-B)	
HS-630	
HS-630 (HS-630-B)	
HS-AC010-30	
HS-AC011-10	
HS-AC100 (1m)	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HS-AC356-5	
HS-AA031-M8 (Optional assembly tool)	HS-AA Assembly tool set M8, planer Ø 32mm, drill, thread cutting set M8 x 1.25, Tool holder, in practical storage box
HS-420M0250708-005	4-20 mA Transmitter HS-420 series, intrinsically safe group I, accelerometer according to Ex ia IIC T6 Ga, , 4-20mA = 25 mm/sec RMS, integrated silicone cable IP68, M8 threaded pin attachment, cable length 5m. Weight: 380 g/unit, Commodity number: 90318080, Country of origin: UK
HS-551-A	HS-551 series, power supply for accelerometers Input: 100mV/g constant current accelerometer (HS-100) Output: AC (o VDC bias) BNC or terminal block
HS-530	HS-500 Single Channel Interface Module with Special Filtering designed to highlight mode Input - 100mV/g Constant Current Accelerometer Output: 1) AC a) AC 'g' via BNC b) AC Enveoloped 'g' via screw terminals Output 2) 0-10 Volts a) Proportional to RMS Velocity b) Proportional to Envelope 'g' "Sensor OK" Function
HS-4200500208-005	4-20 mA Transmitter HS-420 Series, 4-20mA Vibration Sensor, Top Entry, 4-20 mA Output, 0-50 mm/s RMS, integrated shielded armored ETFE cable, M8 x 1.25 threaded pin, cable length: 5 m. Weight: 350g/unit, Commodity number: 90318080, Country of origin: UK.
WT-BL-MI-60-D-MU 4-20MA	ART NO:69218 \ :6 MM \ NL:500MM 1XPT100/A/3 GEV-06L-G1/2-D
WT-BL-MI-60-D 4-20MA	ART NO:39013 \ :6 MM \ NL:200MM 1XPT100/3 DIN EN 60751/ GEV-06L-G1/2-D MAX EL:170 MM
WT-BL-MI-60-D 4-20MA	ART NO:30764 \ :6 MM \ NL:115MM 1XPT100/3 DIN EN 60751 GEV-06L-G1/2-D / MAX EL:85MM MOL
WT-BL-MI-60-D-MU 4-20 MA	
HS-AC095	Cable assembly, BNC plug straight to TNC plug straight, coaxial

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	cable, straight, black, shielded, 80cm, for data collector HS-620 and HS-630.
VBT30	HANSFORD SENSORS HS-630-B 3106364
HS-420I0100205-005	4-20 mA Transmitter Ex ia HS-420 series, intrinsically safe group II, accelerometer according to Ex ia IIC T6 Ga, 4-20mA = 10mm/sec RMS, armored ETFE cable, Quickfit hole - cable length: 5 m Weight: 350g/unit
HS4210505408	
HS-4200250108	
HS-1501000806-002	AC acceleration sensor HS-150 Series, Premium Industrial IEPE Vibration Sensor, Design: top entry housing, Case material: standard 304 stainless steel, Sensitivity: 100 mV/g, Sensitivity tolerance: standard 10% at 3dB, Electrical connection: Integrated, shielded, 3-wire FR-PUR cable, blue, Protection class: IP65, umbrella placed, Cable length: 2 m, Mounting thread: M6 x 1 grub screw
HS-4200250208-005	4-20mA Transmitter HS-420 series, industrial 4-20 mA vibration sensor, Design: top entry housing, Case material: 304 stainless steel, Measuring range: 0 - 25 mm/s, Output signal type: RMS, Frequency range: 10 Hz - 1 kHz, Electrical connection: Integrated, shielded, 2-core ETFE cable with stainless steel braid, Protection class: IP65, umbrella placed, Cable length: 5 m, Mounting thread: M8 x 1.25 set screw.
HS-AC334-05	HS-AC series, cable assembly, Connector 1: straight 2 pin MS screwable, molded coupling, polyamide with stainless steel nut, umbrella placed,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	on free ends, Cable: 2-core, shielded FEP high-temperature cable, up to 200°C, blue, Cable length: 5 m
HS-AC334-10	HS-AC series, cable assembly, Connector 1: straight 2 pin MS screwable, molded coupling, polyamide with stainless steel nut, umbrella placed, on free ends, Cable: 2-core, shielded FEP high-temperature cable, up to 200°C, blue, Cable length: 10 m
HS-4200205001	4-20mA transmitter HS-420 series, industrial 4-20 mA vibration sensor, Design: Top Entry housing, Case material: stainless steel 316L, Measuring range: 0 - 20 mm/s, Output signal type: RMS, Frequency range: 10 Hz - 1 kHz, Electrical connection: 2 pin MS connector, Protection class: IP68, Mounting thread: 1/4"-28UNF threaded hole.
HS 420 020 50 01	
PR-NEWL 17653 Gold LB BMMC NL	
HS-422S1005006 HS-422	HS-422S Series, industrial 4-20 mA acceleration sensor, Design: Side Entry Housing, Case material: 316L stainless steel, Measuring range: 0 - 100 g, Output signal type: RMS, Frequency range: 10 Hz - 5 kHz, Electrical connection: 2 pin MS connector, Protection class: IP68, Mounting thread: M6 x 1 hexagon screw.
HS-420S1005006 4-20 mA Transmitter	HS-420S Series, industrial 4-20 mA vibration sensor, Design: Side Entry Housing, Case material: 316L stainless steel, Measuring range: 0 - 100 mm/s, Output signal type: RMS, Frequency range: 10 Hz - 1 kHz, Electrical connection: 2 pin MS connector, Protection class: IP68, Mounting thread: M6 x 1 screw.
HS-AC334-05 cable assembly	HS-AC series, cable assembly, Connector 1: straight 2 pin MS screwable, overmolded coupling,

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	polyamide with stainless steel nut, Umbrella placed, on free ends, Cable: 2-core, shielded FEP high-temperature cable, up to 200°C, blue, Cable length: 5 m - other lengths on request
HS420T-050-01-06	4-20mA transmitter HS-420 Series, industrial 4-20 mA vibration sensor with temperature output, Design: Top Entry Housing, Case material: 316L stainless steel, Measuring range: 0 - 50 mm/s, Output signal type: RMS, Frequency range: 10 Hz - 1 kHz, Temperature output: 10 mV/°C up to 100°C (other ranges on request), Electrical connection: Integrated, shielded, 4-core PUR cable, blue, Protection class: IP68, Umbrella placed, Cable length: 5 m, Mounting thread: M6 x 1 threaded pin.
HS-AC336-05	Cable assembly HS-AC series, cable assemblies, Connector 1: straight 3-pin MS screw-on, overmolded coupling, polyamide with stainless steel nut, Shield connector 1: Shield connected, on free ends, Cable: 2-core, shielded FEP high-temperature cable, up to 200°C, blue, Cable length: 5 m.
Hs-630x	
Hs-4200105006	
Hs-4200250108	
Hs 4220020208	
Hs-420	
Hs-422	
Hs - 420t0255405	
Hs-420 025 01 08 005	
Hs-1001005406	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Hs-Ac054-006	
Hs-535	
Hs42001000108	
Hs-Ac	
Hs 420 4-20ma	
Hs-423	
HS-4200200208-005	4-20 mA Transmitter HS-420 Series, 4-20mA Vibration Sensor, Top Entry, 4-20 mA Output, 0-20 mm/s RMS, integrated shielded ETFE cable armored, M8 x 1.25 threaded pin - cable length: 5 m. Weight: 350g/unit, Commodity number: 90318080, Country of origin: UK
Hs-420-Bbb-01-Dd	
Hs-620	
Sn:146414	
Hs-4220020208	
Hs-420i0250705	
Hs4200100206	
HS-1001005006	HS-100 series, industrial IEPE vibration sensor, Design: Top Entry case, Housing material: Standard 316L stainless steel, Sensitivity: 100 mV/g, other sensitivities according to datasheet at no extra cost Sensitivity tolerance: Standard 10% at 3dB, Electrical connection: 2-pin MS connector, Protection class: IP68, Mounting thread: M6 x 1 threaded stud - other mounting threads according to datasheet at no extra cost . Please note: A shielded cable assembly is required for operation of the sensor. Please observe your Shielding concept |
Hs-Am011	
Hs - Am005	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Hs-420 025 50 05	
Hs: 4200200208 / Vibration Transmitter, (4-20 Ma, 20mm/Sec Accelerometer)	
Hs-420rt Xxx 01 Xx 005	
Hs-421	
Hs-420t0105412	
Hs-620-500-B Not Available, Doesnã39;T Exist	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.