

Hbm



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Hbm Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime geiniz.

Firmamız Hbm T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
U10m/250kn	Tensile/compres. force trans.U10M/ 250kN Force transducer for tensile and compressive forces Strain gages system 350 Ohm Bayonet device connector (MIL-C-26482 series1 compatible) Nominal range 250 kN Rated output 2...2.5 mV/V With mounted base plate Measuring body material: stainless material Influence of bending moments compensated. HBM accuracy class: 0.04
1-Z30A/10KN	Force transducer / transfer standard for tensile and Pressure forces Strain gauge measuring system Rated force: 10 kN Nominal value: 2 mV/V Accuracy class according to ISO 376 in the force measurement range 20% - 100%: CL00 Six-wire circuit Binder connector, seven-pin TEDS integrated Class only guaranteed with additional available DKD calibration certificate
SG250	
3130.0239-G	
LY15-0.3/120	
SP4MC3MR/3KG-1	
HBM RTNC3/1T BVS13A ATEX E 108 X 0058211	LOAD CELL IT:244464 ART:S0058211
	load cell Rated load: 200kg Minimum division value: 0.0090% of Emax OIML R60 test report Accuracy class: C3 Measuring

1-Z6FC3/200KG-1	body: stainless steel Protection class: IP68 according to EN 60529 Type of cable: Shielded 6-core round cable, PVC Cable length: 3m
1-AD103C	Digital pick-up electronics for dosing applications. DC voltage amplifier with digital measurement signal processing for Output of scaled measured values. Direct computer connection possible. communication via RS 232 interface. Operating voltage 5 V DC stabilized. Test certificate for class III balances 10000d, 0.5 µV/e according to OIML
AE301S6	
1-Z30A/10KN	FORCE TRANSDUCER F7633
S9m-0,5kn	
RTNC3/ 2.2T	
LOADCELL HBM RTNC3/ 2.2T	
HBM C16-A C3-30T	
Z6-FC3	2+/-10% m V/V 50 KG
PW12CC3 -300 KG EXPROOF Loadcell	
Rm4220	
K-CLY4-0015-1-350-O	-FMD- STRAIN GAGE / STRAIN GAUGE / UNIDIRECTIONAL SELF-WIRED 1.5MM, 350 OHM
K-CRY8-0030-1-350-O	-FMD- STRAIN GAGE / STRAIN GAUGE / ROSETTE TYPE 3-WAY SELF-WIRED, 3MM, 350 OHM
K-CXY3-0030-1-350-O	FMD- STRAIN GAGE / STRAIN GAUGE / T TYPE, SELF WIRED, GAUGE GRID SIZE 3MM, 350 OHM
T22/50NM	TORQUE-TRANSDUCER
T40B	
1-PW22C3/20KG-1	Platform load cell Rated load: 20kg Minimum division value: 2g Especially suitable for dynamic weighing Integrated overload protection OIML R60 Test Report Accuracy class: C3 Platform sizes up to 400 x 400 mm according to OIML R76 Material: Aluminum Protection class: IP67 according to EN 60529 Cable type: Shielded 6-core round cable with PVC sheath Cable length: 3m Connector: TE 3640442-6
801009255	SIGNAL CONDITIONER/AMPLIFIER CLIP 600HZ
T20wn/50nm	TORQUE TRANSDUCER 50NM 12PIN CONNECTION
K-T40b-001r-Mf-S-M-Su2-1-U	
P15rva2/50b	
K-U93-20k00-05-Y	

Rlb1c1k	LOAD CELL
Ap02	
Abm75	
K-Pmx	
K-Ly43-3/120-3-7.5m	
1-Z6FC3/200KG-1	load cell Rated load: 200kg Minimum division value: 0.0090% of Emax OIML R60 Test Report Accuracy class: C3 Measuring body: Stainless steel Protection class: IP68 according to EN 60529 Cable type: Shielded 6-core round cable, PVC Cable length: 3m
P2va1/100bar	
1b121000	
1-Mp55	
K-T40b-200q-Mf-S-M-Du2-1-U	
Wg001	
1-Wa/10mm-T	DISPLACEMENT TRANSDUCERS
Z6fd1/30kg-1	
1-Tn/10knm	
1-Wa/2mm-L	
K-C10-25kn-Sb-N-1-S-W-P-B	
1-C6a 5mn	
U2a100kg	
K-T40b-500q-Mf-S-M-Du2-1-U	
Z6fc3-200kg	
Mp60	SIGNAL AMPLIFIER
Z6fc3/100kg-1	
Z6fc3/1t	
Ap815	
1-Z7ad1/2t	
Z6fc3/500kg-1	
1-Wa/20mm-T	TRANSDUCER STANDARD DISPLACEMENT 0-20MM W10TK
K-T40b-005r-Mf-S-M-Du2-0-S	
Sv-725.01a-S6	POWER SUPPLY 24V 110V 50/60HZ

Z7ad1/2t	
K-T40b-200q-Mf-S-M-Su2-1-V	
Z6fc3/200kg-1	
Abc-Pdp-B	AnyBus Communicator
Ae501	
Oec30	
Z953115.07	
1-Kab157-3	
1-Hlcb1c3/550kg-1	
T5-100nm	
P2va2/200bar	
Elcb2hs/550kg-1	
P3ic/10bar	
Z6fc3mi	
Vkk1-4a	
P15rva1/50b	
1-Wa/200mm-L	
Df30dp	
Db25p292780293	
1-Sac-Epwr15-Ce-2	
1-Px878	
K-T40b-500q-Mf-S-M-Du2-0-S	TORQUE FLANGE 500Q:
P2va1/500bar	
1-Mp85adp	
1-T20wn/100nm	
1-Px01pn	
1-Z6fd1/50kg-1	
1-U2b/1kn	FORCE TRANSDUCER
1-Vkk2-8a	
Ts101	TARE AND STORE UNIT

Ae301s6	SIGNAL CONDITIONER/AMPLIFIER CLIP 600HZ 15-26V
1we2111	CONTROL
Mp60dp	PME AMPLIFIER SINGLE CHANNEL 24V 600AZ
Elcb2hs/1.76t-1	
Aed9301b	
K-Fs22-01-500-420	
K-T40-200q-Mf-S-M-Du2-0-S	
We2111	INDICATOR
Sp5c3	
1-Wgx002	
Hlcb1c3/2,2t	load cell Rated load: 2.2t Minimum Sharing: 0.0100% of Emax OIML R60 test report Accuracy class: C3 Measuring body: stainless steel Protection class: IP68 according to EN 60529 Cable Type: Shielded 6-core round cable, PVC Cable length: 6m
Ts40a	
P15rva1/500b	
C16ic3-60t	
Z7ad1/5t	
K-T10f-500q-Sf1-S-0-V6-N-N-15m	
1-Tim-Ec	
Pw16kr 100 Kg By 1-Pw16ac3/100kg-1	
1-Px455	
1-Cp42	
1-Mx840-Pakeasy	
X60	
1-Ad103c	DIGITAL TRANSDUCER MODULE
Rm4220	Strain Gauge Amplifier Module
Z6fd1/200kg-1	
K-Cal-F-D-7-B-S-S	
Z7ad1/500kg	
1-Kab14-15	
P15rva1/10b	

K-Wa-T020w-32k-K1-F1-2-8	
1 Ap03	
Z6fc4/200kg-1	
D-15d/Mont	
1-Mx840-Pakap	
K-U15-25k0-Sb-S-U-B-U	
3-3312.0182	
1-P3mbp/2000bar	PRESSURE TRANSDUCER 2000BAR
K-Z6 -F-C3-200-N-6-N-N	
Vk20a	
K-Wa-T-020w-32s-S2-F1-2-8-10	TRANSDUCER STANDARD DISPLACEMENT 0-20MM IP45
K-P8ap-235-14-T9-0-K-1	
Z6fd1/20kg-1	
Elcb2hs/220kg-1	
Ak22	
T20wn-10	
P2va1/3000bar	
1-Z70	
T5/50nm	TORQUE TRANSDUCER 50NM 7PIN CONNECTION
Ab22a	
Ae301	
P3ic/50bar	
1p3mbp100bar	TRANSDUCER
1-Kab405.30a-3	
K-T40b-200q-Mf-S-M-Su2-1-U	
1-Pw18c3/10kg	
Z6fc4/20kg-1	
Z6fd1-100kg	
Z6fc3 ? 50kg - 2mv/V	
Z7ad1/1t	

1-U2a/20t/Zguw	KNUCKLE EYE FOR TRANSDUCER GALVANIZED
C2/50kn	
Pme-Mp55	MODULE CARRIER/FREQUENCY AMPLIFIER 4.8HZ
1-Caseclip	
K-P3mb-010b-A	PRESSURE TRANSDUCER 10BAR W/3M CABLE
1ml30	
1-Sp4mc3mr/75kg-1	
Z6fc4	
P3icp/1000bar	
K-C9c-05k0-07m0	
T4a50nm	
1-Ae501	
C9c-1kn	
Ap01i	
1-Kab149-6	
1-Sp4mc3mr/50kg-1	
P3ic/2500bar	
1-Ab22a	
P2va1/2000bar	
Cp13	
Hlcb1c3 4.4t	
T40b-500q-Mf-S-M-Su2-0-S	
1-Teds-Db-15p	
K-Ly41-6/350	
P3ic/1000bar	
1-Sp4mc3mr-30kg-1	
1-Kab272-2	
3-4412.0007	
Elcb2hs/1.1t-1	
P2va1/5000bar	

1-Z6fd1-100kg-1	
C2200	TRANSDUCER
P15rva2/10b	
1-Kab154-6	
Mpz1604012 Dmont	
1-3130.0239-G	
K-U15-250k-Sb-S-U-B-J	
1-Ly11-3-350	
1-X60	
K-U10m-125kn	
Aed 9101b, By Aed9101d	
Z7ac3/5t	
Z6fc6/50kg-1	
1tg002	
C2100 Kg	
1-Pw4c3	
1-Thermo-Mxboard	
K-U10m-2k50-Sb-N-1-S-N-U-B-B-0	
Mpz1604012 + D-Mont	
Vkk2-8	
Z6fd1	
1kab01063	
C9b50kn	
K-Ly4-3-05-120-0	
1-Smstrb4-350-2	
Ap01	
1-Scout55	
T20wn20nm	
Ab12	
H35-5k-Se (Series/Model 793) 3mv/V	
1-Wa/300mm-L	

Ly81-1.5/120	
K-Kab-T-0153-01-015-S015	
1-Ae301s6	SIGNAL CONDITIONER/AMPLIFIER CLIP 600HZ
P15rva1/200b	
Mx840a	
Hlcb1c3 2.2t	
P3ic/500bar	
1-Kab150-6	
Z63c200kg	
1-C9b-1-Kn	
1-Tn/200nm	
K-T40fm-020r-Mf-S-M-Du2-A-S	
1-Wa/50mm-T	
K-Ry81-1,5/350	
P15rva2/100b	
Db15p333120182	
1-Px01	
Messkonverter-Mc3	
1-Wa/50mm-L	
Tg009b	
P2va1/7000bar	
1-Tb1a/5knm	
Z6fc6	
U15-25kn	
208479a	RACK W/POWER SUPPLY
1-P15rva1/100b	
1-Wa/500mm-L	
K-Wa-L-020w-31-S-S2-F1-2-8-050	
Z6fc3/20kg-1	
1-Z7ac3/10t	

Z6fc6/200kg-1	
1-U2a/100kg	LOAD CELL
P3ic/20bar	
Z7ac3/10t	
K-Cal-T-W-1-B-S-S-2-0	
1-Mp85a	
I-Aei01	
1-Vk20a	
1ab12	
C16ad1-60t	
D-Mont	
1/4-18npt	
Z6fd1/100kg-1	
Blcb1c3/550kg-1	
1-Kab139a-6	
K-Pw6c-N-C6-10-N-6-6-A	
P15rva2/20b	
S9m-0,5kn	
1-Ws/Zb 12 Alternatif	
T22-5nm	
1-Pw16ac3/50kg-1	
1-Kab153-6	
K-T40b-005r-Mf-S-M-Du2-1-S	
K-Wa-L-200w-31s-S2-F1-2-8-10	
Kab0104-10	
Vkk 1-4 By Vkk1-4a	
Vkk2-8a	
Z6fc4/100kg-1	
Z7ac3/2t	
C9b2kn	
U15-50kn	

P3ic/100bar	
MI30b	
P3icp/10bar	
1-Tn/5knm	
1-Ap08	
1-Ly81-0.6/120	
1-Pmx	
1-Px02	
1-Wa/100mm-T	
1-U2a/20t/Zgow	KNUCKLE EYE FOR TRANSDUCER ROLLER BEARING
P2va1/1000bar	
1-Ae101	
K-Ly41-1,5/350	
K-T40b-005r-Mf-S-M-Du2-O-U	
Usrtm25k15100	LOAD CELL
1-Mx440-Pakeasy	
Fit/H1sr2	LOAD CELL 50KG
K-T40b-003r-Mf-S-M-Su2-1-U	
Mvd2555	
K-T10fs-001r-L-Sf1-G-0-V0-N	
We2110	
D-Teds/Mont-Db	
Z6fc3/50kg-1	
1-C9c/100n-100n-01m5-Y-S	
Z7acc3/Zt	
1-Ly81	
1-Z7ad1/10t	
Z4a	
Z6fd1/500kg-1	
U3/0.5kn	FORCE TRANSDUCER 0.5KN

T40b-005r-St-S-M-Su2-0-S	
1-Smstrb4-120-2	
Z6fc3 ? 100kg ? 2mv/V	
P15rva1/20b	
1-Mp55dp	SIGNAL CONDITIONER SINGLE CHANNEL 4.8KHZ
1-Kab272-0.2	
C9b-10kn	
Z6fc4/500kg-1	
U15-10kn	
Mp55	CARRIER FREQUENCY AMPLIFIER
1-We2111	
1-T4a/5nm	
1-Mp60	
K-T40b-500q-Mf-S-M-Su2-1-U	
P3ic/750bar	
Blcb1c3/1.1t-1	
433010071	
1-Pw16ac3/75kg-1	
1-Kmr-30t	
1-C9b2kn	
Pme-Mp55dp	SIGNAL CONDITIONER SINGLE CHANNEL 4.8KHZ
Hlc-40kn	
Z7acc3	
Z6fc3/10kg-1	
K-Ry81-6/350	
1-Wa/10mm-L	
K-U1a-050n-A-K	FORCE TRANSDUCER 50N 6M CABLE
1-Ntx001	
K-P3-Mb-200b-Yá;Á;	
1-Mc2a	
Z30a/100n	

Pw2ac3	
K-Wa-T-050w-32k-K1-F1-2-2-003m-10m	
1-T4wa-S3/10nm	
Z6fd1/1t	
1-Kab153-15	
K-T40b-200q-Mf-S-M-Du2-0-S	
P3ic/200bar	
1-Ae301	
Pw18c3-20kg	
1-Subhd15-Male	
Kwa-T05w-32k-K1-F1-2-	
K-C9c-100n-05m0-F-T	
K-T40b-001r-Mf-S-M-Du2-A-U	
1-Z6fc3/200kg-1	
Z6fd1/10kg-1	
Z6fc3/30kg-1	
1-Wa/20mm-L	
P15rva2/500b	
1-Kab154-15	
Z6fd150kg	
1-Tb1a/100nm	
P15rva2/200b	
Z6fc4/50kg-1	
1-Mx878b	
1-U2a/200kg	load cell Rated load: 200kg Accuracy class: 0.1 Measuring body: stainless steel Protection class: IP67 according to EN 60529 Cable Type: Shielded 6-core round cable, thermoplastic elastomer Cable length: 3m
K-T40b-002r-Mf-S-M-Su2-1-U	
T20wn/10nm	TORQUE TRANSDUCER 10NM 12V 12PIN CONNECTION
Ae101	
K-Rtn-S-C3-150-N-12-N-N-S-S	

K-T40b-200q-Mf-S-M-Du2-1-S	
T20wn-50	
Dq809	
Z6fd1/5kg-1	
1mc55	
1-Ehls-Icp-B-2	
Z6fc3-500kg	LOAD CELL
1-Ly61-1.5/120	
1-Tn/500nm	
Pw15ahc3mr	
K-Ry81-3/350	
1-Cx22-W	
1-C16ac3/60t/Eexd	
1-Wa/100mm-L	
1-Kab271-3	
Hlcb1c6-220kg	
1-X60-Np	
Ap04	
K-Wa-L-200w-31s-S2-F1-1-8-10m	
K-T40b-200q-Mf-S-M-Su2-0-U	
P3ic/2000bar	
1-P3mbp-1000bar	PRESSURE TRANSDUCER 1000BAR
1kab133a	
Z6fc6/100kg-1	
C9c-50kn	
P2va1/200bar	
1-Mp30	
P3ic/3000bar	
1-Z6fc3/500kg-1	
Mp55dp	SIGNAL CONDITIONER SINGLE CHANNEL 4.8KHZ

1-Hlcb1d1/550kg-1	
C9b-50kn	
1-Vkk1r-4	
Blcb1c3/1.76t-1	
K-T40b-500q-Mf-S-M-Du2-1-S	
C2/10kn	FORCE TRANSDUCER 10KN 3M CABLE
Slb700a/06-1	
K-Wa-T-020w-32k-K1-F1-2-2-3m	
1-Wa/2mm-T	
1-Z7ad1/5t	
1-Pw15phc3/10kg-1	
K-T40b-500q-Mf-S-M-Du2-0-U	
Pw16ac3mr	
Mp85adp	
K-Ly4-350-07-1-2-25	
1-T5/20nm	
U2b-1kn	
K-Cal-T-W-5-B-S-S-2-0	
H358-5k-Se 3mvv	
C2/20kn	FORCE TRANSDUCER 20KN 2MV
Catman Easy	
Fit/1sa31/10kg	LOAD CELL 10KG
P3icp/100bar	