Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Heinrich Kubler

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Heinrich Kubler Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Heinrich Kubler Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
BNA-BV/BNA-EN25/16/B1-M2.100-V42x2...	...-MRA-ZVS 32/245/PN16/A990 Bypass level indicator type BNA-C00 Approval: Bureau Veritas - individual approval pressure: 6 bar; Temp.: -10°C...80°C; Density, medium: 800 kg/m³ Test pressure: 9 bar Chamber dimensions: 42.4 x 2 mm stainless steel 1.4571 (316Ti) Process connection: flange DIN EN 1092-1 DN 25 PN 16 form B1 Center distance: 2100 mm Measuring range: 2100mm Float: ZVS32/245/PN16/A990 Float material: stainless steel 1.4571 Chamber closure at the top: tube sheet Chamber closure below: KSR vessel flange Drain: screw plug G 1/2" Damping element: Damping element below Gasket(s): flat gasket, graphite laminate Screws: stainless steel A4-70 (M) Retaining tab(s): 2 pieces Projection above (T): 100 mm Projection below (U): 255 mm Lateral distance (X): 150 mm (maximum) Nameplate: Laser-marked aluminium Weight: 11.8kg MRA-M2.100 Display for bypass type BMD-SA Measuring range: 2100mm Housing material: aluminum anodized Display element: rollers red/white Lens: Makrolon PC Inspection certificate 3.1 according to EN 10204 Type of certificate: Inspection certificate DIN EN 10204 3.1 Certificate language: English and German Certificate / Certificate for: Bypass Standard Material certificate: Media-wetted pressure-bearing metallic components with pre-supplier certificate (enamel analysis) Pressure and strength test: Hydrostatic internal pressure test

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	***Drawing for review and approval Customs tariff number: 90261089 * Items with Bureau Veritas approval (individual approval)
SWITCH,AG,CH-6341 BAAR KP-39345/5	
Fls-Cbmzz000510800ta2zzgezz0222o032 3szzzzzzzzzz#	ARPP1,5 "-Vos-L368 / 12-B40A Float switch type FLS-SA Material: polypropylene (PP) and 1.4571 Pressure: 0.5 bar Temperature range: -10 ° C to 80 ° C Density, medium: 800 kg / m³ Housing: aluminum Protection class: IP65 Electrical connection: Cable gland M20x1.5 mm Process connection: screw-in thread downwards G 1.5 " Switching function 1: normally closed with increasing level 222 mm Switching function 2: normally open with increasing level 323 mm Switching capacity: max. AC 230V; 100VA; 1A / DC 230V; 50W; 0.5A Float: Buna B40A Number of floats: 1 piece Slide tube: Ø 12 mm Installation length: 368 mm Float limitation: welding studs Weight: 0.8 kg Additional ordering information: Wire colors with strands: L1: brown - brown L2: gray - gray with lock nut made of stainless steel small connection housing with M20 x 1.5 without reduction
Erv1/8"-Vu-L55/8-V27a-5sil	Float switch type FLS-ME Material: Stainless steel 1.4571 (316Ti) Pressure: 2.0 bar Temperature range: -10 ° C to 100 ° C Density, medium: 1000 kg / m³ Electrical connection: cable silicone 5 m Process connection: Screw-in thread upwards G 1/8 " Switching function 1: Switch 30 mm Switching capacity: max. AC 50V; 5VA; 0.25A / DC 75V; 2.5W; 0.15A Float: stainless steel 1.4571 V27A Number of floats: 1 piece Slide tube: Ø 8 mm Installation length: 55 mm Float limitation: welding studs Float can not be installed by process connection
Eiauieaiea	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Fls-Cbmzz000510800ta2zzgezz0222o0315szzzzzzzzzzz#	ARPP1,5 "-Vos-L360 / 12-B40A Float switch type FLS-SA Material: polypropylene (PP) and 1.4571 Pressure: 0.5 bar Temperature range: -10 ° C to 80 ° C Density, medium: 800 kg / m^3 Housing: aluminum Protection class: IP65 Electrical connection: Cable gland M20x1.5 mm Process connection: screw-in thread downwards G 1.5 " Switching function 1: normally closed with increasing level 222 mm Switching function 2: normally open with increasing level 315 mm Switching capacity: max. AC 230V; 100VA; 1A / DC 230V; 50W; 0.5A Float: Buna B40A Number of floats: 1 piece Slide tube: Ø 12 mm Installation length: 360 mm Float limitation: welding studs Weight: 0.8 kg Additional ordering information: Wire colors with strands: L1: brown - brown L2: gray - gray with lock nut made of stainless steel small connection housing with M20 x 1.5 without reduction
Fls-Cbmzz000510800ta2zzgezz0222o0315szzzzzzzzzzzã	
Fls-Cbmzz000510800ta2zzgezz0222o0323szzzzzzzzzzzã	
Kp 80399/1	ALBAVE-VU-M55-SVK44-1 Luvata – Coiltech Water leakage detector QDKZ-09-3

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.