

Herrblitz

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Herrblitz Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Herrblitz Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
A050T	
Herrblitz	
Herrblitz	
Herrblitz	
A050TER	herrblitz pneumatic feeder Control by mechanical valve Rear roller to optimize the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 50 mm (it's the new version of your feeder A050, which is no longer produced)
KITABC+TER	kit repair for feeder ABCTER
C100TER	pneumatic feeders Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 100 mm Max. feeding stroke 100 mm
model DX050	herrblitz pneumatic feeder Equipment and technical features: Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 150 mm Max. feeding stroke 50 mm

Ürün	Açıklama
A100TER	pneumatic feeder Equipment and technical features: Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 100 mm
C050TER	pneumatic feeders Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 100 mm Max. feeding stroke 50 mm
A100TER/P	Control by pneumatic valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 100 mm
A100TERE	Control by electric valve in the voltage you need (choice among 24 VAC / 110 VAC / 220 VAC / 24 VDC) à Please confirm us the voltage needed at the order Rear roller to optimise the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 100 mm
Pneumatic feeder, model A050TER	Equipment and technical features: Control by mechanical valve Rear roller to optimize the strip positioning while entering the feeder Max. strip width 50 mm Max. feeding stroke 50 mm
C100TER	pneumatic feeder Equipment and technical features: Control by mechanical valve Rear roller to optimise the strip positioning while entering the feeder Max. strip width 100 mm Max. feeding stroke 100 mm
Typ: B050 Pos. 66	
Typ: B050 Pos. 157	
Typ: B050 Pos. 102t	
Typ: B050 Pos. 65	

Ürün	Açıklama
Sx150e	
Typ: B050 Pos.7t	
Typ: B050 Pos. 69	
Yb050r	
Db11/Abc/50 +68+69	
Typ: B050 Pos. 1 Hauptblock	
Part 11 For A250t	
C050ter	
Typ: B050 Pos. 207	
Bxd50p (Do19800)	
Multistroke Counter Box Ref 153	
A050ter	
Typ: B050 Pos. 60t	
Typ: B050 Pos. 12	
Db12/Abc	
Va/ Abcx	
Vsabcxter	
Typ: B050 Pos. 105	
Typ: B050 Pos.63t	
Typ: B050 Pos.62t	
Typ: B050 Pos. 11	
Typ: B050 Pos. 13	
Typ: B050 Pos. 83	
Typ: B050 Pos. 5t	
Typ: B050 Pos. 9	
Typ: B050 Pos. 14	

Ürün	Açıklama
Typ: B050 Pos. 64	
9+10/Abc/50	
Typ: B050 Pos.6t+8	
Typ: B050 Pos. 104	
Typ: B050 Pos. 109	
Typ: B050 Pos. 15	