Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Hi Force



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Hi Force Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hi Force Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Coupling Sleeve Cf1	Product description coupling sleeve Brand name Hi-Force Type designation CF1 Operating pressure 700 bar Connection 1 3/8 "NPT AG 84679900
Coupling Connector Cm1	3/8 "NPT IG
TPA07A	Pneum.p. TPA07A 700bar 3-stage
HTWP2140P	Pneum.p. TPA07A 700bar 2-stage
Puller Legs PK104	
Straps PK105	
Strap Bolts PK106	STRAP BOLTS
Adj Screw PK108	
TWG40	Rotation multiplier Mechanically Product description torque multiplier Brand name Hi-Force Type designation TWG40 Drive type mechanical Max. Torque 4,000.00 Nm Material aluminum Customs tariff number 84678900 Net weight 4.2 KG
PRESSURE GAUGE HG 11	
GAUGE MOUNTING BLOCK HGA2	
Hydraulic Hose-Black HC2 (2m)	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
VRC700ZE001	
HEP207322	
Drive Plate RHC054FD001	
TWS45N	pos.3
Pin RHC054ZM001	
Service Kit TWH54NRHTP1-K	
HLS50TP1-K	35201000035000 Sealing kit Seal kit for HLS cylinder 50 T ********** !! ! When placing an order, please state the serial number of the cylinder
HLS 502	50 TONS CAPACITY JACK CARE KIT
HSS 1010	CAPACITY JACK CARE KIT
HP230	CAPACITY JACK CARE KIT
HPS502	CAPACITY JACK CARE KIT
HG50 ½” 14 NPT	CAPACITY JACK CARE KIT
HEP 103	3 POSITION SOLENOID VALVE) + 2 outlet distributor + manometer + 2 3 meter hoses
HP 257	+manometer
SEC002KT015	GASKET FOR: HWTP2141AR
SEC001KT004	GASKET FOR: HWTP2141AR
SEC00KT014	PUMP GASKET FOR: HWTP2141AR
WAC007HD000	1/4"BSP SELF CENTERİNG BONDED WASHER FOR: HWTP2141AR
WAC008KD000	DOWTY WASHER FOR: HWTP2141AR
SEC003KT009	TANK GASKET FOR: HWTP2141AR

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
WAC005EC001	M5 COPPER WASHER FOR: HWTP2141AR
Hydraulic puller SCP103	with integrated pump Extraction force 10 tons, 3-way puller, stroke 82 mm, Piston extension 50 mm, spring for assisted piston return, can be used in any position, complete with Tool case.
Hydraulic puller SCP203	with integrated pump extraction force 20 tons, 3-way puller, stroke 82 mm, Piston extension 100 mm, spring for assisted piston return, can be used in any position, complete with Tool case.
HP257	Hand pump, 2-stage Oil content 5 liters, 1st stage delivery rate 12.9 cm^3 / lever stroke, 2nd stage delivery rate 2.3 cm^3 / lever stroke, Switching pressure 14 bar, 2-way drain valve for single-acting (flow-return), max. leverage 40 kg, steel, bar max.operating pressure, against overpressure. Country of manufacture: Great Britain HI-FORCE HYDRAULIC PUMP CYLINDER
HTWP 2142ARH	
TWH120N	
TWH120NRH-85	
MB 120-85-70	
MB 120-70-65	
HTWH 10	
TWS 45N	
NS104 (AF 17-32MM, 11/16"- 1.1/4")	
NS110 (AF 32-41MM, 1.1/4-1.5/8")	
NS200 (AF 41-50MM, 1.5/8 -2")	
HH2R	
HP227	
HLS302	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
SCP103-317	
PT NO:CF1	
CF1 3/8"NPT	
CM1 700bar 3/8" NPT	
HC2-	2 metre high pressure hydraulic hose (Black, CM1 on one end, 3/8 NPT on other end)
HHS302	33 tonne capacity, single acting, hollow piston cylinder i-Force Model no.: HHS302, 33 tonne capacity, single acting spring return, hollow piston hydraulic cylinder. Closed height 165mm, stroke length 50mm, centre hole diameter 35mm, outside diameter 115mm. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 10.6kg.
HEP103242LS	240V, Two stage, Electric driven compact pump Hi-Force Model no.: HEP103242LS, 240V, single phase, electrically operated compact hydraulic pump. Two speed design with low pressure (up to 150 Bar) flow rate of 2.50Litres/ min and high pressure flow rate of 0.35 Litres/min. Pump supplied fitted with a dual scaled glycerine filled hydraulic pressure gauge, 4.0 Litre capacity oil reservoir and integral carrying handle. The pump also incorporates an electrically operated two way solenoid valve with advance and retract features and a hold feature making the pump suitable for applications with single acting cylinders or tools requiring a “hold” facility. Maximum working pressure 700 Bar, weight 19.2kg
HC5	5 metre high pressure hydraulic hose (Black, CM1 on one end, 3/8 NPT on other end) Hi-Force Model no.: HC5, Five metre length black hydraulic hose assembly, fitted with ergonomically designed hand grips on both ends, CM1 quick release coupler on one end and 3/8”-18NPT male fitting on other end. Maximum working pressure 700 Bar (10,000PSI) with safety factor of 4:1.
35151000015049	hand p. HP227 700bar 2-stage Product description: Pumps for piston jacks brand name: Hi Force

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	type designation: HP227 max. temperature use: 80□ minimum temperature use: -20□ operating pressure: 700 bars pump type: hand pump number of pump stages: 2-stage Delivery capacity 1st stage per stroke: 12.90cc Pumping capacity 2nd stage per stroke: 2.30cc switching pressure: 14.00 bars valve type: 2-way manual valve oil capacity: 2,300.00 cm3 material: steel Color: Red
CP0351ESGEL	Hi-Force "Alligator" Rivet Squeezer
35101000015008	torque.s. Hydraulic TWS100N Product Description Torque Wrench Brand name Hi-Force Type designation TWS100N max. temperature use 80 °C Minimum temperature use -20 °C Type of drive Hydraulic Operating pressure 700 bar Operating pressure return 100.00 bar Max. torque 10,064.00 Nm Output square 1 1/2" Material aluminium Red color Customs tariff number 84678900 Net weight 9KG
HTWP2142P	
V-8245	Duel Check Valve
HTWP2142AR	240V electric driven hydraulic torque wrench pump Hi-Force Model no.: HTWP2142AR, 240 volt electrically driven hydraulic torque wrench pump unit. Two speed design with low pressure flow rate 3.9 litres per minute and high pressure flow rate 0.36 litres per minute. Supplied fitted with auto retract function as standard with externally adjustable torque setting pressure relief valve, 0-700 Bar/0-10,000 P.S.I. 100mm diameter glycerine filled pressure gauge, 5 litre oil reservoir with sight level gauge, temperature gauge, filler and drain plugs and protective rollbar carrying frame and 3m length of control cable. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 34.0kg

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
TWS100N	1.1/2 square drive hydraulic torque wrench (1,006 - 10,064Nm, 730 - 7,308ft. Lbs.) Hi-Force Model no.: TWS100N, 1½" square drive, reversible ratchet design, lightweight aluminium hydraulic torque wrench. Maximum output torque capacity 10064Nm (7308 lbf.ft) at maximum working pressure. Supplied complete with quick release, internal spline design, multi-positional reaction foot and uni-swivel quick connect couplings and calibration certificate in a carrying and storage case. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 9.0kg
HTWH4	Hydraulic torque wrench hose set (4 metre) Hi-Force Model no.: HTWH4, 4 metre length hydraulic torque wrench hose set (2 pcs), supplied fitted with quick release couplings and dust caps at both ends, maximum working pressure 700 Bar (10,000 p.s.i.) with 4:1 safety factor
AHP107-CR	35152000015091 Hydrotest pump Pneumatic Product description Hydrotest pump Brand name Hi-Force Type designation AHP107-CR Max. operating pressure 738.00 bar Type of drive Pneumatic Stepless number of pump stages Liquid volume per stroke 4.00 cm3 conveyor at max. output pressure 0.44L/min Outlet connection thread 1/2"-14NPT Container available Yes Container volume 7.00 l Pressure gauge available Yes Chart recorder available Yes Net weight 28KG
AHP187-CR	35152000015092 Hydrotest pump Pneumatic Product description Hydrotest pump Brand name Hi-Force Type designation AHP187-CR Max. operating pressure 1,293.00 bar Type of drive Pneumatic Stepless number of pump stages Liquid volume per stroke 2.20 cm3 conveyor at max. output pressure 0.39L/min Outlet connection thread 9/16"-18UNF Container available Yes

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Container volume 7.00 l Pressure gauge available Yes Chart recorder available Yes Net weight 28KG
Electrop. TPE25A 700bar 3-stage	Product description Pumps for hydraulic tools brand name Hi Force type designation TPE25A operating pressure 700 bars pump type electric pump number of pump stages 3 tier motor voltage 230.00v engine power 1,100kW Funding capacity 1st level 6.50 l/min Funding capacity 2nd level 1.50 l/min Funding capacity 3rd level 0.75L/min material steel Color Red
HKP56 EQUIPPED	WITH PNEUMATIC PUMP 700 BAR (CONTAIN: JACK HRD56-PUMP AHP1141 - GUN K1 -HOSE HC4 COUPLER CMF1)
HTWP3142P-A	
IB54-206-200	Hi-Force Model no.: IB54-206-200, Hexagon reducer bush to suit TWH54NRH ratchet head when reducing from 2.3/8” to 2” AF size
IS9-200	Hi-Force Model no.: IS9-200, 1” square drive standard length heavy duty impact socket, 2” AF (across flat). Supplied complete with retaining ring and pin.
HHS 603 61 TON	MATERIAL: SINGLE ACTING SPRING RETURN HYDRAULIC CYLINDER WITH CENTER HOLE CAPACITY: 61 TONS

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	STROKE: 76 MM OIL CAPACITY: 651 cm3 EFFECTIVE AREA: 85.7 cm2 CLOSED LENGTH: 226 MM CYLINDER DIAMETER: 160 MM PISTON DIAMETER: 92 MM HOLE DIAMETER: 55 MM WEIGHT: 28.0 KG
Repair kit for Hi-Force SCP303	SCP303TP1-K
HLS 302	Hi-Force Model no.: HLS302, 32 tonne capacity single acting, spring assisted return low height hydraulic cylinder. Closed height 119mm, stroke length 60mm, outside diameter 102mm. Maximum working pressure 700 Bar (10,000 p.s.i.). Weight 7.0kgs. SINGLE ACTING LOW HEIGHT CYLINDERS HI-FORCE/HLS - MODEL
HLS 101	Hi-Force Model no.: HLS101, 10 tonne capacity single acting, spring assisted return low height hydraulic cylinder. Closed height 95mm, stroke length 40mm, outside diameter 70mm. Maximum working pressure 700 Bar (10,000 p.s.i.). Weight 2.4kgs.
HP257	Hi-Force Model no.: HP257, Two speed manually operated hand pump suitable for single acting applications. The pump incorporates a 4.1 litre usable oil reservoir, external pressure release valve, factory set safety relief valve and has a weight of 15.2kg. The pump offers a displacement of 12.9cm3 and 2.3cm3 per stroke at first and second stage, respectively and has a maximum working pressure of 700 Bar (10,000 p.s.i.).
HGA1	Hi-Force Model no.: HGA1, Hydraulic gauge mounting block for fitment of Hi-Force hydraulic pressure gauges, with ½" NPT female gauge connection and 3/8" NPT male to 3/8" NPT female inlet and outlet connections. Maximum pressure 700 Bar (10,000PSI). Weight 0.25kg
HG1	Hi-Force Model no.: HG1, 100mm (4") diameter hydraulic pressure gauge, dual scaled 0-700 Bar / 0-10,000 PSI with ½" NPT bottom male connection. Maximum pressure 700 Bar (10,000PSI). Weight 0.9kg
HC2	Hi-Force Model no.: HC2, Two metre length black hydraulic hose assembly, fitted with ergonomically designed hand grips on both ends, CM1 quick release coupler on one end and 3/8"-18NPT male fitting on other end. Maximum working pressure 700 Bar (10,000PSI) with safety factor of 4:1.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HP227	Hi-Force Model no.: HP227, Two speed manually operated hand pump suitable for single acting applications. The pump incorporates a 2.3 litres usable oil reservoir, external pressure release valve, factory set safety relief valve and has a weight of 10.5kg. The pump offers a displacement of 12.9cm3 and 2.3cm3 per stroke at first and second stage, respectively and has a maximum working pressure of 700 Bar (10,000 p.s.i.).
HGA1	Hi-Force Model no.: HGA1, Hydraulic gauge mounting block for fitment of Hi-Force hydraulic pressure gauges, with ½" NPT female gauge connection and 3/8" NPT male to 3/8" NPT female inlet and outlet connections. Maximum pressure 700 Bar (10,000PSI). Weight 0.25kg
HG1	Hi-Force Model no.: HG1, 100mm (4") diameter hydraulic pressure gauge, dual scaled 0-700 Bar / 0-10,000 PSI with ½" NPT bottom male connection. Maximum pressure 700 Bar (10,000PSI). Weight 0.9kg
HC2	Hi-Force Model no.: HC2, Two metre length black hydraulic hose assembly, fitted with ergonomically designed hand grips on both ends, CM1 quick release coupler on one end and 3/8"-18NPT male fitting on other end. Maximum working pressure 700 Bar (10,000PSI) with safety factor of 4:1.
HSS254	Hi-Force Model no.: HSS254, 25 tonne capacity single acting, spring assisted return hydraulic cylinder. Closed height 225mm, stroke length 102mm, outside diameter 86mm. Maximum working pressure 700 Bar (10,000 p.s.i.). Weight 8.0kgs.
HSS53	Hi-Force Model no.: HSS53, 4.5 tonne capacity single acting, spring assisted return hydraulic cylinder. Closed height 157mm, stroke length 75mm, outside diameter 38mm. Maximum working pressure 700 Bar (10,000 p.s.i.). Weight 1.4kgs.
HSS156	Hi-Force Model no.: HSS156, 14.5 tonne capacity single acting, spring assisted return hydraulic cylinder. Closed height 254mm, stroke length 150mm, outside diameter 70mm. Maximum working pressure 700 Bar (10,000 p.s.i.). Weight 6.6kgs.
HHS102	Hi-Force Model no.: HHS102, 11 tonne capacity, single acting spring return, hollow piston hydraulic cylinder. Closed height 140mm, stroke length 50mm, centre hole diameter 20mm, outside diameter 70mm. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 3.0kg.

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HHS106	Hi-Force Model no.: HHS106, 11 tonne capacity, single acting spring return, hollow piston hydraulic cylinder. Closed height 297mm, stroke length 152mm, centre hole diameter 20mm, outside diameter 70mm. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 10.2kg.
HHS306	Hi-Force Model no.: HHS306, 33 tonne capacity, single acting spring return, hollow piston hydraulic cylinder. Closed height 320mm, stroke length 152mm, centre hole diameter 35mm, outside diameter 115mm. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 19.2kg.
HRA1002	double acting aluminium cylinder, 110 tonne capacity, 51 mm stroke, 258 mm closed heigt, 700 bar maximum working pressure
HP232	Two stage, Single acting, Manually operated aluminium hand pump Hi-Force Model no.: HP232, Two speed, lightweight aluminium, manually operated hand pump suitable for single acting applications. The pump incorporates a 2.0 litres usable oil reservoir, external pressure release valve, factory set safety relief valve and has a weight of 6.9kg. The pump offers a displacement of 12.9cm3 and 2.3cm3 per stroke at first and second stage respectively and has a maximum working pressure of 700 Bar (10,000 p.s.i.)
HFG50TP1-K	Service Kit
MS5-105	Square drive : 1.1/2" Suitable for nut size 105 mm
MB54-70-65	Hexagon reducer bush (70mm across flats to 65mm across flats)
MB54-70-60	Hexagon reducer bush (70mm across flats to 60mm across flats)
MB54-50-41	Hexagon reducer bush (50mm across flats to 41mm across flats)
HSS106	10 tonne capacity, single acting multipurpose cylinder
HSS1012	10 tonne capacity, single acting multipurpose cylinder
HPS300	32 tonne capacity, single acting, low height pad cylinder
HPS20TP1-K	Service Kit

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HLS100TP1-K	Service Kit
HSS25TP1-K	Service Kit
HSS50TP1-K	Service Kit
HVL10TP1-K	Service Kit
TWH27NRH-113	Female hexagon cassette head with AF size 1.13/16"- 46mm to use in conjunction with Hi-Force hydraulic torque wrench drive unit TWH27N, radius 10.5 mm
HG1G	Hi-Force Model no.: HG1G, 100mm (4”) diameter glycerine filled hydraulic pressure gauge, dual scaled 0-700 Bar / 0-10,000 PSI with ½” NPT bottom male connection. Maximum pressure 700 Bar (10,000PSI). Weight 1.0kg
CMF1	Hi-Force Model no.: CMF1, 3/8” NPT quick connect coupler set comprising CF1, female quick connect half coupler and CM1, male quick connect half coupler. Maximum working pressure 700 Bar (10,000PSI)
P59	Power team hydraulic hand pump
P159	Power team hydraulic hand pump
P300	Power team hydraulic hand
C556C	Power team hydraulic jack 55 ton , stroke 158 mm
RH606	Power team hydraulic jack 60
RH306	Power team hydraulic jack 30 ton , stroke 152 mm
HH3R	Hi-Force Model no.: HH3R, Three metre length red hydraulic hose assembly, fitted with ergonomically designed hand grips and 3/8”-18NPT male fitting at both ends. Maximum working pressure 700 Bar (10,000PSI) with safety factor of 4:1.
HP232D	Two stage, Double acting, Manually operated aluminium hand pump
HLS30TP1-K	Service Kit
HHS206-	23 tonne capacity, single acting, hollow

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	piston cylinder
SCP303	30 tonne capacity, Three way, Self contained hydraulic puller
AT6889	HEP517462
TWH210N Gasket Set	BA1793, BA4862, DF1670, BA1788, BG6240
TWH210NRL-100 gasket set	BB2506, BE6559, AY9691
TWH210NRL-95 Gasket set	BB1472, BF2169
TPE25A	
TWH120NRH-209	Female hexagon cassette head for TWH120N Female hexagon cassette head with AF size 2.9/16” - 65 mm to use in conjunction with Hi-Force hydraulic torque wrench drive unit TWH120N. Radius 14.9 mm
HTWP2142AR	240V electric driven hydraulic torque wrench pump Hi-Force Model no.: HTWP2142AR, 240 volt electrically driven hydraulic torque wrench pump unit. Two speed design with low pressure flow rate 3.9 litres per minute and high pressure flow rate 0.36 litres per minute. Supplied fitted with auto retract function as standard with externally adjustable torque setting pressure relief valve, 0-700 Bar/0-10,000 P.S.I. 100mm diameter glycerine filled pressure gauge, 5 litre oil reservoir with sight level gauge, temperature gauge, filler and drain plugs and protective rollbar carrying frame and 3m length of control cable. Maximum working pressure 700 Bar (10,000 p.s.i). Weight 34.0kg
AU9543-700 BAR	
AU3182-700BAR	
SJS10-M	Expanging Wedge
JS-4	Expanging Wedge
SJS10-TK	Expanging Wedge
HPS 200	SINGLE ACTING LOW HEIGHT PAD CYLINDERS HI-FORCE/HPS - MODEL
HPS 500	SINGLE ACTING LOW HEIGHT PAD CYLINDERS HI-FORCE/HPS - MODEL

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HSS104	SINGLE MULTI PURPOSE CYLINDERS HI-FORCE/HSS - MODEL
HSS1010	SINGLE MULTI PURPOSE CYLINDERS HI-FORCE/HSS - MODEL
HHR302	DOUBLE ACTING HOLLOW PISTON CYLINDERS HI-FORCE/ HHR - MODEL
HFL 502	SINGLE ACTING LOW FAILSAFE LOCK RING CYLINDERS HI-FORCE/ HFL - MODEL
3.0	HIGH PRESSURE HYDRAULIC HOSES-RED HI-FORCE - MODEL: LENGHT METRES
4.0	HIGH PRESSURE HYDRAULIC HOSES-RED HI-FORCE - MODEL: LENGHT METRES
HG 63G	PRESSURE GAUGES&GAUGE MAUNTING BLOCKS HI-FORCE MODEL
CF1-9	HIGH PRESSURE COUPLERS AND FITTINGS HI-FORCE MODEL
HLS301	HYDRAULIC CYLINDER HI-FORCE
Jss55	
Bsc022lc001 / Twh54n	Bearing
Hf7	Nipple, 1/4 NPT male to 1/4 NPT male
Hp 110	Single stage, Single acting, Manually operated Steel Hand Pump
Ttc120sa001	End Swivel Gland
HP110	Single stage, Single acting, Manually operated Steel Hand Pump PUMP, HAND PUMP HI-FORCE
Ttc054ns003 / Twh54n	Piston Head
Xhc1.5b	
Hls 502	50 tonne capacity, single acting, low height cylinder
Htwh4	4 Meter
Twh54ntp2-K	Service Kit
S6000x	TORGUE WRENCH PUMPS (HTWP2140 P) METRIC SIZE RATCHET HEADS (TWH54NRH - 80) DRIVE CYLINDERS

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	(TWH54N) IPERIAL SIZE RATCHET HEANDS 8 TWH54NRH2 3/8 " QUARE DRIVE CONVERSION KITS (SDC54-M 1 1/2") (SDC27-M 1") HYDRAULIC HOSES (HTWH 10) QUICK CONNET COUPLINGS (CF 4F) METRIC HEXAGON REDUCER BUSHES (MB54-60-46 60-50 65-50 70-55 75-60 80-65 80-70 80-75) METRIC HEXAGON AFSIZE HEAVY DUTY SOCKETS MS9-24 -27-30-32-36-41-46-50-55-60-65-70-75-80) 1" MS-2 24-27-30-32-36-41-46-50-55-60 3/4" MS5-36-41-46-50-55-60-65-70-75-80 1 1/2" STS-TOP SIDE BOLTTENDS TENSIONERS-METRIC STS2 M36B1, STS2 M39B1, STS3 M42B1, STS3 M45B1, STS3 M48B1, STS3 M52 B2, STS4 M54B2, STS 4M56B2, STS M60B2, STS4 M64B1, STS5 M68B1, STS5 M72 B1, STS6 M76B1, STS6 M80B1
Ttc045sa003 / Twh54n	Swivel Connector Cap
Hp227	Two stage, Single acting, Manually operated steel hand pump
Ttc045sa002 / Twh54n	Female Swivel Connector
Rhc120fr075	Ratchet
Ttc120ea001	Swivel Connector Gland
Ttc0054js001 / Twh54n	Locking Pin
Ttc210ns002	Piston Head
Twh54n	
Tmw200	P35101000015013 Drehmom.s. Manuell
Twh210ntp2-K	Service Kit
Bsc035ld001	Bearing for TWH210N
Tmw550	P35101000015016 Drehmom.s. Manuell
Ttc120ms001	Thrust Pad
Twh120n	Double acting hydraulic torque wrench drive cylinder
Ttc150ds001	
Hls 302	32 tonne capacity, single acting, low height cylinder
SCP203	20 tonne capacity, Three way, Self contained hydraulic puller

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Ttc210ea001	Swivel Connector Gland
Twshtp2-K	Swivel Seal Kit
Tmw850	P35101000015017 Drehmom.s. Manuell
Hp 232	Two stage, Single acting, Manually operated aluminium hand pump
Twh120ntp2-K	Service Kit
Tmw400	P35101000015015 Drehmom.s. Manuell
Xhc1,5b	1,5 Meter hydraulischer PR-Force 1500-Spannschlauch
Ttc054ns002 / Twh54n	Piston Rod
Hls 1002	109 tonne capacity, single acting, low height cylinder
Twm300	300Nm (220ft. Lbs.) capacity manual torque wrench - click type
Ttc120ns002	Piston Rod
Hc4cr	4 metre high pressure hydraulic hose (Red, CM1 on both ends)
Jas103	
Xhc5b	5 Meter Hi-Force 1500 bar hydraulischer Spannschlauch
Ttc045sa002	Female Swivel Connector
Twm400	400Nm (300ft. Lbs.) capacity manual torque wrench - click type
Tmw300	P35101000015014 Drehmom.s. Manuell
Cf4f	Female half coupler, 1/4 NPT female
Cm4f	Male half coupler, 1/4 NPT female
Ay02082019/Ja	H 1260C 3
Ttc210sa001	End Swivel Gland
Ttc120ns003	Piston Head
Hhs206	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
HP245	TANK - TWO-WAY
Ttc210ms001	Thrust Pad
Bsc028lc001	Bearing
Ttc210sa002	Swivel Connector Cap
Rhc120ff001	Bearing
Rhc210br075	Ratchet
Ttc210ns001	Piston
Ttc054ba001 / Twh54n	Body
Twh54	
Rhc210bf001	Bearing
Ttc045sa003	Swivel Connector Cap
SCP103	10 tonne capacity, Three way, Self contained hydraulic puller
Bpc003ts001 / Twh54n	Passage plug
Hss 51	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.