Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Hilge

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine ya da www.yursat.com.tr/iletisim adresindeki iletişim formu üzerinden bizlere ulaşabilirsiniz.

Hilge Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Hilge Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
GEA Hilge HYGIA I Adapta ADY 50/50/4/2	Hilge - centrifugal pump -- As a replacement for type: Euro-Hygia-I-ADAPTA -/- No.: 978441950010 -/- SAP.: 97844195 --
Centrifugal pump Ebara series 3S32-200/756-60Hz	Replacement for standard Durachrom 50.32.200, no.: 34/09/006 horizontal, single-stage centrifugal pump according to EN 733 with stub shaft Lantern and standard motor Limits of use: Temperature: max. 110C Temperature: min. -10C Operating pressure: max. 10 bar Q/H range: 100-400 l/min (6-24 m3/h) / 76.0-57.0 m Fl.S. H max: 78.0 m Impeller construction: closed Shaft seal: mechanical seal Hydraulics: 1-stage with axial suction port Connection dimensions pressure connection: DN 32 suction connection: DN 50 Materials: Housing: stainless steel 1.4301 Impeller: stainless steel 1.4301 Seal carrier: stainless steel 1.4301 Pump shaft: stainless steel 1.4301 Mechanical seal: chrome steel/carbon/EPDM (item 11) O-rings: EPDM (item 12) Engine data: 3~220/380-460V +/-10% 60Hz 7.5kW 2 pin Isokl.F IP55 IE3 PTC sensor
GEA Hilge HYGIA I K KYY 65/50/4/2	DELIVERY MEDIUM & PERFORMANCE: MEASUREMENT STANDARD: Metric CUSTOMER PRODUCT: Water PRODUCT FLOW RATE [M³/H]: 27.00

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	PRODUCT DELIVERY HEAD [M]: 27.00 ADDITIONAL OPERATING POINTS: No PRODUCT TEMPERATURE [°C]: 20.0 PRODUCT VISCOSITY [MPAS]: 1.0 PRODUCT DENSITY [KG/M³]: 1,000.0 CONCENTRATION [%]: 0.0 PARTICLE SIZE [MM]: 0.0 ABRASIVE: No TEST BENCH MEDIUM: Water 20 °C TEST BENCH DELIVERY RATE [M³/H]: 27.00 TEST BENCH HEAD [M]: 27.00 TEST BENCH FREQUENCY [HZ]: 50 PUMP: PUMP SIZE: GEA Hilge HYGIA I DESIGN: K PUMP INSTALLATION POSITION: Horizontal NUMBER OF STAGES: 1 EHEDG CONFORMITY: No 3A CONFORMITY: No HYGIA HOUSING DESIGN: Housing with clamp ring - KLM HOUSING OPTIONS: Standard housing HOUSING COVER OPTIONS: Standard DRAINAGE: No MOTOR STANDARD (MECHANICAL): IEC PAINT COLOR: Gentian blue - RAL 5010 PUMP RATED PRESSURE: PN 10 SURFACE ROUGHNESS: Ra <= 3.2 µm (Ra <= 125 µin) WELD SEAM TREATMENT: Without machining MATERIAL OF PRODUCT-WETTLED PARTS: Cr-Ni-Mo Steel FERRITE CONTENT: Without restriction SURFACE TREATMENT: Welded component in contact with the product CONNECTION & IMPELLER: PIPE STANDARD: DIN EN 10357 CONNECTION TYPE: Thread CONNECTION STANDARD: DIN 11851, threaded socket NOMINAL WIDTH SUCTION SIDE: DN 65 NOMINAL WIDTH PRESSURE SIDE: DN 50 PRESSURE TUBE POSITION: 12:00 (view from pump side) COUNTER CONNECTION: Without counter connections IMPELLER TYPE: Semi-open (cast) IMPELLER SIZE: 185x9 IMPELLER DIAMETER (1st LEVEL): 155 SEAL: ELASTOMER MATERIAL, PUMP: EPDM ELASTOMER CERTIFICATES, PUMP: FDA GLRD DESIGN: Single acting GLRD SPRING (P): Open spring GLRD SEAT (P): 001 seat MATERIAL STATIC RING (P): Hard carbon MATERIAL ROTATING RING (P): Stainless steel

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	GLRD ELASTOMER MATERIAL (P): EPDM ELASTOMER APPROVAL (P): FDA GLRD DESIGN MATE RING (P): - SPRING ROTATION DIRECTION (P): Clockwise GLRD SURFACE ROUGHNESS (P): Ra <= 1.6 µm (Ra <= 62.5 µin) GLRD FERRITE CONTENT (P): Without restriction SEAL HOUSING OPTIONS: Standard COVER HOOD DESIGN: Without hood PUMP INSTALLATION: Without installation PUMP INSTALLATION (ADDITIONAL): Without addition MATERIAL OF STRUCTURE PARTS: Stainless steel MOTOR: MOTOR DESIGN: Three-phase motor MOTOR COUNTRY REGULATIONS: CE - Europe MOTOR FREQUENCY: 50 Hz MOTOR POWER: 4 kW NUMBER OF MOTOR POLES: 2-pole MOTOR PHASES: 3 MOTOR VOLTAGE: 400 VD / 690 VY MOTOR VOLTAGE SWITCHED: 3x 400 V MOTOR EFFICIENCY CLASS: IE3 MOTOR PROTECTION CLASS: IP55 MOTOR PROTECTION: 3x PTC thermistors MOTOR DESIGN: IM B5 MOTOR TERMINAL BOX POSITION: Top MOTOR HOUSING MATERIAL: not defined MOTOR SIZE: 112M ENGINE SUPPLIER: Our Wa
2041293	Stainless steel foot for Hygia K I/II (old installation height)
04P101, 05P101	Viton, Ø243x6mm oring
04P101	35 m3/h, 18.5 kW, 5-7 bar, clamp connection, shaft seal: Carbon/SS/EPDM
05P101	13 m3/h, 15 kW, 5-7 bar, clamp connection, seal: Carbon/SS/EPDM
zu Maxa 100-200 LYY, Nr.: 229/07/6091	Mechanical seal 3a1-L1K-40-aeV03
SPIRAL HOUSING 150/125-KR EN1092-16-Y-OF	
Pump shaft 470/350 40/48 - with bearing	
WHEEL 1020GU-185/25.5-32X55-RS/EL 02	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
GEA Hilge Hygia IK KYY 50/50/2.2/2	Pumping medium & performance: Measurement standard: Metric Customer product: Lemonade, water Product volume flow [m³/h]: 6.00 Delivery head product [m]: 35.00 Additional operating points: No Product temperature [°C]: 20.0 Viscosity of product [mPas]: 1.0 Product density [kg/m³]: 1,000.0 Concentration [%]: 0.0 Particle size [mm]: 0.0 Abrasive: No Medium test bench: water 20 °C Flow rate at the test bench [m³/h]: 6.00 Delivery head at the test bench [m]: 35.30 Frequency on the test bench [Hz]: 50 Pump size: GEA Hilge HYGIA I Type: K Installation position of the pump: Horizontal Number of levels: 1 EHEDG Conformity: No 3A Conformity: No Housing type HYGIA: Housing with clamping ring - KLM Housing options: Standard housing Housing cover options: Standard Emptying: No Motor standard (mechanical): IEC Paint color: Papyrus white - RAL 9018 Pump nominal pressure: PN 10 Surface roughness: Ra <= 3.2 µm (Ra <= 125 µin) Weld treatment: Without machining Material of product-contact parts: Cr-Ni-Mo steel Ferrite content: No restrictions Surface treatment: Product-contacting welded component Connection & impeller: Pipe standard: DIN EN 10357 Connection type: thread
2041293-	VA foot for Hygia KI/II (old Installation height)
Durietta I/200	
97983825	Splash ring (V-ring) VA0-28-FKM (Viton) . Kit, deflector (V-ring) VA0-28-FKM (Viton) PN 97983825
96825865	O-ring 150 x 4 EPDM/FDA PN 96825865 has been replaced by PN 98241140
97657602	Hilge Glrd 3A3-001-19 kiH C1

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
	Kit, Shaft seal 001-19-KIE PN 97657602
96840939	O-ring 22.22 x 2.62 EPDM/FDA PN 96840939 has been replaced by PN 96901913
97986239	Splash ring 50/16x5-FKM (Viton) PN 97986239 has been replaced by PN 98235773
97986239	SPLASH RING
1LA7096-2AA	MOTOR AND PUMP TOGETHER HYGIA-BLOC-I/5 serial number 07/94/104591
1LA5096-2AA	MOTOR AND PUMP TOGETHER EURO-HYGIA-I-BLOC serial number 22/04/138999
Hygiasuperii/60b	
8778026	
8778027	
Pm010113-Laufrad	
8778028	
I /5 Bvy 40/32/4/2	
60000251	MODULE
01/06/30058	
Pm010120-Laufrad	
3a1-001-19 Aee03	
Pm010115-O-Ring	
Hygiablocgi/80a	
Pm010120-O-Ring	
Pm010117-O-Ring	
Pm010114-Dichtung	
Pm010113-O-Ring	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Hygia/Cmf-Laufrad	
8778030	
Pm010118-O-Ring	
Pm010113-Dichtung	
60000261	BREAK ARMATURE
Hygia/Cmf-Dichtung	
8779161	
Pm010120-Dichtung	
Dng-63-160-Ppv-A	
Pm010115-Laufrad	
Hygiablocgii/20c	
Pm010114-O-Ring	
Pm010118-Laufrad	
8778035	
3a1bs238aie01	
C51e18-20-Fda	
9114121 (Ex.9011799)	
8778036	
Pm010115-Dichtung	
Maxana-B-32-160-5.5/2	
Hygia/Cmf-O-Ring	
Eds40.2 6.9340.2ki7 930323302	
Pm010117-Dichtung	
T13e19	
Pm010114-Laufrad	
9090927	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.

Yursat Dış Tic. Mühendislik
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505
Osmangazi/BURSA
info@yursat.com.tr
www.yursat.com.tr

Ürün	Açıklama
Pm010117-Laufrad	
Hygiana-1l/2-Bloc-Super	
S1/25a-52560	
Pm010118-Dichtung	
58016	
8778029	
8778037	
8778034	
8778033	

YURSAT yedek parça tedariği yapan bir şirkettir. Sitemizde bulunan markaların yetkili distribütörü yada temsilcisi değildir.